

## MPE Calculation / RF Exposure

Product: Doorcam2

Applicant: OLIVE AND DOVE CO., LTD.

Model: DC2U-1901

Address: 803 Polaris bldg., 381, Seongnam-daero, Bundang-gu, Gyeonggi-do, South Korea

FCC ID: 2ANMR-DC2U-1901

The FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from the device to the body of the user. According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

**Classification** The antenna of this product is at least 20 cm away from the body of the user. So this product is classified as mobile device.

### Max. tune-up power(dBm)

802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
14.00	14.00	13.00	12.00

$$S = \text{EIRP} / 4 \pi R^2$$

**Where** S = Power density  
EIRP = Effective Isotropically Radiated Power  
R = distance to the centre of radiation of the antenna

**Values** S = 1.0 mW/cm<sup>2</sup> for General population uncontrolled exposure (FCC Part 1.1310 Radiofrequency radiation exposure limits)

$$S = 1.0 \text{ mW/cm}^2$$

PT = 14.00 dBm (25.12 mW) : measured maximum output power

G = Antenna gain = 1.300 dBi (1.349 in linear terms)

$$\text{EIRP} = \text{PT} \times \text{G}$$

$$R = 20 \text{ cm}$$

**Calculation** EIRP = 25.12 x 1.349 = 33.88 mW  
S = 33.88/12.56 x (20)<sup>2</sup> = 33.88/5024  
**S = 0.00674 mW/cm<sup>2</sup>**

**Conclusion** This confirms compliance to the required radio frequency radiation exposure limit of 1.0 mW/cm<sup>2</sup> at 20 cm operation.