


## 11. Out Of Band Emissions

### 11.1 Block Diagram Of Test Setup



### 11.2 Limit

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (2) All emissions shall be limited to a level of  $-27$  dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


### 11.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### 11.4 EUT Operating Conditions



The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data



## 11.5 Test Result













































## 12. Spurious RF Conducted Emissions

### 12.1 Block Diagram Of Test Setup



### 12.2 Limit

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band(i) All emissions shall be limited to a level of  $-27$  dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge..



### 12.3 Test Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### 12.4 Test Result



Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

About: 26.5GHz-40GHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.





















































## 13. Frequency Stability Measurement

### 13.1 Block Diagram Of Test Setup



### 13.2 Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be  $\pm 20$  ppm maximum for the 5 GHz band (IEEE 802.11n specification)..

### 13.3 Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5.  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c - f) / f_c \times 10^6$  ppm and he limit is less than  $\pm 20$  ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is  $-20^\circ\text{C} \sim 70^\circ\text{C}$ .

## 13.4 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	DC 3.87V
Test Mode:	TX Frequency U-NII-1 (5180-5240MHz)		

## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency : 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.87	5180.0102	5180	0.0102	1.9691
		V max (V)	4.45	5180.0105	5180	0.0105	2.0270
		V min (V)	3.29	5180.0113	5180	0.0113	2.1815
Limits				5150-5250 MHz			
Result				Complies			

## Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.87	T (°C)	-20	5180.0114	5180	0.0114	2.2008
		T (°C)	-10	5180.0052	5180	0.0052	1.0039
		T (°C)	0	5180.0032	5180	0.0032	0.6178
		T (°C)	10	5180.0029	5180	0.0029	0.5598
		T (°C)	20	5180.0118	5180	0.0118	2.2780
		T (°C)	30	5180.0084	5180	0.0084	1.6216
		T (°C)	40	5180.0040	5180	0.0040	0.7722
		T (°C)	50	5180.0081	5180	0.0081	1.5637
		T (°C)	60	5180.0049	5180	0.0049	0.9459
		T (°C)	70	5180.0106	5180	0.0106	2.0463
Limits				5150-5250 MHz			
Result				Complies			

## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.87	5200.0047	5200	0.0047	0.9038
		V max (V)	4.45	5200.0015	5200	0.0015	0.2885
		V min (V)	3.29	5200.0078	5200	0.0078	1.5000
Limits				5150-5250 MHz			
Result				Complies			

## Temperature vs. Frequency Stability


TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.87	T (°C)	-20	5200.00280	5200	0.00280	0.5385
		T (°C)	-10	5200.00710	5200	0.00710	1.3654
		T (°C)	0	5200.00210	5200	0.00210	0.4038
		T (°C)	10	5200.00340	5200	0.00340	0.6538
		T (°C)	20	5200.01140	5200	0.01140	2.1923
		T (°C)	30	5200.00550	5200	0.00550	1.0577
		T (°C)	40	5200.01240	5200	0.01240	2.3846
		T (°C)	50	5200.00450	5200	0.00450	0.8654
		T (°C)	60	5200.00930	5200	0.00930	1.7885
		T (°C)	70	5200.00660	5200	0.00660	1.2692
Limits				5150-5250 MHz			
Result				Complies			

## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.87	5240.0026	5240	0.0026	0.4962
		V max (V)	4.45	5240.0109	5240	0.0109	2.0802
		V min (V)	3.29	5240.0012	5240	0.0012	0.2290
Limits				5150-5250 MHz			
Result				Complies			

## Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.87	T (°C)	-20	5240.0021	5240	0.0021	0.4008
		T (°C)	-10	5240.0135	5240	0.0135	2.5763
		T (°C)	0	5240.0044	5240	0.0044	0.8397
		T (°C)	10	5240.0008	5240	0.0008	0.1527
		T (°C)	20	5240.0112	5240	0.0112	2.1374
		T (°C)	30	5240.0087	5240	0.0087	1.6603
		T (°C)	40	5240.0125	5240	0.0125	2.3855
		T (°C)	50	5240.0038	5240	0.0038	0.7252
		T (°C)	60	5240.0121	5240	0.0121	2.3092
		T (°C)	70	5240.0131	5240	0.0131	2.5000
Limits				5150-5250 MHz			
Result				Complies			



Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	DC 3.87V
Test Mode:	TX Frequency(5745-5825MHz)		

## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.87	5745.01050	5745	0.01050	1.8277
		V max (V)	4.45	5745.01100	5745	0.01100	1.9147
		V min (V)	3.29	5745.01330	5745	0.01330	2.3151
Limits				5725-5850 MHz			
Result				Complies			

## Temperature vs. Frequency Stability


TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.87	T (°C)	-20	5745.00770	5745	0.00770	1.3403
		T (°C)	-10	5745.01350	5745	0.01350	2.3499
		T (°C)	0	5745.00920	5745	0.00920	1.6014
		T (°C)	10	5745.00940	5745	0.00940	1.6362
		T (°C)	20	5745.01250	5745	0.01250	2.1758
		T (°C)	30	5745.00820	5745	0.00820	1.4273
		T (°C)	40	5745.01290	5745	0.01290	2.2454
		T (°C)	50	5745.01160	5745	0.01160	2.0191
		T (°C)	60	5745.00170	5745	0.00170	0.2959
		T (°C)	70	5745.00190	5745	0.00190	0.3307
Limits				5725-5850 MHz			
Result				Complies			

## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.87	5785.00030	5785	0.00030	0.0519
		V max (V)	4.45	5785.00050	5785	0.00050	0.0864
		V min (V)	3.29	5785.01320	5785	0.01320	2.2818
Limits				5725-5850 MHz			
Result				Complies			

## Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.87	T (°C)	-20	5785.00350	5785	0.00350	0.6050
		T (°C)	-10	5785.00100	5785	0.00100	0.1729
		T (°C)	0	5785.00020	5785	0.00020	0.0346
		T (°C)	10	5785.00080	5785	0.00080	0.1383
		T (°C)	20	5785.00680	5785	0.00680	1.1755
		T (°C)	30	5785.01190	5785	0.01190	2.0570
		T (°C)	40	5785.00970	5785	0.00970	1.6768
		T (°C)	50	5785.00530	5785	0.00530	0.9162
		T (°C)	60	5785.00670	5785	0.00670	1.1582
		T (°C)	70	5785.00780	5785	0.00780	1.3483
Limits				5725-5850 MHz			
Result				Complies			






## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.87	5825.01310	5825	0.01310	2.2489
		V max (V)	4.45	5825.00570	5825	0.00570	0.9785
		V min (V)	3.29	5825.00190	5825	0.00190	0.3262
Limits				5725-5850 MHz			
Result				Complies			

## Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.87	T (°C)	-20	5825.00520	5825	0.00520	0.8927
		T (°C)	-10	5825.00800	5825	0.00800	1.3734
		T (°C)	0	5825.00730	5825	0.00730	1.2532
		T (°C)	10	5825.00190	5825	0.00190	0.3262
		T (°C)	20	5825.00620	5825	0.00620	1.0644
		T (°C)	30	5825.01220	5825	0.01220	2.0944
		T (°C)	40	5825.00750	5825	0.00750	1.2876
		T (°C)	50	5825.00890	5825	0.00890	1.5279
		T (°C)	60	5825.00540	5825	0.00540	0.9270
		T (°C)	70	5825.01140	5825	0.01140	1.9571
Limits				5725-5850 MHz			
Result				Complies			



## 14. Duty Cycle Of Test Signal

### 14.1 Standard Requirement

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

### 14.2 Formula

Duty Cycle =  $T_{on} / (T_{on} + T_{off})$



### 14.3 Test Procedure



1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak



### 14.4 Test Result

5.1G

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5180	100	0	0
NVNT	n20	5180	100	0	0
NVNT	n40	5190	100	0	0
NVNT	ac20	5180	100	0	0
NVNT	ac40	5190	100	0	0
NVNT	ac80	5210	100	0	0












## 5.8G



Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5745	100	0	0
NVNT	n20	5745	100	0	0
NVNT	n40	5755	100	0	0
NVNT	ac20	5745	100	0	0
NVNT	ac40	5755	100	0	0
NVNT	ac80	5775	100	0	0











## 15. Antenna Requirement

### 15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 15.2 Test Result

The EUT antenna is Internal antenna (antenna gain: -0.17 dBi,). It comply with the standard requirement.

