



RF Test Report

For




Applicant Name: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
Address: A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE, GUANLAN, LONGHUA SHENZHEN, 518XXX China
EUT Name: tablet
Brand Name: OUKITEL
Model Number: OT6
Series Model Number: Refer to section 2

Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Report Number: BTF231127R00403
Test Standards: 47 CFR Part 15.247

Test Conclusion: Pass
FCC ID: 2ANMU-OT6
Test Date: 2023-11-28 to 2023-12-15
Date of Issue: 2023-12-18

Prepared By: 
Chris Liu / Project Engineer
Date: 2023-12-18

Approved By: 
Ryan.CJ/ EMC Manager
Date: 2023-12-18

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2023-12-18	Original
<i>Note: Once the revision has been made, then previous versions reports are invalid.</i>		

Table of Contents

1	INTRODUCTION	5
1.1	Identification of Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Announcement	5
2	PRODUCT INFORMATION	6
2.1	Application Information	6
2.2	Manufacturer Information.....	6
2.3	Factory Information	6
2.4	General Description of Equipment under Test (EUT)	6
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards.....	7
3.2	Uncertainty of Test	7
3.3	Summary of Test Result	7
4	TEST CONFIGURATION	8
4.1	Test Equipment List	8
4.2	Test Auxiliary Equipment	10
4.3	Test Modes.....	10
5	EVALUATION RESULTS (EVALUATION)	11
5.1	Antenna requirement	11
5.1.1	Conclusion:.....	11
6	RADIO SPECTRUM MATTER TEST RESULTS (RF)	12
6.1	Occupied Bandwidth	12
6.1.1	E.U.T. Operation:	12
6.1.2	Test Setup Diagram:.....	12
6.1.3	Test Data:	12
6.2	Maximum Conducted Output Power	13
6.2.1	E.U.T. Operation:	13
6.2.2	Test Setup Diagram:.....	13
6.2.3	Test Data:	13
6.3	Power Spectral Density	14
6.3.1	E.U.T. Operation:	14
6.3.2	Test Setup Diagram:.....	14
6.3.3	Test Data:	14
6.4	Emissions in non-restricted frequency bands	15
6.4.1	E.U.T. Operation:	15
6.4.2	Test Setup Diagram:.....	15
6.4.3	Test Data:	15
6.5	Band edge emissions (Radiated)	16
6.5.1	E.U.T. Operation:	16
6.5.2	Test Setup Diagram:.....	16
6.5.3	Test Data:	17
6.6	Emissions in frequency bands (below 1GHz)	18
6.6.1	E.U.T. Operation:	18
6.6.2	Test Setup Diagram:.....	18
6.6.3	Test Data:	19
6.7	Emissions in frequency bands (above 1GHz)	21
6.7.1	E.U.T. Operation:	21
6.7.2	Test Setup Diagram:.....	21

6.7.3	Test Data:	22
7	TEST SETUP PHOTOS	24
8	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	26
	APPENDIX.....	27

1 Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130
FCC Registration Number:	518915
Designation Number:	CN1330

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 Product Information

2.1 Application Information

Company Name:	SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
Address:	A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE, GUANLAN, LONGHUA SHENZHEN, 518XXX China

2.2 Manufacturer Information

Company Name:	SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
Address:	A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE, GUANLAN, LONGHUA SHENZHEN, 518XXX China

2.3 Factory Information

Company Name:	SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
Address:	A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE, GUANLAN, LONGHUA SHENZHEN, 518XXX China

2.4 General Description of Equipment under Test (EUT)

EUT Name:	tablet
Test Model Number:	OT6
Series Model Number:	OT6 S, OT6 Pro, OT6 Ultra, OT6 Kids
Description of Model name differentiation:	Only the model name is different, everything else is the same
Hardware Version:	R8631-RK3562-V1.0
Software Version:	OUKITEL_OT6_EEA_V01

2.5 Technical Information

Power Supply:	DC 3.8V from battery
Power Adaptor:	Model:PS10UA050K2000EU Input:100-240v~50/60Hz 0.35A Max Output:5.0V==2.0A 10.0W
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz; 802.11n(HT40): 2422MHz to 2452MHz
Number of Channels:	802.11b/g/n(HT20): 11 Channels; 802.11n(HT40): 7 Channels
Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20 and HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type:	PIFA ANT
Antenna Gain [#] :	1.19dBi
Note:	<p>#: The antenna gain provided by the applicant, and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.</p>
Bluetooth Version:	5.2

3 Summary of Test Results

3.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

3.2 Uncertainty of Test

Item	Measurement Uncertainty
Occupied Bandwidth	±69kHz
Transmitter Power, Conducted	±0.87dB
Power Spectral Density	±0.69dB
Conducted Spurious Emissions	±0.95dB
Radiated Spurious Emissions (above 1GHz)	1-6GHz: ±3.94dB 6-18GHz: ±4.16dB
Radiated Spurious Emissions (30M - 1GHz)	±4.12dB

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.3 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
Occupied Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass

4 Test Configuration

4.1 Test Equipment List

Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	/	/
RF Sensor Unit	Techy	TR1029-2	/	/	/
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	/	/
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Band edge emissions (Radiated) Emissions in frequency bands (below 1GHz) Emissions in frequency bands (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	/	/
RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	/	/
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	/	/
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	/	/
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	/	/
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2023-11-13	2024-11-12
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2023-11-16	2024-11-15
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2023-11-13	2024-11-12

4.2 Test Auxiliary Equipment

The EUT was tested as an independent device.

4.3 Test Modes


No.	Test Modes	Description
TM1	802.11b mode	Keep the EUT in 802.11b transmitting mode.
TM2	802.11g mode	Keep the EUT in 802.11g transmitting mode.
TM3	802.11n(HT20) mode	Keep the EUT in 802.11n(HT20) transmitting mode.
TM4	802.11n(HT40) mode	Keep the EUT in 802.11n(HT40) transmitting mode.

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.1 Conclusion:



6 Radio Spectrum Matter Test Results (RF)


6.1 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Method:	ANSI C63.10-2013, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Procedure:	<ul style="list-style-type: none"> a) Set RBW = 100 kHz. b) Set the VBW \geq [3 x RBW]. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.1.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22.1 °C
Humidity:	47.1 %
Atmospheric Pressure:	1010 mbar

6.1.2 Test Setup Diagram:



6.1.3 Test Data:

Please Refer to Appendix for Details.


6.2 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Method:	ANSI C63.10-2013, section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Procedure:	ANSI C63.10-2013, section 11.9.1 Maximum peak conducted output power

6.2.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22.1 °C
Humidity:	47.1 %
Atmospheric Pressure:	1010 mbar

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.


6.3 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Method:	ANSI C63.10-2013, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

6.3.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22.1 °C
Humidity:	47.1 %
Atmospheric Pressure:	1010 mbar

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.


6.4 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Method:	ANSI C63.10-2013 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.4.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22.1 °C
Humidity:	47.1 %
Atmospheric Pressure:	1010 mbar

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.

6.5 Band edge emissions (Radiated)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

6.5.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22 °C
Humidity:	46.4 %
Atmospheric Pressure:	1010 mbar

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	79.53	-30.21	49.32	74.00	-24.68	peak	P
2	2390.000	81.40	-28.75	52.65	74.00	-21.35	peak	P
3	2400.000	79.19	-26.13	53.06	74.00	-20.94	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	80.39	-30.21	50.18	74.00	-23.82	peak	P
2	2390.000	82.26	-28.75	53.51	74.00	-20.49	peak	P
3	2400.000	80.05	-26.13	53.92	74.00	-20.08	peak	P

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	82.49	-28.68	53.81	74.00	-20.19	peak	P
2	2500.000	77.36	-26.68	50.68	74.00	-23.32	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	83.05	-28.68	54.37	74.00	-19.63	peak	P
2	2500.000	77.92	-26.68	51.24	74.00	-22.76	peak	P

6.6 Emissions in frequency bands (below 1GHz)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
Procedure:	ANSI C63.10-2013 section 6.6.4		

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

6.6.1 E.U.T. Operation:


Operating Environment:	
Temperature:	22 °C
Humidity:	46.4 %
Atmospheric Pressure:	1010 mbar

6.6.2 Test Setup Diagram:




6.6.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	30.4238	46.12	-18.70	27.42	40.00	-12.58	peak	P
2	44.5087	27.29	-18.34	8.95	40.00	-31.05	peak	P
3	94.9264	43.07	-29.06	14.01	43.50	-29.49	peak	P
4	166.9438	41.46	-27.63	13.83	43.50	-29.67	peak	P
5	333.6867	41.66	-25.16	16.50	46.00	-29.50	peak	P
6	541.3725	46.45	-21.57	24.88	46.00	-21.12	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	30.8535	46.41	-20.28	26.13	40.00	-13.87	peak	P
2	70.4599	30.77	-19.98	10.79	40.00	-29.21	peak	P
3	86.0491	44.01	-30.52	13.49	40.00	-26.51	peak	P
4	167.8243	40.69	-27.62	13.07	43.50	-30.43	peak	P
5	264.2820	40.13	-25.73	14.40	46.00	-31.60	peak	P
6	543.2742	45.73	-21.59	24.14	46.00	-21.86	peak	P


6.7 Emissions in frequency bands (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.7.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22 °C
Humidity:	46.4 %
Atmospheric Pressure:	1010 mbar

6.7.2 Test Setup Diagram:



6.7.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3270.858	69.79	-29.27	40.52	74.00	-33.48	peak	P
2	3823.371	69.21	-29.02	40.19	74.00	-33.81	peak	P
3	4930.721	69.94	-27.56	42.38	74.00	-31.62	peak	P
4	6106.616	73.03	-25.34	47.69	74.00	-26.31	peak	P
5	8943.274	77.62	-24.42	53.20	74.00	-20.80	peak	P
6 *	11803.280	80.14	-22.54	57.60	74.00	-16.40	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2782.060	63.31	-29.89	33.42	74.00	-40.58	peak	P
2	3629.540	69.55	-29.04	40.51	74.00	-33.49	peak	P
3	4930.721	69.66	-27.56	42.10	74.00	-31.90	peak	P
4	6322.136	72.06	-25.36	46.70	74.00	-27.30	peak	P
5	8106.200	76.46	-25.49	50.97	74.00	-23.03	peak	P
6 *	12079.387	80.41	-22.10	58.31	74.00	-15.69	peak	P

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3671.746	69.11	-29.03	40.08	74.00	-33.92	peak	P
2	5224.153	71.04	-27.19	43.85	74.00	-30.15	peak	P
3	7138.144	74.20	-24.89	49.31	74.00	-24.69	peak	P
4	9205.540	77.57	-23.85	53.72	74.00	-20.28	peak	P
5	10636.847	78.72	-24.22	54.50	74.00	-19.50	peak	P
6 *	12651.128	80.60	-21.53	59.07	74.00	-14.93	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2550.987	60.71	-30.28	30.43	74.00	-43.57	peak	P
2	3485.601	70.52	-29.07	41.45	74.00	-32.55	peak	P
3	4495.124	69.34	-28.79	40.55	74.00	-33.45	peak	P
4	6737.206	72.86	-25.17	47.69	74.00	-26.31	peak	P
5	7875.254	75.77	-25.35	50.42	74.00	-23.58	peak	P
6 *	9475.497	78.00	-23.25	54.75	74.00	-19.25	peak	P

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3270.858	70.86	-29.27	41.59	74.00	-32.41	peak	P
2	4074.389	69.33	-28.96	40.37	74.00	-33.63	peak	P
3	5075.317	71.81	-27.30	44.51	74.00	-29.49	peak	P
4	6583.209	72.20	-25.31	46.89	74.00	-27.11	peak	P
5	9366.577	78.16	-23.50	54.66	74.00	-19.34	peak	P
6 *	12433.621	79.93	-21.69	58.24	74.00	-15.76	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3233.260	69.63	-29.29	40.34	74.00	-33.66	peak	P
2	4074.389	70.55	-28.96	41.59	74.00	-32.41	peak	P
3	5315.541	71.58	-27.11	44.47	74.00	-29.53	peak	P
4	7015.420	73.50	-24.93	48.57	74.00	-25.43	peak	P
5	9366.577	78.46	-23.50	54.96	74.00	-19.04	peak	P
6 *	11871.710	79.48	-22.41	57.07	74.00	-16.93	peak	P

7 Test Setup Photos


Conducted Emission at AC power line



Band edge emissions (Radiated)
Emissions in frequency bands (above 1GHz)



Emissions in frequency bands (below 1GHz)



8 EUT Constructional Details (EUT Photos)

Please refer to the test report No. BTF231127E00401

Appendix


1. Duty Cycle



1.1 Ant1



1.1.1 Test Result



Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	16.397	16.607	98.74	0.06	0.00
		2437	16.396	16.606	98.74	0.06	0.00
		2462	16.396	16.606	98.74	0.06	0.02
802.11g	SISO	2412	5.458	5.780	94.43	0.25	0.00
		2437	5.459	5.781	94.43	0.25	0.03
		2462	5.459	5.952	91.72	0.38	2.74
802.11n (HT20)	SISO	2412	5.094	5.416	94.05	0.27	0.00
		2437	5.094	5.416	94.05	0.27	0.00
		2462	5.094	5.416	94.05	0.27	0.00
802.11n (HT40)	SISO	2422	4.906	5.229	93.82	0.28	0.04
		2437	4.905	5.228	93.82	0.28	0.04
		2452	4.905	5.228	93.82	0.28	0.04



1.1.2 Test Graph
















2. Bandwidth

2.1 OBW


2.1.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	12.152	/	Pass
		2437	1	12.150	/	Pass
		2462	1	12.151	/	Pass
802.11g	SISO	2412	1	18.493	/	Pass
		2437	1	18.499	/	Pass
		2462	1	18.522	/	Pass
802.11n (HT20)	SISO	2412	1	19.090	/	Pass
		2437	1	19.140	/	Pass
		2462	1	19.068	/	Pass
802.11n (HT40)	SISO	2422	1	37.601	/	Pass
		2437	1	37.555	/	Pass
		2452	1	37.612	/	Pass


2.1.2 Test Graph







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV












2.2 6dB BW


2.2.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	8.121	≥ 0.5	Pass
		2437	1	8.079	≥ 0.5	Pass
		2462	1	8.163	≥ 0.5	Pass
802.11g	SISO	2412	1	16.494	≥ 0.5	Pass
		2437	1	16.524	≥ 0.5	Pass
		2462	1	16.502	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	1	17.752	≥ 0.5	Pass
		2437	1	17.732	≥ 0.5	Pass
		2462	1	17.723	≥ 0.5	Pass
802.11n (HT40)	SISO	2422	1	36.371	≥ 0.5	Pass
		2437	1	36.366	≥ 0.5	Pass
		2452	1	36.345	≥ 0.5	Pass


2.2.2 Test Graph







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV











3. Maximum Conducted Output Power

3.1 Power

3.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	14.17	<=30	Pass
		2437	14.62	<=30	Pass
		2462	14.16	<=30	Pass
802.11g	SISO	2412	15.11	<=30	Pass
		2437	15.71	<=30	Pass
		2462	15.75	<=30	Pass
802.11n (HT20)	SISO	2412	15.74	<=30	Pass
		2437	16.35	<=30	Pass
		2462	16.22	<=30	Pass
802.11n (HT40)	SISO	2422	15.84	<=30	Pass
		2437	16.32	<=30	Pass
		2452	16.21	<=30	Pass

Note1: Antenna Gain: Ant1: 1.19dBi;

4. Maximum Power Spectral Density


4.1 PSD



4.1.1 Test Result



Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	-7.37	<=8	Pass
		2437	-8.70	<=8	Pass
		2462	-9.10	<=8	Pass
802.11g	SISO	2412	-18.11	<=8	Pass
		2437	-17.40	<=8	Pass
		2462	-17.44	<=8	Pass
802.11n (HT20)	SISO	2412	-17.48	<=8	Pass
		2437	-17.06	<=8	Pass
		2462	-17.58	<=8	Pass
802.11n (HT40)	SISO	2422	-20.94	<=8	Pass
		2437	-20.71	<=8	Pass
		2452	-20.16	<=8	Pass



Note1: Antenna Gain: Ant1: 1.19dBi;



4.1.2 Test Graph















5. Unwanted Emissions In Non-restricted Frequency Bands


5.1 Ref

5.1.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	2.51
		2437	1	3.66
		2462	1	3.50
802.11g	SISO	2412	1	-4.19
		2437	1	-3.38
		2462	1	-3.71
802.11n (HT20)	SISO	2412	1	-4.06
		2437	1	-3.08
		2462	1	-3.09
802.11n (HT40)	SISO	2422	1	-6.45
		2437	1	-5.86
		2452	1	-5.62

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.


5.1.2 Test Graph







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV












5.2 CSE



5.2.1 Test Result



Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	1	3.66	-16.34	Pass
		2437	1	3.66	-16.34	Pass
		2462	1	3.66	-16.34	Pass
802.11g	SISO	2412	1	-3.38	-23.38	Pass
		2437	1	-3.38	-23.38	Pass
		2462	1	-3.38	-23.38	Pass
802.11n (HT20)	SISO	2412	1	-3.08	-23.08	Pass
		2437	1	-3.08	-23.08	Pass
		2462	1	-3.08	-23.08	Pass
802.11n (HT40)	SISO	2422	1	-5.62	-25.62	Pass
		2437	1	-5.62	-25.62	Pass
		2452	1	-5.62	-25.62	Pass



Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.

5.2.2 Test Graph















802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV















6. Form731

6.1 Form731

6.1.1 Test Result

Lower Freq (MHz)	High Freq (MHz)	MAX Power (W)	MAX Power (dBm)
2412	2462	0.0432	16.35
2422	2452	0.0429	16.32



Test Report Number: BTF231127R00403



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

-- END OF REPORT --