

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2ANN4-AFM201T

### EUT Specification

EUT	WIFI+BLE4.2 Module
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others: BLE: 2402-2480MHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	WiFi: 16.74 dBm (0.0472W) BLE: 6.221 dBm (0.0042W)
<b>Antenna gain (Max)</b>	WiFi: 1.3 dBi BLE: 1.3 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in  $\text{mW/cm}^2$

$P_{out}$ =output power to antenna in  $\text{mW}$

$G$ = gain of antenna in linear scale

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in  $\text{cm}$

$P_d$  the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Operating Mode	Channel Frequency (MHz)	Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm ( $\text{mW/cm}^2$ )	Power density Limits ( $\text{mW/cm}^2$ )
802.11b	2412	16.37	16.37±1	17.37	1.3	0.0146	1
	2437	16.74	16.74±1	17.74	1.3	0.0159	1
	2462	16.73	16.73±1	17.73	1.3	0.0159	1
802.11g	2412	14.46	14.46±1	15.46	1.3	0.0094	1
	2437	14.78	14.78±1	15.78	1.3	0.0102	1
	2462	14.90	14.90±1	15.90	1.3	0.0104	1
802.11n (HT20)	2412	14.34	14.34±1	15.34	1.3	0.0092	1
	2437	14.74	14.74±1	15.74	1.3	0.0101	1
	2462	14.93	14.93±1	15.93	1.3	0.0105	1
BLE	2402	6.173	6.173±1	7.173	1.3	0.0014	1
	2440	6.221	6.221±1	7.221	1.3	0.0014	1
	2480	5.801	5.801±1	6.801	1.3	0.0013	1

**Note: WIFI 2.4G and 4.2 BLE cannot be transmitted simultaneously**