

FCC Radio Test Report

FCC ID: 2ANNWAN-H310C

Original Grant

Report No. : TB-FCC156053

Applicant : Shenzhen Annidigital Technology Co., Ltd

Equipment Under Test (EUT)

EUT Name : IP Camera

Model No. : AN-H310C

Series Model No. : Please see the page 4

Brand Name : anni

Receipt Date : 2017-06-15

Test Date : 2017-06-16 to 2017-06-25

Issue Date : 2017-06-26

Standards : FCC Part 15, Subpart C (15.247:2016)

Test Method : ANSI C63.10: 2013

Conclusions : PASS

In the configuration tested, the EUT complied with the standards specified above,

The EUT technically complies with the FCC and IC requirements

Test/Witness Engineer : IVAN SV

**Approved&
Authorized**



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	5
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	7
1.8 Test Facility.....	8
2. TEST SUMMARY.....	9
3. TEST EQUIPMENT.....	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode	12
4.5 Test Data.....	12
5. RADIATED EMISSION TEST	17
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition	19
5.5 Test Data.....	20
6. RESTRICTED BANDS REQUIREMENT	47
6.1 Test Standard and Limit.....	47
6.2 Test Setup.....	47
6.3 Test Procedure.....	47
6.4 EUT Operating Condition	48
6.5 Test Data.....	48
7. BANDWIDTH TEST.....	69
7.1 Test Standard and Limit.....	69
7.2 Test Setup.....	69
7.3 Test Procedure.....	69
7.4 EUT Operating Condition	69
7.5 Test Data.....	70
8. PEAK OUTPUT POWER TEST.....	78
8.1 Test Standard and Limit.....	78
8.2 Test Setup.....	78

8.3 Test Procedure.....	78
8.4 EUT Operating Condition	78
8.5 Test Data.....	79
9. POWER SPECTRAL DENSITY TEST	82
9.1 Test Standard and Limit.....	82
9.2 Test Setup.....	82
9.3 Test Procedure.....	82
9.4 EUT Operating Condition	82
9.5 Test Data.....	83
10. ANTENNA REQUIREMENT.....	91
10.1 Standard Requirement.....	91
10.2 Antenna Connected Construction	91

1. General Information about EUT

1.1 Client Information

Applicant : Shenzhen Annidigital Technology Co., Ltd
Address : 3rd Floor, Hasee Bldg, NO.1, Banlan Road, Bantian, Buji Town, Longgang, Shenzhen, China
Manufacturer : Shenzhen Annidigital Technology Co., Ltd
Address : 3rd Floor, Hasee Bldg, NO.1, Banlan Road, Bantian, Buji Town, Longgang, Shenzhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	IP Camera
Models No.	:	AN-H310C, AN-H310X, AN-H310X-XX, AN-HXXXX, AN-HXXXX-XX ("X" dedicated to A to Z and/or 0 to 999 up to 10 digits)
Model Difference	:	All models are identical in the same PCB layout interior structure and electrical circuits, The only difference is pixel.
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels <small>see note(3)</small> 802.11n(HT40):7 channels <small>see note(3)</small>
	RF Output Power:	802.11b: 17.45dBm 802.11g: 18.23dBm 802.11n (HT20): 16.72dBm 802.11n (HT40): 15.62dBm
	Antenna Gain:	4dBi PFC Antenna
	Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
Power Supply	:	DC Voltage supplied by AC/DC Adapter.
Power Rating	:	AC/DC Adapter (KSD200): Input: AC 110~240V, 50/60Hz, 0.3A. Output: DC 5V, 2A.
Connecting I/O Port(S)	:	Please refer to the User's Manual

Note:

- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v04.

(2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(3) Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

Note: CH 01~CH 11 for 802.11b/g/n(HT20), CH 03~CH 09 for 802.11n(HT40)


(4) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

Normal Working Mode



TX Mode



1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used "√"
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	NO	NO	1M	

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Normal Working with TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11
Mode 5	TX Mode N(HT40) Mode Channel 03/06/09

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, Middle, lowest available channels, and the worst case data rate as follows:

802.11b Mode: CCK (1 Mbps)
802.11g Mode: OFDM (6 Mbps)
802.11n (HT20) Mode: MCS 0 (6.5 Mbps)
802.11n (HT40) Mode: MCS 0 (13 Mbps)

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
(3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel&Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	MT7601USB.exe		
Channel	CH 01	CH 06	CH 11
IEEE 802.11b DSSS	DEF	DEF	DEF
IEEE 802.11g OFDM	DEF	DEF	DEF
IEEE 802.11n (HT20)	DEF	DEF	DEF
Channel	CH 03	CH 06	CH 09
IEEE 802.11n (HT40)	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(d)& 15.209	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A

Note: "/" for no requirement for this test item.
N/A is an abbreviation for Not Applicable.

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 21, 2016	Jul. 20, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 21, 2016	Jul. 20, 2017
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 21, 2016	Jul. 20, 2017
LISN	Rohde & Schwarz	ENV216	101131	Jul. 21, 2016	Jul. 20, 2017
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 21, 2016	Jul. 20, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 21, 2016	Jul. 20, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.25, 2017	Mar. 24, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.24, 2017	Mar. 23, 2018
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.24, 2017	Mar. 23, 2018
Loop Antenna	Laplace instrument	RF300	0701	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	Sonoma	310N	185903	Mar.25, 2017	Mar. 24, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar.24, 2017	Mar. 23, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.25, 2017	Mar. 24, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 21, 2016	Jul. 20, 2017
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 21, 2016	Jul. 20, 2017
Power Meter	Anritsu	ML2495A	25406005	Jul. 21, 2016	Jul. 20, 2017
Power Sensor	Anritsu	ML2411B	25406005	Jul. 21, 2016	Jul. 20, 2017

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC Part 15.207

4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please see the next page.


EUT:	IP Camera	Model Name :	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	Normal Working with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit dBuV	Over dB	Over Detector
			Level dBuV	Factor dB	ment dBuV			
1		0.2500	30.65	10.02	40.67	61.75	-21.08	QP
2		0.2500	18.28	10.02	28.30	51.75	-23.45	AVG
3		0.4620	26.13	10.02	36.15	56.66	-20.51	QP
4		0.4620	11.52	10.02	21.54	46.66	-25.12	AVG
5		1.1420	29.38	10.06	39.44	56.00	-16.56	QP
6		1.1420	11.50	10.06	21.56	46.00	-24.44	AVG
7		1.3220	31.60	10.06	41.66	56.00	-14.34	QP
8		1.3220	11.04	10.06	21.10	46.00	-24.90	AVG
9 *		1.3860	32.89	10.06	42.95	56.00	-13.05	QP
10		1.3860	12.32	10.06	22.38	46.00	-23.62	AVG
11		5.2460	30.28	9.97	40.25	60.00	-19.75	QP
12		5.2460	17.28	9.97	27.25	50.00	-22.75	AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model Name :	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Neutral		
Test Mode:	Normal Working with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Over Detector
1		0.4660	27.31	10.03	37.34	56.58	-19.24	QP
2		0.4660	11.71	10.03	21.74	46.58	-24.84	AVG
3		0.9420	29.20	10.13	39.33	56.00	-16.67	QP
4		0.9420	12.78	10.13	22.91	46.00	-23.09	AVG
5		1.0060	30.62	10.16	40.78	56.00	-15.22	QP
6		1.0060	12.26	10.16	22.42	46.00	-23.58	AVG
7		1.2020	32.86	10.14	43.00	56.00	-13.00	QP
8		1.2020	13.49	10.14	23.63	46.00	-22.37	AVG
9		1.6019	35.90	10.10	46.00	56.00	-10.00	QP
10		1.6019	16.17	10.10	26.27	46.00	-19.73	AVG
11	*	1.7820	36.70	10.08	46.78	56.00	-9.22	QP
12		1.7820	15.39	10.08	25.47	46.00	-20.53	AVG


Emission Level= Read Level+ Correct Factor

EUT:	IP Camera	Model Name :	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Line		
Test Mode:	Normal Working with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit dBuV	Over dB	Over Detector
			Level dBuV	Factor dB	ment dBuV			
1		0.2060	33.84	10.02	43.86	63.36	-19.50	QP
2		0.2060	26.03	10.02	36.05	53.36	-17.31	AVG
3		0.8420	27.39	10.09	37.48	56.00	-18.52	QP
4		0.8420	13.98	10.09	24.07	46.00	-21.93	AVG
5		1.6740	28.08	10.06	38.14	56.00	-17.86	QP
6		1.6740	14.37	10.06	24.43	46.00	-21.57	AVG
7	*	2.6060	32.12	10.04	42.16	56.00	-13.84	QP
8		2.6060	18.02	10.04	28.06	46.00	-17.94	AVG
9		4.0700	31.45	9.99	41.44	56.00	-14.56	QP
10		4.0700	17.57	9.99	27.56	46.00	-18.44	AVG
11		4.6820	29.90	9.97	39.87	56.00	-16.13	QP
12		4.6820	13.37	9.97	23.34	46.00	-22.66	AVG

Emission Level= Read Level+ Correct Factor



5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard
FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)


5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		297.2241	50.60	-16.34	34.26	46.00	-11.74 QP
2		300.3672	49.72	-16.27	33.45	46.00	-12.55 QP
3		400.4319	47.26	-11.99	35.27	46.00	-10.73 QP
4	*	451.1350	55.33	-11.60	43.73	46.00	-2.27 QP
5		550.9480	44.95	-9.25	35.70	46.00	-10.30 QP
6	!	651.9417	47.69	-7.66	40.03	46.00	-5.97 QP


*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor



Above 1GHz


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.654	30.09	13.56	43.65	54.00	-10.35	AVG
2		4824.021	42.86	13.56	56.42	74.00	-17.58	peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit dBuV/m	Over Detector
			Level dBuV	Factor dB/m	ment dBuV/m		
1	*	4823.897	30.19	13.56	43.75	54.00	-10.25 AVG
2		4824.652	42.33	13.56	55.89	74.00	-18.11 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4873.899	42.73	13.86	56.59	74.00	-17.41 peak
2	*	4874.065	31.76	13.86	45.62	54.00	-8.38 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4873.584	43.83	13.86	57.69	74.00	-16.31 peak
2	*	4874.254	32.46	13.86	46.32	54.00	-7.68 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4923.514	31.97	14.15	46.12	54.00	-7.88 AVG
2		4924.021	44.08	14.15	58.23	74.00	-15.77 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4923.987	43.97	14.15	58.12	74.00	-15.88 peak
2	*	4924.354	32.06	14.15	46.21	54.00	-7.79 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4823.687	30.12	13.56	43.68	54.00	-10.32 AVG
2		4824.556	41.52	13.56	55.08	74.00	-18.92 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4823.654	43.42	13.56	56.98	74.00	-17.02 peak
2	*	4824.622	31.02	13.56	44.58	54.00	-9.42 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4873.854	30.37	13.86	44.23	54.00	-9.77 AVG
2		4874.685	42.35	13.86	56.21	74.00	-17.79 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4873.735	43.01	13.86	56.87	74.00	-17.13 peak
2	*	4874.035	30.39	13.86	44.25	54.00	-9.75 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		4923.608	42.39	14.15	56.54	74.00	-17.46 peak
2	*	4923.987	30.74	14.15	44.89	54.00	-9.11 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4923.574	44.18	14.15	58.33	74.00	-15.67 peak
2	*	4923.621	30.89	14.15	45.04	54.00	-8.96 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4823.587	32.08	13.56	45.64	54.00	-8.36 AVG
2		4824.351	43.69	13.56	57.25	74.00	-16.75 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4823.684	44.09	13.56	57.65	74.00	-16.35 peak
2	*	4824.521	30.41	13.56	43.97	54.00	-10.03 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4873.608	30.35	13.86	44.21	54.00	-9.79 AVG
2		4874.621	43.40	13.86	57.26	74.00	-16.74 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.985	30.01	13.86	43.87	54.00	-10.13	AVG
2		4874.025	43.52	13.86	57.38	74.00	-16.62	peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4923.854	30.44	14.15	44.59	54.00	-9.41 AVG
2		4924.341	42.74	14.15	56.89	74.00	-17.11 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4923.874	29.92	14.15	44.07	54.00	-9.93 AVG
2		4924.084	43.20	14.15	57.35	74.00	-16.65 peak

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4844.054	43.64	13.68	57.32	74.00	-16.68 peak
2	*	4844.321	29.90	13.68	43.58	54.00	-10.42 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4843.956	43.19	13.68	56.87	74.00	-17.13 peak
2	*	4844.221	30.19	13.68	43.87	54.00	-10.13 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4873.691	43.12	13.86	56.98	74.00	-17.02 peak
2	*	4874.674	30.02	13.86	43.88	54.00	-10.12 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4873.984	43.01	13.86	56.87	74.00	-17.13 peak
2	*	4874.521	29.81	13.86	43.67	54.00	-10.33 AVG

Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4903.574	29.84	14.03	43.87	54.00	-10.13 AVG
2		4904.054	42.95	14.03	56.98	74.00	-17.02 peak

Emission Level= Read Level+ Correct Factor

EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4903.841	29.65	14.03	43.68	54.00	-10.32 AVG
2		4904.671	43.91	14.03	57.94	74.00	-16.06 peak

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.247(d)


FCC Part 15.209

FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please see the next page.

(1) Radiation Test


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	43.61	0.77	44.38	74.00	-29.62	peak
2		2390.000	32.36	0.77	33.13	54.00	-20.87	AVG
3	*	2412.800	90.88	0.86	91.74	Fundamental Frequency		AVG
4	X	2413.000	96.49	0.86	97.35	Fundamental Frequency		peak


Emission Level= Read Level+ Correct Factor


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		





No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		2390.000	44.25	0.77	45.02	74.00	-28.98 peak
2		2390.000	32.36	0.77	33.13	54.00	-20.87 AVG
3	*	2412.800	90.33	0.86	91.19	Fundamental Frequency	AVG
4	X	2413.100	95.55	0.86	96.41	Fundamental Frequency	peak


Emission Level= Read Level+ Correct Factor













EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	X	2459.000	97.74	1.06	98.80	Fundamental Frequency	peak
2	*	2465.200	86.99	1.09	88.08	Fundamental Frequency	Avg
3		2483.500	46.47	1.17	47.64	74.00	-26.36 peak
4		2483.500	34.86	1.17	36.03	54.00	-17.97 Avg

Emission Level= Read Level+ Correct Factor




EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		2390.000	49.49	0.77	50.26	74.00	-23.74 peak
2		2390.000	34.20	0.77	34.97	54.00	-19.03 AVG
3	*	2417.400	85.25	0.89	86.14	Fundamental Frequency	AVG
4	X	2419.400	95.11	0.89	96.00	Fundamental Frequency	peak

Emission Level= Read Level+ Correct Factor





EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	X	2459.000	97.74	1.06	98.80	Fundamental Frequency	1 peak
2	*	2465.200	86.99	1.09	88.08	Fundamental Frequency	1 AVG
3		2483.500	46.47	1.17	47.64	74.00	-26.36 peak
4		2483.500	34.86	1.17	36.03	54.00	-17.97 AVG

Emission Level= Read Level+ Correct Factor













(2) Conducted Test

EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		







EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT40) Mode 2422MHz / TX N(HT40) Mode 2452MHz		
Remark:	The EUT is programed in continuously transmitting mode		




7. Bandwidth Test

7.1 Test Standard and Limit

- 7.1.1 Test Standard
FCC Part 15.247 (a)(2)
- 7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	>=500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup




7.3 Test Procedure



- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.


7.4 EUT Operating Condition



The EUT was set to continuously transmitting in each mode and low, Digital photo framesle and high channel for the test.


7.5 Test Data



802.11B Mode**2437 MHz****802.11B Mode****2462 MHz**


EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11G Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.550	16.4050	>=0.5
2437	16.568	16.4188	
2462	16.563	16.4202	
802.11G Mode			
2412 MHz			
 <p>Agilent 16:51:39 Jun 22, 2017</p> <p>Ch Freq 2.412 GHz Occupied Bandwidth Center 2.412000000 GHz</p> <p>Ref 20 dBm Atten 30 dB</p> <p>Log 10 dB/Offst 1 dB</p> <p>Center 2.412 GHz #Res BW 100 kHz Span 25 MHz</p> <p>#VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 16.4050 MHz</p> <p>Transmit Freq Error 2.646 kHz</p> <p>x dB Bandwidth 16.550 MHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -6.00 dB</p>			
<p>Freq/Channel</p> <p>Center Freq 2.412000000 GHz</p> <p>Start Freq 2.399500000 GHz</p> <p>Stop Freq 2.424500000 GHz</p> <p>CF Step 2.50000000 MHz</p> <p>Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>			

802.11G Mode**2437 MHz****802.11G Mode****2462 MHz**




802.11N(HT20) Mode


2437 MHz



802.11N(HT20) Mode


2462 MHz






802.11N(HT40) Mode

2437 MHz



802.11N(HT40) Mode

2452 MHz




8. Peak Output Power Test

8.1 Test Standard and Limit

- 8.1.1 Test Standard
FCC Part 15.247 (b)
- 8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v04. The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

8.4 EUT Operating Condition


The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data

EUT:	IP Camera	Model:	AN-H310C
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	16.31	30
	2437	16.80	
	2462	17.45	
802.11g	2412	16.93	30
	2437	17.69	
	2462	18.23	
802.11n (HT20)	2412	15.24	30
	2437	16.18	
	2462	16.72	
802.11n (HT40)	2422	14.82	30
	2437	15.29	
	2452	15.62	
Result: PASS			

Duty Cycle		
Mode	Channel frequency (MHz)	Test Result
802.11b	2412	>98%
	2437	
	2462	
802.11g	2412	>98%
	2437	
	2462	
802.11n (HT20)	2412	>98%
	2437	
	2462	
802.11n (HT40)	2422	>98%
	2437	
	2452	
Please see below plots		

802.11 B Mode 2437 MHz



Peak Search

Meas Tools

Next Peak

Next Pk Right


Next Pk Left

Min Search

Pk-Pk Search

More
1 of 2

802.11 G Mode 2437 MHz



Peak Search

Meas Tools

Next Peak

Next Pk Right


Next Pk Left

Min Search

Pk-Pk Search


More
1 of 2

802.11 N(HT20) Mode 2437 MHz



Peak Search
Meas Tools
Next Peak
Next Pk Right
Next Pk Left
Min Search
Pk-Pk Search
More 1 of 2

802.11 N(HT40) Mode 2437 MHz



Peak Search
Meas Tools
Next Peak
Next Pk Right
Next Pk Left
Min Search
Pk-Pk Search
More 1 of 2


9. Power Spectral Density Test

9.1 Test Standard and Limit

- 9.1.1 Test Standard
FCC Part 15.247 (e)
- 9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure


The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v04.


- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.


9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

9.5 Test Data









802.11G Mode


2437 MHz



802.11G Mode


2462 MHz






802.11N(HT20) Mode


2437 MHz



802.11N(HT20) Mode

2462 MHz




EUT:	IP Camera	Model:	AN-H310C		
Temperature:	25 °C	Temperature:	25 °C		
Test Voltage:	AC 120V/60HZ				
Test Mode:	TX 802.11N(HT40) Mode				
Channel Frequency (MHz)	Power Density (dBm/3 kHz)	Limit (dBm)			
2422	-17.74	8			
2437	-18.39				
2452	-18.62				
802.11N(HT40) Mode					
2422 MHz					
					

- Peak Search
- Meas Tools▶
- Next Peak
- Next Pk Right
- Next Pk Left
- Min Search
- Pk-Pk Search
- More 1 of 2


802.11N(HT40) Mode

2437 MHz



802.11N(HT40) Mode

2452 MHz



10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 4dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a FPC Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

-----END OF REPORT-----