

FCC Test Report

Applicant : **RNG International Inc.**

Address : **5050 S Archibald Ave, Ontario, California,
91762, United States**

Product Name : **Phoenix 500 Portable Power Station**

Report Date : **Jul. 05, 2023**



Shenzhen Anbotek Compliance Laboratory Limited

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotek.com.cn



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Configuration	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
2. Summary of Test Results	10
3. Conducted Emission Test	11
3.1. Test Standard and Limit	11
3.2. Test Setup	11
3.3. Test Procedure	11
3.4. Test Data	11
4. Radiation Spurious Emission and Band Edge	14
4.1. Test Standard and Limit	14
4.2. Test Setup	14
4.3. Test Procedure	15
4.4. Test Data	16
5. Antenna Requirement	22
5.1. Test Standard and Requirement	22
5.2. Antenna Connected Construction	22
APPENDIX I -- TEST SETUP PHOTOGRAPH	23
APPENDIX II -- EXTERNAL PHOTOGRAPH	23
APPENDIX III -- INTERNAL PHOTOGRAPH	23



TEST REPORT

Applicant : RNG International Inc.
Manufacturer : RENOGY New Energy Co., Ltd
Product Name : Phoenix 500 Portable Power Station
Model No. : RPS5080AA-PCS
Trade Mark : Renogy
Rating(s) : Please see page 6

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2020, KDB558074 D01 DTS Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

May 17, 2023

Date of Test

May 17 ~Jun. 02, 2023

Prepared By

Nian xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue. (Note 1)	Jul. 05, 2023

Note 1:

This is a Class II application which was based on the original report 18220WC20170501. The difference between the original device and current one described as following:

1. Change the inverter.
2. Update External Photograph.

The changes are not related with the other RF parameters, only Conducted Emission and Radiated Emission were retested.



1. General Information

1.1. Client Information

Applicant	:	RNG International Inc.
Address	:	5050 S Archibald Ave, Ontario, California, 91762, United States
Manufacturer	:	RENOGY New Energy Co., Ltd
Address	:	Room 624-625, Taicang German Overseas Students Pioneer Park, 66 Ningbo East Road, Taicang Economic Development Zone, Jiangsu, China
Factory	:	Sunwoda Energy Solution Co., Ltd.
Address	:	Room 201, building C, Sunwoda electronics factory, Tangjia community, Fenghuang street, Guangming District, Shenzhen, Guangdong Province, China

1.2. Description of Device (EUT)

Product Name	:	Phoenix 500 Portable Power Station
Model No.	:	RPS5080AA-PCS
Trade Mark	:	Renogy
Test Power Supply	:	AC 120V, 60Hz/ DC 18V Battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Operation Mode	:	<input checked="" type="checkbox"/> BT BLE
Support Rate	:	<input checked="" type="checkbox"/> 1Mbps <input type="checkbox"/> 2Mbps
Operation Frequency	:	2402~2480MHZ
Number of Channel	:	40 Channels
Modulation Type	:	GFSK
Antenna Type	:	PCB antenna
Antenna Gain(Peak)	:	3.4dBi (Provided by customer)
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



Rating:

Battery Capacity: 18V, 27500mAh/495Wh

DC Input: 10V-50V= 10A, 200W Max

AC Input: 85V-120V (JP)/90V-140V (US,CA)/200V-240V (EU, UK, AU, KR,

CN)~45Hz-55Hz/57Hz-65Hz, 495W Max

USB-A Output: 5V= 2.4A, 12W Max

USB-A Fast Charge Output: 5V= 3A, 9V= 2A 12V= 1.5A, 18W Max

USB-C Output: 5V= 3A, 9V= 3A, 12V= 3A, 15V= 3A, 20V= 5A, 100W Max

CIG Output: 13.6V= 10A 136W Max

AC Output: 100V (JP)/120V (US, CA)/220V-240V (EU, UK, AU, KR, CN)~50Hz/60Hz, 800W Rated, 1600W Surge

Total Output: 1050W Max

1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--

1.4. Description of Test Configuration



Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 0, 19 and 39.



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2022	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G-45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 23, 2022	1 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 19, 2022	1 Year
19.	Power Meter	Agilent	N1914A	MY50001102	Oct.26, 2022	1 Year



1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
	:	Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
5MHz~30MHz	60	50	

Remark:(1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: Low CH (2402MHz)
 Test Specification: AC 120V, 60Hz
 Comment: Live Line
 Temp.(°C)/Hum.(%RH): 22.5°C/49%RH




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	0.1500	46.73	9.82	56.55	65.99	-9.44	QP	
2	0.1500	41.22	9.82	51.04	55.99	-4.95	AVG	
3	0.1819	32.54	9.83	42.37	54.39	-12.02	AVG	
4	0.5540	21.67	9.86	31.53	46.00	-14.47	AVG	
5	0.7180	30.51	9.87	40.38	56.00	-15.62	QP	
6	0.7380	21.76	9.87	31.63	46.00	-14.37	AVG	
7	0.7460	29.10	9.87	38.97	56.00	-17.03	QP	
8	2.2500	32.03	9.83	41.86	56.00	-14.14	QP	
9	3.8540	34.30	9.85	44.15	56.00	-11.85	QP	
10	4.5540	21.23	9.85	31.08	46.00	-14.92	AVG	
11	4.7220	23.56	9.85	33.41	46.00	-12.59	AVG	
12	4.8780	31.98	9.85	41.83	56.00	-14.17	QP	



Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: Low CH (2402MHz)
 Test Specification: AC 120V, 60Hz
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 22.5°C/49%RH



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	0.1500	44.00	9.82	53.82	65.99	-12.17	QP	
2	0.1500	38.49	9.82	48.31	55.99	-7.68	AVG	
3	0.1660	41.35	9.83	51.18	65.15	-13.97	QP	
4	0.1660	39.85	9.83	49.68	55.15	-5.47	AVG	
5	0.7420	30.14	9.87	40.01	56.00	-15.99	QP	
6	0.7420	23.54	9.87	33.41	46.00	-12.59	AVG	
7	3.6820	33.84	9.85	43.69	56.00	-12.31	QP	
8	3.7900	22.18	9.85	32.03	46.00	-13.97	AVG	
9	4.8940	33.42	9.85	43.27	56.00	-12.73	QP	
10	4.9220	22.18	9.85	32.03	46.00	-13.97	AVG	
11	9.5620	32.72	9.96	42.68	50.00	-7.32	AVG	
12	9.6300	40.44	9.97	50.41	60.00	-9.59	QP	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		74.0	Peak	3	

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

–VBW=10Hz, When duty cycle is no less than 98 percent

–VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.



Test Results (30~1000MHz)

Test Mode: Low CH (2402MHz)
 Power Source: DC 18V Battery inside
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 23.5°C/48%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	46.6664	44.34	-17.07	27.27	40.00	-12.73	peak			
2	64.4331	47.84	-19.45	28.39	40.00	-11.61	peak			
3	114.5146	56.07	-18.84	37.23	43.50	-6.27	peak			
4	121.9755	55.46	-19.81	35.65	43.50	-7.85	peak			
5	570.6100	39.56	-8.94	30.62	46.00	-15.38	peak			
6	833.3171	38.43	-5.42	33.01	46.00	-12.99	peak			



Test Results (30~1000MHz)

Test Mode: Low CH (2402MHz)
 Power Source: DC 18V Battery inside
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 23.5°C/48%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.8446	47.53	-16.88	30.65	40.00	-9.35	QP			
2	48.6945	51.39	-17.13	34.26	40.00	-5.74	QP			
3	59.6493	52.43	-17.68	34.75	40.00	-5.25	QP			
4	128.1130	57.91	-20.57	37.34	43.50	-6.16	QP			
5	157.0074	55.35	-20.70	34.65	43.50	-8.85	QP			
6	413.2706	45.53	-12.17	33.36	46.00	-12.64	QP			



Test Results (1GHz-25GHz)

Test Mode: CH00				Test channel: Lowest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	27.66	15.27	42.93	74.00	-31.07	Vertical
7206.00	27.86	18.09	45.95	74.00	-28.05	Vertical
9608.00	28.44	23.76	52.20	74.00	-21.80	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	27.39	15.27	42.66	74.00	-31.34	Horizontal
7206.00	28.09	18.09	46.18	74.00	-27.82	Horizontal
9608.00	27.77	23.76	51.53	74.00	-22.47	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	15.93	15.27	31.20	54.00	-22.80	Vertical
7206.00	16.91	18.09	35.00	54.00	-19.00	Vertical
9608.00	17.91	23.76	41.67	54.00	-12.33	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	15.72	15.27	30.99	54.00	-23.01	Horizontal
7206.00	17.12	18.09	35.21	54.00	-18.79	Horizontal
9608.00	17.28	23.76	41.04	54.00	-12.96	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH19				Test channel: Middle		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	27.21	15.42	42.63	74.00	-31.37	Vertical
7320.00	27.83	18.02	45.85	74.00	-28.15	Vertical
9760.00	27.94	23.80	51.74	74.00	-22.26	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	27.20	15.42	42.62	74.00	-31.38	Horizontal
7320.00	27.96	18.02	45.98	74.00	-28.02	Horizontal
9760.00	27.49	23.80	51.29	74.00	-22.71	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	16.02	15.42	31.44	54.00	-22.56	polarization
7320.00	16.77	18.02	34.79	54.00	-19.21	Vertical
9760.00	17.76	23.80	41.56	54.00	-12.44	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	15.83	15.42	31.25	54.00	-22.75	Vertical
7320.00	17.47	18.02	35.49	54.00	-18.51	Horizontal
9760.00	17.58	23.80	41.38	54.00	-12.62	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH39				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	27.34	15.58	42.92	74.00	-31.08	Vertical
7440.00	27.99	17.93	45.92	74.00	-28.08	Vertical
9920.00	28.64	23.83	52.47	74.00	-21.53	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	27.34	15.58	42.92	74.00	-31.08	Horizontal
7440.00	28.17	17.93	46.10	74.00	-27.90	Horizontal
9920.00	27.87	23.83	51.70	74.00	-22.30	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	17.14	15.58	32.72	54.00	-21.28	Vertical
7440.00	18.04	17.93	35.97	54.00	-18.03	Vertical
9920.00	18.41	23.83	42.24	54.00	-11.76	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	17.01	15.58	32.59	54.00	-21.41	Horizontal
7440.00	18.27	17.93	36.20	54.00	-17.80	Horizontal
9920.00	17.73	23.83	41.56	54.00	-12.44	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1.Result =Reading + Factor

2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



5. Antenna Requirement

5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

5.2. Antenna Connected Construction

The antenna is a **PCB antenna** which permanently attached, and the best case gain of the antenna is 3.4dBi . It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

