

# FCC Test Report

## (Part 90)

Product Name : nRF9160 IOT Module  
Model No : nRF9160  
FCC ID : 2ANPO00NRF9160

Applicant : NORDIC SEMICONDUCTOR ASA

Address : Otto Niensens Vei 12, 7052 Trondheim, Norway

Date of Receipt : 2019/04/01  
Issued Date : 2019/05/28  
Report No. : 1940010R-HPUSP56V00  
Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

# Test Report

Issued Date : 2019/05/28

Report No.: 1940010R-HPUSP56V00



Product Name : nRF9160 IOT Module  
Applicant : NORDIC SEMICONDUCTOR ASA  
Address : Otto Nielsens Vei 12, 7052 Trondheim, Norway  
Manufacturer : NORDIC SEMICONDUCTOR ASA  
Trade Name : nRF91  
Model No. : nRF9160  
EUT Rated Voltage : DC 3.1V-5.5V  
EUT Test Voltage : DC 5V (Power by NB USB Port)  
Measurement Standard : FCC CFR Title 47 Part2 90  
Measurement Reference : TIA/EIA 603-E 2016  
KDB 971168 D01V03  
ANSI C63.26 2015  
Test Result : Complied

Documented By : Anny Chou  
( Senior Adm. Specialist / Anny Chou )

Tested By : Vorana Chen  
( Senior Engineer / Vorana Chen )

Approved By :   
( Director / Vincent Lin )

## TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION .....	4
1.1. EUT Description .....	4
1.2. Antenna List .....	4
1.3. Operational Description .....	5
1.4. Configuration of tested System .....	6
1.5. EUT Setup Procedures .....	6
1.6. Test Facility .....	7
1.7. Type of Emission .....	8
1.8. Voltages and AC currents .....	8
2. Technical Test .....	9
2.1. Summary of test result .....	9
2.2. List of test Equipment .....	10
2.3. Measurement Uncertainty .....	10
3. Conducted Output Power Measurement .....	11
3.1. Test Specification .....	11
3.2. Test Setup .....	11
3.3. Limits .....	11
3.4. Test Procedure .....	11
3.5. Test Result of Maximum Power Output .....	12
3.6. Maximum Conducted Power and ERP/EIRP Power .....	13
4. Occupied Bandwidth .....	14
4.1. Test Specification .....	14
4.2. Test Setup .....	14
4.3. Test Procedure .....	14
4.4. Test Result of Occupied Bandwidth .....	15
5. Spurious Emission At Antenna Terminals (+/-1MHz) .....	20
5.1. Test Specification .....	20
5.2. Setup .....	20
5.3. Limits .....	20
5.4. Test Procedure .....	20
5.5. Test Result of Spurious Emission At Antenna Terminals (+/-1MHz) .....	21
6. Spurious Emission .....	29
6.1. Test Specification .....	29
6.2. Test Setup .....	29
6.3. Limits .....	30
6.4. Test Procedure .....	30
6.5. Test Result of Spurious Emission .....	31
7. Frequency Stability Under Temperature & Voltage Variations .....	63
7.1. Test Specification .....	63
7.2. Test Setup .....	63
7.3. Limits .....	63
7.4. Test Procedure .....	63
7.5. Test Result of Frequency Stability Under Temperature Variations .....	64
Attachment 1: EUT Test Photographs	
Attachment 2: EUT Detailed Photographs	

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	nRF9160 IOT Module
Model No.	nRF9160
Trade Name	nRF91
IMEI No.	35265610
FCC ID	2ANPO00NRF9160
Modulation	LTE Band 14: QPSK/16-QAM
TX Frequency	LTE Band 14: 788~798MHz
Rx Frequency	LTE Band 14: 758~768MHz
Bandwidth	LTE Band 14: 5MHz/10MHz
HW Version	DEV2.1.6
SW Version	mfwRD-m1_nrf9160_0.6.7-31.prealpha
Antenna Type	IMD Antenna

### 1.2. Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	Ethertronics	P822601	2.6 dBi for 698-960 MHz

### 1.3. Operational Description

The information contained within this report is intended to show verification of compliance of the 850MHz to the requirements of FCC 47 CFR Part 2, 90.

The EUT provide all functions described as above. The EUT is tested with maximum rated TX power via the Base Station simulator.

DEKRA has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined

as:


Test Mode:	LTE Band 14 (5M)-QPSK/16QAM
	LTE Band 14 (10M)-QPSK/16QAM

Note :


The maximum power levels are chosen in the LTE Band 14, only these modes were used for all tests.

## 1.4. Configuration of tested System

### (a) Configuration of Radiated measurement



### (b) Configuration of Conducted measurement



## 1.5. EUT Setup Procedures

- (1) Setup the EUT and simulators as shown on 1.3
- (2) Turn on the power of all equipments.
- (3) The EUT was set to communicate with MT8820C.
- (4) Repeat the above procedure (3).

## 1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	23.1
Humidity (%RH)	25-75	52
Barometric pressure (mbar)	860-1060	988

The related certificate for our laboratories about the test site and management system can be downloaded from DEKRA Testing and Certification Co., Ltd. Web Site:

<http://www.dekra.com.tw/english/about/certificates.aspx?bval=5>

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our Web site: [http://www.dekra.com.tw/index\\_en.aspx](http://www.dekra.com.tw/index_en.aspx)

Site Description: File on

Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046  
FCC Registration Number :92195

Site Name: DEKRA Testing and Certification Co., Ltd

Lin Kou Laboratory:

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451,  
Taiwan, R.O.C.  
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789  
E-Mail : [info.tw@dekra.com](mailto:info.tw@dekra.com)

FCC Accreditation Number: TW3023

### 1.7. Type of Emission

Band	Bandwidth (MHz)	TX Frequency (MHz)	Modulation	
			QPSK	16QAM
14	5	790.5	1M12G7D	0M98W7D
14	5	793	1M11G7D	0M97W7D
14	5	795.5	1M11G7D	0M95W7D
14	10	793	1M11G7D	0M97W7D

### 1.8. Voltages and DC currents

LTE Band 14 (5M)	EUT Transmitting (in maximum power) :	DC voltage : 3.8V , DC current : 0.14A
	EUT Standby	: DC voltage : 3.8V , DC current : 0.07A
LTE Band 14 (10M)	EUT Transmitting (in maximum power) :	DC voltage : 3.8V , DC current : 0.14A
	EUT Standby	: DC voltage : 3.8V , DC current : 0.07A



## 2. Technical Test

### 2.1. Summary of test result

FCC Standard	Test Item	Result	Note
2.1046	Conducted Output Power	Pass	
90.542			
2.1049	Occupied Bandwidth	Pass	
90.209			
2.1051	Spurious Emission at Antenna Terminals	Pass	
90.543			
2.1051	Conducted Emission	Pass	
90.543			
2.1053	Field Strength of Spurious Radiation	Pass	
90.543			
2.1055	Frequency Stability for Temperature & Voltage	Pass	
90.213			

## 2.2. List of test Equipment

Conducted /CTR

Instrument	Manufacturer	Type No.	Serial No	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY54510357	2018/05/03
Directional coupler	Agilent	87300C	MY44300353	2018/12/04
Directional coupler	Agilent	778D-012	50550	2018/12/04
Standard Temperature & Humidity Chamber	WIT	TH-1S-B	EQ-201-00146	2019/02/27
Communication Tester	Agilent	MT8820C	6201465467	2018/07/20

Radiated / Site3

Instrument	Manufacturer	Type No.	Serial No	Cal. Date
Bilog Antenna	Schaffner Chase	CBL6112B	2707	2018/06/24
Horn Antenna	R&S	9120D	556	2018/05/03
Pre-Amplifier	Agilent	87405C	MY55380068	2018/08/10
Spectrum Analyzer	Agilent	N9010A	MY54510357	2018/05/03
Communication Tester	Agilent	MT8820C	6201465467	2018/07/20

## 2.3. Measurement Uncertainty

### Conducted Emission

The measurement uncertainty of confidence of 95% is evaluated as  $\pm 1.52$  dB

### Radiated Emission (Below 1GHz)

The measurement uncertainty of confidence of 95% is evaluated as  $\pm 4.22$  dB .

### Radiated Emission (Above 1GHz)


The measurement uncertainty of confidence of 95% is evaluated as  $\pm 4.08$  dB

### 3. Conducted Output Power Measurement

#### 3.1. Test Specification

According to FCC Part 2.1046, 90.542

#### 3.2. Test Setup



#### 3.3. Limits

Band	Limit
LTE Band 14/800	<3W

#### 3.4. Test Procedure

The EUT is tested with maximum rated TX power via the Base Station simulator, and the output power was measured at the antenna terminals of the EUT.

### 3.5. Test Result of Maximum Power Output

Band	Frequency Channel	Modulation	Index	RB No.	RB offset	Max Power (dBm)	Max Power (W)
Band 14 (800MHz)/5MHz	CH23305 790.5MHz	QPSK	0	1	0	23.25	0.211
			0	1	5	23.31	0.214
			0	6	0	22.38	0.173
		16-QAM	0	1	0	<b>22.64</b>	<b>0.184</b>
			0	1	5	22.60	0.182
			0	5	0	21.63	0.146
			0	5	1	21.56	0.143
	CH23330 793MHz	QPSK	1	1	0	23.52	0.225
			1	1	5	<b>23.54</b>	<b>0.226</b>
			1	6	0	22.38	0.173
		16-QAM	1	1	0	22.08	0.161
			1	1	5	22.02	0.159
			1	5	0	21.37	0.137
			1	5	1	21.40	0.138
	CH23355 795.5MHz	QPSK	3	1	0	23.32	0.215
			3	1	5	23.25	0.211
			3	6	0	22.44	0.175
		16-QAM	3	1	0	22.48	0.177
			3	1	5	22.45	0.176
			3	5	0	21.42	0.139
			3	5	1	21.46	0.140

Band	Frequency Channel	Modulation	Index	RB No.	RB offset	Max Power (dBm)	Max Power (W)
Band 14 (800MHz)/10MHz	CH23330 793MHz	QPSK	0	1	0	23.43	0.220
			0	6	0	22.33	0.171
			3	6	0	22.31	0.170
			7	1	5	<b>23.46</b>	<b>0.222</b>
			7	6	0	22.36	0.172
		16-QAM	0	1	0	<b>22.54</b>	<b>0.179</b>
			0	5	0	22.53	0.179
			3	5	0	22.54	0.179
			7	1	5	22.40	0.174
			7	5	1	22.48	0.177

### 3.6. Maximum Conducted Power and ERP/EIRP Power

According to KDB 412172 D01 Section 1.2 Power Approach

$EIRP = P_T + G_T - L_C = ERP + 2.15 \text{ dB}$ ,  $ERP = EIRP - 2.15 \text{ dB}$

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB


LTE Band	BW	Modulation	Conducted Peak Power (dBm)	Conducted Peak Power (W)	Antenna Gain (dBi)	Maximum ERP (W)	Maximum ERP Limit (W)
14	5M	QPSK	23.54	0.226	2.6	0.251	3
		16QAM	22.64	0.184	2.6	0.204	3
	10M	QPSK	23.46	0.222	2.6	0.246	3
		16QAM	22.54	0.179	2.6	0.199	3

## 4. Occupied Bandwidth

### 4.1. Test Secification

According to FCC Part 2.1049, 90.209

### 4.2. Test Setup



### 4.3. Test Procedure

The EUT is tested with maximum rated TX power via the Base Station simulator, and the occupied bandwidth was measured at the antenna terminals of the EUT.

The Resolution BW of the analyzer is set to 1 %~5% of the emission bandwidth. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

The plots below show the resultant display from the Spectrum Analyser.


#### 4.4. Test Result of Occupied Bandwidth

Product	nRF9160 IOT Module
Test Mode	Occupied Bandwidth
Test Site	CTR


Test Mode	Channel	TX Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB bandwidth (MHz)	Result
Band 14 5M QPSK	23305	790.5	1.1191	1.459	Pass
Band 14 5M 16QAM	23305	790.5	0.9789	1.386	Pass
Band 14 5M QPSK	23330	793	1.1069	1.431	Pass
Band 14 5M 16QAM	23330	793	0.9652	1.327	Pass
Band 14 5M QPSK	23355	795.5	1.1149	1.416	Pass
Band 14 5M 16QAM	23355	795.5	0.9533	1.324	Pass
Band 14 10M QPSK	23330	793	1.1078	1.385	Pass
Band 14 10M 16QAM	23330	793	0.9684	1.323	Pass

Product	nRF9160 IOT Module		
Test Mode	Occupied Bandwidth		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 5M		

Band 14 5M QPSK - LTE Mode CH 23305 (790.5MHz)




Band 14 5M 16QAM - LTE Mode CH 23305 (790.5MHz)






Product	nRF9160 IOT Module		
Test Mode	Occupied Bandwidth		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 5M		

Band 14 5M QPSK - LTE Mode CH 23330 (793MHz)




Band 14 5M 16QAM - LTE Mode CH 23330 (793MHz)




Product	nRF9160 IOT Module		
Test Mode	Occupied Bandwidth		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 5M		

Band 14 5M QPSK - LTE Mode CH 23355 (795.5MHz)




Band 14 5M 16QAM - LTE Mode CH 23355 (795.5MHz)




Product	nRF9160 IOT Module		
Test Mode	Occupied Bandwidth		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 10M		

Band 14 10M QPSK - LTE Mode CH 23330 (793MHz)



Band 14 10M 16QAM - LTE Mode CH 23330 (793MHz)




## 5. Spurious Emission At Antenna Terminals (+/-1MHz)

### 5.1. Test Specification

According to Part 2.1051, 90.543

### 5.2. Setup



### 5.3. Limits

The spurious (unwanted) emission limits specified in the individual FCC rule parts applicable to licensed digital transmitters (typically referred to under the heading 'emission limits') normally apply to any and all emissions that are present outside of the authorized frequency band/block and apply to emissions in both the out-of-band and spurious domains. unwanted emissions are required by the licensed rule parts to be attenuated below the transmitter power by a factor of at least  $43 + 10\log(P)$  dB on any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, where P represents the transmitter power expressed in watts.

### 5.4. Test Procedure


In accordance with Part 90.543 (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $65 + 10 \log(P)$  dB in a 6.25 kHz band segment, for mobile and portable stations


### 5.5. Test Result of Spurious Emission At Antenna Terminals (+/-1MHz)

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission At Antenna Terminals (+/-1MHz)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Block Edge Test (Band 14 (5M))		


Band 14 (5M) QPSK Index0(1,0) Lower Channel 23305 (790.5MHz)




Band 14 (5M) QPSK Index3(1,5) Upper Channel 23355 (795.5MHz)




Band 14 (5M) QPSK Index0(6,0) Lower Channel 23305 (790.5MHz)




Band 14 (5M) QPSK Index3(6,0) Upper Channel 23335 (795.5MHz)



Band 14 (5M) 16QAM Index0(1,0) Lower Channel 23305 (790.5MHz)




Band 14 (5M) 16QAM Index3(1,5) Upper Channel 23355 (795.5MHz)






Band 14 (5M) 16QAM Index0(5,0) Lower Channel 23305 (790.5MHz)




Band 14 (5M) 16QAM Index3(5,1) Upper Channel 23355 (795.5MHz)






Product	nRF9160 IOT Module		
Test Mode	Spurious Emission At Antenna Terminals (+/-1MHz)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Block Edge Test (Band 14 (10M))		


Band 14 (10M) QPSK Index0(1,0) Lower Channel 23330 (793MHz)




Band 14 (10M) QPSK Index7(1,5) Upper Channel 23330 (793MHz)




Band 14 (10M) QPSK Index0(6,0) Lower Channel 23330 (793MHz)




Band 14 (10M) QPSK Index7(6,0) Upper Channel 23330 (793MHz)




### Band 14 (10M) 16QAM Index0(1,0) Lower Channel 23330 (793MHz)




### Band 14 (10M) 16QAM Index7(1,5) Upper Channel 23330 (793MHz)



### Band 14 (10M) 16QAM Index0(5,0) Lower Channel 23330 (793MHz)



### Band 14 (10M) 16QAM Index7(5,1) Upper Channel 23330 (793MHz)




## 6. Spurious Emission

### 6.1. Test Specification


According to Part 2.1051, 90.543

### 6.2. Test Setup

#### 6.2.1 Spurious emissions at antenna terminals.



#### 6.2.2 Field strength of spurious radiation.



Note: The Worst case Mode is QPSK Mode for Radiated spurious emissions.

### 6.3. Limits

<b>Limit</b>	<b>&lt;-13dBm</b>
--------------	-------------------

43 + 10Log(P) down on the carrier where P is the power in Watts.

### 6.4. Test Procedure

In accordance with Part 2.1051, 90.543, the spurious emissions from the antenna terminal were measured. The transmitter output power was attenuated using a combination of filters and attenuators and the frequency spectrum investigated from 30MHz to 10GHz. The EUT was set to transmit on full power. The EUT was tested on Low, middle and High channels for both power levels. The resolution and video bandwidth was set to 1MHz/3MHz in accordance with Part 2.1051, 90.543. The spectrum analyzer detector was set to Max Hold. In addition, measurements were made up to the 10<sup>th</sup> harmonic of the fundamental. The device was then replaced with a substitution antenna, which input signal was adjusted until the received level matched that of the previously detected emission.

- (1) The EUT is tested with maximum rated TX power via the Base Station simulator.
- (2) The EUT is tested in three orthogonal planes, The worst case was showing in this report.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to TIA/EIA 603-E on radiated measurement.


90.543(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.



### 6.5. Test Result of Spurious Emission

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Conducted)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	LTE-Band 14 (5M)	Test Range	30MHz~10GHz


#### LTE-Band 14 (5M) QPSK Index0 (1,5) CH23305 (790.5MHz)

Frequency (MHz)	Reading Level (dBm)	Path Loss (dB)	Emission Level (dBm)	Limit (dBm)
1579	-57.320	0.58	-56.740	-40
2368	-48.270	0.70	-47.570	-13
3157	-40.220	1.01	-39.210	-13
3946	-59.320	1.18	-58.140	-13
4735	-53.791	1.23	-52.561	-13
5525	-62.180	1.45	-60.730	-13
6313	-58.550	1.56	-56.990	-13
7115	-65.007	1.59	-63.417	-13
7905	-66.536	1.82	-64.716	-13













Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Conducted)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	LTE-Band 14 (5M)	Test Range	30MHz~10GHz

**LTE- Band 14 (5M) 16QAM Index0 (1,0) CH23305 (790.5MHz)**

Frequency (MHz)	Reading Level (dBm)	Path Loss (dB)	Emission Level (dBm)	Limit (dBm)
1576	-56.172	0.58	-55.592	-40
2365	-48.143	0.70	-47.443	-13
3154	-39.458	1.01	-38.448	-13
3943	-57.386	1.18	-56.206	-13
4729	-51.013	1.23	-49.783	-13
5518	-61.845	1.45	-60.395	-13
6307	-56.728	1.56	-55.168	-13
7096	-63.524	1.59	-61.934	-13
7885	-67.705	1.82	-65.885	-13











Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Conducted)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	LTE-Band 14 (5M)	Test Range	30MHz~10GHz

**LTE-Band 14 (5M) QPSK Index1 (1,5) CH23330 (793MHz)**

Frequency (MHz)	Reading Level (dBm)	Path Loss (dB)	Emission Level (dBm)	Limit (dBm)
1585	-57.615	0.58	-57.035	-40
2380	-48.948	0.70	-48.248	-13
3172	-39.878	1.01	-38.868	-13
3964	-59.080	1.18	-57.900	-13
4756	-52.500	1.23	-51.270	-13
5551	-61.762	1.45	-60.312	-13
6343	-57.485	1.56	-55.925	-13
7135	-65.964	1.59	-64.374	-13
7927	-66.280	1.82	-64.460	-13










Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Conducted)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	LTE-Band 14 (5M)	Test Range	30MHz~10GHz


**LTE- Band 14 (5M) 16QAM Index0 (1,0) CH23330 (793MHz)**

Frequency (MHz)	Reading Level (dBm)	Path Loss (dB)	Emission Level (dBm)	Limit (dBm)
1586	-54.910	0.58	-54.330	-40
2377	-48.540	0.70	-47.840	-13
3169	-38.720	1.01	-37.710	-13
3961	-60.020	1.18	-58.840	-13
4753	-53.355	1.23	-52.125	-13
5545	-62.332	1.45	-60.882	-13
6334	-57.127	1.56	-55.567	-13
7137	-64.680	1.59	-63.090	-13
7930	-66.074	1.82	-64.254	-13






















Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Conducted)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	LTE-Band 14 (5M)	Test Range	30MHz~10GHz

**LTE- Band 14 (5M) 16QAM Index3 (1,0) CH23355 (795.5MHz)**

Frequency (MHz)	Reading Level (dBm)	Path Loss (dB)	Emission Level (dBm)	Limit (dBm)
1594	-54.500	0.58	-53.920	-40
2389	-50.340	0.70	-49.640	-13
3187	-38.070	1.01	-37.060	-13
3985	-59.320	1.18	-58.140	-13
4780	-53.693	1.23	-52.463	-13
5578	-61.570	1.45	-60.120	-13
6373	-57.192	1.56	-55.632	-13
7160	-64.850	1.59	-63.260	-13
7955	-65.627	1.82	-63.807	-13













Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Conducted)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	LTE-Band 14 (10M)	Test Range	30MHz~10GHz

**LTE- Band 14 (10M) QPSK Index7 (1,5) CH23330 (793MHz)**

Frequency (MHz)	Reading Level (dBm)	Path Loss (dB)	Emission Level (dBm)	Limit (dBm)
1594	-57.981	0.58	-57.401	-40
2392	-48.896	0.70	-48.196	-13
3190	-39.802	1.01	-38.792	-13
3985	-60.156	1.18	-58.976	-13
4783	-52.393	1.23	-51.163	-13
5581	-60.492	1.45	-59.042	-13
6379	-58.049	1.56	-56.489	-13
7175	-64.612	1.59	-63.022	-13
7972	-66.929	1.82	-65.109	-13











Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Conducted)		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	LTE-Band 14 (10M)	Test Range	30MHz~10GHz

**LTE- Band 14 10M 16QAM Index0 (1,0) CH23330 (793MHz)**

Frequency (MHz)	Reading Level (dBm)	Path Loss (dB)	Emission Level (dBm)	Limit (dBm)
1576	-55.821	0.58	-55.241	-40
2365	-48.150	0.70	-47.450	-13
3154	-39.342	1.01	-38.332	-13
3943	-56.938	1.18	-55.758	-13
4732	-51.110	1.23	-49.880	-13
5521	-60.488	1.45	-59.038	-13
6310	-56.297	1.56	-54.737	-13
7099	-64.175	1.59	-62.585	-13
7888	-67.681	1.82	-65.861	-13







Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (5M) QPSK(1,5)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (5M) QPSK Index0 (1,5) CH23305 (790.5MHz)

1576	-45.066	-49.442	1.630	9.800	-41.272	-13
2364	-63.876	-64.368	2.100	10.600	-55.868	-13
3152	-51.014	-51.991	2.350	12.300	-42.041	-13
3940	-58.752	-58.326	2.700	12.600	-48.426	-13
4728	-59.823	-56.346	2.830	12.700	-46.476	-13
5516	-63.534	-59.644	3.200	13.000	-49.844	-13

#### Vertical Emissions Band 14 (5M) QPSK Index0 (1,5) CH23305 (790.5MHz)

1576	-46.226	-50.004	1.630	9.800	-41.834	-13
2364	-63.833	-63.888	2.100	10.600	-55.388	-13
3152	-39.185	-39.237	2.350	12.300	-29.287	-13
3940	-60.318	-58.286	2.700	12.600	-48.386	-13
4728	-62.311	-58.065	2.830	12.700	-48.195	-13
5516	-63.533	-59.074	3.200	13.000	-49.274	-13

#### Note:

1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (5M) 16QAM(1,0)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (5M) 16QAM Index0 (1,0) CH23305 (790.5MHz)

1576	-49.644	-54.020	1.630	9.800	-45.850	-40
2364	-64.462	-64.739	2.100	10.600	-56.239	-13
3152	-56.137	-57.131	2.350	12.300	-47.181	-13
3940	-61.877	-61.533	2.700	12.600	-51.633	-13
4728	-63.149	-59.672	2.830	12.700	-49.802	-13
5516	-64.189	-60.299	3.200	13.000	-50.499	-13

#### Vertical Emissions Band 14 (5M) 16QAM Index0 (1,0) CH23305 (790.5MHz)

1576	-49.504	-53.282	1.630	9.800	-45.112	-40
2364	-64.635	-64.356	2.100	10.600	-55.856	-13
3152	-42.586	-42.643	2.350	12.300	-32.693	-13
3940	-63.271	-61.386	2.700	12.600	-51.486	-13
4728	-63.704	-59.478	2.830	12.700	-49.608	-13
5516	-62.884	-58.496	3.200	13.000	-48.696	-13

#### Note:

1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.



Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (5M) QPSK(1,5)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (5M) QPSK Index1 (1,5) CH23330 (793MHz)

1582	-47.954	-52.277	1.630	9.800	-44.107	-13
2373	-64.821	-65.241	2.100	10.600	-56.741	-13
3164	-51.829	-52.771	2.350	12.300	-42.821	-13
3955	-58.034	-57.362	2.700	12.600	-47.462	-13
4746	-62.459	-58.905	2.830	12.700	-49.035	-13
5537	-63.823	-60.077	3.200	13.000	-50.277	-13

#### Vertical Emissions Band 14 (5M) QPSK Index1 (1,5) CH23330 (793MHz)

1582	-47.704	-51.497	1.630	9.800	-43.327	-13
2373	-64.483	-64.427	2.100	10.600	-55.927	-13
3164	-41.541	-41.583	2.350	12.300	-31.633	-13
3955	-61.556	-59.482	2.700	12.600	-49.582	-13
4746	-63.231	-58.906	2.830	12.700	-49.036	-13
5537	-63.798	-59.516	3.200	13.000	-49.716	-13

#### Note:

1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (5M) 16QAM(1,0)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (5M) QPSK Index1 (1,0) CH23330 (793MHz)

1582	-46.563	-50.886	1.630	9.800	-42.716	-13
2373	-63.448	-64.011	2.100	10.600	-55.511	-13
3164	-55.492	-56.434	2.350	12.300	-46.484	-13
3955	-58.687	-58.097	2.700	12.600	-48.197	-13
4746	-60.167	-56.633	2.830	12.700	-46.763	-13
5537	-63.388	-59.930	3.200	13.000	-50.13	-13

#### Vertical Emissions Band 14 (5M) QPSK Index1 (1,0) CH23330 (793MHz)

1582	-45.957	-49.750	1.630	9.800	-41.580	-13
2373	-62.630	-62.518	2.100	10.600	-54.018	-13
3164	-40.698	-40.740	2.350	12.300	-30.790	-13
3955	-60.701	-58.627	2.700	12.600	-48.727	-13
4746	-63.686	-59.361	2.830	12.700	-49.491	-13
5537	-64.197	-59.950	3.200	13.000	-50.150	-13

#### Note:

1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (5M) QPSK(1,0)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (5M) QPSK Index3 (1,0) CH23355 (795.5MHz)

1594	-46.946	-51.131	1.630	9.800	-42.961	-13
2391	-62.765	-63.393	2.100	10.600	-54.893	-13
3188	-52.713	-53.691	2.350	12.300	-43.741	-13
3985	-58.414	-57.569	2.700	12.600	-47.669	-13
4782	-61.813	-58.184	2.830	12.700	-48.314	-13
5579	-64.079	-60.573	3.200	13.000	-50.773	-13

#### Vertical Emissions Band 14 (5M) QPSK Index3 (1,0) CH23355 (795.5MHz)

1594	-46.954	-50.778	1.630	9.800	-42.608	-13
2391	-62.751	-62.806	2.100	10.600	-54.306	-13
3188	-40.271	-40.299	2.350	12.300	-30.349	-13
3985	-59.493	-57.335	2.700	12.600	-47.435	-13
4782	-62.943	-58.539	2.830	12.700	-48.669	-13
5579	-63.090	-58.949	3.200	13.000	-49.149	-13

#### Note:

1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (5M) 16QAM(1,0)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (5M) 16QAM Index3 (1,0) CH23355 (795.5MHz)

1594	-48.204	-52.389	1.630	9.800	-44.219	-13
2391	-61.884	-62.512	2.100	10.600	-54.012	-13
3188	-56.809	-57.787	2.350	12.300	-47.837	-13
3985	-58.298	-57.453	2.700	12.600	-47.553	-13
4782	-62.41	-58.781	2.830	12.700	-48.911	-13
5579	-63.509	-60.003	3.200	13.000	-50.203	-13

#### Vertical Emissions Band 14 (5M) 16QAM Index3 (1,0) CH23355 (795.5MHz)

1594	-46.067	-49.891	1.630	9.800	-41.721	-13
2391	-62.447	-62.502	2.100	10.600	-54.002	-13
3188	-40.578	-40.606	2.350	12.300	-30.656	-13
3985	-59.057	-56.899	2.700	12.600	-46.999	-13
4782	-63.117	-58.713	2.830	12.700	-48.843	-13
5579	-63.760	-59.655	3.200	13.000	-49.855	-13

#### Note:

1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (10M) QPSK(1,5)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (10M) QPSK Index7 (1,5) CH23330 (793MHz)

1594	-48.243	-52.428	1.630	9.800	-44.258	-13
2391	-63.997	-64.625	2.100	10.600	-56.125	-13
3188	-50.579	-51.557	2.350	12.300	-41.607	-13
3985	-57.167	-56.322	2.700	12.600	-46.422	-13
4782	-59.959	-56.330	2.830	12.700	-46.460	-13
5579	-64.317	-60.859	3.200	13.000	-51.059	-13

#### Vertical Emissions Band 14 (10M) QPSK Index7 (1,5) CH23330 (793MHz)

1594	-48.728	-52.552	1.630	9.800	-44.382	-13
2391	-63.428	-63.483	2.100	10.600	-54.983	-13
3188	-40.567	-40.595	2.350	12.300	-30.645	-13
3985	-60.710	-58.552	2.700	12.600	-48.652	-13
4782	-64.005	-59.581	2.830	12.700	-49.711	-13
5579	-63.392	-59.393	3.200	13.000	-49.593	-13

Note:

1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	nRF9160 IOT Module		
Test Mode	Spurious Emission (Radiated) - Multi Band Dipole Antenna (STAF)		
Date of Test	2019/04/12	Test Site	Site3
Test Condition	Band 14 (10M) 16QAM(1,0)	Test Range	9KHz ~10GHz

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(GHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)

#### Horizontal Emissions Band 14 (10M) 16QAM Index0 (1,0) CH23330 (793MHz)

1576	-46.160	-50.536	1.630	9.800	-42.366	-13
2364	-63.392	-63.884	2.100	10.600	-55.384	-13
3152	-53.549	-54.543	2.350	12.300	-44.593	-13
3940	-58.634	-58.290	2.700	12.600	-48.390	-13
4728	-63.565	-60.088	2.830	12.700	-50.218	-13
5516	-64.391	-60.501	3.200	13.000	-50.701	-13

#### Vertical Emissions Band 14 (10M) 16QAM Index0 (1,0) CH23330 (793MHz)

1576	-46.325	-50.103	1.630	9.800	-41.933	-13
2364	-62.815	-62.647	2.100	10.600	-54.147	-13
3152	-42.496	-42.553	2.350	12.300	-32.603	-13
3940	-61.687	-59.676	2.700	12.600	-49.776	-13
4728	-63.640	-59.394	2.830	12.700	-49.524	-13
5516	-63.339	-58.845	3.200	13.000	-49.045	-13

#### Note:


1. Receiver setting (Peak Detector) : RBW:1MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 6 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

## 7. Frequency Stability Under Temperature & Voltage Variations

### 7.1. Test Specification

According to Part 2.1055, 90.213

### 7.2. Test Setup



### 7.3. Limits

<b>Limit</b>	<b>&lt;±2.5ppm</b>
--------------	--------------------

### 7.4. Test Procedure

The frequency stability of transmitter is measured by:

- (a) Temperature: The temperature is varied from -30 °C to 50 °C in 10 °C increment using a standard temperature & Humidity chamber.
- (b) Primary Supply Voltage: The primary supply voltage is varied 85% to 115% of the nominal value for non hand-carried equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating endpoint which shall be specified by the manufacturer.

The EUT was connected via the base station simulator. Universal Radio Communication Tester, (MT8820C), was used to measure The Frequency Error. The maximum result of measurements was recorded.

## 7.5. Test Result of Frequency Stability Under Temperature Variations

Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (5M) CH23305(790.5MHz) –QPSK	Test Range	-30°C ~+50°C

### Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	0.791	0.0107	±1.98
-20	0.791	0.0075	±1.98
-10	0.791	0.0097	±1.98
0	0.791	0.0135	±1.98
10	0.791	0.0106	±1.98
20	0.791	0.0068	±1.98
30	0.791	-0.0094	±1.98
40	0.791	0.0164	±1.98
50	0.791	0.0133	±1.98

### Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.791	-0.0044	±1.98
3.8	0.791	0.0068	±1.98
3.1	0.791	0.0047	±1.98



Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (5M) CH23305(790.5MHz) –16QAM	Test Range	-30°C ~+50°C

#### Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	(GHz)	(KHz)	(KHz)
-20	0.791	0.0090	±1.98
-10	0.791	0.0074	±1.98
0	0.791	0.0156	±1.98
10	0.791	0.0139	±1.98
20	0.791	0.0117	±1.98
30	0.791	0.0060	±1.98
40	0.791	-0.0078	±1.98
50	0.791	0.0115	±1.98

#### Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.791	-0.0059	±1.98
3.8	0.791	0.0060	±1.98
3.1	0.791	0.0045	±1.98

Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (5M) CH23330(793MHz) –QPSK	Test Range	-30°C ~+50°C

#### Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	0.793	-0.0103	±1.98
-20	0.793	0.0138	±1.98
-10	0.793	0.0149	±1.98
0	0.793	-0.0085	±1.98
10	0.793	0.0113	±1.98
20	0.793	0.0108	±1.98
30	0.793	-0.0132	±1.98
40	0.793	0.0118	±1.98
50	0.793	0.0147	±1.98

#### Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.793	-0.0089	±1.98
3.8	0.793	0.0108	±1.98
3.1	0.793	-0.0076	±1.98

Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (5M) CH23330(793MHz) –16QAM	Test Range	-30°C ~+50°C

#### Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	0.793	0.0162	±1.98
-20	0.793	-0.0108	±1.98
-10	0.793	-0.0142	±1.98
0	0.793	0.0076	±1.98
10	0.793	0.0115	±1.98
20	0.793	0.0117	±1.98
30	0.793	-0.0111	±1.98
40	0.793	0.0120	±1.98
50	0.793	-0.0094	±1.98

#### Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.793	-0.0080	±1.98
3.8	0.793	0.0117	±1.98
3.1	0.793	-0.0045	±1.98

Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (5M) CH23355(795.5MHz) –QPSK	Test Range	-30°C ~+50°C

Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	0.796	0.0080	±1.99
-20	0.796	-0.0115	±1.99
-10	0.796	-0.0113	±1.99
0	0.796	-0.0099	±1.99
10	0.796	0.0143	±1.99
20	0.796	0.0055	±1.99
30	0.796	-0.0119	±1.99
40	0.796	0.0041	±1.99
50	0.796	-0.0062	±1.99

Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.796	-0.0040	±1.99
3.8	0.796	0.0055	±1.99
3.1	0.796	0.0054	±1.99

Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (5M) CH23355(795.5MHz) –16QAM	Test Range	-30°C ~+50°C

#### Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	0.796	0.0077	±1.99
-20	0.796	0.0162	±1.99
-10	0.796	-0.0129	±1.99
0	0.796	0.0045	±1.99
10	0.796	0.0129	±1.99
20	0.796	0.0053	±1.99
30	0.796	-0.0133	±1.99
40	0.796	-0.0041	±1.99
50	0.796	-0.0046	±1.99

#### Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.796	-0.0042	±1.99
3.8	0.796	0.0053	±1.99
3.1	0.796	0.0051	±1.99

Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (10M) CH23330(793MHz)-QPSK	Test Range	-30°C ~+50°C

#### Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	0.793	0.0128	±1.98
-20	0.793	-0.0087	±1.98
-10	0.793	-0.0099	±1.98
0	0.793	0.0107	±1.98
10	0.793	0.0154	±1.98
20	0.793	0.0066	±1.98
30	0.793	-0.0100	±1.98
40	0.793	0.0113	±1.98
50	0.793	0.0159	±1.98

#### Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.793	-0.0124	±1.98
3.8	0.793	0.0066	±1.98
3.1	0.793	-0.0086	±1.98

Product	nRF9160 IOT Module		
Test Mode	Frequency Stability Under Temperature Variations & Voltage Variations		
Date of Test	2019/04/12	Test Site	CTR
Test Condition	Band 14 (10M) CH23330(793MHz)-16QAM	Test Range	-30°C~+50°C

#### Frequency Stability Under Temperature Variations

Temperature Interval(°C)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
-30	0.793	0.0109	±1.98
-20	0.793	-0.0098	±1.98
-10	0.793	-0.0149	±1.98
0	0.793	0.0115	±1.98
10	0.793	-0.0102	±1.98
20	0.793	0.0056	±1.98
30	0.793	-0.0107	±1.98
40	0.793	-0.0129	±1.98
50	0.793	-0.0063	±1.98

#### Voltage Variations

DC Voltage (V)	Test Frequency (GHz)	Deviation (kHz)	Limit (kHz)
5.5	0.793	-0.0106	±1.98
3.8	0.793	0.0056	±1.98
3.1	0.793	0.0069	±1.98