



TEST REPORT

Applicant: MEIZU TECHNOLOGY CO., LTD.
Address: MEIZU Tech Bldg, Technology & Innovation Coast,
Zhuhai, 519085, Guangdong, China
Equipment Type: Mobile Phone
Model Name: M416L
Brand Name: MEIZU
FCC ID: 2ANQ6-M416L
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Jul. 02, 2024
Test Date: Jul. 07, 2024 - Jul. 26, 2024
Date of Issue: Aug. 05, 2024

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Liang Yongming**Checked by:** Xia Long**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Aug. 05, 2024</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Ancillary Equipment	5
2.5	Technical Information	5
3	SUMMARY OF TEST RESULTS	6
3.1	Test Standards	6
3.2	Verdict	6
3.3	Test Uncertainty	6
4	GENERAL TEST CONFIGURATIONS	7
4.1	Test Enclosure List	7
4.2	Test Configurations	7
4.3	Test Setups	8
5	TEST ITEMS	10
5.1	Emission Tests	10
ANNEX A	TEST RESULTS	15
A.1	Radiated Emission	15
A.2	Conducted Emission, AC Ports	21
ANNEX B	TEST SETUP PHOTOS	24
ANNEX C	EUT EXTERNAL PHOTOS	24
ANNEX D	EUT INTERNAL PHOTOS	24

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	MEIZU TECHNOLOGY CO., LTD.
Address	MEIZU Tech Bldg, Technology & Innovation Coast, Zhuhai, 519085, Guangdong, China

2.2 Manufacturer Information

Manufacturer	MEIZU TECHNOLOGY CO., LTD.
Address	MEIZU Tech Bldg, Technology & Innovation Coast, Zhuhai, 519085, Guangdong, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	M416L
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V1.0
Software Version	Android 14
Dimensions (Approx.)	170.8mm*78mm*9.35mm
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	N/A
	Model No.	BA416
	Serial No.	N/A
	Capacity	Rated: 4850mAh/18.76Wh Typical: 4900mAh/18.96Wh
	Rated Voltage	3.87 V
	Limit Charge Voltage	4.45 V
	Manufacturer	Shenzhen shi jiuliyuan electronic technology co., LTD
Ancillary Equipment 2	Adapter	
	Brand Name	N/A
	Model No.	PS10UA050K2000UU (US Plug)
	Serial No.	N/A
	Rated Input	100-240V~, 50/60Hz, 0.35A
	Rated Output	5.0V $\overline{\text{---}}$ 2.0A, 10.0W
	Manufacturer	Shenzhen Flypower Technology Co., Ltd
Ancillary Equipment 3	Type-C Cable	
	Model No.	X70
	Length (Approx.)	1.0 m
	Manufacturer	HeYuan Hengyue Communication Technology Co., LTD

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/7/12/17/26/66 Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(HT20/40) and 802.11ac(VHT20/40/80) U-NII-1/2A/2C/3, GPS, GLONASS, Galileo, BDS
Classification of equipment	Class B
The highest internal frequency of EUT	5.85 GHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	Pass	--

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.2 dB
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
Laptop	HONOR	KPRC-W10	N/A	N/A	N/A	☒
Earphone	OPPO	N/A	N/A	1m	N/A	☒
SD Card	Kingston	SDG3/64GB	N/A	N/A	N/A	☒

4.2 Test Configurations


All test modes of EUT are listed in the table below.

Test Mode Configuration	Description
Mode 1	<u>The Video Playback Test Mode</u> EUT + Battery + Type-C Cable + Adapter + SD Card + Earphone
Mode 2	<u>The Camera Test Mode</u> EUT + Battery + Type-C Cable + Adapter + SD Card + Earphone
Mode 3	<u>The Video Playback Test Mode(Without Earphone)</u> EUT + Battery + Type-C Cable + Adapter + SD Card
Mode 4	<u>The Data Transmission Test Mode</u> EUT + Battery + Type-C Cable + SD Card + Earphone + Laptop


Test Case	Test Mode Configuration	Worst Mode
Radiated Emission	Mode 1~Mode 4	4
Conducted Emission, AC Ports	Mode 1~Mode 3	2
Note: All operation modes were tested, but only test data of the worst mode was presented in this report.		

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \times \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \times \log(d_{10m}/d_{3m})$$
Where:
 L_{3m} is Average Class A limit at 3m;
 L_{10m} is Average Class A limit at 10m;
 d_{10m} is Measurement distance in 10m;
 d_{3m} is Measurement distance in 3m.
For this case: $L_{3m} = 49.5 + 20 \times \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_x)	Highest measurement frequency (F_M)
$F_x \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_x \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_x \leq 1 \text{ GHz}$	5 GHz
$F_x \geq 1 \text{ GHz}$	5 * F_x or 40 GHz, whichever is lower.
Note: F_x is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The Radiated Emission is required to be investigated to the upper frequency of 5th harmonic of the highest internal frequency of EUT or 40 GHz, whichever is lower. The test results above 18GHz are only noise and are not recorded in the report.

Sample No.	S53	Temperature	21.8℃
Humidity	60%RH	Pressure	101kPa
Test Engineer	Chen Jingran	Test Date	2024.07.07-2024.07.26


Test Mode 4

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	65.454	31.21	-28.18	40.0	8.79	Peak	33.00	200	Vertical	Pass
2	161.969	29.96	-25.32	43.5	13.54	Peak	102.00	100	Vertical	Pass
3	398.794	31.89	-21.27	46.0	14.11	Peak	158.00	100	Vertical	Pass
4	480.031	37.31	-19.45	46.0	8.69	Peak	303.00	100	Vertical	Pass
5	591.533	27.14	-16.53	46.0	18.86	Peak	111.00	200	Vertical	Pass
6	959.987	35.67	-10.29	46.0	10.33	Peak	236.00	100	Vertical	Pass


2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	64.677	27.40	-28.09	40.0	12.60	Peak	193.00	100	Horizontal	Pass
2	161.920	29.51	-25.32	43.5	13.99	Peak	288.00	200	Horizontal	Pass
3	291.803	27.83	-25.18	46.0	18.17	Peak	4.00	100	Horizontal	Pass
4	395.738	36.65	-21.30	46.0	9.35	Peak	70.00	100	Horizontal	Pass
5	480.000	44.26	-19.45	46.0	1.74	Peak	98.00	101	Horizontal	N/A
5*	480.000	42.75	-19.45	46.0	3.25	QP	98.00	101	Horizontal	Pass
6	960.036	33.85	-10.29	54.0	20.15	Peak	95.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2023.09.05	2024.09.04	☒
Amplifier (30MHz-1GHz)	COM-MV	ZT30-1000M	B2017119081	2023.12.05	2024.12.04	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00867	2022.04.12	2025.04.11	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2021.08.19	2024.08.18	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

3) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1439.900	41.64	-15.24	74.0	32.36	Peak	186.50	100	Vertical	Pass
1**	1439.900	33.12	-15.24	54.0	20.88	AV	186.50	100	Vertical	Pass
2	2223.300	46.72	-8.37	74.0	27.28	Peak	0.50	100	Vertical	Pass
2**	2223.300	37.95	-8.37	54.0	16.05	AV	0.50	100	Vertical	Pass
3	2959.300	48.00	-5.56	74.0	26.00	Peak	137.00	100	Vertical	Pass
3**	2959.300	38.66	-5.56	54.0	15.34	AV	137.00	100	Vertical	Pass
4	4512.200	44.64	-4.70	74.0	29.36	Peak	226.10	100	Vertical	Pass
4**	4512.200	35.70	-4.70	54.0	18.30	AV	226.10	100	Vertical	Pass
5	6536.400	49.57	-1.05	74.0	24.43	Peak	205.90	100	Vertical	Pass
5**	6536.400	40.20	-1.05	54.0	13.80	AV	205.90	100	Vertical	Pass
6	10252.775	49.90	19.52	74.0	24.10	Peak	0.90	100	Vertical	Pass
6**	10252.775	40.15	19.52	54.0	13.85	AV	0.90	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1437.800	41.95	-15.16	74.0	32.05	Peak	184.60	100	Horizontal	Pass
1**	1437.800	31.49	-15.16	54.0	22.51	AV	184.60	100	Horizontal	Pass
2	2218.800	46.17	-8.61	74.0	27.83	Peak	333.20	100	Horizontal	Pass
2**	2218.800	36.76	-8.61	54.0	17.24	AV	333.20	100	Horizontal	Pass
3	3177.000	45.78	-8.10	74.0	28.22	Peak	155.50	100	Horizontal	Pass
3**	3177.000	36.18	-8.10	54.0	17.82	AV	155.50	100	Horizontal	Pass
4	5143.000	46.24	-3.83	74.0	27.76	Peak	165.40	100	Horizontal	Pass
4**	5143.000	36.56	-3.83	54.0	17.44	AV	165.40	100	Horizontal	Pass
5	6738.800	49.37	-1.39	74.0	24.63	Peak	359.20	100	Horizontal	Pass
5**	6738.800	39.06	-1.39	54.0	14.94	AV	359.20	100	Horizontal	Pass
6	11032.188	51.44	21.04	74.0	22.56	Peak	158.90	100	Horizontal	Pass
6**	11032.188	42.28	21.04	54.0	11.72	AV	158.90	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2023.09.05	2024.09.04	☒
EMI Receiver	R&S	FSV-40	101544	2023.12.27	2024.12.26	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2023.12.05	2024.12.04	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2023.12.05	2024.12.04	☒
Amplifier (18-40GHz)	COM-MV	KA_LNA18- 40G-01	18050001	2024.06.15	2027.06.14	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	☒
Test Antenna- Horn	A-INFOMW	LB-180400KF	J211060273	2024.06.15	2027.06.14	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2021.08.19	2024.08.18	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒


A.2 Conducted Emission, AC Ports

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (240 VAC, 50 Hz) shown here.

Sample No.	S53	Temperature	25.1℃
Humidity	53%RH	Pressure	101kPa
Test Engineer	Yang Yang	Test Date	2024.07.09


Test Mode 2

1) AC Ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.178	51.55	9.78	64.58	13.03	Peak	L	Pass
1**	0.178	34.55	9.78	54.58	20.03	AV	L	Pass
2	0.538	48.19	10.02	56.00	7.81	Peak	L	Pass
2**	0.538	40.21	10.02	46.00	5.79	AV	L	Pass
3	0.712	43.58	10.53	56.00	12.42	Peak	L	Pass
3**	0.712	30.80	10.53	46.00	15.20	AV	L	Pass
4	1.132	43.78	10.27	56.00	12.22	Peak	L	Pass
4**	1.132	28.84	10.27	46.00	17.16	AV	L	Pass
5	2.150	42.73	10.18	56.00	13.27	Peak	L	Pass
5**	2.150	28.41	10.18	46.00	17.59	AV	L	Pass
6	3.326	42.30	10.40	56.00	13.70	Peak	L	Pass
6**	3.326	26.53	10.40	46.00	19.47	AV	L	Pass

2) AC Ports - N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.174	48.30	9.78	64.77	16.47	Peak	N	Pass
1**	0.174	35.23	9.78	54.77	19.54	AV	N	Pass
2	0.444	45.04	10.09	56.99	11.95	Peak	N	Pass
2**	0.444	35.94	10.09	46.99	11.05	AV	N	Pass
3	0.536	52.77	10.01	56.00	3.23	Peak	N	Pass
3**	0.536	42.40	10.01	46.00	3.60	AV	N	Pass
4	0.638	47.74	10.20	56.00	8.26	Peak	N	Pass
4**	0.638	31.41	10.20	46.00	14.59	AV	N	Pass
5	0.982	47.59	10.00	56.00	8.41	Peak	N	Pass
5**	0.982	35.05	10.00	46.00	10.95	AV	N	Pass
6	2.208	46.46	10.03	56.00	9.54	Peak	N	Pass
6**	2.208	29.70	10.03	46.00	16.30	AV	N	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2023.09.05	2024.09.04	☒
LISN	SCHWARZB ECK	NSLK 8127	8127-687	2024.05.09	2025.05.08	☒
Shielded Room	YiHeng Electronic Co., Ltd	3.5m*3.1m*2. 8m	112	2022.02.19	2025.02.18	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2460766-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2460766-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2460766-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--