

RADIO TEST REPORT

FCC ID: 2ANQ6-MZTW50

Product: Meizu True Wireless Sports Bluetooth Earphones
Trade Mark: MEIZU
Model No.: MEIZU TW50
Serial Model: N/A
Report No.: SER180316005001E
Issue Date: 28 Mar. 2018

Prepared for

Meizu Technology Co., Ltd.
Meizu Tech Bldg., Technology & Innovation Coast, ZhuHai 519085,
China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China
Tel.: +86-755-6115 6588
Fax.: +86-755-6115 6599
Website:<http://www.ntek.org.cn>

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	SUMMARY OF TEST RESULTS.....	4
	TECHNICAL REQUIREMENT	4
3	FACILITIES AND ACCREDITATIONS	6
3.1	FACILITIES.....	6
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	6
3.3	MEASUREMENT UNCERTAINTY	6
4	GENERAL DESCRIPTION OF EUT	7
5	DESCRIPTION OF TEST MODES	9
6	SETUP OF EQUIPMENT UNDER TEST	10
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	10
6.2	SUPPORT EQUIPMENT.....	11
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	12
7	TEST REQUIREMENTS	14
7.1	CONDUCTED EMISSIONS TEST	14
7.2	RADIATED SPURIOUS EMISSION	19
7.3	NUMBER OF HOPPING CHANNEL.....	31
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT	33
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME)	39
7.6	20DB BANDWIDTH TEST	46
7.7	PEAK OUTPUT POWER.....	52
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	58
7.9	SPURIOUS RF CONDUCTED EMISSION.....	65
7.10	ANTENNA APPLICATION	72
7.11	TECHNICAL REQUIREMENT	72



1 TEST RESULT CERTIFICATION

Applicant's name	Meizu Technology Co., Ltd.
Address	Meizu Tech Bldg., Technology & Innovation Coast, ZhuHai 519085, China
Manufacturer's Name	Meizu Technology Co., Ltd.
Address	Meizu Tech Bldg., Technology & Innovation Coast, ZhuHai 519085, China
Product description	
Product name	Meizu True Wireless Sports Bluetooth Earphones
Model and/or type reference	MEIZU TW50
Serial Model	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 16 Mar. 2018 ~ 03 Apr. 2018

Testing Engineer : Eileen Liu.
(Eileen Liu)

Technical Manager : Jason chen
(Jason Chen)


Authorized Signatory : Sam. chen
(Sam Chen)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	
15.247(g)(h)	Technical Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. There are left and right ear plugs on the EUT. Both have been tested.



3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A-1.

FCC- Accredited : Test Firm Registration Number: 463705.

A2LA-Lab. : Designation Number: CN1184
The Certificate Registration Number is 4298.01
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(>6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Meizu True Wireless Sports Bluetooth Earphones
Trade Mark	MEIZU
FCC ID	2ANQ6-MZTW50
Model No.	MEIZU TW50
Serial Model	N/A
Difference between the Left unit and right unit	The circuit diagram and the electronic components between the left and right ear is the same, The part placement between the two is the mirror relationship. Just their PCB Layout is a bit different. The R unit is the Main earplugs, its working principle is that the Main earplug drives another earplugs L.
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Bluetooth Version	BT V4.2
Number of Channels	79 Channels
Antenna Type	FPCB Antenna
Antenna Gain	0.03 dBi
Power supply	<input checked="" type="checkbox"/> DC supply: DC 3.7V/85mAh from Battery.
	<input type="checkbox"/> Adapter supply:
HW Version	v1.3
SW Version	v180327

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for $\pi/4$ -DQPSK modulation; 3Mbps for 8-DPSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
...	...
39	2441
40	2442
...	...
77	2479
78	2480

Note: $f_c=2402\text{MHz}+k \times 1\text{MHz}$ $k=0$ to 78

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission	
Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases	
Final Test Mode	Description
Mode 1	normal link mode
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 2Mbps on left and 1Mbps on right was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

For Conducted Test Cases	
Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)
Mode 5	Hopping mode


Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

1. AC power line Conducted Emission was tested under maximum output power.


6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1	Meizu True Wireless Sports Bluetooth Earphones	MEIZU	MEIZU TW50	2ANQ6-MZTW50	EUT
E-2	Adapter	N/A	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Type-C Cable	NO	NO	0.6m
C-2	RF Cable	NO	NO	0.5m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2017.06.06	2018.06.05	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2017.10.26	2018.10.25	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2017.06.06	2018.06.05	1 year
4	Test Receiver	R&S	ESPI	101318	2017.06.06	2018.06.05	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2017.04.09	2018.04.08	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2017.06.06	2018.06.05	1 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2017.04.09	2018.04.08	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2017.07.06	2018.07.05	1 year
9	Amplifier	EMC	EMC051835SE	980246	2017.08.09	2018.08.08	1 year
10	Amplifier	MITEQ	TTA1840-35-HG	177156	2017.06.06	2018.06.05	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.06	2018.06.05	1 year
12	Power Meter	DARE	RPR3006W	15I00041SN084	2017.08.07	2018.08.06	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
15	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
16	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year
17	Filter	TRILTHIC	2400MHz	29	2017.04.19	2018.04.18	1 year
18	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
 And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2017.06.06	2018.06.05	1 year
2	LISN	R&S	ENV216	101313	2017.04.19	2018.04.18	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2017.06.06	2018.06.05	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2017.06.06	2018.06.05	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard


According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Test Configuration



7.1.4 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.5 Test Results

Pass


7.1.6 Test Results

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model Name :	MEIZU TW50
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.3820	21.47	9.83	31.30	58.23	-26.93	QP
0.3820	1.01	9.83	10.84	48.23	-37.39	AVG
0.5020	21.81	9.83	31.64	56.00	-24.36	QP
0.5020	1.58	9.83	11.41	46.00	-34.59	AVG
0.8139	16.19	9.87	26.06	56.00	-29.94	QP
0.8139	-1.88	9.87	7.99	46.00	-38.01	AVG

Remark:

- All readings are Quasi-Peak and Average values.
- Factor = Insertion Loss + Cable Loss.




EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model Name :	MEIZU TW50
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1700	30.40	9.92	40.32	64.96	-24.64	QP
0.1700	2.15	9.92	12.07	54.96	-42.89	AVG
0.3940	21.16	9.93	31.09	57.98	-26.89	QP
0.3940	2.36	9.93	12.29	47.98	-35.69	AVG
0.4939	22.10	9.93	32.03	56.10	-24.07	QP
0.4939	2.61	9.93	12.54	46.10	-33.56	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model Name :	MEIZU TW50
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor (dB)	Measure-ment (dB μ V)	Limits (dB μ V)	Margin (dB)	Remark
0.4259	23.46	9.83	33.29	57.33	-24.04	QP
0.4259	2.31	9.83	12.14	47.33	-35.19	AVG
0.5180	24.10	9.83	33.93	56.00	-22.07	QP
0.5180	2.49	9.83	12.32	46.00	-33.68	AVG
0.6460	21.95	9.83	31.78	56.00	-24.22	QP
0.6460	1.34	9.83	11.17	46.00	-34.83	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model Name :	MEIZU TW50
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.4219	23.07	9.93	33.00	57.41	-24.41	QP
0.4219	3.80	9.93	13.73	47.41	-33.68	AVG
0.5140	24.20	9.93	34.13	56.00	-21.87	QP
0.5140	4.68	9.93	14.61	46.00	-31.39	AVG
0.8219	21.57	9.93	31.50	56.00	-24.50	QP
0.8219	3.22	9.93	13.15	46.00	-32.85	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54


Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz]/\text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $20 \log(\text{Specific distance}/ \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission below 1GHz (30MHz to 1GHz)


All the modulation modes have been tested, and the worst result was report as below:

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model Name :	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1
Test Voltage :	DC 3.7V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	31.2893	6.19	20.65	26.84	40.00	-13.16	QP
V	109.4116	9.53	10.23	19.76	43.50	-23.74	QP
V	198.5878	6.53	13.75	20.28	43.50	-23.22	QP
V	299.3158	6.58	14.71	21.29	46.00	-24.71	QP
V	845.0878	7.12	25.68	32.80	46.00	-13.20	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	31.0704	6.11	20.74	26.85	40.00	-13.15	QP
H	43.6584	5.97	14.58	20.55	40.00	-19.45	QP
H	208.5801	5.98	13.45	19.43	43.50	-24.07	QP
H	313.2760	14.66	13.31	27.97	46.00	-18.03	QP
H	872.1832	6.95	25.93	32.88	46.00	-13.12	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4 (Left)	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(π/4-DQPSK)--Above 1G									
4804	54.41	5.21	35.59	44.30	50.91	74.00	-23.09	Pk	Vertical
4804	37.32	5.21	35.59	44.30	33.82	54.00	-20.18	AV	Vertical
7206	49.66	6.48	36.27	44.60	47.81	74.00	-26.19	Pk	Vertical
7206	32.21	6.48	36.27	44.60	30.36	54.00	-23.64	AV	Vertical
4804	51.83	5.21	35.55	44.30	48.29	74.00	-25.71	Pk	Horizontal
4804	34.99	5.21	35.55	44.30	31.45	54.00	-22.55	AV	Horizontal
7206	52.35	6.48	36.27	44.52	50.58	74.00	-23.42	Pk	Horizontal
7206	35.63	6.48	36.27	44.52	33.86	54.00	-20.14	AV	Horizontal
Mid Channel (2441 MHz)(π/4-DQPSK)--Above 1G									
4882	51.41	5.21	35.66	44.20	48.08	74.00	-25.92	Pk	Vertical
4882	35.68	5.21	35.66	44.20	32.35	54.00	-21.65	AV	Vertical
7323	50.45	7.10	36.50	44.43	49.62	74.00	-24.38	Pk	Vertical
7323	33.80	7.10	36.50	44.43	32.97	54.00	-21.03	AV	Vertical
4882	53.84	5.21	35.66	44.20	50.51	74.00	-23.49	Pk	Horizontal
4882	36.86	5.21	35.66	44.20	33.53	54.00	-20.47	AV	Horizontal
7323	51.83	7.10	36.50	44.43	51.00	74.00	-23.00	Pk	Horizontal
7323	34.64	7.10	36.50	44.43	33.81	54.00	-20.19	AV	Horizontal
High Channel (2480 MHz)(π/4-DQPSK)-- Above 1G									
4960	51.89	5.21	35.52	44.21	48.41	74.00	-25.59	Pk	Vertical
4960	35.93	5.21	35.52	44.21	32.45	54.00	-21.55	AV	Vertical
7440	50.84	7.10	36.53	44.60	49.87	74.00	-24.13	Pk	Vertical
7440	34.63	7.10	36.53	44.60	33.66	54.00	-20.34	AV	Vertical
4960	51.10	5.21	35.52	44.21	47.62	74.00	-26.38	Pk	Horizontal
4960	34.51	5.21	35.52	44.21	31.03	54.00	-22.97	AV	Horizontal
7440	50.35	7.10	36.53	44.60	49.38	74.00	-24.62	Pk	Horizontal
7440	34.23	7.10	36.53	44.60	33.26	54.00	-20.74	AV	Horizontal

- Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
 (2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
 (3)All other emissions more than 20dB below the limit.

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4 (Right)	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(GFSK)--Above 1G									
4804	54.08	5.21	35.59	44.30	50.58	74.00	-23.42	Pk	Vertical
4804	36.06	5.21	35.59	44.30	32.56	54.00	-21.44	AV	Vertical
7206	50.96	6.48	36.27	44.60	49.11	74.00	-24.89	Pk	Vertical
7206	34.16	6.48	36.27	44.60	32.31	54.00	-21.69	AV	Vertical
4804	55.28	5.21	35.55	44.30	51.74	74.00	-22.26	Pk	Horizontal
4804	37.70	5.21	35.55	44.30	34.16	54.00	-19.84	AV	Horizontal
7206	51.23	6.48	36.27	44.52	49.46	74.00	-24.54	Pk	Horizontal
7206	36.74	6.48	36.27	44.52	34.97	54.00	-19.03	AV	Horizontal
Mid Channel (2441 MHz)(GFSK)--Above 1G									
4882	54.91	5.21	35.66	44.20	51.58	74.00	-22.42	Pk	Vertical
4882	38.98	5.21	35.66	44.20	35.65	54.00	-18.35	AV	Vertical
7323	49.78	7.10	36.50	44.43	48.95	74.00	-25.05	Pk	Vertical
7323	32.69	7.10	36.50	44.43	31.86	54.00	-22.14	AV	Vertical
4882	53.54	5.21	35.66	44.20	50.21	74.00	-23.79	Pk	Horizontal
4882	36.46	5.21	35.66	44.20	33.13	54.00	-20.87	AV	Horizontal
7323	50.75	7.10	36.50	44.43	49.92	74.00	-24.08	Pk	Horizontal
7323	33.10	7.10	36.50	44.43	32.27	54.00	-21.73	AV	Horizontal
High Channel (2480 MHz)(GFSK)-- Above 1G									
4960	53.36	5.21	35.52	44.21	49.88	74.00	-24.12	Pk	Vertical
4960	36.33	5.21	35.52	44.21	32.85	54.00	-21.15	AV	Vertical
7440	52.70	7.10	36.53	44.60	51.73	74.00	-22.27	Pk	Vertical
7440	34.30	7.10	36.53	44.60	33.33	54.00	-20.67	AV	Vertical
4960	53.29	5.21	35.52	44.21	49.81	74.00	-24.19	Pk	Horizontal
4960	37.02	5.21	35.52	44.21	33.54	54.00	-20.46	AV	Horizontal
7440	50.58	7.10	36.53	44.60	49.61	74.00	-24.39	Pk	Horizontal
7440	34.63	7.10	36.53	44.60	33.66	54.00	-20.34	AV	Horizontal

- Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
 (2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
 (3)All other emissions more than 20dB below the limit.

■ Spurious Emission in Band edge

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4 (Left)	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
2Mbps (π/4-DQPSK)-hopping									
2390.00	54.09	3.14	27.21	43.80	40.64	74	-33.36	Pk	Horizontal
2390.00	37.47	3.14	27.21	43.80	24.02	54	-29.98	AV	Horizontal
2390.00	54.35	3.14	27.21	43.80	40.90	74	-33.10	Pk	Vertical
2390.00	38.48	3.14	27.21	43.80	25.03	54	-28.97	AV	Vertical
2400.00	71.96	3.21	27.33	43.80	58.70	74	-15.30	Pk	Vertical
2400.00	47.91	3.21	27.33	43.80	34.65	54	-19.35	AV	Vertical
2400.00	77.98	3.21	27.33	43.80	64.72	74	-9.28	Pk	Horizontal
2400.00	49.73	3.21	27.33	43.80	36.47	54	-17.53	AV	Horizontal
2483.50	56.77	3.58	27.70	44.00	44.05	74	-29.95	Pk	Vertical
2483.50	42.05	3.58	27.70	44.00	29.33	54	-24.67	AV	Vertical
2483.50	60.35	3.58	27.70	44.00	47.63	74	-26.37	Pk	Horizontal
2483.50	44.45	3.58	27.70	44.00	31.73	54	-22.27	AV	Horizontal
2Mbps(π/4-DQPSK)- Non-hopping									
2390.00	52.87	3.14	27.21	43.80	39.42	74	-34.58	Pk	Horizontal
2390.00	37.03	3.14	27.21	43.80	23.58	54	-30.42	AV	Horizontal
2390.00	54.16	3.14	27.21	43.80	40.71	74	-33.29	Pk	Vertical
2390.00	38.51	3.14	27.21	43.80	25.06	54	-28.94	AV	Vertical
2400.00	72.30	3.21	27.33	43.80	59.04	74	-14.96	Pk	Vertical
2400.00	47.41	3.21	27.33	43.80	34.15	54	-19.85	AV	Vertical
2400.00	83.34	3.21	27.33	43.80	70.08	74	-3.92	Pk	Horizontal
2400.00	51.68	3.21	27.33	43.80	38.42	54	-15.58	AV	Horizontal
2483.50	59.38	3.58	27.70	44.00	46.66	74	-27.34	Pk	Vertical
2483.50	42.77	3.58	27.70	44.00	30.05	54	-23.95	AV	Vertical
2483.50	61.74	3.58	27.70	44.00	49.02	74	-24.98	Pk	Horizontal
2483.50	45.61	3.58	27.70	44.00	32.89	54	-21.11	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4 (Right)	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps (GFSK)-hopping									
2390.00	53.54	3.14	27.21	43.80	40.09	74	-33.91	Pk	Horizontal
2390.00	33.78	3.14	27.21	43.80	20.33	54	-33.67	AV	Horizontal
2390.00	54.18	3.14	27.21	43.80	40.73	74	-33.27	Pk	Vertical
2390.00	35.29	3.14	27.21	43.80	21.84	54	-32.16	AV	Vertical
2400.00	75.74	3.21	27.33	43.80	62.48	74	-11.52	Pk	Vertical
2400.00	50.48	3.21	27.33	43.80	37.22	54	-16.78	AV	Vertical
2400.00	79.46	3.21	27.33	43.80	66.20	74	-7.80	Pk	Horizontal
2400.00	55.68	3.21	27.33	43.80	42.42	54	-11.58	AV	Horizontal
2483.50	61.00	3.58	27.70	44.00	48.28	74	-25.72	Pk	Vertical
2483.50	41.31	3.58	27.70	44.00	28.59	54	-25.41	AV	Vertical
2483.50	62.11	3.58	27.70	44.00	49.39	74	-24.61	Pk	Horizontal
2483.50	42.75	3.58	27.70	44.00	30.03	54	-23.97	AV	Horizontal
1Mbps(GFSK)- Non-hopping									
2390.00	53.32	3.14	27.21	43.80	39.87	74	-34.13	Pk	Horizontal
2390.00	36.80	3.14	27.21	43.80	23.35	54	-30.65	AV	Horizontal
2390.00	54.00	3.14	27.21	43.80	40.55	74	-33.45	Pk	Vertical
2390.00	37.48	3.14	27.21	43.80	24.03	54	-29.97	AV	Vertical
2400.00	78.39	3.21	27.33	43.80	65.13	74	-8.87	Pk	Vertical
2400.00	53.72	3.21	27.33	43.80	40.46	54	-13.54	AV	Vertical
2400.00	82.11	3.21	27.33	43.80	68.85	74	-5.15	Pk	Horizontal
2400.00	54.79	3.21	27.33	43.80	41.53	54	-12.47	AV	Horizontal
2483.50	61.60	3.58	27.70	44.00	48.88	74	-25.12	Pk	Vertical
2483.50	42.61	3.58	27.70	44.00	29.89	54	-24.11	AV	Vertical
2483.50	63.51	3.58	27.70	44.00	50.79	74	-23.21	Pk	Horizontal
2483.50	45.92	3.58	27.70	44.00	33.20	54	-20.80	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 3260MHz-18000MHz

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4 (Left)	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Reading Level (dBμV)	Cable Loss (dB)	Antenna (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detect or Type	Comment
3260	60.11	4.04	29.57	44.70	49.02	74	-24.98	Pk	Vertical
3260	44.28	4.04	29.57	44.70	33.19	54	-20.81	AV	Vertical
3260	59.97	4.04	29.57	44.70	48.88	74	-25.12	Pk	Horizontal
3260	43.67	4.04	29.57	44.70	32.58	54	-21.42	AV	Horizontal
3332	61.52	4.26	29.87	44.40	51.25	74	-22.75	Pk	Vertical
3332	44.84	4.26	29.87	44.40	34.57	54	-19.43	AV	Vertical
3332	67.59	4.26	29.87	44.40	57.32	74	-16.68	Pk	Horizontal
3332	46.92	4.26	29.87	44.40	36.65	54	-17.35	AV	Horizontal
17797	48.87	10.99	43.95	43.50	60.31	74	-13.69	Pk	Vertical
17797	32.11	10.99	43.95	43.50	43.55	54	-10.45	AV	Vertical
17788	45.65	11.81	43.69	44.60	56.55	74	-17.45	Pk	Horizontal
17788	30.12	11.81	43.69	44.60	41.02	54	-12.98	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4 (Right)	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Reading Level (dBμV)	Cable Loss (dB)	Antenna (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
3260	59.98	4.04	29.57	44.70	48.89	74	-25.11	Pk	Vertical
3260	44.11	4.04	29.57	44.70	33.02	54	-20.98	AV	Vertical
3260	58.98	4.04	29.57	44.70	47.89	74	-26.11	Pk	Horizontal
3260	44.32	4.04	29.57	44.70	33.23	54	-20.77	AV	Horizontal
3332	61.21	4.26	29.87	44.40	50.94	74	-23.06	Pk	Vertical
3332	45.32	4.26	29.87	44.40	35.05	54	-18.95	AV	Vertical
3332	67.98	4.26	29.87	44.40	57.71	74	-16.29	Pk	Horizontal
3332	47.01	4.26	29.87	44.40	36.74	54	-17.26	AV	Horizontal
17797	48.95	10.99	43.95	43.50	60.39	74	-13.61	Pk	Vertical
17797	32.12	10.99	43.95	43.50	43.56	54	-10.44	AV	Vertical
17788	45.56	11.81	43.69	44.60	56.46	74	-17.54	Pk	Horizontal
17788	30.19	11.81	43.69	44.60	41.09	54	-12.91	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

7.3 NUMBER OF HOPPING CHANNEL

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and ANSI C63.10-2013

7.3.2 Conformance Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW \geq RBW

Sweep = auto

Detector function = peak


Trace = max hold

7.3.6 Test Results


EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 5(1Mbps)	Test By:	Eileen Liu

Number of Hopping (Channel)	Adaptive Frequency hopping (Channel)	limit	Verdict
79	20	≥ 15	Pass

Number of Hopping Channel Plot (Left)



Number of Hopping Channel Plot (Right)



7.4 HOPPING CHANNEL SEPARATION MEASUREMENT

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.4.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Measurement Bandwidth or Channel Separation

RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.4.6 Test Results


EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

	Modulation Mode	Channel Number	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)		Verdict
Left	GFSK	0	2402	0.996	>701.333	2/3 of 20dB BW	PASS
		39	2441	1.000	>692.000	2/3 of 20dB BW	PASS
		78	2480	0.996	>684.000	2/3 of 20dB BW	PASS
	$\pi/4$ -DQPSK	0	2402	1.000	>792.000	2/3 of 20dB BW	PASS
		39	2441	1.004	>786.000	2/3 of 20dB BW	PASS
		78	2480	1.004	>788.667	2/3 of 20dB BW	PASS
	8-DPSK	0	2402	1.000	>792.000	2/3 of 20dB BW	PASS
		39	2441	1.000	>805.333	2/3 of 20dB BW	PASS
		78	2480	1.004	>800.667	2/3 of 20dB BW	PASS


	Modulation Mode	Channel Number	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)		Verdict
Right	GFSK	0	2402	1.004	>702.000	2/3 of 20dB BW	PASS
		39	2441	1.004	>697.333	2/3 of 20dB BW	PASS
		78	2480	1.004	>700.667	2/3 of 20dB BW	PASS
	$\pi/4$ -DQPSK	0	2402	1.000	>770.667	2/3 of 20dB BW	PASS
		39	2441	0.992	>793.333	2/3 of 20dB BW	PASS
		78	2480	1.000	>792.667	2/3 of 20dB BW	PASS
	8-DPSK	0	2402	0.996	>788.667	2/3 of 20dB BW	PASS
		39	2441	1.000	>793.333	2/3 of 20dB BW	PASS
		78	2480	1.004	>792.000	2/3 of 20dB BW	PASS

Test Plot (Left)


(1Mbps) Channel Separation plot on channel 00-01




(2Mbps) Channel Separation plot on channel 00-01




(1Mbps) Channel Separation plot on channel 39-40




(2Mbps) Channel Separation plot on channel 39-40



(1Mbps) Channel Separation plot on channel 77-78




(2Mbps) Channel Separation plot on channel 77-78




Test Plot (Left)


(3Mbps) Channel Separation plot on channel 00-01



(3Mbps) Channel Separation plot on channel 39-40




(3Mbps) Channel Separation plot on channel 77-78




Test Plot (Right)


(1Mbps) Channel Separation plot on channel 00-01




(2Mbps) Channel Separation plot on channel 00-01




(1Mbps) Channel Separation plot on channel 39-40




(2Mbps) Channel Separation plot on channel 39-40



(1Mbps) Channel Separation plot on channel 77-78




(2Mbps) Channel Separation plot on channel 77-78




Test Plot (Right)


(3Mbps) Channel Separation plot on channel 00-01



(3Mbps) Channel Separation plot on channel 39-40



(3Mbps) Channel Separation plot on channel 77-78



7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

7.5.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and ANSI C63.10-2013

7.5.2 Conformance Limit

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.4

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW \geq 1MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Measure the maximum time duration of one single pulse.

Set the EUT for DH5, DH3 and DH1 packet transmitting.

Measure the maximum time duration of one single pulse.

7.5.6 Test Results

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Left:

Modulation Mode	Channel Number	Packet type	Mode	Hops Over Occupanc	Pulse width	dwell time (ms)	Limit	Verdict
				(ms)	(ms)		(ms)	
GFSK	39	DH1	Normal	320	0.453	145.06	<400	PASS
	39		AFH	160	0.453	72.53	<400	PASS
	39	DH3	Normal	160	1.733	277.28	<400	PASS
	39		AFH	80	1.733	138.64	<400	PASS
	39	DH5	Normal	106.67	2.973	317.13	<400	PASS
	39		AFH	53.33	2.973	158.55	<400	PASS
$\pi/4$ -DQPSK	39	2DH1	Normal	320	0.480	153.60	<400	PASS
	39		AFH	160	0.480	76.80	<400	PASS
	39	2DH3	Normal	160	1.733	277.28	<400	PASS
	39		AFH	80	1.733	138.64	<400	PASS
	39	2DH5	Normal	106.67	3.013	321.40	<400	PASS
	39		AFH	53.33	3.013	160.68	<400	PASS
8DPSK	39	3DH1	Normal	320	0.507	162.14	<400	PASS
	39		AFH	160	0.507	81.07	<400	PASS
	39	3DH3	Normal	160	1.733	277.28	<400	PASS
	39		AFH	80	1.733	138.64	<400	PASS
	39	3DH5	Normal	106.67	2.973	317.13	<400	PASS
	39		AFH	53.33	2.973	158.55	<400	PASS

Right:

Modulation Mode	Channel Number	Packet type	Mode	Hops Over Occupanc	Pulse width	dwell time (ms)	Limit	Verdict
				(ms)	(ms)		(ms)	
GFSK	39	DH1	Normal	320	0.467	149.344	<400	PASS
	39		AFH	160	0.467	74.672	<400	PASS
	39	DH3	Normal	160	1.733	277.280	<400	PASS
	39		AFH	80	1.733	138.640	<400	PASS
	39	DH5	Normal	106.67	2.960	315.743	<400	PASS
	39		AFH	53.33	2.960	157.857	<400	PASS
π/4-DQPSK	39	2DH1	Normal	320	0.480	153.600	<400	PASS
	39		AFH	160	0.480	76.800	<400	PASS
	39	2DH3	Normal	160	1.720	275.200	<400	PASS
	39		AFH	80	1.720	137.600	<400	PASS
	39	2DH5	Normal	106.67	3.013	321.397	<400	PASS
	39		AFH	53.33	3.013	160.683	<400	PASS
8DPSK	39	3DH1	Normal	320	0.507	162.144	<400	PASS
	39		AFH	160	0.507	81.072	<400	PASS
	39	3DH3	Normal	160	1.720	275.200	<400	PASS
	39		AFH	80	1.720	137.600	<400	PASS
	39	3DH5	Normal	106.67	2.987	318.623	<400	PASS
	39		AFH	53.33	2.987	159.297	<400	PASS

Note:

A Period Time = (channel number)*0.4

DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)

DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)


DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

For Example:


- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Test Plot (Left)


Package Transfer Time Plot CH39-DH1




Package Transfer Time Plot CH39-2DH1




Package Transfer Time Plot CH39-DH3




Package Transfer Time Plot CH39-2DH3



Package Transfer Time Plot CH39-DH5




Package Transfer Time Plot CH39-2DH5




Test Plot (Left)


Package Transfer Time Plot CH39-3DH1



Package Transfer Time Plot CH39-3DH3




Package Transfer Time Plot CH39-3DH5




Test Plot (Right)


Package Transfer Time Plot CH39-DH1




Package Transfer Time Plot CH39-2DH1




Package Transfer Time Plot CH39-DH3




Package Transfer Time Plot CH39-2DH3



Package Transfer Time Plot CH39-DH5




Package Transfer Time Plot CH39-2DH5




Test Plot (Right)


Package Transfer Time Plot CH39-3DH1



Package Transfer Time Plot CH39-3DH3



Package Transfer Time Plot CH39-3DH5



7.6 20DB BANDWIDTH TEST

7.6.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.6.2 Conformance Limit

No limit requirement.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq 1% of the 20 dB bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.6.6 Test Results

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Left:

Test Channel	Frequency	Measured Bandwidth (KHz)	Limit	Verdict
	(MHz)		(kHz)	
1Mbps				
0	2402	1052	N/A	PASS
39	2441	1038	N/A	PASS
78	2480	1026	N/A	PASS
2Mbps				
0	2402	1188	N/A	PASS
39	2441	1179	N/A	PASS
78	2480	1183	N/A	PASS
3Mbps				
0	2402	1188	N/A	PASS
39	2441	1208	N/A	PASS
78	2480	1201	N/A	PASS


Right:

Test Channel	Frequency	Measured Bandwidth (KHz)	Limit	Verdict
	(MHz)		(kHz)	
1Mbps				
0	2402	1053	N/A	PASS
39	2441	1046	N/A	PASS
78	2480	1051	N/A	PASS
2Mbps				
0	2402	1156	N/A	PASS
39	2441	1190	N/A	PASS
78	2480	1189	N/A	PASS
3Mbps				
0	2402	1183	N/A	PASS
39	2441	1190	N/A	PASS
78	2480	1188	N/A	PASS


Note: N/A (Not Applicable)

Test Plot (Left)


20dB Bandwidth plot on channel 00 (1Mbps)




20dB Bandwidth plot on channel 00 (2Mbps)




20dB Bandwidth plot on channel 39 (1Mbps)




20dB Bandwidth plot on channel 39 (2Mbps)



20dB Bandwidth plot on channel 78 (1Mbps)




20dB Bandwidth plot on channel 78 (2Mbps)




Test Plot (Left)

20dB Bandwidth plot on channel 00 (3Mbps)



20dB Bandwidth plot on channel 39 (3Mbps)




20dB Bandwidth plot on channel 78 (3Mbps)




Test Plot (Right)


20dB Bandwidth plot on channel 00 (1Mbps)




20dB Bandwidth plot on channel 00 (2Mbps)




20dB Bandwidth plot on channel 39 (1Mbps)




20dB Bandwidth plot on channel 39 (2Mbps)



20dB Bandwidth plot on channel 78 (1Mbps)




20dB Bandwidth plot on channel 78 (2Mbps)




Test Plot (Right)


20dB Bandwidth plot on channel 00 (3Mbps)



20dB Bandwidth plot on channel 39 (3Mbps)



20dB Bandwidth plot on channel 78 (3Mbps)



7.7 PEAK OUTPUT POWER

7.7.1 Applicable Standard

According to FCC Part 15.247(b)(1) and ANSI C63.10-2013

7.7.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.5.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq the 20 dB bandwidth of the emission being measured

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.7.6 Test Results

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Left:


Test Channel	Frequency	Power Setting	Peak Output Power	LIMIT	Verdict
	(MHz)		(dBm)	(dBm)	
1Mbps					
0	2402	Default	5.15	30	PASS
39	2441	Default	5.38	30	PASS
78	2480	Default	4.80	30	PASS
2Mbps					
0	2402	Default	5.16	20.97	PASS
39	2441	Default	5.39	20.97	PASS
78	2480	Default	4.82	20.97	PASS
3Mbps					
0	2402	Default	5.16	20.97	PASS
39	2441	Default	5.31	20.97	PASS
78	2480	Default	4.82	20.97	PASS

Right:


Test Channel	Frequency	Power Setting	Peak Output Power	LIMIT	Verdict
	(MHz)		(dBm)	(dBm)	
1Mbps					
0	2402	Default	5.83	30	PASS
39	2441	Default	5.66	30	PASS
78	2480	Default	4.15	30	PASS
2Mbps					
0	2402	Default	5.82	20.97	PASS
39	2441	Default	5.63	20.97	PASS
78	2480	Default	4.14	20.97	PASS
3Mbps					
0	2402	Default	5.80	20.97	PASS
39	2441	Default	5.64	20.97	PASS
78	2480	Default	4.15	20.97	PASS

Test Plot (Left)


Peak output Power plot on channel 00 (1Mbps)




Peak output Power plot on channel 00 (2Mbps)




Peak output Power plot on channel 39 (1Mbps)




Peak output Power plot on channel 39 (2Mbps)



Peak output Power plot on channel 78 (1Mbps)




Peak output Power plot on channel 78 (2Mbps)




Test Plot (Left)


Peak output Power plot on channel 00 (3Mbps)



Peak output Power plot on channel 39 (3Mbps)




Peak output Power plot on channel 78 (3Mbps)




Test Plot (Right)


Peak output Power plot on channel 00 (1Mbps)




Peak output Power plot on channel 00 (2Mbps)




Peak output Power plot on channel 39 (1Mbps)




Peak output Power plot on channel 39 (2Mbps)



Peak output Power plot on channel 78 (1Mbps)




Peak output Power plot on channel 78 (2Mbps)




Test Plot (Right)


Peak output Power plot on channel 00 (3Mbps)



Peak output Power plot on channel 39 (3Mbps)



Peak output Power plot on channel 78 (3Mbps)



7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.6.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.


Repeat above procedures until all measured frequencies were complete.

7.8.6 Test Results

EUT:	Meizu True Wireless Sports Bluetooth Earphones	Model No.:	MEIZU TW50
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2 /Mode4/ Mode 5	Test By:	Eileen Liu


Test Plot (Left)

GFSK: Band Edge-Low Channel




Copyright 2000-2008 Agilent Technologies

GFSK: Band Edge-High Channel




Copyright 2000-2008 Agilent Technologies

GFSK: Band Edge-Low Channel (Hopping Mode)



Copyright 2000-2008 Agilent Technologies


GFSK: Band Edge-High Channel (Hopping Mode)




Copyright 2000-2008 Agilent Technologies

Test Plot (Left)


π /4-DQPSK: Band Edge-Low Channel




π /4-DQPSK: Band Edge-High Channel



π /4-DQPSK: Band Edge-Low Channel
(Hopping Mode)




π /4-DQPSK: Band Edge-High Channel
(Hopping Mode)





Test Plot (Left)


8-DPSK: Band Edge-Low Channel



8-DPSK: Band Edge-High Channel



 8-DPSK: Band Edge-Low Channel
(Hopping Mode)


8-DPSK: Band Edge-High Channel (Hopping Mode)




Test Plot (Right)


GFSK: Band Edge-Low Channel




GFSK: Band Edge-High Channel







GFSK: Band Edge-Low Channel (Hopping Mode)




GFSK: Band Edge-High Channel (Hopping Mode)





Test Plot (Right)
 π /4-DQPSK: Band Edge-Low Channel

 π /4-DQPSK: Band Edge-High Channel

 π /4-DQPSK: Band Edge-Low Channel
(Hopping Mode)

 π /4-DQPSK: Band Edge-High Channel
(Hopping Mode)


Test Plot (Right)


8-DPSK: Band Edge-Low Channel



8-DPSK: Band Edge-High Channel


 8-DPSK: Band Edge-Low Channel
(Hopping Mode)


8-DPSK: Band Edge-High Channel (Hopping Mode)



7.9 SPURIOUS RF CONDUCTED EMISSION

7.9.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013.

7.9.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.4 Test Setup

Please refer to Section 6.1 of this test report.

7.9.5 Test Procedure

Establish an emission level by using the following procedure:





- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.





Then the limit shall be attenuated by at least 20 dB relative to the maximum amplitude level in 100 kHz.





7.9.6 Test Results

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

The worst mode on left is $\pi/4$ -DQPSK mode, and on right is GFSK mode, and the report only show the worst mode data.


Test Plot($\pi/4$ -DQPSK)- (Left)
 $\pi/4$ -DQPSK on channel 00

 $\pi/4$ -DQPSK on channel 00

 $\pi/4$ -DQPSK on channel 00

 $\pi/4$ -DQPSK on channel 00


Test Plot (Left)
 π /4-DQPSK on channel 39

 π /4-DQPSK on channel 39

 π /4-DQPSK on channel 39

 π /4-DQPSK on channel 39



Test Plot (Left)
 π /4-DQPSK on channel 78

 π /4-DQPSK on channel 78

 π /4-DQPSK on channel 78

 π /4-DQPSK on channel 78


Test Plot (GFSK)-(Right)


GFSK on channel 00




GFSK on channel 00











GFSK on channel 00



GFSK on channel 00



Test Plot (Right)
GFSK on channel 39

GFSK on channel 39

GFSK on channel 39

GFSK on channel 39


Test Plot (Right)
GFSK on channel 78

GFSK on channel 78

GFSK on channel 78

GFSK on channel 78


7.10 ANTENNA APPLICATION

7.10.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.10.2 Result

The EUT antenna is permanent attached FPCB antenna(Gain:0.03dBi). It comply with the standard requirement.

7.11 TECHNICAL REQUIREMENT

7.11.1 Requirement

15.247 (g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

15.247 (h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Note: Spread spectrum systems are sharing these bands on a noninterference basis with systems supporting critical Government requirements that have been allocated the usage of these bands, secondary only to ISM equipment operated under the provisions of part 18 of this chapter. Many of these Government systems are airborne radiolocation systems that emit a high EIRP which can cause interference to other users. Also, investigations of the effect of spread spectrum interference to U. S. Government operations in the 902-928 MHz band may require a future decrease in the power limits allowed for spread spectrum operation.

7.11.2 Result

The EUT complies with the two requirements of 15.247(g)& 15.247(h).



END OF REPORT