

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594

Report No.: SZEM180100039503

Fax: +86 (0) 755 2671 0594 Page: 1 of 7

1 Cover Page

RF MPE REPORT

Application No.:	SZEM1801000395CR (SHEM1711007616CR)		
Applicant:	Digital Peripheral Solutions Inc		
FCC ID:	2ANQL-QCW4K1MC		
Equipment Under Tes	t (EUT):		
NOTE: The following sa	imple(s) was/were submitted and identified by the client as		
Product Name:	4K WI-FI CUBE SECURITY CAMRA		
Model No.(EUT):	QCW4K1MCW		
Add Model No.:	QCW4K1MCB		
Standards:	FCC PART 15 Subpart C		
Date of Receipt:	2017-11-13		
Date of Test:	2017-11-17 to 2018-01-15		
Date of Issue:	2018-01-15		
Test Result:	Pass*		

* In the configuration tested, the EUT complied with the standards specified above.

ack Zhang

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_ecdocument.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction. documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to thesample(s) tested and such sample(s) are retained for 90 days only



Report No.: SZEM180100039503

Page: 2 of 7

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	1	2018-01-15	/	Original

Authorized for issue by:		
	Forychon	
	Foray Chen /Project Engineer	
	Eric Fu	
	Eric Fu /Reviewer	



Report No.: SZEM180100039503

Page: 3 of 7

2 Contents

		Pa	ıge
1	C	OVER PAGE	1
2	C	CONTENTS	3
3	G	ENERAL INFORMATION	4
	3.1	CLIENT INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	TECHNICAL SPECIFICATIONS	4
	3.3	TEST LOCATION	5
	3.4	TEST FACILITY	5
4	T	EST STANDARDS AND LIMITS	6
		FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	
5	N	IEASUREMENT AND CALCULATION	6
		MAXIMUM TRANSMIT POWER	
	5.2	MPE CALCULATION	7



Report No.: SZEM180100039503

Page: 4 of 7

3 General Information

3.1 Client Information

Applicant:	Digital Peripheral Solutions Inc		
Address of Applicant:	8015 E Crystal Drive , Anaheim,CA 92807		
Manufacturer:	Digital Peripheral Solutions Inc		
Address of Manufacturer:	8015 E Crystal Drive , Anaheim,CA 92807		
Factory:	1, ZHEJIANG DAHUA VISION TECHNOLOGY CO.,LTD. 2, ZHEJIANG DAHUA ZHILIAN CO.,LTD.		
Address of Factory:	1, No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China 2, No.28, Dongqiao Road, Dongzhou Street, Fuyang District, Hangzhou, P.R.China.		

3.1 General Description of E.U.T.

Product Description:	Fixed product with 2.4 WiFi function
Rated Input:	DC 12V 1A
Test Voltage:	AC 120V 60Hz for Adapter

Parameter of adapter:

	Model No.:	ADS-12AM	-12 12012EPCU
	Rated Input:	AC 100~240V, 50/60Hz 0.3A	
Adapter:	Rated Output:	DC 5V 2.0A	
·	Cable langth	AC port:	2 wires
	Cable length:	DC port:	150 cm

3.2 Technical Specifications

Operation Frequency:	802.11 b/g/n(HT20): 2412MHz-2462MHz 802.11 (HT40): 2422MHz-2452MHz
Modulation Type:	802.11 b DSSS(CCK, DQPSK, DBPSK) 802.11 g/n(OFDM(64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	802.11 b/g/n(HT20): 11 802.11 (HT40):7
Data Rate:	802.11b: 1/2/5.5/11Mbps, 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0-7
Antenna Type	Chip Antenna
Antenna Gain	2.0 dBi



Report No.: SZEM180100039503

Page: 5 of 7

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM180100039503

Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SZEM180100039502.

Test mode	Test Frequency (MHz)	Output Power (dBm)	Output Power (mW)
	2412	12.22	16.67
802.11b	2437	12.36	17.22
	2462	12.98	19.86
	2412	8.74	7.48
802.11g	2437	9.25	8.41
	2462	9.68	9.29
	2412	8.36	6.85
802.11 n(HT20)	2437	8.99	7.93
	2462	9.51	8.93
	2422	9.39	8.69
802.11 n(HT40)	2437	9.67	9.27
	2452	9.96	9.91



Report No.: SZEM180100039503

Page: 7 of 7

5.2 MPE Calculation

The Max Conducted Average Output Power is 19.86mW;

The best case gain of the antenna is 2dBi. 2dB logarithmic terms convert to numeric result is nearly 1.58

For FCC:

According to the formula S= $\frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note

dBm

- 1) P (Watts) = Power Input to antenna = 10^{10} / 1000
- 2) G (Antenna gain in numeric) = 10[^] (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{PG}{4R^2\pi} = \frac{19.86 \times 1.58}{4 \times 400 \times 3.14} = 0.0062 \text{ mW/cm}^2$$

So the device is exclusion from SAR test.

-- End of the Report--