



Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: 2ANSE-CPVIK

ISED: 24548-CPVIK

<i>Items to be covered by Single modular transmitters.</i>	<i>Answer from applicant</i>
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	The wireless chipset is shielded.
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	Yes, the module has buffered modulation/data inputs.
3. The module must contain power supply regulation on the module	Yes, the module has power regulation on the module.
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	The antenna is integrated on the module.
5. The module must demonstrate compliance in a stand-alone configuration.	Measured with the host.
6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748).	The module has a permanently affixed FCC ID label.
7. The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	The module is tested according FCC Part 15 Subpart C.
8. The module must comply with RF exposure requirements.	The module meets RF Exposure requirements.

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or authorized representative): Imad Hjije

Date: 16/12/2021

Signature: