

S

T

S

L

A

B



RADIO TESTREPORT

Report No.: STS1808215W01

Issued for


SIDAS SAS

18, rue Léon Béridot- BP 353, 38509 Voiron, France

Product Name:	Integration Mono button BLE Therm-ic
Brand Name:	SIDAS, THERM-IC
Model Name:	I-Pack Mono button B
Series Model:	N/A
FCC ID:	2ANSXMBB
Test Standard:	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail: sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's name: SIDAS SAS
Address: 18, rue Léon Béridot- BP 353, 38509 Voiron, France
Manufacture's Name: Shenzhen Komkia Technologies Co., Ltd.
Address: Building D,OA-04, Fenghuang 3rd Industrial Zone, Fuyong Town,
BaoAn District, Shenzhen City. Guangdong, 518103 China

Product description

Product Name: Integration Mono button BLE Therm-ic
Brand Name: SIDAS, THERM-IC
Model Name: I-Pack Mono button B
SeriesModel: N/A
Test Standards: CFR47 FCC Part 15: Subpart C Section 15.247
CFR47 FCC Part 15: Subpart C Section 15.207
CFR47 FCC Part 15: Subpart C Section 15.209
CFR47 FCC Part 15: Subpart B Section 15.107
CFR47 FCC Part 15: Subpart B Section 15.109

Test procedure: ANSI C63.10: 2013, ANSI C63.4: 2014

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC/IC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests: 24 Aug. 2018 -31 Aug. 2018

Date of Issue: 05 Sep. 2018

Test Result: **Pass**

Testing Engineer :



(Chris Chen)

Technical Manager :



(Sean She)

Authorized Signatory :



(Vita Li)





Table of Contents

Page

1	SUMMARY OF TEST RESULTS	6
1.1	TEST FACTORY	7
1.2	MEASUREMENT UNCERTAINTY	7
2	GENERAL INFORMATION	8
2.1	GENERAL DESCRIPTION OF EUT	8
2.2	DESCRIPTION OF TEST MODES	10
2.3	BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4	DESCRIPTION OF SUPPORT UNITS	11
2.5	EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3	EMC EMISSION TEST	13
3.1	CONDUCTED EMISSION MEASUREMENT	13
3.2	RADIATED EMISSION MEASUREMENT	16
3.3	RADIATED SPURIOUS EMISSION MEASUREMENT	22
4	CONDUCTED SPURIOUS & BAND EDGE EMISSION	33
4.1	APPLIED PROCEDURES / LIMIT	33
4.2	TEST PROCEDURE	33
4.3	DEVIATION FROM STANDARD	33
4.4	TEST SETUP	33
4.5	EUT OPERATION CONDITIONS	33
4.6	TEST RESULTS	34
5	POWER SPECTRAL DENSITY TEST	37
5.1	APPLIED PROCEDURES / LIMIT	37
5.2	TEST PROCEDURE	37
5.3	DEVIATION FROM STANDARD	37
5.4	TEST SETUP	37
5.5	EUT OPERATION CONDITIONS	37
5.6	TEST RESULTS	38
6	BANDWIDTH TEST	40
6.1	APPLIED PROCEDURES / LIMIT	40
6.2	TEST PROCEDURE	40
6.3	DEVIATION FROM STANDARD	40
6.4	TEST SETUP	40
6.5	EUT OPERATION CONDITIONS	40
6.6	TEST RESULTS	41



7	PEAK OUTPUT POWER TEST	43
7.1	APPLIED PROCEDURES / LIMIT	43
7.2	TEST PROCEDURE	43
7.3	DEVIATION FROM STANDARD	43
7.4	TEST SETUP	43
7.5	EUT OPERATION CONDITIONS	43
7.6	TEST RESULTS	44
8	ANTENNA REQUIREMENT	45
8.1	STANDARD REQUIREMENT	45
8.2	EUT ANTENNA	45
9	APPENDIX- PHOTOS OF TEST SETUP	46



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	05 Sept.2018	STS1808215W01	ALL	Initial Issue





1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

KDB 558074 D01 DTS Meas Guidance v04

FCC Part 15,Subpart C			
StandardSection	Test Item	Judgment	Remark
FCC Part 15.207(a)	Conducted Emission	N/A	
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS	
FCC Part 15.247(b)(3)	Output Power	PASS	
FCC Part 15.247(d)	Radiated Spurious Emission	PASS	
FCC Part 15.247(d)	Conducted Spurious & Band EdgeEmission	PASS	
FCC Part 15.247(e)	Power Spectral Density	PASS	
FCC Part 15.205	Restricted Band Edge Emission	PASS	
FCC Part 15.247(d)&15.209(a)	Band Edge Emission	PASS	
FCC Part 15.247(b)(4) &15.203	Antenna Requirement	PASS	

FCC Part 15,Subpart B			
StandardSection	Test Item	Judgment	Remark
FCC Part 15.107(a)	Conducted Emission	N/A	Class B limit
FCC Part 15.109(a))	Radiated Emission	PASS	Class B limit

NOTE:

- 1) 'N/A' denotes test is not applicable in this test report
- 2) All tests were performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.



1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add.: 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road, Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649

FCC Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.71\text{dB}$
4	Spurious emissions,conducted	$\pm 0.63\text{dB}$
5	All emissions,radiated (9KHz-30MHz)	$\pm 3.02\text{dB}$
6	All emissions,radiated(30MHz-200MHz)	$\pm 3.80\text{dB}$
7	All emissions,radiated(200MHz-1000MHz)	$\pm 3.97\text{dB}$
8	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name	Integration Mono button BLE Therm-ic		
Trade Name	SIDAS, THERM-IC		
Model Name	I-Pack Mono button B		
Series Model	N/A		
Model Difference	N/A		
Product Description	The Integration Mono button BLE Therm-ic is a device used to control the temperature of a 6.6ohm heating element, either through switching through modes using a button or through the connection to a phone using the Bluetooth(4.0 Low Energy) standard 2.4GHz frequency. It is powered by the 3.7 V output of a detachable battery.		
	Operation Frequency:	2402 - 2480 MHz	
	Modulation Type:	GFSK	
	Bit Rate of Transmitter:	1 Mbps	
	Number Of Channel:	40 channels	
	Antenna Designation:	Please see Note 4	
	Antenna Gain(dBi):	-0.5dBi	
	Duty Cycle:	>98%	
Channel List	Please refer to the Note 2.		
Power Rating	Input: DC 3.7V		
Hardware version	N/A		
Software version	N/A		
Radio Hardware version	N/A		
Radio Software version	N/A		
Test Software	N/A		
RF Power Setting TEST Software (power class)	N/A		
Connecting I/O Port(s)	Please refer to the User's Manual		



Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

RF Channel and Frequency of BLE			
RF Channel	Freq.(MHz)	RF Channel	Freq.(MHz)
37	2402	18	2442
00	2404	19	2444
01	2406	20	2446
02	2408	21	2448
03	2410	22	2450
04	2402	23	2452
05	2414	24	2454
06	2416	25	2456
07	2418	26	2458
08	2420	27	2460
09	2422	28	2480
10	2424	29	2464
38	2426	30	2466
11	2428	31	2468
12	2430	32	2470
13	2432	33	2472
14	2434	34	2474
15	2436	35	2476
16	2438	36	2478
17	2440	39	2480

- 3 Note:

- 1) In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test;
- 2) Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480MHz.

4

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	Mono Button	PCB Antenna	N/A	-0.5	BLE Antenna




2.2 DESCRIPTION OF TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX BLE CH37	1 Mbps
Mode 2	TX BLE CH17	1 Mbps
Mode 3	TX BLE CH39	1 Mbps
Mode4	Normal operating mode	/

Note:


- 1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- 2) Controlled using a bespoke application on the laptop PC supplied by the customer. The application was used to enable a continuous transmission mode and to select the test channels, data rates and modulation schemes as required.






2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiation Test Set(Part 15C)



Radiation Test Set(Part 15B)



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Notebook	DELL	VOSTRO.3800	N/A	N/A
E-3	3.7V lithium battery	N/A	N/A	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	NO	100cm	N/A

Note:

- 1) The support equipment was authorized by Declaration of Confirmation.
- 2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- 3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test Equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	102086	2017.10.15	2018.10.14
Spectrum Analyzer	Agilent	E4407B	MY50140340	2018.03.08	2019.03.07
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2018.11.01
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1343	2017.10.27	2018.10.26
SHF-EHF Horn Antenna(18G-40GHz)	A-INFO	LB-180400-KF	N/A	2018.03.11	2019.03.10
Temperature & Humidity	HH660	Mieo	N/A	2017.10.15	2018.10.14
Temperature & Humidity	HH660	Mieo	N/A	2017.10.15	2018.10.14
Pre-amplifier (0.1M-3GHz)	EM	EM330	60538	2018.03.11	2019.03.10
PreAmplifier (1G-26.5GHz)	Agilent	8449B	60538	2017.10.15	2018.10.14
Passive Loop(9K--30MHz)	ZHNAN	ZN3090C	16035	2018.03.11	2019.03.10
Low frequency cable	EM	R01	N/A	2018.03.11	2019.03.10
Low frequency cable	EM	R06	N/A	2018.03.11	2019.03.10
High frequency cable	SCHWARZBECK	R04	N/A	2018.03.11	2019.03.10
High frequency cable	SCHWARZBECK	R02	N/A	2018.03.11	2019.03.10
Semi-anechoic chamber	Changling	966	N/A	2017.10.15	2018.10.14
turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Max-full Antenna Corp	MF	MFA-440H	N/A	N/A	N/A

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2017.10.15	2018.10.14
Power Meter	R&S	NRP	100510	2017.10.15	2018.10.14
Spectrum Analyzer	Agilent	N9020A	MY51110105	2017.10.15	2018.10.14
Signal Analyzer	Agilent	N9020A	MY49100060	2018.03.09	2019.03.10

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



3 EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

operating frequency band. In case the emission fall within the restricted band specified on Part 15.207(a), 107(a) limit in the table below has to be followed.

This item was performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- 1) The tighter limit applies at the band edges.
- 2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT

Temperature:	25°C	Relative Humidity:	61%
Test Voltage:	N/A	Phase:	L/N
Test Mode:	N/A		

Note: The EUT is power by DC, this test item is not apply.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Class A (at 10m) dBuV/m	Class B (at 3m) dBuV/m
30~88	39.0	40.0
88~216	43.5	43.5
216~960	46.5	46.0
Above 960	49.5	54.0

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Note:

- 1) The tighter limit applies at the band edges.
- 2) Emission level (dBuV/m)=20log Emission level (uV/m).


3.2.2 TEST PROCEDURE

- a) The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 0.8 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f) For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP

a) Radiated Emission Test-Up Frequency 30MHz~1GHz



b) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.5 TEST RESULTS

Between 30-1000MHz:


Temperature:	26.9 °C	Relative Humidity:	62%
Pressure:	1010hPa	Phase:	Horizontal
Test Voltage:	DC 3.7V	Test Mode:	Mode 4 (Part 15B)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.2110	29.55	-11.30	18.25	40.00	-21.75	QP
2	68.1512	43.27	-24.15	19.12	40.00	-20.88	QP
3	122.8340	40.10	-17.65	22.45	43.50	-21.05	QP
4	301.4223	30.22	-14.78	15.44	46.00	-30.56	QP
5	564.6390	30.24	-6.59	23.65	46.00	-22.35	QP
6	996.4995	28.65	-0.09	28.56	54.00	-25.44	QP

Remark:

1. All readings are Quasi-Peak .


2. Margin = Result (Result =Reading + Factor)-Limit





Temperature:	26.9 °C	Relative Humidity:	62%
Pressure:	1010hPa	Phase:	Vertical
Test Voltage:	DC 3.7V	Test Mode:	Mode 4 (Part 15B)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.9542	28.63	-12.20	16.43	40.00	-23.57	QP
2	68.1512	42.24	-24.15	18.09	40.00	-21.91	QP
3	122.8340	41.02	-17.65	23.37	43.50	-20.13	QP
4	375.9384	31.72	-12.73	18.99	46.00	-27.01	QP
5	541.3721	30.85	-6.97	23.88	46.00	-22.12	QP
6	982.6200	28.75	-0.14	28.61	54.00	-25.39	QP


Remark:**1. All readings are Quasi-Peak .****2. Margin = Result (Result =Reading + Factor)-Limit**



Between 1GHz – 13GHz

Temperature:	24 °C	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Phase:	Horizontal

RE_FCC Test Case_FCC 15B 1GHz-13GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	1591.409	31.12	-18.85	74.0	-42.88	Peak	H	Pass
2	3000.000	39.75	-13.73	74.0	-34.25	Peak	H	Pass
3	4838.162	43.04	-8.42	74.0	-30.96	Peak	H	Pass
4	6816.184	49.18	-3.86	74.0	-24.82	Peak	H	Pass
5	10242.757	49.86	-0.20	74.0	-24.14	Peak	H	Pass
6**	12520.480	40.38	1.49	54.0	-13.62	Av	H	Pass
6	12520.480	51.96	1.49	74.0	-22.04	Peak	H	Pass



Temperature:	24 °C	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Phase:	Vertical

RE_FCC Test Case_FCC 15B 1GHz-13GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	1563.437	31.83	-19.00	74.0	-42.17	Peak	V	Pass
2	2486.513	36.52	-13.49	74.0	-37.48	Peak	V	Pass
3	2998.002	41.43	-11.24	74.0	-32.57	Peak	V	Pass
4	6796.204	48.53	-4.07	74.0	-25.47	Peak	V	Pass
5	9503.497	51.40	2.61	74.0	-22.60	Peak	V	Pass
6**	11951.049	39.75	1.02	54.0	-14.25	Av	V	Pass
6	11951.049	51.78	1.02	74.0	-22.22	Peak	V	Pass



3.3 RADIATED SPURIOUS EMISSION MEASUREMENT

3.3.1 RADIATED EMISSION LIMITS

in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted	1 MHz /3MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2300 to 2422 MHz Upper Band Edge: 2452to 2500 MHz
RB / VB (emission in restricted band)	1 MHz /3MHz



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.3.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed test to three orthogonal axis. The worst case emissions were reported

3.3.3 TEST SETUP


a) Radiated Emission Test-Up Frequency Below 30MHz



b) Radiated Emission Test-Up Frequency 30MHz~1GHz



c) Radiated Emission Test-Up Frequency Above 1GHz



3.3.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



3.3.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

3.3.6 TEST RESULT

9KHz-30MHz

Temperature:	26.9°C	Relative Humidity:	62%
Test Voltage:	DC 3.7V	Polarization :	--
Test Mode :	TX Mode		

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dB μ v) + distance extrapolation factor.