

Appendix E

RF Test Data for 5.8G WLAN (Conducted Measurement)

Product Name: All-in-One VR

Trade Mark: Firepack

Test Model: EM_A839

Environmental Conditions


Temperature:	23.8 ° C
Relative Humidity:	53.8%
ATM Pressure:	100.0 kPa
Test Engineer:	Alisa Huang
Supervised by:	Wang Chuang

E.1 Duty Cycle


Ant0

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5785	100	0.00	0.01
11N20 SISO	5785	100	0.00	0.01
11N40 SISO	5755	100	0.00	0.01
11AC20 SISO	5785	100	0.00	0.01
11AC40 SISO	5755	100	0.00	0.01
11AC80 SISO	5775	100	0.00	0.01


On Time and Duty Cycle




IEEE 802.11a




IEEE 802.11n HT20




IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11AC40





IEEE 802.11AC80

Ant1


Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5785	100	0.00	0.01
11N20 SISO	5785	100	0.00	0.01
11N40 SISO	5755	100	0.00	0.01
11AC20 SISO	5785	100	0.00	0.01
11AC40 SISO	5755	100	0.00	0.01
11AC80 SISO	5775	100	0.00	0.01

On Time and Duty Cycle







IEEE 802.11n HT20




IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11AC40



IEEE 802.11AC80

E.2 Maximum Conduct Output Power

Ant 0

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	149	5745	3.88	0	3.88	30	Pass
	157	5785	3.97	0	3.97		Pass
	165	5825	2.91	0	2.91		Pass
11N20 SISO	149	5745	3.51	0	3.51	30	Pass
	157	5785	4.08	0	4.08		Pass
	165	5825	3.71	0	3.71		Pass
11N40 SISO	151	5755	3.79	0	3.79	30	Pass
	159	5795	3.95	0	3.95		Pass
11AC20 SISO	149	5745	3.71	0	3.71	30	Pass
	157	5785	3.78	0	3.78		Pass
	165	5825	4.09	0	4.09		Pass
11AC40 SISO	151	5755	3.62	0	3.62	30	Pass
	159	5795	4.23	0	4.23		Pass
11AC80 SISO	155	5775	3.85	0	3.85	30	Pass

Ant 1

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	149	5745	3.95	0	3.95	30	Pass
	157	5785	4.24	0	4.24		Pass
	165	5825	3.13	0	3.13		Pass
11N20 SISO	149	5745	4.07	0	4.07	30	Pass
	157	5785	4.40	0	4.40		Pass
	165	5825	3.29	0	3.29		Pass
11N40 SISO	151	5755	4.30	0	4.30	30	Pass
	159	5795	4.36	0	4.36		Pass
11AC20 SISO	149	5745	4.35	0	4.35	30	Pass
	157	5785	4.07	0	4.07		Pass
	165	5825	3.41	0	3.41		Pass
11AC40 SISO	151	5755	4.03	0	4.03	30	Pass
	159	5795	2.42	0	2.42		Pass
11AC80 SISO	155	5775	4.26	0	4.26	30	Pass

ANT0+ANT1

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)			Limit (dBm)
			Ant0	Ant1	Sum	
11N20	149	5745	3.51	4.07	6.81	30
	157	5785	4.08	4.40	7.25	
	165	5825	3.71	3.29	6.52	
11N40	151	5755	3.79	4.30	7.06	30
	159	5795	3.95	4.36	7.17	
11AC20	149	5745	3.71	4.35	7.05	30
	157	5785	3.78	4.07	6.94	
	165	5825	4.09	3.41	6.77	
11AC40	151	5755	3.62	4.03	6.84	30
	159	5795	4.23	2.42	6.43	
11AC80	155	5775	3.85	4.26	7.07	30

E.3 Power Spectral Density

Ant0

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/300KHz)	Duty Cycle Factor (dB)	RBW Factor (dB)	Report Power Density (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
11A	149	5745	-4.07	0	2.218	-1.85	30	Pass
	157	5785	-2.26	0	2.218	-0.04		Pass
	165	5825	-1.87	0	2.218	0.35		Pass
11N20 SISO	149	5745	-5.61	0	2.218	-3.39	30	Pass
	157	5785	-3.51	0	2.218	-1.30		Pass
	165	5825	-1.67	0	2.218	-1.54		Pass
11N40 SISO	151	5755	-9.39	0	2.218	-7.17	30	Pass
	159	5795	-8.01	0	2.218	-5.79		Pass
11AC20 SISO	149	5745	-7.36	0	2.218	-5.14	30	Pass
	157	5785	-5.57	0	2.218	-3.35		Pass
	165	5825	-4.08	0	2.218	-1.87		Pass
11AC40 SISO	151	5755	-10.23	0	2.218	-8.01	30	Pass
	159	5795	-5.60	0	2.218	-3.38		Pass
11AC80 SISO	155	5775	-7.35	0	2.218	-5.13	30	Pass


Ant1

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/300KHz)	Duty Cycle Factor (dB)	RBW Factor (dB)	Report Power Density (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
11A	149	5745	-5.04	0	2.218	-2.82	30	Pass
	157	5785	-5.47	0	2.218	-3.25		Pass
	165	5825	-5.24	0	2.218	-3.02		Pass
11N20 SISO	149	5745	-9.45	0	2.218	-7.23	30	Pass
	157	5785	-9.39	0	2.218	-7.17		Pass
	165	5825	-10.74	0	2.218	-8.52		Pass
11N40 SISO	151	5755	-12.34	0	2.218	-10.12	30	Pass
	159	5795	-12.51	0	2.218	-10.29		Pass
11AC20 SISO	149	5745	-9.80	0	2.218	-7.58	30	Pass
	157	5785	-9.41	0	2.218	-7.19		Pass
	165	5825	-10.37	0	2.218	-8.15		Pass
11AC40 SISO	151	5755	-12.56	0	2.218	-10.34	30	Pass
	159	5795	-12.02	0	2.218	-9.80		Pass
11AC80 SISO	155	5775	-15.66	0	2.218	-13.44	30	Pass


ANT0+ANT1

Test Mode	Channel	Frequency (MHz)	Report Power Density (dBm/500KHz)			Limit (dBm)
			Ant0	Ant1	Sum	
11N20	149	5745	-3.39	-7.23	-1.89	30
	157	5785	-1.30	-7.17	-0.30	
	165	5825	-1.54	-8.52	-0.75	
11N40	151	5755	-7.17	-10.12	-5.39	30
	159	5795	-5.79	-10.29	-4.47	
11AC20	149	5745	-5.14	-7.58	-3.18	30
	157	5785	-3.35	-7.19	-1.85	
	165	5825	-1.87	-8.15	-0.95	
11AC40	151	5755	-8.01	-10.34	-6.01	30
	159	5795	-3.38	-9.80	-2.49	
11AC80	155	5775	-5.13	-13.44	-4.53	30


Power Spectral Density



IEEE 802.11a / Channel 149 / 5745MHz




IEEE 802.11a / Channel 157 / 5785MHz




IEEE 802.11na / Channel 165 / 5825MHz


Power Spectral Density



IEEE 802.11n20 / Channel 149 / 5745MHz




IEEE 802.11n20 / Channel 157 / 5785MHz




IEEE 802.11n20 / Channel 165 / 5825MHz


Power Spectral Density




IEEE 802.11n40 / Channel 151 / 5755MHz




IEEE 802.11n40 / Channel 159 / 5795MHz




IEEE 802.11ac20 / Channel 149 / 5745MHz




IEEE 802.11ac20 / Channel 157 / 5785MHz




IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz




IEEE 802.11ac40 / Channel 159 / 5795MHz




IEEE 802.11ac80 / Channel 155/ 5775MHz

Ant1


Power Spectral Density



IEEE 802.11a / Channel 149 / 5745MHz




IEEE 802.11na / Channel 157 / 5785MHz




IEEE 802.11na / Channel 165 / 5825MHz



Power Spectral Density




IEEE 802.11n20 / Channel 149 / 5745MHz




IEEE 802.11n20 / Channel 157 / 5785MHz







IEEE 802.11n40 / Channel 159 / 5795MHz




IEEE 802.11ac20 / Channel 149 / 5745MHz




IEEE 802.11ac20 / Channel 157 / 5785MHz




IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz



IEEE 802.11ac40 / Channel 159 / 5795MHz




IEEE 802.11ac80 / Channel 155/ 5775MHz

E.4 Emission Bandwidth


Ant0

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	149	5745	16.39	>=0.5	Pass
	157	5785	16.36		Pass
	165	5825	16.36		Pass
11N20 SISO	149	5745	17.61	>=0.5	Pass
	157	5785	17.58		Pass
	165	5825	13.42		Pass
11N40 SISO	151	5755	35.48	>=0.5	Pass
	159	5795	34.53		Pass
11AC20S ISO	149	5745	17.33	>=0.5	Pass
	157	5785	17.58		Pass
	165	5825	17.55		Pass
11AC40S ISO	151	5755	35.94	>=0.5	Pass
	159	5795	35.29		Pass
11AC80S ISO	155	5775	72.69	>=0.5	Pass


6dB Bandwidth



IEEE 802.11a / Channel 149 / 5745MHz




IEEE 802.11a / Channel 157 / 5785MHz




IEEE 802.11a / Channel 165 / 5825MHz


6dB Bandwidth



IEEE 802.11n20 / Channel 149 / 5745MHz




IEEE 802.11n20 / Channel 157 / 5785MHz




IEEE 802.11n20 / Channel 165 / 5825MHz


26dB Bandwidth




IEEE 802.11n40 / Channel 151 / 5755MHz




IEEE 802.11n40 / Channel 159 / 5795MHz




IEEE 802.11ac20 / Channel 149 / 5745MHz




IEEE 802.11ac20 / Channel 157/ 5785MHz




IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz



IEEE 802.11ac40 / Channel 159 / 5795MHz




IEEE 802.11ac80 / Channel 155 / 5775MHz


Ant1

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	149	5745	16.36	>=0.5	Pass
	157	5785	16.33		Pass
	165	5825	16.36		Pass
11N20 SISO	149	5745	17.61	>=0.5	Pass
	157	5785	17.55		Pass
	165	5825	17.58		Pass
11N40 SISO	151	5755	36.11	>=0.5	Pass
	159	5795	35.46		Pass
11AC20S ISO	149	5745	17.59	>=0.5	Pass
	157	5785	17.57		Pass
	165	5825	17.57		Pass
11AC40S ISO	151	5755	36.13	>=0.5	Pass
	159	5795	36.01		Pass
11AC80S ISO	155	5775	75.91	>=0.5	Pass


6dB Bandwidth



IEEE 802.11a / Channel 149 / 5745MHz




IEEE 802.11a / Channel 157 / 5785MHz




IEEE 802.11a / Channel 165 / 5825MHz


6dB Bandwidth



IEEE 802.11n20 / Channel 149 / 5745MHz




IEEE 802.11n20 / Channel 157 / 5785MHz




IEEE 802.11n20 / Channel 165 / 5825MHz


26dB Bandwidth




IEEE 802.11n40 / Channel 151 / 5755MHz




IEEE 802.11n40 / Channel 159 / 5795MHz




IEEE 802.11ac20 / Channel 149 / 5745MHz




IEEE 802.11ac20 / Channel 157/ 5785MHz




IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz



IEEE 802.11ac40 / Channel 159 / 5795MHz



IEEE 802.11ac80 / Channel 155 / 5775MHz

E.5 Undesirable Emissions Measurement


Ant0

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11A	149	5650.0	-48.15	2.00	-46.15	Peak	-27.0	Pass
		5650.0	-60.46	2.00	-58.46	Average	-27.0	Pass
		5700.0	-47.83	2.00	-45.83	Peak	10	Pass
		5700.0	-60.06	2.00	-58.06	Average	10	Pass
		5720.0	-47.30	2.00	-45.30	Peak	15.6	Pass
		5720.0	-59.89	2.00	-57.89	Average	15.6	Pass
		5725.0	-47.21	2.00	-45.21	Peak	27.0	Pass
		5725.0	-59.21	2.00	-57.21	Average	27.0	Pass
	165	5850.0	-46.62	2.00	-44.62	Peak	27.0	Pass
		5850.0	-58.62	2.00	-56.62	Average	27.0	Pass
		5855.0	-46.11	2.00	-44.11	Peak	15.6	Pass
		5855.0	-59.05	2.00	-57.05	Average	15.6	Pass
		5875.0	-48.35	2.00	-46.35	Peak	10	Pass
		5875.0	-59.32	2.00	-57.32	Average	10	Pass
		5925.0	-48.40	2.00	-46.40	Peak	-27.0	Pass
		5925.0	-59.93	2.00	-57.93	Average	-27.0	Pass
11N20 SISO	149	5650.0	-47.53	2.00	-45.53	Peak	-27.0	Pass
		5650.0	-60.34	2.00	-58.34	Average	-27.0	Pass
		5700.0	-47.73	2.00	-45.73	Peak	10	Pass
		5700.0	-59.82	2.00	-57.82	Average	10	Pass
		5720.0	-47.78	2.00	-45.78	Peak	15.6	Pass
		5720.0	-59.99	2.00	-57.99	Average	15.6	Pass
		5725.0	-47.38	2.00	-45.38	Peak	27.0	Pass
		5725.0	-59.33	2.00	-57.33	Average	27.0	Pass
	165	5850.0	-44.47	2.00	-42.47	Peak	27.0	Pass
		5850.0	-59.16	2.00	-57.16	Average	27.0	Pass
		5855.0	-47.29	2.00	-45.29	Peak	15.6	Pass
		5855.0	-59.69	2.00	-57.69	Average	15.6	Pass
		5875.0	-48.09	2.00	-46.09	Peak	10	Pass
		5875.0	-59.95	2.00	-57.95	Average	10	Pass
		5925.0	-49.12	2.00	-47.12	Peak	-27.0	Pass
		5925.0	-60.47	2.00	-58.47	Average	-27.0	Pass


Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11N40 SISO	151	5650.0	-48.98	2.00	-46.98	Peak	-27.0	Pass
		5650.0	-60.38	2.00	-58.38	Average	-27.0	Pass
		5700.0	-47.14	2.00	-45.14	Peak	10	Pass
		5700.0	-60.08	2.00	-58.08	Average	10	Pass
		5720.0	-48.35	2.00	-46.35	Peak	15.6	Pass
		5720.0	-59.70	2.00	-57.70	Average	15.6	Pass
		5725.0	-47.25	2.00	-45.25	Peak	27.0	Pass
		5725.0	-58.67	2.00	-56.67	Average	27.0	Pass
	159	5850.0	-48.27	2.00	-46.27	Peak	27.0	Pass
		5850.0	-59.19	2.00	-57.19	Average	27.0	Pass
		5855.0	-47.96	2.00	-45.96	Peak	15.6	Pass
		5855.0	-59.37	2.00	-57.37	Average	15.6	Pass
		5875.0	-48.09	2.00	-46.09	Peak	10	Pass
		5875.0	-59.64	2.00	-57.64	Average	10	Pass
		5925.0	-48.42	2.00	-46.42	Peak	-27.0	Pass
		5925.0	-60.10	2.00	-58.10	Average	-27.0	Pass
11AC20 SISO	149	5650.0	-48.71	2.00	-46.71	Peak	-27.0	Pass
		5650.0	-60.51	2.00	-58.51	Average	-27.0	Pass
		5700.0	-49.30	2.00	-47.30	Peak	10	Pass
		5700.0	-60.03	2.00	-58.03	Average	10	Pass
		5720.0	-48.12	2.00	-46.12	Peak	15.6	Pass
		5720.0	-60.21	2.00	-58.21	Average	15.6	Pass
		5725.0	-48.20	2.00	-46.20	Peak	27.0	Pass
		5725.0	-59.73	2.00	-57.73	Average	27.0	Pass
	165	5850.0	-46.73	2.00	-44.73	Peak	27.0	Pass
		5850.0	-58.84	2.00	-56.84	Average	27.0	Pass

11AC4 0 SISO	151	5855.0	-45.93	2.00	-43.93	Peak	15.6	Pass
		5855.0	-59.26	2.00	-57.26	Average	15.6	Pass
		5875.0	-46.82	2.00	-44.82	Peak	10	Pass
		5875.0	-59.39	2.00	-57.39	Average	10	Pass
		5925.0	-46.95	2.00	-44.95	Peak	-27.0	Pass
		5925.0	-60.03	2.00	-58.03	Average	-27.0	Pass
		5650.0	-47.58	2.00	-45.58	Peak	-27.0	Pass
		5650.0	-60.43	2.00	-58.43	Average	-27.0	Pass
	159	5700.0	-47.65	2.00	-45.65	Peak	10	Pass
		5700.0	-60.06	2.00	-58.06	Average	10	Pass
		5720.0	-48.13	2.00	-46.13	Peak	15.6	Pass
		5720.0	-59.74	2.00	-57.74	Average	15.6	Pass
		5725.0	-47.42	2.00	-45.42	Peak	27.0	Pass
		5725.0	-58.75	2.00	-56.75	Average	27.0	Pass
		5850.0	-46.61	2.00	-44.61	Peak	27.0	Pass
		5850.0	-58.92	2.00	-56.92	Average	27.0	Pass
		5855.0	-45.96	2.00	-43.96	Peak	15.6	Pass
		5855.0	-59.07	2.00	-57.07	Average	15.6	Pass
11AC8 0 SISO	155	5875.0	-47.36	2.00	-45.36	Peak	10	Pass
		5875.0	-59.33	2.00	-57.33	Average	10	Pass
		5925.0	-48.12	2.00	-46.12	Peak	-27.0	Pass
		5925.0	-59.91	2.00	-57.91	Average	-27.0	Pass
		5725.0	-45.27	2.00	-43.27	Peak	27.0	Pass
		5720.0	-45.83	2.00	-43.83	Peak	15.6	Pass
		5700.0	-47.31	2.00	-45.31	Peak	10	Pass
		5650.0	-49.08	2.00	-47.08	Peak	-27.0	Pass
		5725.0	-57.20	2.00	-55.20	Average	27.0	Pass
		5720.0	-57.65	2.00	-55.65	Average	15.6	Pass
		5700.0	-58.81	2.00	-56.81	Average	10	Pass
		5650.0	-59.60	2.00	-57.60	Average	-27.0	Pass
		5850.0	-45.27	2.00	-43.27	Peak	27.0	Pass
		5855.0	-45.83	2.00	-43.83	Peak	15.6	Pass
		5875.0	-47.31	2.00	-45.31	Peak	10	Pass
		5925.0	-49.08	2.00	-47.08	Peak	-27.0	Pass
		5850.0	-57.20	2.00	-55.20	Average	27.0	Pass
		5855.0	-57.65	2.00	-55.65	Average	15.6	Pass
		5875.0	-58.81	2.00	-56.81	Average	10	Pass
		5925.0	-59.60	2.00	-57.60	Average	-27.0	Pass

Undesirable Emissions Measurement




IEEE 802.11a / Channel 149 / 5745MHz / Peak




IEEE 802.11a / Channel 148 / 5745MHz / Average

Undesirable Emissions Measurement




IEEE 802.11a / Channel 165 / 5825MHz / Peak




IEEE 802.11a / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n20 / Channel 149 / 5745MHz / Peak




IEEE 802.11n20 / Channel 149 / 5745MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n20 / Channel 165 / 5825MHz / Peak




IEEE 802.11n20 / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 151 / 5755MHz / Peak




IEEE 802.11n40 / Channel 151 / 5755MHz / Average


Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 159 / 5795MHz / Peak




IEEE 802.11n40 / Channel 159 / 5795MHz / Average




IEEE 802.11ac20 / Channel 149 / 5745MHz / Peak




IEEE 802.11ac20 / Channel 149 / 5745MHz / Average




IEEE 802.11ac20 / Channel 165 / 5825MHz / Peak




IEEE 802.11ac20 / Channel 165 / 5825MHz / Average




IEEE 802.11ac40 / Channel 151 / 5755MHz / Peak




IEEE 802.11ac40 / Channel 151 / 5755MHz / Average




IEEE 802.11ac40 / Channel 159 / 5795MHz / Peak




IEEE 802.11ac40 / Channel 159 / 5795MHz / Average



IEEE 802.11ac80 / Channel 155 / 5775MHz / Peak



IEEE 802.11ac80 / Channel 155 / 5775MHz / Average



Frequency

Auto Tune

Center Freq
5.742500000 GHz


Start Freq
5.650000000 GHz

Stop Freq
5.835000000 GHz

CF Step
18.500000 MHz
Auto Man

Freq Offset
0 Hz

IEEE 802.11ac80 / Channel 155/ 5775MHz / Peak



Frequency

Auto Tune

Center Freq
5.830000000 GHz

Start Freq
5.735000000 GHz

Stop Freq
5.925000000 GHz

CF Step
19.000000 MHz
Auto Man

Freq Offset
0 Hz

IEEE 802.11ac80 / Channel 155 / 5775MHz / Average


Ant1

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11A	149	5650.0	-49.32	2.00	-47.32	Peak	-27.0	Pass
		5650.0	-60.81	2.00	-58.81	Average	-27.0	Pass
		5700.0	-48.71	2.00	-46.71	Peak	10	Pass
		5700.0	-60.44	2.00	-58.44	Average	10	Pass
		5720.0	-48.21	2.00	-46.21	Peak	15.6	Pass
		5720.0	-59.99	2.00	-57.99	Average	15.6	Pass
		5725.0	-44.19	2.00	-42.19	Peak	27.0	Pass
		5725.0	-58.81	2.00	-56.81	Average	27.0	Pass
	165	5850.0	-48.56	2.00	-46.56	Peak	27.0	Pass
		5850.0	-59.99	2.00	-57.99	Average	27.0	Pass
		5855.0	-48.51	2.00	-46.51	Peak	15.6	Pass
		5855.0	-60.15	2.00	-58.15	Average	15.6	Pass
		5875.0	-48.58	2.00	-46.58	Peak	10	Pass
		5875.0	-60.37	2.00	-58.37	Average	10	Pass
		5925.0	-48.67	2.00	-46.67	Peak	-27.0	Pass
		5925.0	-60.69	2.00	-58.69	Average	-27.0	Pass
11N20 SISO	149	5650.0	-48.46	2.00	-46.46	Peak	-27.0	Pass
		5650.0	-60.89	2.00	-58.89	Average	-27.0	Pass
		5700.0	-49.41	2.00	-47.41	Peak	10	Pass
		5700.0	-60.40	2.00	-58.40	Average	10	Pass
		5720.0	-48.68	2.00	-46.68	Peak	15.6	Pass
		5720.0	-60.58	2.00	-58.58	Average	15.6	Pass
		5725.0	-42.58	2.00	-40.58	Peak	27.0	Pass
		5725.0	-59.88	2.00	-57.88	Average	27.0	Pass
	165	5850.0	-48.04	2.00	-46.04	Peak	27.0	Pass
		5850.0	-60.25	2.00	-58.25	Average	27.0	Pass
		5855.0	-48.06	2.00	-46.06	Peak	15.6	Pass
		5855.0	-60.38	2.00	-58.38	Average	15.6	Pass
		5875.0	-48.73	2.00	-46.73	Peak	10	Pass
		5875.0	-60.50	2.00	-58.50	Average	10	Pass
		5925.0	-48.91	2.00	-46.91	Peak	-27.0	Pass
		5925.0	-60.76	2.00	-58.76	Average	-27.0	Pass


Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11N40 SISO	151	5650.0	-48.90	2.00	-46.90	Peak	-27.0	Pass
		5650.0	-60.63	2.00	-58.63	Average	-27.0	Pass
		5700.0	-48.34	2.00	-46.34	Peak	10	Pass
		5700.0	-60.34	2.00	-58.34	Average	10	Pass
		5720.0	-48.00	2.00	-46.00	Peak	15.6	Pass
		5720.0	-59.69	2.00	-57.69	Average	15.6	Pass
		5725.0	-47.35	2.00	-45.35	Peak	27.0	Pass
		5725.0	-58.81	2.00	-56.81	Average	27.0	Pass
	159	5850.0	-49.01	2.00	-47.01	Peak	27.0	Pass
		5850.0	-59.88	2.00	-57.88	Average	27.0	Pass
		5855.0	-47.89	2.00	-45.89	Peak	15.6	Pass
		5855.0	-59.95	2.00	-57.95	Average	15.6	Pass
		5875.0	-48.73	2.00	-46.73	Peak	10	Pass
		5875.0	-60.05	2.00	-58.05	Average	10	Pass
		5925.0	-48.92	2.00	-46.92	Peak	-27.0	Pass
		5925.0	-60.38	2.00	-58.38	Average	-27.0	Pass
11AC20 SISO	149	5650.0	-49.04	2.00	-47.04	Peak	-27.0	Pass
		5650.0	-60.80	2.00	-58.80	Average	-27.0	Pass
		5700.0	-49.30	2.00	-47.30	Peak	10	Pass
		5700.0	-60.26	2.00	-58.26	Average	10	Pass
		5720.0	-48.33	2.00	-46.33	Peak	15.6	Pass
		5720.0	-60.51	2.00	-58.51	Average	15.6	Pass
		5725.0	-46.97	2.00	-44.97	Peak	27.0	Pass
		5725.0	-59.80	2.00	-57.80	Average	27.0	Pass
	165	5850.0	-47.50	2.00	-45.50	Peak	27.0	Pass
		5850.0	-60.23	2.00	-58.23	Average	27.0	Pass
		5855.0	-47.82	2.00	-45.82	Peak	15.6	Pass
		5855.0	-60.30	2.00	-58.30	Average	15.6	Pass
		5875.0	-48.77	2.00	-46.77	Peak	10	Pass
		5875.0	-60.46	2.00	-58.46	Average	10	Pass

		5925.0	-47.72	2.00	-45.72	Peak	-27.0	Pass
		5925.0	-60.72	2.00	-58.72	Average	-27.0	Pass
11AC4 0 SISO	151	5650.0	-47.77	2.00	-45.77	Peak	-27.0	Pass
		5650.0	-60.68	2.00	-58.68	Average	-27.0	Pass
		5700.0	-48.51	2.00	-46.51	Peak	10	Pass
		5700.0	-60.33	2.00	-58.33	Average	10	Pass
		5720.0	-48.21	2.00	-46.21	Peak	15.6	Pass
		5720.0	-59.69	2.00	-57.69	Average	15.6	Pass
		5725.0	-46.96	2.00	-44.96	Peak	27.0	Pass
		5725.0	-58.78	2.00	-56.78	Average	27.0	Pass
	159	5850.0	-47.64	2.00	-45.64	Peak	27.0	Pass
		5850.0	-59.80	2.00	-57.80	Average	27.0	Pass
		5855.0	-48.50	2.00	-46.50	Peak	15.6	Pass
		5855.0	-59.89	2.00	-57.89	Average	15.6	Pass
		5875.0	-48.88	2.00	-46.88	Peak	10	Pass
		5875.0	-60.05	2.00	-58.05	Average	10	Pass
		5925.0	-48.96	2.00	-46.96	Peak	-27.0	Pass
		5925.0	-60.33	2.00	-58.33	Average	-27.0	Pass
11AC8 0 SISO	155	5725.0	-48.26	2.00	-46.26	Peak	27.0	Pass
		5720.0	-48.06	2.00	-46.06	Peak	15.6	Pass
		5700.0	-49.00	2.00	-47.00	Peak	10	Pass
		5650.0	-48.74	2.00	-46.74	Peak	-27.0	Pass
		5725.0	-59.25	2.00	-57.25	Average	27.0	Pass
		5720.0	-59.36	2.00	-57.36	Average	15.6	Pass
		5700.0	-59.67	2.00	-57.67	Average	10	Pass
		5650.0	-59.99	2.00	-57.99	Average	-27.0	Pass
		5850.0	-48.26	2.00	-46.26	Peak	27.0	Pass
		5855.0	-48.06	2.00	-46.06	Peak	15.6	Pass
		5875.0	-49.00	2.00	-47.00	Peak	10	Pass
		5925.0	-48.74	2.00	-46.74	Peak	-27.0	Pass
		5850.0	-59.25	2.00	-57.25	Average	27.0	Pass
		5855.0	-59.36	2.00	-57.36	Average	15.6	Pass
		5875.0	-59.67	2.00	-57.67	Average	10	Pass
		5925.0	-59.99	2.00	-57.99	Average	-27.0	Pass

Undesirable Emissions Measurement




IEEE 802.11a / Channel 149 / 5745MHz / Peak




IEEE 802.11a / Channel 148 / 5745MHz / Average

Undesirable Emissions Measurement




IEEE 802.11a / Channel 165 / 5825MHz / Peak




IEEE 802.11a / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n20 / Channel 149 / 5745MHz / Peak




IEEE 802.11n20 / Channel 149 / 5745MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n20 / Channel 165 / 5825MHz / Peak




IEEE 802.11n20 / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 151 / 5755MHz / Peak




IEEE 802.11n40 / Channel 151 / 5755MHz / Average


Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 159 / 5795MHz / Peak




IEEE 802.11n40 / Channel 159 / 5795MHz / Average




IEEE 802.11ac20 / Channel 149 / 5745MHz / Peak




IEEE 802.11ac20 / Channel 149 / 5745MHz / Average




IEEE 802.11ac20 / Channel 165 / 5825MHz / Peak




IEEE 802.11ac20 / Channel 165 / 5825MHz / Average




IEEE 802.11ac40 / Channel 151 / 5755MHz / Peak




IEEE 802.11ac40 / Channel 151 / 5755MHz / Average




IEEE 802.11ac40 / Channel 159 / 5795MHz / Peak




IEEE 802.11ac40 / Channel 159 / 5795MHz / Average




IEEE 802.11ac80 / Channel 155 / 5775MHz / Peak



IEEE 802.11ac80 / Channel 155 / 5775MHz / Average



IEEE 802.11ac80 / Channel 155/ 5775MHz / Peak



IEEE 802.11ac80 / Channel 155 / 5775MHz / Average