

FCC TEST REPORT

For

EmdoorVR Technology Co., Ltd

All-in-One VR

Test Model: EM_A839

Prepared for	:	EmdoorVR Technology Co., Ltd
Address	:	Meigu bld, Wonderful life wisdom Valley technology Park, No.83 Dabao RD., Xin an ST, Baoan dist., Shenzhen, China
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	November 28, 2019
Number of tested samples	:	1
Serial number	:	Prototype
Date of Test	:	November 28, 2019 ~ January 17, 2020
Date of Report	:	January 20, 2020

FCC TEST REPORT
FCC CFR 47 PART 15E (15.407)**Report Reference No.** : **LCS191023060AED**

Date of Issue : January 20, 2020

Testing Laboratory Name : **Shenzhen LCS Compliance Testing Laboratory Ltd.**Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street,
Baoan District, Shenzhen, ChinaTesting Location/ Procedure : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name** : **EmdoorVR Technology Co., Ltd**Address : Meigu bld, Wonderful life wisdom Valley technology Park, No.83
Dabao RD., Xin an ST, Baoan dist., Shenzhen, China**Test Specification**

Standard : FCC CFR 47 PART 15E (15.407)

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description. : **All-in-One VR**

Trade Mark : Firepack

Test Model : EM_A839

DC 3.8V by Li-ion Battery(2100mAh)

Ratings : Adapter Input: AC 100-240V, 50/60Hz, 0.5A


Adapter Output: DC 5V/3A, 9V/2A, 12V/1.5A

Result : **Positive****Supervised by:**

Jin Wang/ Technique principal

Compiled by:

Linda He / File administrators

Approved by:

Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCS191023060AED	January 20, 2020 Date of issue
-----------------------------------	-----------------------------------

EUT.....	: All-in-One VR
Test Model.....	: EM_A839
Applicant.....	: EmdoorVR Technology Co., Ltd
Address.....	: Meigu bld, Wonderful life wisdom Valley technology Park, No.83 Dabao RD., Xin an ST, Baoan dist., Shenzhen, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: EmdoorVR Technology Co., Ltd
Address.....	: Meigu bld, Wonderful life wisdom Valley technology Park, No.83 Dabao RD., Xin an ST, Baoan dist., Shenzhen, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Visionsky (SZ) Industrial Co., Ltd Shiyan Branch
Address.....	: Floor 4,1 Bldg A, No.34 Shilong Ave, Shuitian District, Shiyan St, Baoan district, Shenzhen, China
Telephone.....	: /
Fax.....	: /

Test Result:	Positive
--------------	----------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	January 20, 2020	Initial Issue	Gavin Liang

TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. DESCRIPTION OF DEVICE (EUT)	6
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	7
1.3. EXTERNAL I/O PORT	7
1.4. DESCRIPTION OF TEST FACILITY	7
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
1.6. MEASUREMENT UNCERTAINTY	8
1.7. DESCRIPTION OF TEST MODES	8
1.8. CHANNEL LIST AND FREQUENCY	9
1.9. DIRECTIONAL ANTENNA GAIN	9
2. TEST METHODOLOGY	10
2.1. EUT CONFIGURATION	10
2.2. EUT EXERCISE	10
2.3. GENERAL TEST PROCEDURES	10
3. SYSTEM TEST CONFIGURATION	11
3.1. JUSTIFICATION	11
3.2. EUT EXERCISE SOFTWARE	11
3.3. SPECIAL ACCESSORIES	11
3.4. BLOCK DIAGRAM/SCHEMATICS	11
3.5. EQUIPMENT MODIFICATIONS	11
3.6. TEST SETUP	11
4. SUMMARY OF TEST RESULTS	12
5. TEST RESULT	13
5.1. ON TIME AND DUTY CYCLE	13
5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT	14
5.3. POWER SPECTRAL DENSITY MEASUREMENT	16
5.4. 26dB OCCUPIED BANDWIDTH MEASUREMENT	18
5.5. 99% OCCUPIED BANDWIDTH MEASUREMENT	19
5.6. RADIATED EMISSIONS MEASUREMENT	20
5.7. POWER LINE CONDUCTED EMISSIONS	42
5.8 UNDESIRABLE EMISSIONS MEASUREMENT	49
5.9. FREQUENCY STABILITY	52
5.10. ANTENNA REQUIREMENTS	54
6. LIST OF MEASURING EQUIPMENTS	55
7. TEST SETUP PHOTOGRAPHS OF EUT	56
8. EXTERIOR PHOTOGRAPHS OF THE EUT	56
9. INTERIOR PHOTOGRAPHS OF THE EUT	56

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: All-in-One VR
Test Model	: EM_A839 DC 3.8V by Li-ion Battery(2100mAh)
Power Supply	: Adapter Input: AC 100-240V, 50/60Hz, 0.5A Adapter Output: DC 5V/3A, 9V/2A, 12V/1.5A
Hardware Version	: EM_A839_MB_V1.1
Software Version	: VR1103/20191025105352
Bluetooth	:
Frequency Range	: 2402MHz ~ 2480MHz
Channel Number	: 79 channels for Bluetooth V4.0 (DSS) 40 channels for Bluetooth V4.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V4.0 (DSS) 2MHz for Bluetooth V4.0 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.0 (DSS) GFSK for Bluetooth V4.0 (DTS)
Bluetooth Version	: V4.0
2.4G WLAN	:
Frequency Range	: 2412MHz ~ 2462 MHz
Channel Spacing	: 5MHz
Channel Number	: 11 channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth(2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK,DQPSK,DBPSK); IEEE 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
5G WLAN	:
Frequency Range	: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz 4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz)
Channel Number	: 5 Channels for 40MHz bandwidth(5510-5670MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 Channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5290MHz) 2 Channels for 80MHz bandwidth(5530-5610MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a/n/ac: OFDM (64QAM, 16QAM, QPSK, BPSK) Internal Antenna(ANT 0), used for WIFI TX/RX,
Antenna Description	: 2.0dBi(Max.) for 2.4G Band, 1.9dBi(Max.) for 5G Band; Internal Antenna(ANT 1), used for WIFI/Bluetooth TX/RX, 2.0dBi(Max.) for 2.4G Band, 1.9dBi(Max.) for 5G Band

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
--	Adapter	A138A-150U-CNA	/	S Doc

Note: Support equipment is provided by the laboratory

1.3. External I/O Port

I/O Port Description	Quantity	Cable
Micro USB Port	1	N/A
AUX Port	1	N/A
TF Port	1	N/A

1.4. Description of Test Facility

FCC Registration Number is 254912.

Industry Canada Registration Number is 9642A.

EMSD Registration Number is ARCB0108.

UL Registration Number is 100571-492.

TUV SUD Registration Number is SCN1081.

TUV RH Registration Number is UA 50296516-001.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	±3.10dB	(1)
	:	30MHz~200MHz	±2.96dB	(1)
	:	200MHz~1000MHz	±3.10dB	(1)
	:	1GHz~26.5GHz	±3.80dB	(1)
	:	26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	±1.63dB	(1)
Power disturbance	:	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, which was determined to be IEEE 802.11ac VHT20 mode (High Channel, at Antenna Chain0).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11ac VHT20 mode (High Channel, at Antenna Chain0).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

IEEE 802.11a Mode: 6 Mbps, OFDM.

IEEE 802.11ac VHT20 Mode: MCS0

IEEE 802.11n HT20 Mode: MCS0, OFDM.

IEEE 802.11ac VHT40 Mode: MCS0, OFDM.

IEEE 802.11n HT40 Mode: MCS0, OFDM.

IEEE 802.11ac VHT80 Mode: MCS0, OFDM.

Antenna & Bandwidth

Antenna	Chain0 (ANT0)			Chain1 (ANT1)			Simultaneously
Bandwidth Mode	20MHz	40MHz	80MHz	20MHz	40MHz	80MHz	/
IEEE 802.11a	☒	☐	☐	☒	☐	☐	☐
IEEE 802.11n	☒	☒	☐	☒	☒	☐	☒
IEEE 802.11ac	☒	☒	☒	☒	☒	☒	☒

1.8. Channel List and Frequency

U-NI-1

Frequency Band	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
5180~5240MHz	36	5180	44	5220
	38	5190	46	5230
	40	5200	48	5240
	42	5210	/	/

For IEEE 802.11a/n HT20/ac VHT20, Channel 36, 40 and 48 were tested.

For IEEE 802.11n HT40/ac VHT40, Channel 38 and 46 were tested.

For IEEE 802.11ac VHT80, Channel 42 was tested.

U-NI-2A

Frequency Band	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
5260~5320MHz	52	5260	60	5300
	54	5270	62	5310
	56	5280	64	5320
	58	5290	/	/

For IEEE 802.11a/n HT20/ac VHT20, Channel 52, 56 and 64 were tested.

For IEEE 802.11n HT40/ac VHT40, Channel 54 and 62 were tested.

For IEEE 802.11ac VHT80, Channel 58 was tested.

U-NI-2C

Frequency Band	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
5500~5700MHz	100	5500	112	5560
	102	5510	114	5570
	104	5520	116	5580
	106	5530	132	5660
	108	5540	134	5670
	110	5550	140	5700

For IEEE 802.11a/n HT20/ac VHT20, Channel 100, 132 and 140 were tested.

For IEEE 802.11n HT40/ac VHT40, Channel 102, 110 and 134 were tested.

For IEEE 802.11ac VHT80, Channel 106 were tested.

1.9. Directional Antenna Gain

The TX chains are correlated and antenna gain is unequal among the chains. The directional gain is:

Antenna 0 Gain (dBi)	Antenna 1 Gain (dBi)	Correlated Chains Directional Gain (dBi)
1.9	1.9	4.91

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB789033 D02 General UNII Test Procedures New Rules v02r01 and KDB 662911 D01 Multiple Transmitter Output v02r01 are required to be used for this kind of FCC 15.407 UII device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz and 1.5 m above ground plane above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software provided by application.

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart E			
FCC Rules	Description of Test	Result	Remark
/	On Time and Duty Cycle	/	Only reported; Appendix D.1
§15.407(a)	Maximum Conducted Output Power	Compliant	Appendix D.2
§15.407(a)	Power Spectral Density	Compliant	Appendix D.3
§15.407(a)	26dB Bandwidth	Compliant	Appendix D.4
§2.1049	99% Occupied Bandwidth	Compliant	Appendix D.4
§15.209, §15.407(b)	Radiated Emissions	Compliant	Note 1
§15.209, §15.407(b)	Band edge Emissions	Compliant	Appendix D.5
§15.407(g)	Frequency Stability	Compliant	Note 1
§15.207(a)	AC Conducted Emissions	Compliant	Note 1
§15.203	Antenna Requirements	Compliant	Note 1
§15.407 §2.1093	RF Exposure	Compliant	Note 2

Remark:

1. Note 1 – Test results inside test report;
2. Note 2 – Test results in other test report (Maximum Permissible Exposure Report);

5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None; for reporting purpose only


5.1.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

5.1.3. Test Procedures

- 1). Set the Centre frequency of the spectrum analyzer to the transmitting frequency;
- 2). Set the span=0MHz, RBW=8MHz, VBW=50MHz, Sweep time=10.13ms;
- 3). Detector = peak;
- 4). Trace mode = Single hold.

5.1.4. Test Setup Layout



5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test result

For reporting purpose only.

Please refer to Appendix D.1

5.2. Maximum Conducted Output Power Measurement

5.2.1. Standard Applicable

(1) For the band 5.15~5.25GHz

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the band 5.25-5.35 GHz and 5.47-5.725 GHz

The maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the power meter.

5.2.3. Test Procedures


The transmitter output (antenna port) was connected to the power meter.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Section 3 (a) Method PM (Measurement using an RF average power meter):

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.
 - The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
 - At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.

- The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in section II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- (iv) Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log (1/0.25)$ if the duty cycle is 25%).

5.2.4. Test Setup Layout



5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.6. Test Result of Maximum Conducted Output Power

Limits

UNII Band 1

Mode	Antenna 0 Gain (dBi)	Antenna 1 Gain (dBi)	Directional Gain (dBi)	Power Limit (dBm)	Maximum Power (dBm)
IEEE 802.11n/ac	1.9	1.9	4.91	24.00	24.00

UNII Band 2A and UNII Band 2C

Mode	Antenna 0 Gain (dBi)	Antenna 1 Gain (dBi)	Directional Gain (dBi)	Power Limit (dBm)	Maximum Power (dBm)
IEEE 802.11n/ac	1.9	1.9	4.91	24.00	24.00

PASS

Please refer to Appendix D.2

Remark:

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80;
4. Report conducted power = Measured conducted average power + Duty Cycle factor;
5. For power measurements on IEEE 802.11 devices;
 - Array Gain = 0 dB (i.e., no array gain) for $NANT \leq 4$;
 - Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;
 - Array Gain = $5 \log (NANT/NS)$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $NANT \geq 5$.

5.3. Power Spectral Density Measurement

5.3.1. Standard Applicable

For 5.15~5.25GHz

- (i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.note1
- (ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.note1
- (iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.
- (iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. note1

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.25-5.35 GHz and 5.47-5.725 GHz

The maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


5.3.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.3.3. Test Procedures

- 1). The transmitter was connected directly to a Spectrum Analyzer through a directional couple.
- 2). The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
- 3). Set the RBW = 1MHz.
- 4). Set the VBW $\geq$ 3MHz
- 5). Span=Encompass the entire emissions bandwidth (EBW) of the signal (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- 6). Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- 7). Manually set sweep time $\geq 10 \times (\text{number of points in sweep}) \times (\text{total on/off period of the transmitted signal})$.
- 8). Set detector = power averaging (rms).
- 9). Sweep time = auto couple.
- 10). Trace mode = max hold.
- 11). Allow trace to fully stabilize.
- 12). Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively).
- 13). Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add $10 \log (1/0.25) = 6 \text{ dB}$ if the duty cycle is 25%.
- 14). Use the peak marker function to determine the maximum power level in any 1MHz band segment within the fundamental EBW.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.6. Test Result of Power Spectral Density

Limits**UNII Band 1**

Mode	Antenna 0 Gain (dBi)	Antenna 1 Gain (dBi)	Directional Gain (dBi)	PSD Limit (dBm)	Maximum PSD (dBm)
IEEE 802.11n/ac	1.9	1.9	4.91	11.00	11.00

UNII Band 2A and UNII Band 2C

Mode	Antenna 0 Gain (dBi)	Antenna 1 Gain (dBi)	Directional Gain (dBi)	PSD Limit (dBm)	Maximum PSD (dBm)
IEEE 802.11n/ac	1.9	1.9	4.91	11.00	11.00

PASS

Please refer to Appendix D.3

Remark

1. Measured power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80;
4. Report conducted PSD = Measured conducted average power + Duty Cycle factor;
5. For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain.
Array gain = $10 \log (N_{ant})$, where N_{ant} is the number of transmit antennas

5.4. 26dB Occupied Bandwidth Measurement

5.4.1. Standard Applicable

No restriction limits. But resolution bandwidth within band edge measurement is 1% of the 99% occupied bandwidth.

5.4.2. Measuring Instruments and Setting


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span	> 26dB Bandwidth
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The RBW = 1% - 3% of occupied bandwidth, VBW = 3*RBW;
3. Measured the spectrum width with power higher than 26dB below carrier.

5.4.4. Test Setup Layout



5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.6. Test Result of 99% and 26dB Occupied Bandwidth

PASS

Please refer to Appendix D.4

Remark:

1. Measured 26dB bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80;

5.5. 99% Occupied Bandwidth Measurement

5.5.1. Standard Applicable

According to §2.1049: The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable.

5.5.2. Measuring Instruments and Setting


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Set RBW = 1%~5% OBW; VBW $\geq$ 3*RBW;
3. Measured the 99% occupied bandwidth by related function of the spectrum analyzer.

5.5.4. Test Setup Layout



5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.6. Test Result of 99% Occupied Spectrum Bandwidth

PASS

Please refer to Appendix D.4

Remark:

1. Measured 99% bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80;

5.6. Radiated Emissions Measurement

5.6.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz (68.2dBuV/m at 3m).

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

5.6.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 ^m carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

5.6.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 0.8 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 1 meter.

--- The EUT was set into operation.

Premeasurement:


--- The antenna is moved spherical over the EUT in different polarizations of the antenna.

Final measurement:


--- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


5.6.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.6.6. Results of Radiated Emissions (9 KHz~30MHz)

Temperature	23.6℃	Humidity	52.6%
Test Engineer	Alisa Huang	Configurations	IEEE 802.11a/n/ac

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dB)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.

5.6.7. Results of Radiated Emissions (30MHz~1GHz)

Temperature	23.6℃	Humidity	52.6%
Test Engineer	Alisa Huang	Configurations	IEEE 802.11 ac VHT20 mode

Test result for IEEE 802.11ac VHT20 mode

5.2G Horizontal



Site:

Antenna::Horizontal Temperature(C):23.6(C)


Limit:

FCC Part15 RE-Class B_30-1000MHz

Humidity(%):52.6%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	43.0505	39.65	-16.82	22.83	40.00	-17.17	QP
2	55.8047	46.31	-17.31	29.00	40.00	-11.00	QP
3	70.5836	48.36	-20.58	27.78	40.00	-12.22	QP
4	89.5899	39.00	-20.05	18.95	43.50	-24.55	QP
5	344.3855	37.21	-14.51	22.70	46.00	-23.30	QP
6 *	501.1790	49.38	-11.43	37.95	46.00	-8.05	QP

Vertical



Site:

Antenna::Vertical

Temperature(C):23.6(C)


Limit:

FCC Part15 RE-Class B_30-1000MHz

Humidity(%):52.6%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	30.5306	36.64	-19.18	17.46	40.00	-22.54	QP
2 *	43.6584	35.62	-16.71	18.91	40.00	-21.09	QP
3	102.0013	31.07	-18.36	12.71	43.50	-30.79	QP
4	140.8350	33.44	-21.98	11.46	43.50	-32.04	QP
5	275.1570	33.85	-16.17	17.68	46.00	-28.32	QP
6	701.7610	29.99	-8.30	21.69	46.00	-24.31	QP

5.3G Horizontal



Site:

Antenna::Horizontal Temperature(C):23.6(C)


Limit:

FCC Part15 RE-Class B_30-1000MHz

Humidity(%):52.6%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	43.6584	36.30	-16.71	19.59	40.00	-20.41	QP
2	68.1514	33.72	-20.02	13.70	40.00	-26.30	QP
3	82.9385	34.45	-21.58	12.87	40.00	-27.13	QP
4	157.5588	35.58	-21.35	14.23	43.50	-29.27	QP
5	250.3012	35.10	-16.69	18.41	46.00	-27.59	QP
6	319.9370	34.22	-15.15	19.07	46.00	-26.93	QP

Vertical



Site:

Antenna::Vertical

Temperature(C):23.6(C)


Limit:

FCC Part15 RE-Class B_30-1000MHz

Humidity(%):52.6%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	43.6584	31.44	-16.71	14.73	40.00	-25.27	QP
2	57.9992	30.88	-17.66	13.22	40.00	-26.78	QP
3	74.6568	33.32	-21.30	12.02	40.00	-27.98	QP
4	171.3925	32.55	-20.63	11.92	43.50	-31.58	QP
5	270.3747	33.81	-16.25	17.56	46.00	-28.44	QP
6	729.3582	28.47	-7.95	20.52	46.00	-25.48	QP

5.5G Horizontal



Site:

Antenna::Horizontal Temperature(C):23.6(C)


Limit:

FCC Part15 RE-Class B_30-1000MHz

Humidity(%):52.6%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	43.6584	36.11	-16.71	19.40	40.00	-20.60	QP
2	68.3907	37.59	-20.08	17.51	40.00	-22.49	QP
3	101.6443	34.82	-18.37	16.45	43.50	-27.05	QP
4	158.1123	39.66	-21.33	18.33	43.50	-25.17	QP
5	250.3010	35.01	-16.69	18.32	46.00	-27.68	QP
6	434.0649	32.11	-12.67	19.44	46.00	-26.56	QP

Vertical



Site:

Antenna::Vertical

Temperature(C):23.6(C)

Limit:

FCC Part15 RE-Class B_30-1000MHz

Humidity(%):52.6%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	30.4237	37.53	-19.18	18.35	40.00	-21.65	QP
2	43.6584	34.48	-16.71	17.77	40.00	-22.23	QP
3	58.8185	32.54	-17.79	14.75	40.00	-25.25	QP
4	101.2883	30.84	-18.36	12.48	43.50	-31.02	QP
5	157.5587	32.77	-21.35	11.42	43.50	-32.08	QP
6	319.9368	32.81	-15.15	17.66	46.00	-28.34	QP

Note:

(1). Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11ac VHT20 mode).

(2). Emission level (dBuV/m) = 20 log Emission level (uV/m).

(3). Reading + Factor = Level, Level – Limit = Margin

Factor= Antenna Factor - Cable Loss - Preamp Factor

5.6.8. Results for Radiated Emissions (1 – 40 GHz)

Note: All the modes have been tested and recorded worst mode in the report.

ANT0 (worst mode) – UNII Band 1

IEEE 802.11a

Channel 36 / 5180 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.54	45.95	33.21	35.82	9.52	52.86	68.20	-15.34	Peak	Horizontal
15.54	35.60	33.21	35.82	9.52	42.51	54.00	-11.49	Average	Horizontal
15.54	42.30	32.82	35.82	9.52	48.82	68.20	-19.38	Peak	Vertical
15.54	40.24	32.82	35.82	9.52	46.76	54.00	-7.24	Average	Vertical

Channel 40 / 5200 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.60	45.35	33.21	35.82	9.52	52.26	68.20	-15.94	Peak	Horizontal
15.60	38.85	33.21	35.82	9.52	45.76	54.00	-8.24	Average	Horizontal
15.60	42.01	32.82	35.82	9.52	48.53	68.20	-19.67	Peak	Vertical
15.60	32.13	32.82	35.82	9.52	38.65	54.00	-15.35	Average	Vertical

Channel 48 / 5240 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.72	43.02	33.21	35.82	9.52	49.93	68.20	-18.27	Peak	Horizontal
15.72	30.87	33.21	35.82	9.52	37.78	54.00	-16.22	Average	Horizontal
15.72	44.48	32.82	35.82	9.52	51.00	68.20	-17.20	Peak	Vertical
15.72	38.32	32.82	35.82	9.52	44.84	54.00	-9.16	Average	Vertical

ANT0+ANT1 (worst mode) – UNII Band 1

IEEE 802.11n HT20

Channel 36 / 5180 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.54	45.83	33.21	35.82	9.52	52.74	68.20	-15.46	Peak	Horizontal
15.54	31.94	33.21	35.82	9.52	38.85	54.00	-15.15	Average	Horizontal
15.54	44.87	32.82	35.82	9.52	51.39	68.20	-16.81	Peak	Vertical
15.54	32.45	32.82	35.82	9.52	38.97	54.00	-15.03	Average	Vertical

Channel 40 / 5200 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.60	47.36	33.21	35.82	9.52	54.27	68.20	-13.93	Peak	Horizontal
15.60	31.65	33.21	35.82	9.52	38.56	54.00	-15.44	Average	Horizontal
15.60	47.92	32.82	35.82	9.52	54.44	68.20	-13.76	Peak	Vertical
15.60	33.90	32.82	35.82	9.52	40.42	54.00	-13.58	Average	Vertical

Channel 48 / 5240 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.72	44.65	33.21	35.82	9.52	51.56	68.20	-16.64	Peak	Horizontal
15.72	33.09	33.21	35.82	9.52	40.00	54.00	-14.00	Average	Horizontal
15.72	41.50	32.82	35.82	9.52	48.02	68.20	-20.18	Peak	Vertical
15.72	32.33	32.82	35.82	9.52	38.85	54.00	-15.15	Average	Vertical

IEEE 802.11ac VHT20

Channel 36 / 5180 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.54	46.90	33.21	35.82	9.52	53.81	68.20	-14.39	Peak	Horizontal
15.54	35.71	33.21	35.82	9.52	42.62	54.00	-11.38	Average	Horizontal
15.54	48.58	32.82	35.82	9.52	55.10	68.20	-13.10	Peak	Vertical
15.54	37.42	32.82	35.82	9.52	43.94	54.00	-10.06	Average	Vertical

Channel 40 / 5200 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.60	40.33	33.21	35.82	9.52	47.24	68.20	-20.96	Peak	Horizontal
15.60	34.33	33.21	35.82	9.52	41.24	54.00	-12.76	Average	Horizontal
15.60	46.25	32.82	35.82	9.52	52.77	68.20	-15.43	Peak	Vertical
15.60	39.18	32.82	35.82	9.52	45.70	54.00	-8.30	Average	Vertical

Channel 48 / 5240 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.72	42.72	33.21	35.82	9.52	49.63	68.20	-18.57	Peak	Horizontal
15.72	33.24	33.21	35.82	9.52	40.15	54.00	-13.85	Average	Horizontal
15.72	43.40	32.82	35.82	9.52	49.92	68.20	-18.28	Peak	Vertical
15.72	35.82	32.82	35.82	9.52	42.34	54.00	-11.66	Average	Vertical

IEEE 802.11n HT40

Channel 38 / 5190 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.57	43.18	33.21	35.82	9.52	50.09	68.20	-18.11	Peak	Horizontal
15.57	34.85	33.21	35.82	9.52	41.76	54.00	-12.24	Average	Horizontal
15.57	48.30	32.82	35.82	9.52	54.82	68.20	-13.38	Peak	Vertical
15.57	38.35	32.82	35.82	9.52	44.87	54.00	-9.13	Average	Vertical

Channel 46 / 5230 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.69	48.66	33.21	35.82	9.52	55.57	68.20	-12.63	Peak	Horizontal
15.69	32.20	33.21	35.82	9.52	39.11	54.00	-14.89	Average	Horizontal
15.69	40.67	32.82	35.82	9.52	47.19	68.20	-21.01	Peak	Vertical
15.69	30.36	32.82	35.82	9.52	36.88	54.00	-17.12	Average	Vertical

IEEE 802.11ac VHT40

Channel 38 / 5190 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.57	48.34	33.21	35.82	9.52	55.25	68.20	-12.95	Peak	Horizontal
15.57	37.18	33.21	35.82	9.52	44.09	54.00	-9.91	Average	Horizontal
15.57	47.30	32.82	35.82	9.52	53.82	68.20	-14.38	Peak	Vertical
15.57	33.29	32.82	35.82	9.52	39.81	54.00	-14.19	Average	Vertical

Channel 46 / 5230 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.69	42.66	33.21	35.82	9.52	49.57	68.20	-18.63	Peak	Horizontal
15.69	37.55	33.21	35.82	9.52	44.46	54.00	-9.54	Average	Horizontal
15.69	43.62	32.82	35.82	9.52	50.14	68.20	-18.06	Peak	Vertical
15.69	34.66	32.82	35.82	9.52	41.18	54.00	-12.82	Average	Vertical

IEEE 802.11ac VHT80

Channel 42 / 5210 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.63	41.13	33.21	35.82	9.52	48.04	68.20	-20.16	Peak	Horizontal
15.63	37.81	33.21	35.82	9.52	44.72	54.00	-9.28	Average	Horizontal
15.63	49.95	32.82	35.82	9.52	56.47	68.20	-11.73	Peak	Vertical
15.63	30.34	32.82	35.82	9.52	36.86	54.00	-17.14	Average	Vertical

ANT0 (worst mode) – UNII Band 2A

IEEE 802.11a

Channel 52 / 5260 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.78	43.60	33.21	35.82	9.52	50.51	68.20	-17.69	Peak	Horizontal
15.78	32.34	33.21	35.82	9.52	39.25	54.00	-14.75	Average	Horizontal
15.78	50.63	32.82	35.82	9.52	57.15	68.20	-11.05	Peak	Vertical
15.78	30.60	32.82	35.82	9.52	37.12	54.00	-16.88	Average	Vertical

Channel 56 / 5280 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.84	49.71	33.21	35.82	9.52	56.62	68.20	-11.58	Peak	Horizontal
15.84	38.99	33.21	35.82	9.52	45.90	54.00	-8.10	Average	Horizontal
15.84	47.18	32.82	35.82	9.52	53.70	68.20	-14.50	Peak	Vertical
15.84	33.44	32.82	35.82	9.52	39.96	54.00	-14.04	Average	Vertical

Channel 64 / 5320 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.96	41.69	33.21	35.82	9.52	48.60	68.20	-19.60	Peak	Horizontal
15.96	36.75	33.21	35.82	9.52	43.66	54.00	-10.34	Average	Horizontal
15.96	49.04	32.82	35.82	9.52	55.56	68.20	-12.64	Peak	Vertical
15.96	32.15	32.82	35.82	9.52	38.67	54.00	-15.33	Average	Vertical

ANT0+ANT1 (worst mode) – UNII Band 2A

IEEE 802.11n HT20

Channel 52 / 5260 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.78	42.83	33.21	35.82	9.52	49.74	68.20	-18.46	Peak	Horizontal
15.78	30.92	33.21	35.82	9.52	37.83	54.00	-16.17	Average	Horizontal
15.78	41.65	32.82	35.82	9.52	48.17	68.20	-20.03	Peak	Vertical
15.78	40.34	32.82	35.82	9.52	46.86	54.00	-7.14	Average	Vertical

Channel 56 / 5280 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.84	44.06	33.21	35.82	9.52	50.97	68.20	-17.23	Peak	Horizontal
15.84	33.28	33.21	35.82	9.52	40.19	54.00	-13.81	Average	Horizontal
15.84	47.00	32.82	35.82	9.52	53.52	68.20	-14.68	Peak	Vertical
15.84	36.24	32.82	35.82	9.52	42.76	54.00	-11.24	Average	Vertical

Channel 64 / 5320 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.96	40.84	33.21	35.82	9.52	47.75	68.20	-20.45	Peak	Horizontal
15.96	37.36	33.21	35.82	9.52	44.27	54.00	-9.73	Average	Horizontal
15.96	42.38	32.82	35.82	9.52	48.90	68.20	-19.30	Peak	Vertical
15.96	33.62	32.82	35.82	9.52	40.14	54.00	-13.86	Average	Vertical

IEEE 802.11ac VHT20

Channel 52 / 5260 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.78	40.08	33.21	35.82	9.52	46.99	68.20	-21.21	Peak	Horizontal
15.78	38.82	33.21	35.82	9.52	45.73	54.00	-8.27	Average	Horizontal
15.78	43.07	32.82	35.82	9.52	49.59	68.20	-18.61	Peak	Vertical
15.78	32.01	32.82	35.82	9.52	38.53	54.00	-15.47	Average	Vertical

Channel 56 / 5280 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.84	49.02	33.21	35.82	9.52	55.93	68.20	-12.27	Peak	Horizontal
15.84	38.68	33.21	35.82	9.52	45.59	54.00	-8.41	Average	Horizontal
15.84	50.80	32.82	35.82	9.52	57.32	68.20	-10.88	Peak	Vertical
15.84	39.50	32.82	35.82	9.52	46.02	54.00	-7.98	Average	Vertical

Channel 64 / 5320 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.96	49.33	33.21	35.82	9.52	56.24	68.20	-11.96	Peak	Horizontal
15.96	31.03	33.21	35.82	9.52	37.94	54.00	-16.06	Average	Horizontal
15.96	50.77	32.82	35.82	9.52	57.29	68.20	-10.91	Peak	Vertical
15.96	31.09	32.82	35.82	9.52	37.61	54.00	-16.39	Average	Vertical

IEEE 802.11n HT40

Channel 54 / 5270 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.81	47.94	33.21	35.82	9.52	54.85	68.20	-13.35	Peak	Horizontal
15.81	36.71	33.21	35.82	9.52	43.62	54.00	-10.38	Average	Horizontal
15.81	46.42	32.82	35.82	9.52	52.94	68.20	-15.26	Peak	Vertical
15.81	30.68	32.82	35.82	9.52	37.20	54.00	-16.80	Average	Vertical

Channel 62 / 5310 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.93	42.81	33.21	35.82	9.52	49.72	68.20	-18.48	Peak	Horizontal
15.93	33.15	33.21	35.82	9.52	40.06	54.00	-13.94	Average	Horizontal
15.93	43.71	32.82	35.82	9.52	50.23	68.20	-17.97	Peak	Vertical
15.93	33.23	32.82	35.82	9.52	39.75	54.00	-14.25	Average	Vertical

IEEE 802.11ac VHT40

Channel 54 / 5270 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.81	40.47	33.21	35.82	9.52	47.38	68.20	-20.82	Peak	Horizontal
15.81	31.25	33.21	35.82	9.52	38.16	54.00	-15.84	Average	Horizontal
15.81	47.67	32.82	35.82	9.52	54.19	68.20	-14.01	Peak	Vertical
15.81	33.24	32.82	35.82	9.52	39.76	54.00	-14.24	Average	Vertical

Channel 62 / 5310 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.93	48.19	33.21	35.82	9.52	55.10	68.20	-13.10	Peak	Horizontal
15.93	34.13	33.21	35.82	9.52	41.04	54.00	-12.96	Average	Horizontal
15.93	44.35	32.82	35.82	9.52	50.87	68.20	-17.33	Peak	Vertical
15.93	36.55	32.82	35.82	9.52	43.07	54.00	-10.93	Average	Vertical

IEEE 802.11ac VHT80

Channel 58 / 5290 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
15.87	48.94	33.21	35.82	9.52	55.85	68.20	-12.35	Peak	Horizontal
15.87	33.45	33.21	35.82	9.52	40.36	54.00	-13.64	Average	Horizontal
15.87	41.25	32.82	35.82	9.52	47.77	68.20	-20.43	Peak	Vertical
15.87	32.03	32.82	35.82	9.52	38.55	54.00	-15.45	Average	Vertical

ANT0 (worst mode) – UNII Band 2C

IEEE 802.11a

Channel 100 / 5500 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.50	50.31	33.21	35.82	9.52	57.22	68.20	-10.98	Peak	Horizontal
16.50	33.37	33.21	35.82	9.52	40.28	54.00	-13.72	Average	Horizontal
16.50	47.90	32.82	35.82	9.52	54.42	68.20	-13.78	Peak	Vertical
16.50	34.81	32.82	35.82	9.52	41.33	54.00	-12.67	Average	Vertical

Channel 116 / 5580 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.74	45.89	33.21	35.82	9.52	52.80	68.20	-15.40	Peak	Horizontal
16.74	38.81	33.21	35.82	9.52	45.72	54.00	-8.28	Average	Horizontal
16.74	48.12	32.82	35.82	9.52	54.64	68.20	-13.56	Peak	Vertical
16.74	33.44	32.82	35.82	9.52	39.96	54.00	-14.04	Average	Vertical

Channel 140 / 5700 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
17.10	44.49	33.21	35.82	9.52	51.40	68.20	-16.80	Peak	Horizontal
17.10	36.15	33.21	35.82	9.52	43.06	54.00	-10.94	Average	Horizontal
17.10	45.34	32.82	35.82	9.52	51.86	68.20	-16.34	Peak	Vertical
17.10	37.32	32.82	35.82	9.52	43.84	54.00	-10.16	Average	Vertical

ANT0+ANT1 (worst mode) – UNII Band 2C

IEEE 802.11n HT20

Channel 100 / 5500 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.50	48.78	33.21	35.82	9.52	55.69	68.20	-12.51	Peak	Horizontal
16.50	31.09	33.21	35.82	9.52	38.00	54.00	-16.00	Average	Horizontal
16.50	40.21	32.82	35.82	9.52	46.73	68.20	-21.47	Peak	Vertical
16.50	31.63	32.82	35.82	9.52	38.15	54.00	-15.85	Average	Vertical

Channel 116 / 5580 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.74	49.42	33.21	35.82	9.52	56.33	68.20	-11.87	Peak	Horizontal
16.74	34.79	33.21	35.82	9.52	41.70	54.00	-12.30	Average	Horizontal
16.74	46.22	32.82	35.82	9.52	52.74	68.20	-15.46	Peak	Vertical
16.74	39.05	32.82	35.82	9.52	45.57	54.00	-8.43	Average	Vertical

Channel 140 / 5700 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
17.10	48.39	33.21	35.82	9.52	55.30	68.20	-12.90	Peak	Horizontal
17.10	39.20	33.21	35.82	9.52	46.11	54.00	-7.89	Average	Horizontal
17.10	40.73	32.82	35.82	9.52	47.25	68.20	-20.95	Peak	Vertical
17.10	34.44	32.82	35.82	9.52	40.96	54.00	-13.04	Average	Vertical

IEEE 802.11ac VHT20

Channel 100 / 5500 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.50	44.76	33.21	35.82	9.52	51.67	68.20	-16.53	Peak	Horizontal
16.50	35.55	33.21	35.82	9.52	42.46	54.00	-11.54	Average	Horizontal
16.50	46.29	32.82	35.82	9.52	52.81	68.20	-15.39	Peak	Vertical
16.50	35.64	32.82	35.82	9.52	42.16	54.00	-11.84	Average	Vertical

Channel 116 / 5580 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.74	46.14	33.21	35.82	9.52	53.05	68.20	-15.15	Peak	Horizontal
16.74	38.50	33.21	35.82	9.52	45.41	54.00	-8.59	Average	Horizontal
16.74	40.20	32.82	35.82	9.52	46.72	68.20	-21.48	Peak	Vertical
16.74	31.96	32.82	35.82	9.52	38.48	54.00	-15.52	Average	Vertical

Channel 140 / 5700 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
17.10	40.99	33.21	35.82	9.52	47.90	68.20	-20.30	Peak	Horizontal
17.10	38.58	33.21	35.82	9.52	45.49	54.00	-8.51	Average	Horizontal
17.10	47.53	32.82	35.82	9.52	54.05	68.20	-14.15	Peak	Vertical
17.10	30.68	32.82	35.82	9.52	37.20	54.00	-16.80	Average	Vertical

IEEE 802.11n HT40

Channel 102 / 5510 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.53	44.93	33.21	35.82	9.52	51.84	68.20	-16.36	Peak	Horizontal
16.53	31.10	33.21	35.82	9.52	38.01	54.00	-15.99	Average	Horizontal
16.53	41.41	32.82	35.82	9.52	47.93	68.20	-20.27	Peak	Vertical
16.53	40.67	32.82	35.82	9.52	47.19	54.00	-6.81	Average	Vertical

Channel 110 / 5550 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.77	50.70	33.21	35.82	9.52	57.61	68.20	-10.59	Peak	Horizontal
16.77	38.00	33.21	35.82	9.52	44.91	54.00	-9.09	Average	Horizontal
16.77	43.32	32.82	35.82	9.52	49.84	68.20	-18.36	Peak	Vertical
16.77	32.69	32.82	35.82	9.52	39.21	54.00	-14.79	Average	Vertical

Channel 134 / 5670 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
17.01	40.50	33.21	35.82	9.52	47.41	68.20	-20.79	Peak	Horizontal
17.01	32.19	33.21	35.82	9.52	39.10	54.00	-14.90	Average	Horizontal
17.01	47.76	32.82	35.82	9.52	54.28	68.20	-13.92	Peak	Vertical
17.01	37.46	32.82	35.82	9.52	43.98	54.00	-10.02	Average	Vertical

IEEE 802.11ac VHT40

Channel 102 / 5510 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.53	44.02	33.21	35.82	9.52	50.93	68.20	-17.27	Peak	Horizontal
16.53	33.58	33.21	35.82	9.52	40.49	54.00	-13.51	Average	Horizontal
16.53	50.00	32.82	35.82	9.52	56.52	68.20	-11.68	Peak	Vertical
16.53	38.75	32.82	35.82	9.52	45.27	54.00	-8.73	Average	Vertical

Channel 110 / 5550 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.77	43.60	33.21	35.82	9.52	50.51	68.20	-17.69	Peak	Horizontal
16.77	40.10	33.21	35.82	9.52	47.01	54.00	-6.99	Average	Horizontal
16.77	40.36	32.82	35.82	9.52	46.88	68.20	-21.32	Peak	Vertical
16.77	32.45	32.82	35.82	9.52	38.97	54.00	-15.03	Average	Vertical

Channel 134 / 5670 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
17.01	40.96	33.21	35.82	9.52	47.87	68.20	-20.33	Peak	Horizontal
17.01	30.83	33.21	35.82	9.52	37.74	54.00	-16.26	Average	Horizontal
17.01	45.24	32.82	35.82	9.52	51.76	68.20	-16.44	Peak	Vertical
17.01	33.87	32.82	35.82	9.52	40.39	54.00	-13.61	Average	Vertical

IEEE 802.11ac VHT80

Channel 106 / 5530 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
16.59	47.26	33.21	35.82	9.52	54.17	68.20	-14.03	Peak	Horizontal
16.59	30.09	33.21	35.82	9.52	37.00	54.00	-17.00	Average	Horizontal
16.59	50.41	32.82	35.82	9.52	56.93	68.20	-11.27	Peak	Vertical
16.59	35.68	32.82	35.82	9.52	42.20	54.00	-11.80	Average	Vertical

Notes:

- 1). Measuring frequencies from 9 KHz ~ 40GHz, No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz ~ 40GHz were made with an instrument using Peak detector mode.
- 3). 18~40GHz at least have 20dB margin. No recording in the test report.
- 4). Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80;
- 5). Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

- 6) Reading + Factor = Measured Level, Measured Level – Limit = Margin

Factor= Antenna Factor - Cable Loss - Preamp Factor

5.7. Power Line Conducted Emissions


5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency


5.7.2 Block Diagram of Test Setup



5.7.3 Test Results

PASS.

The test data please refer to following page.

**AC Conducted Emission of charge from adapter mode @ AC 120V/60Hz @ (IEEE 802.11ac VHT20 mode)
(worst case)****5.2G Line**

Site LAB

Phase: **L1**

Temperature: 24.5


Limit: FCC PART 15B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 53.6 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1725	34.39	19.16	53.55	64.84	-11.29	QP	
2		0.1758	11.10	19.17	30.27	54.68	-24.41	AVG	
3		0.2625	29.55	19.24	48.79	61.35	-12.56	QP	
4		0.2686	9.85	19.24	29.09	51.16	-22.07	AVG	
5		0.5235	22.16	19.17	41.33	56.00	-14.67	QP	
6		0.5370	7.99	19.14	27.13	46.00	-18.87	AVG	
7		1.5675	17.66	19.34	37.00	56.00	-19.00	QP	
8		1.6080	5.96	19.35	25.31	46.00	-20.69	AVG	
9		7.3365	14.02	19.59	33.61	60.00	-26.39	QP	
10		7.5570	0.14	19.60	19.74	50.00	-30.26	AVG	
11		9.1049	17.21	19.66	36.87	60.00	-23.13	QP	
12		9.2084	4.37	19.66	24.03	50.00	-25.97	AVG	

Neutral



Site LAB

Phase: **N**

Temperature: 24.5


Limit: FCC PART 15B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 53.6 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.2085	24.98	19.19	44.17	63.26	-19.09	QP	
2		0.2175	10.72	19.20	29.92	52.91	-22.99	AVG	
3	*	0.4110	20.44	19.32	39.76	57.63	-17.87	QP	
4		0.4245	8.74	19.32	28.06	47.36	-19.30	AVG	
5		1.0680	18.71	19.27	37.98	56.00	-18.02	QP	
6		1.1040	7.69	19.27	26.96	46.00	-19.04	AVG	
7		1.7700	15.83	19.38	35.21	56.00	-20.79	QP	
8		1.8375	5.19	19.39	24.58	46.00	-21.42	AVG	
9		5.9235	12.39	19.54	31.93	60.00	-28.07	QP	
10		6.2430	-1.03	19.54	18.51	50.00	-31.49	AVG	
11		10.3830	14.92	19.72	34.64	60.00	-25.36	QP	
12		10.7205	-1.38	19.76	18.38	50.00	-31.62	AVG	

5.3G Line



Site LAB

Phase: **L1**

Temperature: 24.5


Limit: FCC PART 15B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 53.6 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1768	30.92	19.17	50.09	64.63	-14.54	QP	
2		0.1814	14.51	19.17	33.68	54.42	-20.74	AVG	
3		0.2953	26.40	19.27	45.67	60.37	-14.70	QP	
4		0.3119	15.40	19.28	34.68	49.92	-15.24	AVG	
5		0.7661	22.66	19.32	41.98	56.00	-14.02	QP	
6	*	0.7752	13.28	19.31	32.59	46.00	-13.41	AVG	
7		1.6754	21.79	19.36	41.15	56.00	-14.85	QP	
8		1.6975	10.06	19.37	29.43	46.00	-16.57	AVG	
9		4.7759	17.72	19.49	37.21	56.00	-18.79	QP	
10		4.8479	6.03	19.49	25.52	46.00	-20.48	AVG	
11		13.2629	15.30	19.97	35.27	60.00	-24.73	QP	
12		13.3170	1.01	19.98	20.99	50.00	-29.01	AVG	

Neutral



Site LAB

Phase: **N**

Temperature: 24.5


Limit: FCC PART 15B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 53.6 %

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1680	31.48	19.16	50.64	65.06	-14.42	QP	
2	0.1703	17.71	19.16	36.87	54.95	-18.08	AVG	
3	0.2535	30.07	19.23	49.30	61.64	-12.34	QP	
4	0.2760	16.53	19.25	35.78	50.94	-15.16	AVG	
5	0.7570	24.18	19.32	43.50	56.00	-12.50	QP	
6 *	0.7752	14.45	19.31	33.76	46.00	-12.24	AVG	
7	1.4858	20.78	19.34	40.12	56.00	-15.88	QP	
8	1.5179	7.63	19.34	26.97	46.00	-19.03	AVG	
9	6.7560	18.05	19.57	37.62	60.00	-22.38	QP	
10	6.8010	4.77	19.58	24.35	50.00	-25.65	AVG	
11	9.4875	16.00	19.68	35.68	60.00	-24.32	QP	
12	9.5594	0.55	19.68	20.23	50.00	-29.77	AVG	

5.5G Line



Site LAB

Phase: L1

Temperature: 24.5


Limit: FCC PART 15B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 53.6 %

No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
	MHz	Level	Factor	ment				
		dBuV	dB	dBuV	dBuV	dB		
1	0.1723	31.39	19.16	50.55	64.85	-14.30	QP	
2	0.2162	17.11	19.20	36.31	52.96	-16.65	AVG	
3	0.2625	29.05	19.24	48.29	61.35	-13.06	QP	
4	0.3165	12.16	19.28	31.44	49.80	-18.36	AVG	
5	0.5816	23.42	19.16	42.58	56.00	-13.42	QP	
6	0.5864	13.00	19.17	32.17	46.00	-13.83	AVG	
7 *	1.5668	23.66	19.34	43.00	56.00	-13.00	QP	
8	1.5806	13.48	19.34	32.82	46.00	-13.18	AVG	
9	4.8750	16.78	19.49	36.27	56.00	-19.73	QP	
10	5.1135	4.82	19.49	24.31	50.00	-25.69	AVG	
11	9.1049	15.21	19.66	34.87	60.00	-25.13	QP	
12	10.9905	2.99	19.78	22.77	50.00	-27.23	AVG	

Neutral



Site LAB

Phase:

N

Temperature:

24.5

Limit: FCC PART 15B Conduction(QP)

Power:

AC 120V/60Hz

Humidity:

53.6 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.2084	30.98	19.19	50.17	63.27	-13.10	QP	
2		0.2094	18.09	19.19	37.28	53.23	-15.95	AVG	
3		0.7258	21.09	19.30	40.39	56.00	-15.61	QP	
4		0.7752	12.91	19.31	32.22	46.00	-13.78	AVG	
5		1.0679	19.21	19.27	38.48	56.00	-17.52	QP	
6		1.1309	8.64	19.28	27.92	46.00	-18.08	AVG	
7		1.4729	17.53	19.34	36.87	56.00	-19.13	QP	
8		1.4902	9.05	19.34	28.39	46.00	-17.61	AVG	
9		4.3528	15.51	19.47	34.98	56.00	-21.02	QP	
10		4.3935	2.54	19.47	22.01	46.00	-23.99	AVG	
11		8.0700	15.41	19.64	35.05	60.00	-24.95	QP	
12		8.2858	3.03	19.65	22.68	50.00	-27.32	AVG	

***Note: Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11ac VHT20 mode).


5.8 Undesirable Emissions Measurement

5.8.1 Limit

According to §15.407 (b) Undesirable emission limits. Except as shown in paragraph (b) (7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (a) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (b) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (c) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (d) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (e) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (f) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
- (g) The provisions of §15.205 apply to intentional radiators operating under this section.
- (h) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

5.8.2 Test Configuration



5.8.3 Test Procedure

According to KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section G: Unwanted Emission Measurement

1. Unwanted Emissions in the Restricted Bands

- a) For all measurements, follow the requirements in section II.G.3. "General Requirements for Unwanted Emissions Measurements."
- b) At frequencies below 1000 MHz, use the procedure described in section II.G.4. "Procedure for Unwanted Emissions Measurements below 1000 MHz."
- c) At frequencies above 1000 MHz, measurements performed using the peak and average measurement procedures described in sections II.G.5. and II.G.6, respectively, must satisfy the respective peak and average limits. If all peak measurements satisfy the average limit, then average measurements are not required.
- d) For conducted measurements above 1000 MHz, EIRP shall be computed as specified in section II.G.3.b) and then field strength shall be computed as follows (see KDB Publication 412172):
 - i) $E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{meters}]) + 104.77$, where E = field strength and d = distance at which field strength limit is specified in the rules;

- ii) $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$, for $d = 3$ meters
- e) For conducted measurements below 1000 MHz, the field strength shall be computed as specified in d), above, and then an additional 4.7 dB shall be added as an upper bound on the field strength that would be observed on a test range with a ground plane for frequencies between 30 MHz and 1000 MHz, or an additional 6 dB shall be added for frequencies below 30 MHz.
2. Unwanted Emissions that fall Outside of the Restricted Bands
- a) For all measurements, follow the requirements in section II.G.3. "General Requirements for Unwanted Emissions Measurements."
- b) At frequencies below 1000 MHz, use the procedure described in section II.G.4. "Procedure for Unwanted Emissions Measurements below 1000 MHz."
- c) At frequencies above 1000 MHz, use the procedure for maximum emissions described in section II.G.5., "Procedure for Unwanted Maximum Unwanted Emissions Measurements Above 1000 MHz."
- d) Section 15.407(b) (1-3) specifies the unwanted emissions limit for the U-NII-1 and 2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz. However, an out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz dBm/MHz peak emission limit.
- i) Section 15.407(b) (4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b) (4) (i). An alternative to the band emissions mask is specified in Section 15.407(b) (4) (ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the alternative limit.
- e) If radiated measurements are performed, field strength is then converted to EIRP as follows:
- i) $\text{EIRP} = (E \times d)^2 / 30$
Where:
- E is the field strength in V/m;
 - d is the measurement distance in meters;
 - EIRP is the equivalent isotopically radiated power in watts;
- ii) Working in dB units, the above equation is equivalent to:
 $\text{EIRP} [\text{dBm}] = E [\text{dB}\mu\text{V/m}] + 20 \log (d [\text{meters}]) - 104.77$
- iii) Or, if d is 3 meters:
 $\text{EIRP} [\text{dBm}] = E [\text{dB}\mu\text{V/m}] - 95.23$
- 3) Radiated versus Conducted Measurements.
- The unwanted emission limits in both the restricted and non-restricted bands are based on radiated measurements; however, as an alternative, antenna-port conducted measurements in conjunction with cabinet emissions tests will be permitted to demonstrate compliance provided that the following steps are performed:
- (i) Cabinet emissions measurements. A radiated test shall be performed to ensure that cabinet emissions are below the emission limits. For the cabinet-emission measurements the antenna may be replaced by a termination matching the nominal impedance of the antenna.
- (ii) Impedance matching. Conducted tests shall be performed using equipment that matches the nominal impedance of the antenna assembly used with the EUT.
- (iii) EIRP calculation. A value representative of an upper bound on out-of-band antenna gain (in dBi) shall be added to the measured antenna-port conducted emission power to compute EIRP within the specified measurement bandwidth. (For emissions in the restricted bands, additional calculations are required to convert EIRP to field strength at the specified distance.) The upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands or 2 dBi, whichever is greater.³ However, for devices that operate in multiple bands using the same transmit antenna, the highest gain of the antenna within the operating band nearest to the out-of-band frequency being measured may be used in lieu of the overall highest gain when measuring emissions at frequencies within 20% of the absolute frequency at the nearest edge of that band, but in no case shall a value less than 2 dBi be selected.
- (iv) EIRP adjustments for multiple outputs. For devices with multiple outputs occupying the same or overlapping frequency ranges in the same band (e.g., MIMO or beamforming devices), compute the total EIRP as follows:
- Compute EIRP for each output, as described in (iii), above.
 - Follow the procedures specified in KDB Publication 662911 for summing emissions across the outputs or adjusting emission levels measured on individual outputs by $10 \log (N_{\text{ANT}})$, where N_{ANT} is the number of outputs.
 - Add the array gain term specified in KDB Publication 662911 for out-of-band and spurious signals.
- (v) Direction of maximum emission.
For all radiated emissions tests, measurements shall correspond to the direction of maximum emission level for each measured emission (see ANSI C63.10 for guidance).

5.8.4 Test Results

PASS

Please refer to Appendix D.5

Remark:

1. Measured Undesirable emission at difference data rate for each mode and recorded worst case for each mode;
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80;
4. Covert Radiated E Level At 3m = Conducted average power + Directional Gain + $104.77 - 20 \cdot \log(3)$;

5.9. Frequency Stability


5.9.1 Standard Applicable

According to FCC §15.407(g) "Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual."

According to FCC §2.1055(a) "The frequency stability shall be measured with variation of ambient temperature as follows:"

- (1) From -30° to $+50^{\circ}$ centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.
- (2) From -20° to $+50^{\circ}$ centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.
- (3) From 0° to $+50^{\circ}$ centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

5.9.2 Test Configuration



5.9.3 Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10 degree increased per stage until the highest temperature of +50 degree reached.

5.9.4 Test Results

PASS

Remark:

1. Measured all conditions and recorded worst case.
2. Measured at both antenna 0 and antenna 1, recorded worst case at antenna 0;

IEEE 802.11a Mode / 5180 – 5240 MHz / 5180 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 4.18V	5179.784	5150 – 5250	PASS
20	DC 3.42V	5179.750	5150 – 5250	PASS
50	DC 3.80V	5179.676	5150 – 5250	PASS
40	DC 3.80V	5179.712	5150 – 5250	PASS
30	DC 3.80V	5179.757	5150 – 5250	PASS
20	DC 3.80V	5179.714	5150 – 5250	PASS
10	DC 3.80V	5179.759	5150 – 5250	PASS
0	DC 3.80V	5179.604	5150 – 5250	PASS
-10	DC 3.80V	5179.747	5150 – 5250	PASS
-20	DC 3.80V	5179.670	5150 – 5250	PASS
-30	DC 3.80V	5180.247	5150 – 5250	PASS

IEEE 802.11a Mode / 5180 – 5240 MHz / 5240 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 4.18V	5239.874	5150 – 5250	PASS
20	DC 3.42V	5239.684	5150 – 5250	PASS
50	DC 3.80V	5239.763	5150 – 5250	PASS
40	DC 3.80V	5239.717	5150 – 5250	PASS
30	DC 3.80V	5239.772	5150 – 5250	PASS
20	DC 3.80V	5239.737	5150 – 5250	PASS
10	DC 3.80V	5239.769	5150 – 5250	PASS
0	DC 3.80V	5239.699	5150 – 5250	PASS
-10	DC 3.80V	5239.610	5150 – 5250	PASS
-20	DC 3.80V	5239.624	5150 – 5250	PASS
-30	DC 3.80V	5239.757	5150 – 5250	PASS

5.10. Antenna Requirements

5.10.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.10.2 Antenna Connected Construction

5.10.2.1. Standard Applicable

According to § 15.203 & RSS-Gen, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.10.2.2. Antenna Connector Construction

The gains of antennas used for transmitting are 1.9dBi, and the antenna are Internal Antennas connect to PCB board and no consideration of replacement. Please see EUT photo for details.

5.10.2.3. Results: Compliance.

6. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRVS	100444	2019-06-11	2020-06-10
2	Power Sensor	R&S	NRV-Z81	100458	2019-06-11	2020-06-10
3	Power Sensor	R&S	NRV-Z32	10057	2019-06-11	2020-06-10
4	Test Software	Tonscend	JS1120-2	/	N/A	N/A
5	RF Control Unit	Tonscend	JS0806-2	N/A	2019-06-11	2020-06-10
6	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2019-11-22	2020-11-21
7	DC Power Supply	Agilent	E3642A	N/A	2019-11-14	2020-11-13
8	EMI Test Software	AUDIX	E3	/	N/A	N/A
9	3m Full Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2019-06-12	2020-06-11
10	Positioning Controller	MF	MF-7082	N/A	2019-06-12	2020-06-11
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2018-07-26	2021-07-25
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2018-07-26	2021-07-25
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2018-07-02	2021-07-01
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2017-09-21	2020-09-20
15	Broadband Preamplifier	SCHWARZBECK	BBV 9719	9719-025	2019-06-17	2020-06-16
16	EMI Test Receiver	R&S	ESR 7	101181	2019-06-12	2020-06-11
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2019-11-14	2020-11-13
18	Broadband Preamplifier	/	BP-01M18G	P190501	2019-07-01	2020-06-30
19	RF Cable-R03m	Jye Bao	RG142	CB021	2019-06-12	2020-06-11
20	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2019-06-12	2020-06-11
21	6dB Attenuator	/	100W/6dB	1172040	2019-06-11	2020-06-10
22	3dB Attenuator	/	2N-3dB	/	2019-06-11	2020-06-10
23	EMI Test Receiver	R&S	ESPI	101840	2019-06-11	2020-06-10
24	Artificial Mains	R&S	ENV216	101288	2019-06-12	2020-06-11
25	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2019-06-11	2020-06-10

Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.

7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----