

## RF Exposure Report

**Report No.:** FCC\_RF Exposure\_SL20062601-PCE-001

**Host Model:** CEECOACH PLUS

**Host FCC ID:** 2ANUY-CEECPLUS

**BT module FCC ID:** WAP3027

**Received Date:** 08/10/2020

**Test Date:** 08/17/2020 - 09/07/2020

**Issued Date:** 09/08/2020

**Applicant:** Peiker Consumer Electronics Evolution GmbH

**Address:** Gartenstraße 25, 61352 Bad Homburg vor der Höhe, Germany

**Manufacturer:** Peiker Consumer Electronics Evolution GmbH

**Address:** Gartenstraße 25, 61352 Bad Homburg vor der Höhe, Germany

**Issued By:** Bureau Veritas Consumer Products Services, Inc.

**Lab Address:** 775 Montague Expressway, Milpitas, CA 95035

**Test Location (1):** 775 Montague Expressway, Milpitas, CA 95035

**FCC Registration /  
Designation Number:** 540430



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 Evaluation Result</b> .....	<b>5</b>
<b>3 SAR Test Exclusion Thresholds</b> .....	<b>6</b>
<b>4 Conclusion</b> .....	<b>6</b>



### Release Control Record

Issue No.	Description	Date Issued
FCC_RF Exposure_SL20062601-PCE-001	Original Release	09/08/2020



## 2 Evaluation Result

Following FCC KDB 447498 D01 “General SAR test exclusion guidance”

The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  
$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]}{\leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}}$$
  - $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
  - Power and distance are rounded to the nearest mW and mm before calculation.
  - The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.
- 2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:
  - a) [Threshold at 50 mm in step 1) + (test separation distance - 50mm) · ( f(MHz)/150)] mW, at 100MHz to 1500 MHz
  - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at  $> 1500$  MHz and  $\leq 6$  GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
  - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.
  - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq 50$  mm.
  - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

### 3 SAR Test Exclusion Thresholds

MODE	Frequency (MHz)	Max. Power (dBm)	Tune-Up Tolerance	Min. test separation distance (mm)	1-g SAR test exclusion calculation value	1-g SAR test exclusion thresholds	Result
2.4GHz Short Range	2405	1.25	±1dB	5	0.52	3	Pass
BT	2441	-0.24	±1dB	5	0.372	3	Pass
BLE	2480	2.82	±1dB	5	0.759	3	Pass

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The antenna type is 2.4 GHz Inverted F Antenna with -1.1 dBi gain.
3. BLE/ BT antenna type is chip with -1 dBi gain.
4. Output power level is time-averaged output power.

### 4 Conclusion

Total Simultaneous SAR test exclusion calculation value

$$2.4\text{GHz Short Range} + \text{BT} = 0.52 + 0.372 = 0.892 < 3$$

$$2.4\text{GHz Short Range} + \text{BLE} = 0.52 + 0.759 = 1.279 < 3$$

The SAR evaluation is not required.

--- END ---