

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : Stanley Black & Decker, Inc.
400 Executive Blvd S, Southington, CT 06489 USA

Manufacturer : Stanley Black & Decker, Inc.
400 Executive Blvd S, Southington, CT 06489 USA

Product Name : Spot Light

Type/Model : SPL10000M

TEST RESULT : PASS

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

For BT, as we can see from the test report 170500717SHA-001

Frequency band (MHz)	Max power		Antenna Gain		R	S
2400-2483.5MHz	-2.86dBm	0.518mW	2.0dBi	1.585	20cm	0.00016

The sum of the MPE ratios = 0.00016mW/cm²

This level is below the simultaneous transmission MPE test exclusion requirements (≤ 1.0).

Date of issue: Oct 9, 2017

Prepared by:



Teddy Yin (*Project Engineer*)

Reviewed by:


Daniel Zhao (*Reviewer*)

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.
To ensure compliance, operations at closer than this distance is not recommended.