

Conducted test results

No.1-4299/22-02-03_Annex_MR

October 20, 2023

Test Standard(s) FCC 15.247

This document is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.

Authorized

Michael Dorongovski

Lab Manager
Radio Labs

Table of Content

FCC 15.247 # Bandwidths ~ Generic 0G9	3
FCC 15.247 # Bandwidths ~ Generic 0G9	7
FCC 15.247 # Bandwidths ~ Generic 0G9	11
FCC 15.247 # Maximum peak conducted output power ~ Generic 0G9	15
FCC 15.247 # Maximum peak conducted output power ~ Generic 0G9	18
FCC 15.247 # Maximum peak conducted output power ~ Generic 0G9	21
FCC 15.247 # Peak power spectral density DTS ~ Generic 0G9	24
FCC 15.247 # Peak power spectral density DTS ~ Generic 0G9	26
FCC 15.247 # Peak power spectral density DTS ~ Generic 0G9	28
FCC 15.247 # TX spurious conducted 20dBc ~ Generic 0G9	30
FCC 15.247 # TX spurious conducted 20dBc ~ Generic 0G9	33
FCC 15.247 # TX spurious conducted 20dBc ~ Generic 0G9	36

FCC 15.247 # Bandwidths ~ Generic 0G9

Test References

TC Start	21.06.2023 14:32:47
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 Bandwidths DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 903 MHz

RESULT: Reference Power cond.


TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.45	dBm	INFO
Ref. Frequency	--	--	903.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.45 8.45 30
Start [MHz] Stop [MHz]	902.675 903.325
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE




Plot: Bandwidth within Band




BW within Band 99PCT

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	500.450	kHz	INFO
T1 99%	902.000000	--	902.7428	MHz	PASS
T2 99%	--	928.000000	903.2433	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	500	--	568	kHz	PASS
T1 20dB	902.000000	--	902.7046	MHz	PASS
T2 20dB	--	928.000000	903.2722	MHz	PASS

Verdict

PASS

FCC 15.247 # Bandwidths ~ Generic 0G9

Test References

TC Start	21.06.2023 14:57:13
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 Bandwidths DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	True Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 909.4 MHz

RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.41	dBm	INFO
Ref. Frequency	--	--	909.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.41 8.46 30
Start [MHz] Stop [MHz]	909.075 909.725
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE




Plot: Bandwidth within Band



BW within Band 99PCT

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	506.364	kHz	INFO
T1 99%	902.000000	--	909.1424	MHz	PASS
T2 99%	--	928.000000	909.6488	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	500	--	584	kHz	PASS
T1 20dB	902.000000	--	909.1000	MHz	PASS
T2 20dB	--	928.000000	909.6839	MHz	PASS

Verdict

PASS

FCC 15.247 # Bandwidths ~ Generic 0G9

Test References

TC Start	21.06.2023 15:14:33
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 Bandwidths DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	True Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 914.2 MHz

RESULT: Reference Power cond.


TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.38	dBm	INFO
Ref. Frequency	--	--	914.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.38 8.47 30
Start [MHz] Stop [MHz]	913.875 914.525
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE




Plot: Bandwidth within Band



BW within Band 99PCT

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	505.454	kHz	INFO
T1 99%	902.000000	--	913.9426	MHz	PASS
T2 99%	--	928.000000	914.4481	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	500	--	579	kHz	PASS
T1 20dB	902.000000	--	913.9030	MHz	PASS
T2 20dB	--	928.000000	914.4822	MHz	PASS

Verdict

PASS

FCC 15.247 # Maximum peak conducted output power ~ Generic 0G9

Test References

TC Start	21.06.2023 14:22:23
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 903 MHz

RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.45	dBm	INFO
Ref. Frequency	--	--	903.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.45 8.45 30
Start [MHz] Stop [MHz]	902.675 903.325
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 50 1001 SWE



RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	--	30	14.36	dBm	PASS
Frequency at Peak	--	--	902.775	MHz	INFO

Verdict

FCC 15.247 # Maximum peak conducted output power ~ Generic 0G9

Test References

TC Start	21.06.2023 14:46:49
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	True Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 909.4 MHz

RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.43	dBm	INFO
Ref. Frequency	--	--	909.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.44 8.46 30
Start [MHz] Stop [MHz]	909.075 909.725
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 50 1001 SWE



RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	--	30	14.33	dBm	PASS
Frequency at Peak	--	--	909.232	MHz	INFO

Verdict

FCC 15.247 # Maximum peak conducted output power ~ Generic 0G9

Test References

TC Start	21.06.2023 15:04:11
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	True Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 914.2 MHz

RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.41	dBm	INFO
Ref. Frequency	--	--	914.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.41 8.47 30
Start [MHz] Stop [MHz]	913.875 914.525
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 50 1001 SWE



RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	--	30	14.34	dBm	PASS
Frequency at Peak	--	--	914.398	MHz	INFO

Verdict

FCC 15.247 # Peak power spectral density DTS ~ Generic 0G9

Test References

TC Start	21.06.2023 14:31:39
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	ANSI C63.10-2013: 11.10.2 Method PKPSD (peak PSD)
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 903 MHz

RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.44	dBm	INFO
Ref. Frequency	--	--	903.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.44 8.45 30
Start [MHz] Stop [MHz]	902.838 903.163
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 100 1001 SWE



RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Peak power Density	--	8	-4.07	dBm/3KHz	PASS

Verdict

PASS

FCC 15.247 # Peak power spectral density DTS ~ Generic 0G9

Test References

TC Start	21.06.2023 14:56:04
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	ANSI C63.10-2013: 11.10.2 Method PKPSD (peak PSD)
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	True Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 909.4 MHz

RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.43	dBm	INFO
Ref. Frequency	--	--	909.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.43 8.46 30
Start [MHz] Stop [MHz]	909.238 909.563
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 100 1001 SWE



RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Peak power Density	--	8	-4.2	dBm/3KHz	PASS

Verdict

PASS

FCC 15.247 # Peak power spectral density DTS ~ Generic 0G9

Test References

TC Start	21.06.2023 15:13:25
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	ANSI C63.10-2013: 11.10.2 Method PKPSD (peak PSD)
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	True Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI


Test at TX 914.2 MHz

RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.41	dBm	INFO
Ref. Frequency	--	--	914.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.41 8.47 30
Start [MHz] Stop [MHz]	914.038 914.363
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 100 1001 SWE



RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Peak power Density	--	8	-4.1	dBm/3KHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 20dBc ~ Generic 0G9

Test References

TC Start	21.06.2023 14:33:28
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions conducted DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer


Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI

Test at TX 903 MHz

RESULT: Reference Power cond.


TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.44	dBm	INFO
Ref. Frequency	--	--	903.200	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.44 0 30
Start [MHz] Stop [MHz]	12505.000 12750.000
RBW [MHz] VBW [MHz]	0.100000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 20 2001 SWE



TX emissions band zoomed

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 903.00 MHz	--	--	14.32	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 901.25 MHz	0	--	29.76	dB	INFO

Verdict

PASS

FCC 15.247 # TX spurious conducted 20dBc ~ Generic 0G9

Test References

TC Start	21.06.2023 14:57:53
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions conducted DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	True Freq [MHz] 909.4
Frequency high to test	False Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer


Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI

Test at TX 909.4 MHz


RESULT: Reference Power cond.

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.41	dBm	INFO
Ref. Frequency	--	--	909.500	MHz	INFO



READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.41 0 30
Start [MHz] Stop [MHz]	12505.000 12750.000
RBW [MHz] VBW [MHz]	0.100000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 20 2001 SWE



TX emissions band zoomed

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 909.50 MHz	--	--	14.29	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 12367.75 MHz	0	--	30.01	dB	INFO

Verdict

PASS

FCC 15.247 # TX spurious conducted 20dBc ~ Generic 0G9

Test References

TC Start	21.06.2023 15:15:14
Ambit Temp [°C] Humidity [rel%]	0.0 0
System Version	4.0.3.0
Test Specification	FCC 15.247 -
Test Method	
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions conducted DTS
Add. Information	

Test Parameter

Technology to test	Generic 0G9
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 903
Frequency mid to test	False Freq [MHz] 909.4
Frequency high to test	True Freq [MHz] 914.2
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer


Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60
Switch matrix,CTCadvanced,RSM-1 NI DAQ,31534892,NI

Test at TX 914.2 MHz

RESULT: Reference Power cond.


TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.39	dBm	INFO
Ref. Frequency	--	--	914.400	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.39 0 30
Start [MHz] Stop [MHz]	12505.000 12750.000
RBW [MHz] VBW [MHz]	0.100000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	200 20 2001 SWE



TX emissions band zoomed

RESULT

TEST DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 914.50 MHz	--	--	14.30	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 12434.5 MHz	0	--	29.76	dB	INFO

Verdict

PASS

- END OF DOCUMENT -