

■ Report No.: DDT-R18092104-1E3

■Issued Date: Oct. 17, 2018

RF EXPOSURE REPORT

FOR

Applicant		Comson (Shenzhen) Electronic Technology Co., Ltd.	
Address	••	3rd Floor, Building 22#, No. 6 Xingye 1st road, Fenghuang Community, Fuyong, Bao'an District, Shenzhen.	
Equipment under Test		PORTABLE AMP SPEAKER	
Model No.		TWS404, KS-386L	
Trade Mark	••	tyler Ocoumson	
FCC ID	1	2ANXIKS386LTWS404	
Manufacturer		Comson (Shenzhen) Electronic Technology Co., Ltd.	
Address	••	3rd Floor, Building 22#, No. 6 Xingye 1st road, Fenghuang Community, Fuyong, Bao'an District, Shenzhen.	

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, http://www.dgddt.com



TABLE OF CONTENTS

	Test report declares	3
1.	General information	5
1.1.	Description of Equipment	5
1.2.	Assess laboratory	5
2.	RF Exposure evaluation for FCC	5

TEST REPORT DECLARE

Applicant	:	Comson (Shenzhen) Electronic Technology Co., Ltd.	
Address	:	3rd Floor, Building 22#, No. 6 Xingye 1st road, Fenghuang Community, Fuyong, Bao'an District, Shenzhen.	
Equipment under Test	:	PORTABLE AMP SPEAKER	
Model No.	:	TWS404, KS-386L	
Trade mark	:	tyler Ocoumson	
Manufacturer	:	Comson (Shenzhen) Electronic Technology Co., Ltd.	
Address	:	3rd Floor, Building 22#, No. 6 Xingye 1st road, Fenghuang Community, Fuyong, Bao'an District, Shenzhen.	

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R18092104-1E3		
Date of Receipt:	Sep. 21, 2018	Date of Test:	Sep. 21, 2018 ~ Oct. 16, 2018

Prepared By:

Sam Li/Engineer

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
	Initial issue	Oct. 17, 2018	

1. General information

1.1. Description of Equipment

:	PORTABLE AMP SPEAKER
:	TWS404, KS-386L
	Model difference except color difference, other appearance and function are all the same
:	Please reference user manual of this device
:	AC 100V-240V 50/60Hz
:	Bluetooth V4.2
:	2402MHz-2480MHz
:	GFSK, π/4-DQPSK, 8DPSK
:	1Mbps, 2Mbps, 3Mbps
:	Integral PCB antenna, maximum PK gain: -2dBi
:	Series production
	: :

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,

Guangdong Province, China, 523808

Tel: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz, -1.40dBm (0.72mW) output power]

 $(0.72/5) \cdot [\sqrt{2.402(GHz)}] = 0.223 < 3.0 \text{ for } 1-g \text{ SAR}$

Then SAR evaluation is not required

END OF REPORT