

RF Exposure Requirements

Product Description: Wireless mouse Dongle

Model No.: ME4

FCC ID: 2AO23-ME4

According to the KDB 447498 D01 V06, the following RF exposure evaluation shall to demonstrate RF exposure compliance.

General 2.4GHz Technique

Tx frequency range: 2405 MHz ~ 2475 MHz

Type of Modulation: GFSK

Antenna Type: Integral antenna (Gain: -1 dBi)

The maximum radiated output power (e.i.r.p): -6.13 dBm

The conducted output power specified is -1 dBm

Tolerance: ± 1 dB

The maximum radiated emission for the EUT is 89.10 dB μ V/m at 3m

The maximum conducted output power specified is 0 dBm = 1.0 mW

The source- based time-averaging conducted output power
= 1.0 * Duty cycle mW = 0.022 mW (Duty Cycle = 2.20%)

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 * 5 / \text{sqrt}(2.480)$ mW

= 9.5 mW

Source-based time-averaged Conducted output power is 0.022 mW < 9.5mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.