

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone:	+86 (0) 755 2601 2053
Fax:	+86 (0) 755 2671 0594
Email:	ee.shenzhen@sgs.com

Report No.: SZEM181000928801 Page: 1 of 21

TEST REPORT

Test Result:	Pass*
Date of Issue:	2018-11-08
Date of Test:	2018-10-26 to 2018-11-02
Date of Receipt:	2018-10-26
Standard(s) :	47 CFR Part 15, Subpart C
FCC ID:	2AO23QIC32
Trade mark:	Heyday
	Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Model No.:	PW001, QIC32, QIC29 🜲
EUT Name:	QI charger 5w
Equipment Under Test (EUT)):
Address of Factory:	Building A4, 2nd/3rd/4th floor of building A3, in Fuzhong Industrial Area Xiashiwei Road of Fuyong Street, Bao'an District, Shenzhen
Factory:	Shenzhen Rihuida Electronic Co., Ltd
Address of Manufacturer:	Building A4, 2nd/3rd/4th floor of building A3, in Fuzhong Industrial Area Xiashiwei Road of Fuyong Street, Bao'an District, Shenzhen
Manufacturer:	Shenzhen Rihuida Electronic Co., Ltd
Address of Applicant:	7157 Shady Oak Road Eden Prairie Washington Minnesota 55344 United States
Applicant:	Chua, Inc.
Application No.:	SZEM1810009288CR

* In the configuration tested, the EUT complied with the standards specified above.



EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Report No.: SZEM181000928801 Page: 2 of 21

	Revision Record					
Version	Chapter	Date	Modifier	Remark		
01		2018-11-08		Original		

Authorized for issue by:		
	Peter. Comy	
	Peter Geng /Project Engineer	-
	Evic Fu	
	Eric Fu /Reviewer	-



Report No.: SZEM181000928801 Page: 3 of 21

2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C	N/A	47 CFR Part 15, Subpart C 15.203	Pass
Conducted Emissions at Mains Terminals (150kHz-30MHz)	47 CFR Part 15, Subpart C	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions (9kHz-1GHz)	47 CFR Part 15, Subpart C	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Restricted Bands	47 CFR Part 15, Subpart C	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.205	Pass
20% Bandwidth	47 CFR Part 15, Subpart C	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.215	Pass

Declaration of EUT Family Grouping:

Model No.: PW001, QIC32, QIC29

Only the model QIC32 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on color and model No..



Report No.: SZEM181000928801 Page: 4 of 21

3 Contents

		Page
1	COVER PAGE	1
2	TEST SUMMARY	3
3	CONTENTS	4
4	GENERAL INFORMATION	5
	 4.1 DETAILS OF E.U.T. 4.2 DESCRIPTION OF SUPPORT UNITS 4.3 MEASUREMENT UNCERTAINTY 4.4 TEST LOCATION. 4.5 TEST FACILITY. 4.6 DEVIATION FROM STANDARDS. 4.7 ABNORMALITIES FROM STANDARD CONDITIONS 	
5	EQUIPMENT LIST	7
6	RADIO SPECTRUM TECHNICAL REQUIREMENT	9
7	6.1 ANTENNA REQUIREMENT 6.1.1 Test Requirement: 6.1.2 Conclusion	9 9
-	 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	10 10 10 13 13 13 13 13 13 13 15 16 16 16
8	PHOTOGRAPHS	21
	 8.1 TEST SETUP 8.2 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS) 	21 21



Report No.: SZEM181000928801 Page: 5 of 21

4 General Information

4.1 Details of E.U.T.

Power supply:	Input: DC 5V/2A
	Output: 5W
Operation frequency:	110.42-175.00 kHz
Modulation type:	Load modulation
Cable:	USB charging line: 20cm, unshielded
Antenna type:	Inductive Loop Coil Antenna
Remark:	This device has been tested the worst status of full load and the device has been tested with mobile phone at zero charge, intermediate charge, and full charge.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A1357 W010A051	REF. No.SEA0500
iPhone 8	Apple	A1863	F4GVQ656JC6D
Micro USB Cable	PHILIPS	SWR2101	REF. No.SEA0700

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	± 7.25 x 10 ⁻⁸
2	Duty cycle	± 0.37%
3	Occupied Bandwidth	± 3%
4	RF conducted power	± 0.75dB
5	RF power density	± 2.84dB
6	Conducted Spurious emissions	± 0.75dB
7	DE Dedicted newer	± 4.5dB (below 1GHz)
/	RF Radialed power	± 4.8dB (above 1GHz)
0	Dedicted Cruvicus emission test	± 4.5dB (Below 1GHz)
0	Radiated Spurious emission test	± 4.8dB (Above 1GHz)
9	Temperature test	± 1 ℃
10	Humidity test	± 3%
11	Supply voltages	± 1.5%
12	Time	± 3%



Report No.: SZEM181000928801 Page: 6 of 21

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC

Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

FCC – Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Report No.: SZEM181000928801 Page: 7 of 21

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2020-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2018-07-12	2019-07-11
LISN	Rohde & Schwarz	ENV216	SEM007-01	2018-09-25	2019-09-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2018-04-02	2019-04-01
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018-04-02	2019-04-01

20dB Bandwidth/Restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24

Radiated emission(below 30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2018-03-31	2021-03-30
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2018-07-12	2019-07-11
EMI Test Receiver (9kHz-3GHz)	Rohde & Schwarz	ESCI	SEM004-01	2018-04-02	2019-04-01
Trilog-Broadband Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-01-26	2019-01-25
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2018-04-13	2019-04-12
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21



Report No.: SZEM181000928801 Page: 8 of 21

Radiated emission(30MHz-1GHz)									
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)				
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-08-05	2020-08-04				
MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2018-09-25	2019-09-24				
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017-06-27	2020-06-26				
Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2018-04-02	2019-04-01				
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A				
Coaxial Cable	SGS	N/A	SEM025-01	2018-07-12	2019-07-11				

General used equipment									
Equipment	Manufacturer	Manufacturer Model No Inventory No			Cal Due Date				
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2018-09-27	2019-09-26				
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2018-09-27	2019-09-26				
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2018-09-27	2019-09-26				
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07				



Report No.: SZEM181000928801 Page: 9 of 21

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 Limit:

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently

attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement.



Report No.: SZEM181000928801 Page: 10 of 21

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement Test Method: Limit: 47 CFR Part 15, Subpart C 15.207 ANSI C63.10 (2013) Section 6.2

	Limit (c	lBuV)
Frequency range (MHZ)	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature:21.5 °CHumidity:52.2 % RHAtmospheric Pressure:1010mbarTest modea:Charge mode_Keep the EUT charging(5W)

7.1.2 Measurement Procedure and Data

1) The mains terminal disturbance voltage test was conducted in a shielded room.

2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 500hm/50 μ H + 50hm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor



Report No.: SZEM181000928801 Page: 11 of 21



Mode:a; Line:Live Line

Site Condi	: Shi ition: Liu	ielding ne	g Room						
Job N	lo. : 092	288CR							
Test	mode: a								
		Cable	LISN	Read		Limit	0ver		
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark	
	MHz	dB	dB	dBuV	dBuV	dBuV	dB		
1	0.17	0.02	9.66	21.13	30.81	54.72	-23.91	Peak	
2	0.22	0.03	9.66	23.15	32.84	52.83	-19.99	Peak	
3	0.62	0.07	9.67	19.62	29.36	46.00	-16.64	Peak	
4	1.05	0.09	9.74	10.40	20.23	46.00	-25.77	Peak	
5	4.01	0.16	9.72	12.61	22.49	46.00	-23.51	Peak	
6	8.15	0.17	9.81	22.39	32.37	50.00	-17.63	Peak	



Report No.: SZEM181000928801 Page: 12 of 21

Mode:a; Line:Neutral Line



Site :	Shielding	Room
Condition:	Neutral	
Job No. :	09288CR	
Test mode:	а	

it Over	Limit		Read	LISN	Cable		
ne Limit Remark	Line	Level	Level	Factor	Loss	Freq	
uV dB	dBuV	dBuV	dBuV	dB	dB	MHz	
59 -25.00 Peak	55.69	30.69	21.05	9.63	0.01	0.16	1
73 -16.46 Peak	51.73	35.27	25.60	9.64	0.03	0.25	2
00 -16.79 Peak	46.00	29.21	19.50	9.64	0.07	0.63	3
00 -24.27 Peak	46.00	21.73	11.93	9.71	0.09	1.05	4
00 -23.48 Peak	46.00	22.52	12.67	9.69	0.16	4.07	5
00 -19.34 Peak	50.00	30.66	20.73	9.76	0.17	6.77	6
59 -25.00 Peak 73 -16.46 Peak 00 -16.79 Peak 00 -24.27 Peak 00 -23.48 Peak 00 -19.34 Peak	55.69 51.73 46.00 46.00 46.00 50.00	30.69 35.27 29.21 21.73 22.52 30.66	21.05 25.60 19.50 11.93 12.67 20.73	9.63 9.64 9.64 9.71 9.69 9.76	0.01 0.03 0.07 0.09 0.16 0.17	0.16 0.25 0.63 1.05 4.07 6.77	1 2 3 4 5 6



Report No.: SZEM181000928801 Page: 13 of 21

7.2 20dB Bandwidth and Restricted Bands

Test Requirement	47 CFR Part 15, Subpart C 15.215
Test Method:	ANSI C63.10 (2013) Section 7.8.7
Limit:	N/A

7.2.1 E.U.T. Operation

Operating Environment:

Temperature:24.2 °CHumidity:44.7 % RHAtmospheric Pressure:1015mbarTest modea:Charge mode_Keep the EUT charging(5W)

7.2.2 Test Setup Diagram



Ground Reference Plane

7.2.3 Measurement Procedure and Data



Report No.: SZEM181000928801 Page: 14 of 21





Report No.: SZEM181000928801 Page: 15 of 21

7.3 Radiated Emissions (30MHz-1GHz)

Test Requirement:47 CFR Part 15, Subpart C 15.205 & 15.209Test Method:ANSI C63.10 (2013) Section 6.4,6.5,6.6Frequency Range:9kHz to 1GHzMeasurement Distance:3m and 10mLimit:Image: Compare the section of the section of

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report No.: SZEM181000928801 Page: 16 of 21

7.3.1 E.U.T. Operation

Operating Environment:

Temperature:23.9 °CHumidity:60.4 % RHAtmospheric Pressure:1015mbarTest modea:Charge mode_Keep the EUT charging(5W)

7.3.2 Test Setup Diagram



Above 1GHz

Test Receiver

Ground Reference Plane

7.3.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.



Report No.: SZEM181000928801 Page: 17 of 21

Mode: a; 0.009-0.15MHz



Condition: 10m Job No. : 09288CR Test Mode: a

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 pp 3	0.01 0.03 0.10	0.28 0.17 0.05	18.47 13.73 11.97	32.55 32.56 32.56	73.19 73.52 64.70	59.39 54.86 44.16	105.52 96.78 86.30	-46.13 -41.92 -42.14



Report No.: SZEM181000928801 Page: 18 of 21

Mode: a; 0.15-30MHz



Condition: 10m Job No. : 09288CR Test Mode: a

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
-								
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
			40.00				70.00	
1	0.25	0.08	12.00	32.56	/3.6/	53.19	/8.80	-25.61
2 pp	0.86	0.20	12.00	32.56	62.15	41.79	48.03	-6.24
3	3.14	0.38	12.18	32.54	51.79	31.81	48.63	-16.82



Report No.: SZEM181000928801 Page: 19 of 21

Mode:a; Polarization:Horizontal;



Condition: 3m HORIZONTAL Job No. : 09288CR Test mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	36.77	0.60	18.97	27.64	24.60	16.53	40.00	-23.47
2	90.22	1.10	13.12	27.51	29.76	16.47	43.50	-27.03
3	147.40	1.31	14.39	27.52	26.64	14.82	43.50	-28.68
4	386.63	2.16	22.07	27.71	24.24	20.76	46.00	-25.24
5	554.83	2.66	25.74	27.78	24.74	25.36	46.00	-20.64
6 pp	854.02	3.42	29.22	27.23	24.37	29.78	46.00	-16.22



Report No.: SZEM181000928801 Page: 20 of 21

Mode:a; Polarization:Vertical;



Condition: 3m VERTICAL Job No. : 09288CR Test mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.86	0.60	20.92	27.66	26.17	20.03	40.00	-19.97
2	112.52	1.23	13.42	27.51	33.69	20.83	43.50	-22.67
3 pp	115.32	1.24	13.30	27.51	44.13	31.16	43.50	-12.34
4	125.01	1.26	13.26	27.52	35.30	22.30	43.50	-21.20
5	152.13	1.32	14.82	27.52	33.57	22.19	43.50	-21.31
6	185.14	1.38	16.06	27.53	29.01	18.92	43.50	-24.58



Report No.: SZEM181000928801 Page: 21 of 21

8 Photographs

- 8.1 Test Setup Refer to Setup Photos
- 8.2 EUT Constructional Details (EUT Photos) Refer to EUT external and internal photos

- End of the Report -