

TEST REPORT

Product Name : **Mi Smart Compact Projector**
Model Number : **M055MGN**
FCC ID : **2AO2D-M055MGN**

Prepared for : Fengmi (Beijing) Technology Co., Ltd.
Address : 301,3F,Building 3,No.10,Barracks South Street,Renhe
Town,Shunyi District,Beijing,China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ES191115017W01-1
Date(s) of Tests : November 16,2019 to November 29, 2019
June 02, 2021 to June 16, 2021
Date of issue : June 22, 2021

Table of Contents

| | | |
|-----|---|----|
| 1 | TEST RESULT CERTIFICATION | 3 |
| 2 | EUT TECHNICAL DESCRIPTION | 4 |
| 3 | SUMMARY OF TEST RESULT | 5 |
| 4 | TEST METHODOLOGY | 6 |
| 4.1 | GENERAL DESCRIPTION OF APPLIED STANDARDS | 6 |
| 4.2 | MEASUREMENT EQUIPMENT USED | 6 |
| 4.3 | DESCRIPTION OF TEST MODES | 9 |
| 5 | FACILITIES AND ACCREDITATIONS | 10 |
| 5.1 | FACILITIES | 10 |
| 5.2 | EQUIPMENT | 10 |
| 5.3 | LABORATORY ACCREDITATIONS AND LISTINGS | 10 |
| 6 | TEST SYSTEM UNCERTAINTY | 11 |
| 7 | SETUP OF EQUIPMENT UNDER TEST | 12 |
| 7.1 | RADIO FREQUENCY TEST SETUP 1 | 12 |
| 7.2 | RADIO FREQUENCY TEST SETUP 2 | 12 |
| 7.3 | CONDUCTED EMISSION TEST SETUP | 14 |
| 7.4 | BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM | 15 |
| 7.5 | SUPPORT EQUIPMENT | 15 |
| 8 | FREQUENCY HOPPING SYSTEM REQUIREMENTS | 16 |
| 8.1 | STANDARD APPLICABLE | 16 |
| 8.2 | EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE | 16 |
| 8.3 | EQUAL HOPPING FREQUENCY USE | 17 |
| 8.4 | FREQUENCY HOPPING SYSTEM | 17 |
| 9 | TEST REQUIREMENTS | 18 |
| 9.1 | 20DB BANDWIDTH | 18 |
| 9.2 | CARRIER FREQUENCY SEPARATION | 24 |
| 9.3 | NUMBER OF HOPPING FREQUENCIES | 30 |
| 9.4 | AVERAGE TIME OF OCCUPANCY (DWELL TIME) | 32 |
| 9.5 | MAXIMUM PEAK CONDUCTED OUTPUT POWER | 35 |
| 9.6 | CONDUCTED SUPRIIOUS EMISSION | 41 |
| 9.7 | RADIATED SPURIOUS EMISSION | 48 |
| 9.8 | CONDUCTED EMISSION TEST | 61 |
| 9.9 | ANTENNA APPLICATION | 64 |

1 TEST RESULT CERTIFICATION

Applicant : Fengmi (Beijing) Technology Co., Ltd.

Address : 301,3F,Building 3,No.10,Barracks South Street,Renhe Town,Shunyi District, Beijing,China

Manufacturer : Fengmi (Beijing) Technology Co., Ltd.

Address : 301,3F,Building 3,No.10,Barracks South Street,Renhe Town,Shunyi District, Beijing,China

EUT : Mi Smart Compact Projector

Model Name : M055MGN

Trademark : N/A

Measurement Procedure Used:

| APPLICABLE STANDARDS | |
|---|-------------|
| STANDARD | TEST RESULT |
| FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C | PASS |

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test : November 16,2019 to November 29, 2019
June 02, 2021 to June 16, 2021

Prepared by :

Sewen Guo /Editor

Reviewer :

Sevin Li /Supervisor

Approve & Authorized Signer :

Lisa Wang/Manager

2 EUT TECHNICAL DESCRIPTION

| Characteristics | Description |
|-------------------------------|--|
| Product | Mi Smart Compact Projector |
| Model Number | M055MGN |
| Device Type | Bluetooth V4.2 |
| Data Rate | 1Mbps for BT GFSK modulation 2Mbps for BT pi/4-DQPSK modulation 3Mbps for BT 8DPSK modulation |
| Modulation: | GFSK modulation for BT (1Mbps) pi/4-DQPSK modulation for BT (2Mbps) 8DPSK modulation for BT (3Mbps) |
| Operating Frequency Range(s): | 2402-2480MHz |
| Number of Channels: | 79 channels |
| Transmit Power Max: | 9.838 dBm |
| Antenna Type | Internal Antenna |
| Antenna Gain | 3.97 dBi |
| Power supply | <input checked="" type="checkbox"/> DC 19V for adapter |
| | <input checked="" type="checkbox"/> Adapter : Model: DSA-65PFG-19 FUS 190342 Input:AC100-240V,50/60Hz,2.0A Output:DC19V,3.42A |
| Temperature Range: | 0°C ~ +40°C |

Note:

- 1) for more details, please refer to the User's manual of the EUT.
- 2) Update the TV board circuit on the basis of the original report (ES191115017W01); update the Radiated Spurious Emissions test, and other test data are quoted from the original report.

3 SUMMARY OF TEST RESULT

| FCC Part Clause | Test Parameter | Verdict | Remark |
|--|--|---------|--------|
| 15.247(a)(1) | 20 dB Bandwidth | PASS | NOTE2 |
| 15.247(a)(1) | Carrier Frequency Separation | PASS | NOTE2 |
| 15.247(a)(1) | Number of Hopping Frequencies | PASS | NOTE2 |
| 15.247(a)(1) | Average Time of Occupancy (Dwell Time) | PASS | NOTE2 |
| 15.247(b)(1) | Maximum Peak Conducted Output Power | PASS | NOTE2 |
| 15.247(c) | Conducted Spurious Emissions | PASS | NOTE2 |
| 15.247(d) 15.209 | Radiated Spurious Emissions | PASS | |
| 15.207 | Conducted Emission | PASS | NOTE2 |
| 15.203 | Antenna Application | PASS | NOTE2 |
| 15.247 (a) (1)/g/h | Frequency Hopping System | PASS | NOTE2 |
| NOTE1: N/A (Not Applicable) | | | |
| NOTE2: Update the TV board circuit on the basis of the original report (ES191115017W01); update the Radiated Spurious Emissions test, and other test data are quoted from the original report. | | | |

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AO2D-M055MGN filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

4.2 MEASUREMENT EQUIPMENT USED

Conducted Emission Test Equipment

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|---------------------------|-----------------|-----------|------------|--------------|---------------|
| Test Receiver | Rohde & Schwarz | ESCI | 101384 | May 18, 2019 | 1 Year |
| L.I.S.N. | Rohde & Schwarz | ENV216 | 5 | May 18, 2019 | 1 Year |
| L.I.S.N. | Kyoritsu | KNW-407 | 8-1492-9 | May 18, 2019 | 1 Year |
| Absorbing Clamp | Rohde & Schwarz | MDS-21 | 833711/025 | July 5, 2019 | 1 Year |
| Loop antenna | Laplace | RF300 | 8006 | July 1, 2019 | 1 Year |
| Van der Hoofden test-head | Schwarzbeck | VDHH 9502 | 9502-054 | May 18, 2019 | 1 Year |
| Pulse Limiter | Rohde & Schwarz | ESH3-Z2 | 100107 | May 18, 2019 | 1 Year |

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|---------------------------|-----------------|-----------|------------|---------------|---------------|
| Test Receiver | Rohde & Schwarz | ESCI | 101384 | May 15, 2021 | 1 Year |
| L.I.S.N. | Rohde & Schwarz | ENV216 | 5 | May 15, 2021 | 1 Year |
| L.I.S.N. | Kyoritsu | KNW-407 | 8-1492-9 | May 16, 2021 | 1 Year |
| Absorbing Clamp | Rohde & Schwarz | MDS-21 | 833711/025 | July 4, 2020 | 1 Year |
| Loop antenna | Laplace | RF300 | 8006 | June 30, 2020 | 1 Year |
| Van der Hoofden test-head | Schwarzbeck | VDHH 9502 | 9502-054 | May 15, 2021 | 1 Year |
| Pulse Limiter | Rohde & Schwarz | ESH3-Z2 | 100107 | May 15, 2021 | 1 Year |

For Spurious Emissions Test

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|-------------------|-----------------|----------------|--------------|---------------|---------------|
| EMI Test Receiver | Rohde & Schwarz | ESU 26 | 100154 | May 18, 2019 | 1 Year |
| Pre-Amplifier | Lunar EM | LNA30M3G-25 | J10100000070 | May 18, 2019 | 1 Year |
| Bilog Antenna | Schwarzbeck | VULB9163 | 659 | Sep 22, 2019 | 2 Year |
| Horn antenna | Schwarzbeck | BBHA9120D | 9120D-1177 | July 5, 2018 | 2 Year |
| Pre-Amplifier | SKET | LNPA_0118G-45 | SK2019051801 | May 18, 2019 | 1 Year |
| Loop Antenna | Schwarzbeck | FMZB1519 | 1519-012 | July 14, 2019 | 2 Year |
| Spectrum Analyzer | Rohde & Schwarz | FSV40 | 100967 | May 18, 2019 | 1 Year |
| Horn antenna | Schwarzbeck | BBHA9120D | 9120D-1198 | May 17, 2019 | 2 Year |
| Bilog Antenna | Schwarzbeck | VULB9163 | 660 | July 16, 2019 | 2 Year |
| Cable | H+B | NmSm-05-C15052 | N/A | May 18, 2019 | 1 Year |
| Cable | H+B | NmSm-2-C15201 | N/A | May 18, 2019 | 1 Year |
| Cable | H+B | NmNm-7-C15702 | N/A | May 18, 2019 | 1 Year |

| | | | | | |
|-----------------------------|-------|------------------------------|-----------|--------------|--------|
| Cable | H+B | SAC-40G-1 | 414 | May 18, 2019 | 1 Year |
| Cable | H+B | SUCOFLEX104 | MY14871/4 | May 18, 2019 | |
| Cable | H+B | BLU18A-NmSm-650 0 | D8501 | May 18, 2019 | 1 Year |
| Band reject Filter(50dB) | WI/DE | WRCGV-2400(2400- 2485MHz) | 2 | May 18, 2019 | 1 Year |

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|-----------------------------|-----------------|------------------------------|--------------|---------------|------------------|
| EMI Test Receiver | Rohde & Schwarz | ESU 26 | 100154 | May 15, 2021 | 1 Year |
| Pre-Amplifie | Lunar EM | LNA30M3G-25 | J10100000070 | May 15, 2021 | 1 Year |
| Bilog Antenna | Schwarzbeck | VULB9163 | 659 | Sep 22, 2019 | 2 Year |
| Horn antenna | Schwarzbeck | BBHA9120D | 9120D-1177 | July 4, 2020 | 2 Year |
| Pre-Amplifie | SKET | LNPA_0118G-45 | SK2019051801 | May 15, 2021 | 1 Year |
| Loop Antenna | Schwarzbeck | FMZB1519 | 1519-012 | July 14, 2019 | 2 Year |
| Spectrum Analyzer | Rohde & Schwarz | FSV40 | 100967 | May 15, 2021 | 1 Year |
| Horn antenna | Schwarzbeck | BBHA9120D | 9120D-1198 | May 15, 2021 | 2 Year |
| Bilog Antenna | Schwarzbeck | VULB9163 | 660 | July 16, 2019 | 2 Year |
| Cable | H+B | NmSm-05-C15052 | N/A | May 15, 2021 | 1 Year |
| Cable | H+B | NmSm-2-C15201 | N/A | May 15, 2021 | 1 Year |
| Cable | H+B | NmNm-7-C15702 | N/A | May 15, 2021 | 1 Year |
| Cable | H+B | SAC-40G-1 | 414 | May 15, 2021 | 1 Year |
| Cable | H+B | SUCOFLEX104 | MY14871/4 | May 15, 2021 | |
| Cable | H+B | BLU18A-NmSm-650 0 | D8501 | May 15, 2021 | 1 Year |
| Band reject Filter(50dB) | WI/DE | WRCGV-2400(2400- 2485MHz) | 2 | May 15, 2021 | 1 Year |

For other test items:

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|--|--------------|------------|---------------------------|--------------|------------------|
| Vector Signal Generater | Agilent | N5182B | My53050553 | May 17, 2019 | 1 Year |
| Analog Signal Generator | Agilent | N5171B | My53050878 | May 17, 2019 | 1 Year |
| Signal Analyzer | Agilent | N9010A | My53470879 | May 17, 2019 | 1 Year |
| Power Analyzer | Agilent | PS-X10-200 | N/A | May 17, 2019 | 1 Year |
| Wideband Radio Communication Tester | R&S | CMW500 | 1201.0002K50- 140822zk | May 17, 2019 | 1 Year |
| Test Accessories | Agilent | PS-X10-100 | N/A | May 17, 2019 | 1 Year |
| Temperature&Humidity test chamber | ESPEC | EL-02KA | 12107166 | May 17, 2019 | 1 Year |
| Blocking Box | Agilent | AD211 | N/A | May 17, 2019 | 1 Year |

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|-------------------------------------|--------------|------------|-----------------------|--------------|---------------|
| Vector Signal Generator | Agilent | N5182B | My53050553 | May 15, 2021 | 1 Year |
| Analog Signal Generator | Agilent | N5171B | My53050878 | May 15, 2021 | 1 Year |
| Signal Analyzer | Agilent | N9010A | My53470879 | May 15, 2021 | 1 Year |
| Power Analyzer | Agilent | PS-X10-200 | N/A | May 15, 2021 | 1 Year |
| Wideband Radio Communication Tester | R&S | CMW500 | 1201.0002K50-140822zk | May 15, 2021 | 1 Year |
| Test Accessories | Agilent | PS-X10-100 | N/A | May 15, 2021 | 1 Year |
| Temperature&Humidity test chamber | ESPEC | EL-02KA | 12107166 | May 15, 2021 | 1 Year |
| Blocking Box | Agilent | AD211 | N/A | May 15, 2021 | 1 Year |

Remark: Each piece of equipment is scheduled for calibration once a year.



4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth GFSK modulation; 2Mbps for Bluetooth pi/4-DQPSK modulation; 3Mbps for Bluetooth 8DPSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---|-----------------|---------|-----------------|---------|-----------------|
| 0 | 2402 | 39 | 2441 | ... | ... |
| 1 | 2403 | 40 | 2442 | 76 | 2478 |
| 2 | 2404 | 41 | 2443 | 77 | 2479 |
| ... | ... | ... | ... | 78 | 2480 |
| Note: $f_c = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ $k=1$ to 79 | | | | | |

Test Frequency and channel for Bluetooth

| Lowest Frequency | | Middle Frequency | | Highest Frequency | |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 0 | 2402 | 39 | 2441 | 78 | 2480 |

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at:

EMTEK (Shenzhen) Co., Ltd.

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTINGS

| Site Description | |
|------------------|---|
| EMC Lab. | <p>: Accredited by CNAS The Certificate Registration Number is L2291. The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)</p> <p>Accredited by FCC Designation Number: CN1204 Test Firm Registration Number: 882943</p> <p>Accredited by A2LA The Certificate Number is 4321.01.</p> <p>Accredited by Industry Canada The Conformity Assessment Body Identifier is CN0008</p> |
| Name of Firm | : EMTEK (SHENZHEN) CO., LTD. |
| Site Location | : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China |

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


| Parameter | Uncertainty |
|--------------------------------|-------------------------|
| Radio Frequency | $\pm 1 \times 10^{-5}$ |
| Maximum Peak Output Power Test | $\pm 1.0\text{dB}$ |
| Conducted Emissions Test | $\pm 2.0\text{dB}$ |
| Radiated Emission Test | $\pm 2.0\text{dB}$ |
| Occupied Bandwidth Test | $\pm 1.0\text{dB}$ |
| Band Edge Test | $\pm 3\text{dB}$ |
| All emission, radiated | $\pm 3\text{dB}$ |
| Antenna Port Emission | $\pm 3\text{dB}$ |
| Temperature | $\pm 0.5^\circ\text{C}$ |
| Humidity | $\pm 3\%$ |

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

| EUT Cable List and Details | | | |
|----------------------------|------------|---------------------|------------------------|
| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| Adapter cable | 1.5 | Unshielded | Without Ferrite |

| Auxiliary Cable List and Details | | | |
|----------------------------------|------------|---------------------|------------------------|
| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| HDMI cable | 1.5 | Shielded | With Ferrite |

| Auxiliary Equipment List and Details | | | |
|--------------------------------------|--------------|-------|----------------------------|
| Description | Manufacturer | Model | Serial Number |
| Notebook | acer | ZR1 | LXTECOCO76643158 372500 |

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

8.2 EUT Pseudorandom Frequency Hopping Sequence


The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels.

The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

9 TEST REQUIREMENTS

9.1 20DB BANDWIDTH

9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.1.2 Conformance Limit

No limit requirement.

9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.1.4 Test Procedure

The EUT was operating in Bluetooth mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.


Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Modulation Mode | Channel Number | Channel Frequency (MHz) | Measurement Bandwidth (MHz) | Limit (MHz) | Verdict |
|-----------------|----------------|-------------------------|-----------------------------|-------------|---------|
| GFSK | 00 | 2402 | 1.048 | N/A | PASS |
| | 39 | 2441 | 1.036 | N/A | PASS |
| | 78 | 2480 | 1.044 | N/A | PASS |
| pi/4-DQPSK | 00 | 2402 | 1.359 | N/A | PASS |
| | 39 | 2441 | 1.360 | N/A | PASS |
| | 78 | 2480 | 1.359 | N/A | PASS |
| 8DPSK | 00 | 2402 | 1.335 | N/A | PASS |
| | 39 | 2441 | 1.323 | N/A | PASS |
| | 78 | 2480 | 1.357 | N/A | PASS |

Note: N/A (Not Applicable)

Test Model 20dB Bandwidth
Bluetooth
Channel 0: 2402MHz GFSK Modulation




Test Model 20dB Bandwidth
Bluetooth
Channel 39: 2441MHz GFSK Modulation




Test Model 20dB Bandwidth
Bluetooth
Channel 78: 2480MHz GFSK Modulation




Test Model 20dB Bandwidth
Bluetooth
Channel 0: 2402MHz pi/4-DQPSK Modulation




Test Model 20dB Bandwidth
Bluetooth
Channel 39: 2441MHz pi/4-DQPSK Modulation



Test Model 20dB Bandwidth
Bluetooth
Channel 78: 2480MHz pi/4-DQPSK Modulation




| | |
|------------|--------------------|
| Test Model | 20dB Bandwidth |
| | Bluetooth |
| | Channel 0: 2402MHz |
| | 8DPSK Modulation |



| | |
|------------|---------------------|
| Test Model | 20dB Bandwidth |
| | Bluetooth |
| | Channel 39: 2441MHz |
| | 8DPSK Modulation |



| | |
|------------------|---------------------|
| Test Model | 20dB Bandwidth |
| | Bluetooth |
| | Channel 78: 2480MHz |
| 8DPSK Modulation | |



9.2 CARRIER FREQUENCY SEPARATION

9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.2.4 Test Procedure

■ According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Set the RBW =100kHz. Set VBW =300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.


Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |


| Modulation Mode | Channel Number | Channel Frequency (MHz) | Measurement Bandwidth (kHz) | Limit (kHz) | Verdict |
|-----------------|----------------|-------------------------|-----------------------------|-------------|---------|
| GFSK | 0 | 2402 | 1002 | >699 | PASS |
| | 39 | 2441 | 1008 | >691 | PASS |
| | 78 | 2480 | 1008 | >696 | PASS |
| pi/4-DQPSK | 0 | 2402 | 1008 | >906 | PASS |
| | 39 | 2441 | 1005 | >907 | PASS |
| | 78 | 2480 | 1008 | >906 | PASS |
| 8DPSK | 0 | 2402 | 1002 | >890 | PASS |
| | 39 | 2441 | 1002 | >882 | PASS |
| | 78 | 2480 | 1002 | >905 | PASS |

Note: Limit = 20dB bandwidth * 2/3


Test Model Carrier Frequency Separation
Bluetooth
Channel 0: 2402MHz GFSK Modulation




Test Model Carrier Frequency Separation
Bluetooth
Channel 39: 2441MHz GFSK Modulation



Test Model Carrier Frequency Separation
Bluetooth
Channel 78: 2480MHz GFSK Modulation



Test Model Carrier Frequency Separation
Bluetooth
Channel 0: 2402MHz pi/4-DQPSK Modulation




Test Model

Carrier Frequency Separation

Bluetooth

Channel 39: 2441MHz

pi/4-DQPSK Modulation




Test Model

Carrier Frequency Separation

Bluetooth

Channel 78: 2480MHz


pi/4-DQPSK Modulation



Test Model Carrier Frequency Separation
Bluetooth
Channel 0: 2402MHz 8DPSK Modulation



Test Model Carrier Frequency Separation
Bluetooth
Channel 39: 2441MHz 8DPSK Modulation




Test Model

Carrier Frequency Separation

Bluetooth

Channel 78: 2480MHz

8DPSK Modulation



9.3 NUMBER OF HOPPING FREQUENCIES

9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.3.4 Test Procedure

■ According to FCC Part 15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2400-2483.5MHz)

RBW \geq 100KHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.


Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Modulation Mode | Hopping Channel Frequency Range | Quantity of Hopping Channel | Quantity of Hopping Channel limit |
|-----------------|---------------------------------|-----------------------------|-----------------------------------|
| GFSK | 2402-2480 | 79 | > 15 |
| pi/4-DQPSK | 2402-2480 | 79 | > 15 |
| 8DPSK | 2402-2480 | 79 | > 15 |

Test Model

Number Of Hopping Frequencies
Bluetooth
Span: 2400-2483.5MHz



9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.4.4 Test Procedure

■ According to FCC Part 15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

9.4.5 Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |


Bluetooth (GFSK,) mode have been tested:

| Modulation Mode | Channel Number | Packet type | Pulse width (ms) | Dwell Time (ms) | Limit (ms) | Verdict |
|---|----------------|-------------|------------------|-----------------|------------|---------|
| GFSK | 0 | DH1 | 0.384 | 122.880 | <400 | PASS |
| | 0 | DH3 | 1.638 | 262.080 | <400 | PASS |
| | 0 | DH5 | 2.880 | 307.200 | <400 | PASS |
| Note: Dwell Time(DH1)=PW*(1600/2/79)*31.6 Dwell Time(DH3)=PW*(1600/4/79)*31.6 Dwell Time(DH5)=PW*(1600/6/79)*31.6 | | | | | | |


| | |
|------------|--|
| Test Model | Average Time Of Occupancy (Dwell Time) |
| | Bluetooth |
| | CH 0: 2402MHz |
| | GFSK DH1 |



| | |
|------------|--|
| Test Model | Average Time Of Occupancy (Dwell Time) |
| | Bluetooth |
| | CH 0: 2402MHz |
| | GFSK DH3 |



Test Model Average Time Of Occupancy (Dwell Time)
Bluetooth
CH 0: 2402MHz GFSK DH5



9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.5.4 Test Procedure

■ According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel (about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured (about 3MHz)

Set VBW ≥ RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold


Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.

Test Results


| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Operation Mode | Channel Number | Channel Frequency (MHz) | Measurement Level (dBm) | Limit (dBm) | Verdict |
|----------------|----------------|-------------------------|-------------------------|-------------|---------|
| GFSK | 0 | 2402 | 8.598 | 30 | PASS |
| | 39 | 2441 | 9.838 | 30 | PASS |
| | 78 | 2480 | 9.679 | 30 | PASS |
| pi/4-DQPSK | 0 | 2402 | 8.606 | 30 | PASS |
| | 39 | 2441 | 9.380 | 30 | PASS |
| | 78 | 2480 | 9.024 | 30 | PASS |
| 8DPSK | 0 | 2402 | 9.062 | 30 | PASS |
| | 39 | 2441 | 9.801 | 30 | PASS |
| | 78 | 2480 | 9.551 | 30 | PASS |
| Note: N/A | | | | | |


Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 0: 2402MHz GFSK




Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 39: 2441MHz GFSK




Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 78: 2480MHz GFSK




Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 0: 2402MHz pi/4-DQPSK




Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 39: 2441MHz pi/4-DQPSK




Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 78: 2480MHz pi/4-DQPSK




Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 0: 2402MHz 8DPSK



Test Model Maximum Peak Conducted Output Power
Bluetooth
Channel 39: 2441MHz 8DPSK



| | | |
|------------|-------------------------------------|-------|
| Test Model | Maximum Peak Conducted Output Power | |
| | Bluetooth | |
| | Channel 78: 2480MHz | 8DPSK |



9.6 CONDUCTED SUPRIIOUS EMISSION

9.6.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conduceted level.

Note that the channel found to contain the maximum conduceted level can be used to establish the reference level.

■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW $\geq 1\%$ of the span=100kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

■ Conducted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz). Set RBW = 100 kHz Set VBW \geq RBW


Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


9.6.5 Test Results

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:


Maximum Conduced Level RBW=100kHz
Test Model Bluetooth
Channel 0: 2402MHz GFSK




Conduced Spurious RF Conducted Emission
Test Model Bluetooth
Channel 0: 2402MHz GFSK



Test Model Band-edge Conducted Emissions
Bluetooth
Channel 0: 2402MHz GFSK




Test Model Maximum Conducted Level RBW=100kHz
Bluetooth
Channel 39: 2441MHz GFSK




Test Model Conducted Spurious RF Conducted Emission
Bluetooth
Channel 39: 2441MHz GFSK




Test Model Maximum Conducted Level RBW=100kHz
Bluetooth
Channel 78: 2480MHz GFSK



Test Model Conducted Spurious RF Conducted Emission
Bluetooth
Channel 78: 2480MHz GFSK



Test Model Band-edge Conducted Emissions
Bluetooth
Channel 78: 2480MHz GFSK




Test Model Maximum Conducted Level RBW=100kHz
Bluetooth
Hopping GFSK




Test Model Conducted Spurious RF Conducted Emission
Bluetooth
Hopping GFSK



Test Model Band-edge Conducted Emissions
Bluetooth
Hopping GFSK



Test Model Band-edge Conducted Emissions
Bluetooth
Hopping GFSK



9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| 10.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (2) |
| 13.36-13.41 | | | |

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

| Restricted Frequency(MHz) | Field Strength (μV/m) | Field Strength (dBμV/m) | Measurement Distance |
|---------------------------|-----------------------|-------------------------|----------------------|
| 0.009-0.490 | 2400/F(KHz) | 20 log (uV/m) | 300 |
| 0.490-1.705 | 24000/F(KHz) | 20 log (uV/m) | 30 |
| 1.705-30 | 30 | 29.5 | 30 |
| 30-88 | 100 | 40 | 3 |
| 88-216 | 150 | 43.5 | 3 |
| 216-960 | 200 | 46 | 3 |
| Above 960 | 500 | 54 | 3 |

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

| | |
|--------------------|-----------|
| Temperature: | 21.6° C |
| Relative Humidity: | 45% |
| ATM Pressure: | 1011 mbar |

| Freq. (MHz) | Ant.Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|-----------------|---------------------------|----|------------------|----|----------|----|
| | | PK | AV | PK | AV | PK | AV |
| -- | -- | -- | -- | -- | -- | -- | -- |

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

| | | | |
|------------|------|------------|--------------------|
| Test mode: | GFSK | Frequency: | Channel 0: 2402MHz |
| Test By: | ZXW | Test date: | June 11 2021 |

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|----------|------------------------|-------|------------------|-------|----------|--------|
| | H/V | PK | AV | PK | AV | PK | AV |
| 4806.3 | V | 55.73 | 41.24 | 74.00 | 54.00 | -18.27 | -12.76 |
| 7173.32 | V | 51.42 | 40.67 | 74.00 | 54.00 | -22.58 | -13.33 |
| 9840.25 | V | 49.95 | 37.85 | 74.00 | 54.00 | -24.05 | -16.15 |
| 4805.79 | H | 57.07 | 41.22 | 74.00 | 54.00 | -16.93 | -12.78 |
| 7157.44 | H | 52.34 | 38.44 | 74.00 | 54.00 | -21.66 | -15.56 |
| 9910.11 | H | 49.47 | 35.67 | 74.00 | 54.00 | -24.53 | -18.33 |

| | | | |
|------------|------|------------|---------------------|
| Test mode: | GFSK | Frequency: | Channel 39: 2441MHz |
| Test By: | ZXW | Test date: | June 11 2021 |

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|----------|------------------------|-------|------------------|-------|----------|--------|
| | H/V | PK | AV | PK | AV | PK | AV |
| 4887.65 | V | 58.59 | 42.45 | 74.00 | 54.00 | -15.41 | -11.55 |
| 7481.36 | V | 53.61 | 39.49 | 74.00 | 54.00 | -20.39 | -14.51 |
| 10269.14 | V | 47.46 | 37.02 | 74.00 | 54.00 | -26.54 | -16.98 |
| 4880.68 | H | 59.00 | 42.21 | 74.00 | 54.00 | -15.00 | -11.79 |
| 7555.51 | H | 51.25 | 38.35 | 74.00 | 54.00 | -22.75 | -15.65 |
| 10226.74 | H | 47.78 | 35.28 | 74.00 | 54.00 | -26.22 | -18.72 |

| | | | |
|------------|------|------------|---------------------|
| Test mode: | GFSK | Frequency: | Channel 78: 2480MHz |
| Test By: | ZXW | Test date: | June 11 2021 |

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|----------|------------------------|-------|------------------|-------|----------|--------|
| | H/V | PK | AV | PK | AV | PK | AV |
| 4969.40 | V | 57.87 | 41.31 | 74.00 | 54.00 | -16.13 | -12.69 |
| 7367.36 | V | 50.76 | 38.57 | 74.00 | 54.00 | -23.24 | -15.43 |
| 1160.45 | V | 47.74 | 37.57 | 74.00 | 54.00 | -26.26 | -16.43 |
| 4963.31 | H | 55.01 | 42.76 | 74.00 | 54.00 | -18.99 | -11.24 |
| 7681.38 | H | 50.96 | 38.22 | 74.00 | 54.00 | -23.04 | -15.78 |
| 1254.14 | H | 48.54 | 37.22 | 74.00 | 54.00 | -25.46 | -16.78 |

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

| | | | |
|------------|------|------------|--------------------|
| Test mode: | GFSK | Frequency: | Channel 0: 2402MHz |
| Test By: | ZXW | Test date: | June 11 2021 |

| Frequency (MHz) | Polarity H/V | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m) |
|-----------------|--------------|-----------------------|-------------------|-----------------------|-------------------|
| 2387.92 | H | 54.40 | 74 | 36.40 | 54 |
| 2389.04 | V | 54.31 | 74 | 36.31 | 54 |

| | | | |
|------------|------|------------|---------------------|
| Test mode: | GFSK | Frequency: | Channel 78: 2480MHz |
| Test By: | ZXW | Test date: | June 11 2021 |


| Frequency (MHz) | Polarity H/V | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m) |
|-----------------|--------------|-----------------------|-------------------|-----------------------|-------------------|
| 2484.29 | H | 55.37 | 74 | 37.37 | 54 |
| 2483.79 | V | 54.20 | 74 | 36.20 | 54 |

| | | | |
|------------|------|------------|--------------|
| Test mode: | GFSK | Frequency: | Hopping |
| Test By: | ZXW | Test date: | June 11 2021 |

| Frequency (MHz) | Polarity H/V | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m) |
|-----------------|--------------|-----------------------|-------------------|-----------------------|-------------------|
| 2400.00 | H | 54.02 | 74 | 36.02 | 54 |
| 2483.50 | H | 56.21 | 74 | 38.21 | 54 |
| 2400.00 | V | 52.89 | 74 | 34.89 | 54 |
| 2483.50 | V | 53.14 | 74 | 35.14 | 54 |


- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

| | | | |
|------------|---|-------------------------|---|
| Test Model | Spurious Emission in Restricted Band 2310-2390MHz | | |
| | Bluetooth | | |
| | Channel 0: 2402MHz | GFSK | H |
| Test By: | ZXW | Test date: June 11 2021 | |




| | | | | | |
|--------|-------------------------|---------------|--------------|--------------|--------|
| Site | 3m Chamber #1 | Polarization: | Horizontal | Temperature: | 21.6 C |
| Limit: | (RE)FCC PART 15 CLASS B | Power: | AC 120V/60Hz | Humidity: | 45 % |

| | | | |
|------------|---|-------------------------|---|
| Test Model | Spurious Emission in Restricted Band 2310-2390MHz | | |
| | Bluetooth | | |
| | Channel 0: 2402MHz | GFSK | V |
| Test By: | ZXW | Test date: June 11 2021 | |




| | | | | | |
|--------|-------------------------|---------------|--------------|--------------|--------|
| Site | 3m Chamber #1 | Polarization: | Vertical | Temperature: | 21.6 C |
| Limit: | (RE)FCC PART 15 CLASS B | Power: | AC 120V/60Hz | Humidity: | 45 % |

| | | | |
|------------|---|-------------------------|---|
| Test Model | Spurious Emission in Restricted Band 2483.5-2500MHz | | |
| | Bluetooth | | |
| | Channel 78: 2480MHz | GFSK | H |
| Test By: | ZXW | Test date: June 11 2021 | |




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 21.6 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 45 %

| | | | |
|------------|---|-------------------------|---|
| Test Model | Spurious Emission in Restricted Band 2483.5-2500MHz | | |
| | Bluetooth | | |
| | Channel 78: 2480MHz | GFSK | V |
| Test By: | ZXW | Test date: June 11 2021 | |




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 21.6 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 45 %

| | | | |
|------------|--|------|---|
| Test Model | Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz | | |
| | Bluetooth | | |
| | Hopping | | |
| Test By: | ZXW | GFSK | H |
| | Test date: June 11 2021 | | |




| | | | |
|------------|--|------|---|
| Test Model | Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz | | |
| | Bluetooth | | |
| | Hopping | | |
| Test By: | ZXW | GFSK | V |
| | Test date: June 11 2021 | | |



■ Spurious Emission below 1GHz (30MHz to 1GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:



Site 3m Chamber #3

Polarization: **Vertical**

Temperature: 21.6 C

Limit: (RE)FCC PART 15 CLASS B


Power: AC 120V/60Hz

Humidity: 45 %


Mode:BT-2402

Note:


| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|--------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | * | 33.6066 | 48.50 | -16.89 | 31.61 | 40.00 | -8.39 | QP | | |
| 2 | | 94.1804 | 48.14 | -17.68 | 30.46 | 43.50 | -13.04 | QP | | |
| 3 | | 186.1960 | 40.76 | -17.10 | 23.66 | 43.50 | -19.84 | QP | | |
| 4 | | 330.0500 | 38.48 | -11.96 | 26.52 | 46.00 | -19.48 | QP | | |
| 5 | | 744.2133 | 29.42 | -1.69 | 27.73 | 46.00 | -18.27 | QP | | |
| 6 | | 989.9692 | 40.31 | -1.70 | 38.61 | 54.00 | -15.39 | QP | | |



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|--------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 95.2597 | 41.75 | -17.53 | 24.22 | 43.50 | -19.28 | QP | | |
| 2 | * | 128.8450 | 49.76 | -17.47 | 32.29 | 43.50 | -11.21 | QP | | |
| 3 | | 241.0416 | 44.07 | -15.71 | 28.36 | 46.00 | -17.64 | QP | | |
| 4 | | 360.1320 | 39.87 | -10.77 | 29.10 | 46.00 | -16.90 | QP | | |
| 5 | | 446.6098 | 37.26 | -8.47 | 28.79 | 46.00 | -17.21 | QP | | |
| 6 | | 989.9692 | 41.86 | -1.70 | 40.16 | 54.00 | -13.84 | QP | | |



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|--------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | Comment |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 128.3377 | 49.83 | -17.48 | 32.35 | 43.50 | -11.15 | QP | | |
| 2 | | 215.8346 | 47.09 | -16.73 | 30.36 | 43.50 | -13.14 | QP | | |
| 3 | * | 330.0501 | 51.61 | -11.96 | 39.65 | 46.00 | -6.35 | QP | | |
| 4 | | 444.4615 | 40.38 | -8.51 | 31.87 | 46.00 | -14.13 | QP | | |
| 5 | | 889.1674 | 38.00 | -0.36 | 37.64 | 46.00 | -8.36 | QP | | |
| 6 | | 990.4032 | 42.26 | -1.68 | 40.58 | 54.00 | -13.42 | QP | | |



Site 3m Chamber #3

Polarization: **Vertical**

Temperature: 21.6 C

Limit: (RE)FCC PART 15 CLASS B


Power: AC 120V/60Hz

Humidity: 45 %


Mode: BT-2442

Note:

| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|--------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | * | 32.2642 | 48.84 | -17.09 | 31.75 | 40.00 | -8.25 | QP | | |
| 2 | | 94.5941 | 47.16 | -17.59 | 29.57 | 43.50 | -13.93 | QP | | |
| 3 | | 129.1843 | 43.59 | -17.47 | 26.12 | 43.50 | -17.38 | QP | | |
| 4 | | 330.0502 | 43.81 | -11.96 | 31.85 | 46.00 | -14.15 | QP | | |
| 5 | | 832.5870 | 35.65 | 0.77 | 36.42 | 46.00 | -9.58 | QP | | |
| 6 | | 990.4032 | 42.00 | -1.68 | 40.32 | 54.00 | -13.68 | QP | | |



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|--------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | Comment |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | * | 32.6913 | 49.98 | -17.03 | 32.95 | 40.00 | -7.05 | QP | | |
| 2 | | 93.8507 | 46.48 | -17.74 | 28.74 | 43.50 | -14.76 | QP | | |
| 3 | | 187.1778 | 40.78 | -17.15 | 23.63 | 43.50 | -19.87 | QP | | |
| 4 | | 330.1948 | 39.53 | -11.95 | 27.58 | 46.00 | -18.42 | QP | | |
| 5 | | 893.4650 | 31.69 | -0.42 | 31.27 | 46.00 | -14.73 | QP | | |
| 6 | | 990.4033 | 41.90 | -1.68 | 40.22 | 54.00 | -13.78 | QP | | |



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1 | | 128.6193 | 49.08 | -17.48 | 31.60 | 43.50 | -11.90 | QP | | |
| 2 | | 179.3863 | 46.25 | -17.44 | 28.81 | 43.50 | -14.69 | QP | | |
| 3 | | 219.5560 | 48.07 | -16.64 | 31.43 | 46.00 | -14.57 | QP | | |
| 4 | * | 330.0502 | 47.07 | -11.96 | 35.11 | 46.00 | -10.89 | QP | | |
| 5 | | 446.6098 | 40.34 | -8.47 | 31.87 | 46.00 | -14.13 | QP | | |
| 6 | | 893.4650 | 34.79 | -0.42 | 34.37 | 46.00 | -11.63 | QP | | |

9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207(a)

9.8.2 Conformance Limit

| Conducted Emission Limit | | |
|---|------------|---------|
| Frequency(MHz) | Quasi-peak | Average |
| 0.15-0.5 | 66-56 | 56-46 |
| 0.5-5.0 | 56 | 46 |
| 5.0-30.0 | 60 | 50 |
| Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz. | | |

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

Pass

The 120V & 240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #2

Phase: N

Temperature: 25.0

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 49 %

Mode: BT mode

Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1 | | 0.2660 | 40.73 | 9.91 | 50.64 | 61.24 | -10.60 | QP | |
| 2 | | 0.2660 | 27.04 | 9.91 | 36.95 | 51.24 | -14.29 | AVG | |
| 3 | | 0.3980 | 39.08 | 9.91 | 48.99 | 57.90 | -8.91 | QP | |
| 4 | | 0.3980 | 25.17 | 9.91 | 35.08 | 47.90 | -12.82 | AVG | |
| 5 | | 0.4940 | 37.80 | 9.92 | 47.72 | 56.10 | -8.38 | QP | |
| 6 | | 0.4940 | 26.48 | 9.92 | 36.40 | 46.10 | -9.70 | AVG | |
| 7 | | 1.0260 | 37.76 | 9.93 | 47.69 | 56.00 | -8.31 | QP | |
| 8 | | 1.0260 | 25.84 | 9.93 | 35.77 | 46.00 | -10.23 | AVG | |
| 9 | * | 2.7220 | 38.16 | 9.94 | 48.10 | 56.00 | -7.90 | QP | |
| 10 | | 2.7220 | 24.17 | 9.94 | 34.11 | 46.00 | -11.89 | AVG | |
| 11 | | 3.7100 | 37.41 | 9.94 | 47.35 | 56.00 | -8.65 | QP | |
| 12 | | 3.7100 | 23.58 | 9.94 | 33.52 | 46.00 | -12.48 | AVG | |



Site Conduction #2

Phase: **L1**

Temperature: 25.0

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 49 %

Mode: BT mode

Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1 | | 0.3220 | 37.61 | 9.91 | 47.52 | 59.66 | -12.14 | QP | |
| 2 | | 0.3220 | 23.80 | 9.91 | 33.71 | 49.66 | -15.95 | AVG | |
| 3 | * | 0.4460 | 36.86 | 9.92 | 46.78 | 56.95 | -10.17 | QP | |
| 4 | | 0.4460 | 24.28 | 9.92 | 34.20 | 46.95 | -12.75 | AVG | |
| 5 | | 0.6420 | 35.72 | 9.92 | 45.64 | 56.00 | -10.36 | QP | |
| 6 | | 0.6420 | 23.60 | 9.92 | 33.52 | 46.00 | -12.48 | AVG | |
| 7 | | 0.7660 | 35.69 | 9.92 | 45.61 | 56.00 | -10.39 | QP | |
| 8 | | 0.7660 | 23.60 | 9.92 | 33.52 | 46.00 | -12.48 | AVG | |
| 9 | | 1.0940 | 35.37 | 9.93 | 45.30 | 56.00 | -10.70 | QP | |
| 10 | | 1.0940 | 23.95 | 9.93 | 33.88 | 46.00 | -12.12 | AVG | |
| 11 | | 3.0820 | 34.19 | 9.94 | 44.13 | 56.00 | -11.87 | QP | |
| 12 | | 3.0820 | 18.69 | 9.94 | 28.63 | 46.00 | -17.37 | AVG | |

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

| Standard | Requirement |
|---------------------|--|
| FCC CRF Part 15.203 | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. |

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.9.2 Result

PASS.

The EUT has 1 antenna: a Internal Antenna for BT with classic model, the gain is 3.97 dBi;

Note: ☒ Antenna use a permanently attached antenna which is not replaceable.
☐ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

| Frequency(MHz) | Ant_F(dB) | Cab_L(dB) | Preamp(dB) | Correct Factor(dB) |
|----------------|-----------|-----------|------------|--------------------|
| 0.009 | 20.6 | 0.03 | \ | 20.63 |
| 0.15 | 20.7 | 0.1 | \ | 20.8 |
| 1 | 20.9 | 0.15 | \ | 21.05 |
| 10 | 20.1 | 0.28 | \ | 20.38 |
| 30 | 18.8 | 0.45 | \ | 19.25 |
| | | | | |
| 30 | 11.7 | 0.62 | 27.9 | -15.58 |
| 100 | 12.5 | 1.02 | 27.8 | -14.28 |
| 300 | 12.9 | 1.91 | 27.5 | -12.69 |
| 600 | 19.2 | 2.92 | 27 | -4.88 |
| 800 | 21.1 | 3.54 | 26.6 | -1.96 |
| 1000 | 22.3 | 4.17 | 26.2 | 0.27 |
| | | | | |
| 1000 | 25.6 | 1.76 | 41.4 | -14.04 |
| 3000 | 28.9 | 3.27 | 43.2 | -11.03 |
| 5000 | 31.1 | 4.2 | 44.6 | -9.3 |
| 8000 | 36.2 | 5.95 | 44.7 | -2.55 |
| 10000 | 38.4 | 6.3 | 43.9 | 0.8 |
| 12000 | 38.5 | 7.14 | 42.3 | 3.34 |
| 15000 | 40.2 | 8.15 | 41.4 | 6.95 |
| 18000 | 45.4 | 9.02 | 41.3 | 13.12 |
| | | | | |
| 18000 | 37.9 | 1.81 | 47.9 | -8.19 |
| 21000 | 37.9 | 1.95 | 48.7 | -8.85 |
| 25000 | 39.3 | 2.01 | 42.8 | -1.49 |
| 28000 | 39.6 | 2.16 | 46.0 | -4.24 |
| 31000 | 41.2 | 2.24 | 44.5 | -1.06 |
| 34000 | 41.5 | 2.29 | 46.6 | -2.81 |
| 37000 | 43.8 | 2.30 | 46.4 | -0.3 |
| 40000 | 43.2 | 2.50 | 42.2 | 3.5 |

----- END OF REPORT -----