



FCC CERTIFICATION TEST REPORT

Applicant	:	Aurender Inc.
Address of Applicant	:	#1612, Obiz Tower, 126, Beolmal-ro, Dongan-gu, Anyang-si, Gyeonggi-do, Republic of Korea
Manufacturer	:	Guangzhou Aoli Electronic Technology Co., Ltd
Address of Manufacturer	:	One of 101, No.1, Baiyun Road East, Fenghuang Village, Huadu District, Guangzhou City, Guangdong Province
Equipment under Test	:	Bluetooth Low Energy Remote
Model No.	:	RC1000
FCC ID	:	2AO2TAURRC1000
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013
Report No.	:	DDT-RE24030524-1E01
Issue Date	:	2024/06/26
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test.....	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	9
2.6.	Test environment conditions.....	9
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	10
3.	Equipment Used During Conductive Test	11
4.	6 dB Bandwidth.....	12
4.1.	Block diagram of test setup	12
4.2.	Limits.....	12
4.3.	Test procedure.....	12
4.4.	Test result	13
4.5.	Test graphs	14
6.	Maximum Peak Output Power.....	15
6.1.	Block diagram of test setup	15
6.2.	Limits.....	15
6.3.	Test procedure.....	15
6.4.	Test result	16
6.5.	Test graphs	17
7.	Power Spectral Density	18
7.1.	Block diagram of test setup	18
7.2.	Limits.....	18
7.3.	Test procedure.....	18
7.4.	Test result	19
7.5.	Test graphs	20
8.	Band Edge Compliance (Conducted Method).....	21
8.1.	Block diagram of test setup	21
8.2.	Limits.....	21
8.3.	Test procedure.....	21
8.4.	Test result	22
8.5.	Test graphs	23
9.	RF Conducted Spurious Emissions.....	24

9.1.	Block diagram of test setup	24
9.2.	Limits.....	24
9.3.	Test procedure.....	24
9.4.	Test result	25
9.5.	Test graphs.....	26
10.	Duty Cycle.....	29
10.1.	Block diagram of test setup	29
10.2.	Limit.....	29
10.3.	Test procedure.....	29
10.4.	Test result	30
10.5.	Test graphs.....	31
11.	Antenna Requirements	32
11.1.	Limit.....	32
11.2.	Result.....	32
12.	Radiated Emission.....	33
12.1.	Test equipment	33
12.2.	Block diagram of test setup	34
12.3.	Limits.....	35
12.4.	Assistant equipment used for test	36
12.5.	Test procedure.....	36
12.6.	Test result	38
12.7.	Test data	39
13.	Band Edge Compliance	47
13.1.	Test equipment	47
13.2.	Block diagram of test setup	48
13.3.	Limits.....	48
13.4.	Assistant equipment used for test	48
13.5.	Test procedure.....	48
13.6.	Test result	48
13.7.	Test data.....	49
14.	Power Line Conducted Emissions.....	53
14.1.	Test equipment	53
14.2.	Block diagram of test setup	53
14.3.	Limits.....	53
14.4.	Assistant equipment used for test	53
14.5.	Test procedure.....	53
14.6.	Test result	54
15.	Test Setup Photograph.....	55

16.	Photos of the EUT	57
-----	-------------------------	----

Test Report Declare

Applicant	:	Aurender Inc.
Address of Applicant	:	#1612, Obiz Tower, 126, Beolmal-ro, Dongan-gu, Anyang-si, Gyeonggi-do, Republic of Korea
Equipment under Test	:	Bluetooth Low Energy Remote
Model No.	:	RC1000
Manufacturer	:	Guangzhou Aoli Electronic Technology Co., Ltd
Address of Manufacturer	:	One of 101, No.1, Baiyun Road East, Fenghuang Village, Huadu District, Guangzhou City, Guangdong Province

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10:2013

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24030524-1E01		
Date of Receipt:	2024/04/30	Date of Test:	2024/04/30~2024/06/26

Prepared By:*Bobo Chen***Bobo Chen/Engineer****Approved By:****Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/06/26	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth	FCC Part 15: 15.247(a)(2)	/	Pass
2	Peak Output Power	FCC Part 15: 15.247(b)(3)	/	Pass
3	Power Spectral Density	FCC Part 15:15.247(e)	/	Pass
4	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d)	/	Pass
5	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d)	/	Pass
6	Band Edge Compliance	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d)	/	Pass
7	Power Line Conducted Emissions	FCC Part 15: 15.207(a)	/	N/A
8	Antenna Requirement	FCC Part 15: 15.203	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: Bluetooth Low Energy Remote
Model Number	: RC1000
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 3V

Radio Specification	: Bluetooth LE
Operation Frequency	: 2402 MHz-2480 MHz
Modulation	: GFSK

Antenna information	
Antenna Type	: PCB
Max Antenna Gain(dBi)	: -0.68

Bluetooth LE 1Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: BLE FCC Tool V1.08.exe(firmware or software)

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK 1M	7	CH0	2402
	7	CH19	2440
	7	CH39	2480

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method)
	5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
	1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 4#)				
Signal &Spectrum Analyzer	R&S	FSV3044	101173	2025/03/31
Wideband Radio Communication Tester	R&S	CMW500	168801	2025/03/31
MXG Vector Signal Generator	Agilent	N5182A	MY48180737	2025/03/31
PSG Vector Signal Generator	Agilent	E8267D	US49060192	2024/09/05
RF Control Unit	Tonsend	JS0806-2	2118060485	2025/03/31
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2025/04/22
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

4. 6 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:


RBW:	100 kHz
VBW:	$\geq [3 \times \text{RBW}]$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.

4.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	24.4℃,49.9%RH	Test Date:	2024.04.30
Test Power Supply:	DC 3V	Sample Number:	S24030524-005


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.71	2401.64	2402.35	0.5	PASS
		2440	0.72	2439.64	2440.36	0.5	PASS
		2480	0.72	2479.64	2480.36	0.5	PASS

4.5. Test graphs



5. Maximum Peak Output Power

5.1. Block diagram of test setup



5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

5.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.9.1.1.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.

5.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	24.4℃,49.9%RH	Test Date:	2024.04.30
Test Power Supply:	DC 3V	Sample Number:	S24030524-005


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
BLE_1M	Ant1	2402	1.04	≤30	0.36	≤36	PASS
		2440	1.45	≤30	0.77	≤36	PASS
		2480	1.56	≤30	0.88	≤36	PASS

5.5. Test graphs



6. Power Spectral Density

6.1. Block diagram of test setup



6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.10.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.


If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	24.4℃,49.9%RH	Test Date:	2024.04.30
Test Power Supply:	DC 3V	Sample Number:	S24030524-005


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-14.30	≤8.00	PASS
		2440	-13.88	≤8.00	PASS
		2480	-13.85	≤8.00	PASS

6.5. Test graphs



7. Band Edge Compliance (Conducted Method)

7.1. Block diagram of test setup



7.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.


(4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

7.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	24.4℃,49.9%RH	Test Date:	2024.04.30
Test Power Supply:	DC 3V	Sample Number:	S24030524-005


EUT Set Mode	CH or Frequency	Measured Range	Verdict
GFSK 1M	2402	2.310 GHz - 2.410 GHz	Pass
	2480	2.470 GHz - 2.500 GHz	Pass

7.5. Test graphs



8. RF Conducted Spurious Emissions

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

- Connect EUT's antenna output to spectrum analyzer by RF cable.
- Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span/RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold


Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


8.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	24.4℃,49.9%RH	Test Date:	2024.04.30
Test Power Supply:	DC 3V	Sample Number:	S24030524-005


Mode	Freq. (MHz)	Verdict
GFSK 1M	2402	Pass
	2440	Pass
	2480	Pass

8.5. Test graphs







BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_0~Reference



BLE_1M_Ant1_2480_30~1000




BLE_1M_Ant1_2480_1000~26500



9. Duty Cycle

9.1. Block diagram of test setup



9.2. Limit

Just for Report.

9.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
 - Centre Frequency: The centre frequency of the middle hopping channel.
 - Resolution BW: 10 MHz.
 - Video BW: 10 MHz.
 - Span: Zero span.
 - Detector: Peak.
 - Trace Mode: Clear Write.
 - Sweep: Video Trigger
- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle

9.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	24.4℃,49.9%RH	Test Date:	2024.04.30
Test Power Supply:	DC 3V	Sample Number:	S24030524-005

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	0.38	0.63	60.32	2.20
		2440	0.38	0.63	60.32	2.20
		2480	0.38	0.63	60.32	2.20

9.5. Test graphs



10. Antenna Requirements

10.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

10.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


11.Radiated Emission

11.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI TEST RECEIVER	R&S	ESU26	100472	2025/03/31
PSA Series Spectrum Analyzer	Agilent	E4447A	MY50180031	2025/03/31
Active Loop Antenna	Schwarzbeck	FMZB-1519	1519-038	2025/09/10
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	2025/07/11
Double Ridged Horn Antenna	Schwarzbeck	BBHA 9120 D	02468	2024/09/17
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	2025/04/25
Pre-amplifier	COM-POWER	PAM-118A	18040084	2024/07/14
Pre-amplifier	COM-POWER	PAM-840A	461369	2025/03/31
RE Cable	N/A	W23.02 CP1-X2 + W23.09 AP1-X8+ JCT26S-NJ-NJ-1.5M	4.5M+8M+1.5M	2025/03/31
RF Cable	Yuhu	JCTB810-NJ-NJ-9M+ ZT26S-SMAJ-SMAJ-1M	21123964	2025/03/31
Band Reject Filter(2400-2500 MHz)	REBES	BRM50702	G555	N/A
Band Reject Filter(5150-5880 MHz)	REBES	BRM50716	G392	N/A
High Pass Filter(8000-25000 MHz)	XB	XBLBQ-GTA67	210820-2-3	N/A
Test Software	Tonscend	JS32-RE	V 5.0.0.1	N/A
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/04/01
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22

11.2. Block diagram of test setup





11.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	⁽²⁾
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

11.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

11.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in GFSK 1M, Tx 2480 MHz mode.

11.6. Test result

PASS. (See below detailed test result)

11.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-03

Tested By:

Genliu

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC BELOW 1G 遥控器\20240603-104915_H

Memo:

Sample Number: S24030524-005



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.488	30.02	10.35	3.76	-30.99	13.14	40.00	26.86	QP	Horizontal
2	45.467	26.46	12.78	3.85	-30.77	12.32	40.00	27.68	QP	Horizontal
3	111.552	23.1	11.79	4.28	-30.87	8.30	43.50	35.20	QP	Horizontal
4	433.833	30.65	15.91	5.75	-30.03	22.28	46.00	23.72	QP	Horizontal
5	683.838	26.47	19.22	6.64	-29.90	22.43	46.00	23.57	QP	Horizontal
6	995.802	24.75	22.44	7.45	-28.14	26.50	54.00	27.50	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-03

Tested By:

Genliu

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC BELOW 1G 遥控器\20240603-105007_V

Memo:

Sample Number: S24030524-005



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.187	30.63	11.02	3.78	-30.95	14.48	40.00	25.52	QP	Vertical
2	59.977	30.81	12.79	3.96	-30.63	16.93	40.00	23.07	QP	Vertical
3	69.491	36.98	10.16	4.02	-30.57	20.59	40.00	19.41	QP	Vertical
4	94.606	29.66	10.34	4.18	-30.79	13.39	43.50	30.11	QP	Vertical
5	224.902	25.39	11.29	4.87	-30.53	11.02	46.00	34.98	QP	Vertical
6	446.173	23.69	15.80	5.80	-30.01	15.28	46.00	30.72	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\1

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1474.300	46.39	25.40	3.69	-36.94	38.54	74.00	35.46	PK	Horizontal
2	3879.800	45.87	31.08	5.07	-40.38	41.64	74.00	32.36	PK	Horizontal
3	4802.900	46.26	32.58	5.53	-40.15	44.22	74.00	29.78	PK	Horizontal
4	7393.700	43.19	36.71	6.65	-41.68	44.87	74.00	29.13	PK	Horizontal
5	11463.500	42.37	39.24	8.42	-39.31	50.72	74.00	23.28	PK	Horizontal
6	15890.300	40.08	38.12	10.08	-39.29	48.99	74.00	25.01	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\2

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2249.500	44.32	27.31	4.75	-37.72	38.66	74.00	35.34	PK	Vertical
2	3873.000	46.85	31.04	5.07	-40.37	42.59	74.00	31.41	PK	Vertical
3	4978.000	45.45	33.16	5.64	-40.09	44.16	74.00	29.84	PK	Vertical
4	7354.600	43.66	36.79	6.63	-41.59	45.49	74.00	28.51	PK	Vertical
5	11511.100	42.67	39.18	8.45	-39.33	50.97	74.00	23.03	PK	Vertical
6	15655.700	39.82	38.54	9.92	-39.15	49.13	74.00	24.87	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2440MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\3

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2218.900	45.87	27.61	4.73	-37.63	40.58	74.00	33.42	PK	Horizontal
2	3915.500	46.04	31.17	5.06	-40.40	41.87	74.00	32.13	PK	Horizontal
3	4881.100	48.54	33.30	5.58	-40.12	47.30	74.00	26.70	PK	Horizontal
4	7320.600	45.75	36.86	6.61	-41.50	47.72	74.00	26.28	PK	Horizontal
5	11431.200	42.12	39.27	8.40	-39.29	50.50	74.00	23.50	PK	Horizontal
6	16136.800	40.40	37.86	10.18	-39.47	48.97	74.00	25.03	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2440MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器V4

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2235.900	44.43	27.44	4.74	-37.68	38.93	74.00	35.07	PK	Vertical
2	3849.200	46.00	30.90	5.08	-40.36	41.62	74.00	32.38	PK	Vertical
3	4881.100	46.39	33.30	5.58	-40.12	45.15	74.00	28.85	PK	Vertical
4	7320.600	44.05	36.86	6.61	-41.50	46.02	74.00	27.98	PK	Vertical
5	11477.100	41.47	39.22	8.43	-39.31	49.81	74.00	24.19	PK	Vertical
6	15769.600	39.65	38.36	10.00	-39.22	48.79	74.00	25.21	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2480MHz

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\5

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2207.000	44.32	27.73	4.72	-37.60	39.17	74.00	34.83	PK	Horizontal
2	3861.100	46.07	30.97	5.07	-40.37	41.74	74.00	32.26	PK	Horizontal
3	4959.300	49.81	33.12	5.63	-40.10	48.46	74.00	25.54	PK	Horizontal
4	7439.600	47.17	36.62	6.67	-41.80	48.66	74.00	25.34	PK	Horizontal
5	12138.400	41.52	39.30	8.83	-39.61	50.04	74.00	23.96	PK	Horizontal
6	15757.700	40.08	38.38	9.99	-39.21	49.24	74.00	24.76	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\6

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2280.100	44.99	27.00	4.77	-37.80	38.96	74.00	35.04	PK	Vertical
2	3856.000	45.77	30.94	5.07	-40.36	41.42	74.00	32.58	PK	Vertical
3	4959.300	48.56	33.12	5.63	-40.10	47.21	74.00	26.79	PK	Vertical
4	7522.900	44.35	36.45	6.72	-42.01	45.51	74.00	28.49	PK	Vertical
5	11506.000	41.94	39.19	8.45	-39.33	50.25	74.00	23.75	PK	Vertical
6	15582.600	39.47	38.63	9.87	-39.11	48.86	74.00	25.14	PK	Vertical

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

12.Band Edge Compliance

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI TEST RECEIVER	R&S	ESU26	100472	2025/03/31
PSA Series Spectrum Analyzer	Agilent	E4447A	MY50180031	2025/03/31
Active Loop Antenna	Schwarzbeck	FMZB-1519	1519-038	2025/09/10
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	2025/07/11
Double Ridged Horn Antenna	Schwarzbeck	BBHA 9120 D	02468	2024/09/17
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	2025/04/25
Pre-amplifier	COM-POWER	PAM-118A	18040084	2024/07/14
Pre-amplifier	COM-POWER	PAM-840A	461369	2025/03/31
RE Cable	N/A	W23.02 CP1-X2 + W23.09 AP1-X8+ JCT26S-NJ-NJ-1.5M	4.5M+8M+1.5M	2025/03/31
RF Cable	Yuhu	JCTB810-NJ-NJ-9M+ ZT26S-SMAJ-SMAJ-1M	21123964	2025/03/31
Band Reject Filter(2400-2500 MHz)	REBES	BRM50702	G555	N/A
Band Reject Filter(5150-5880 MHz)	REBES	BRM50716	G392	N/A
High Pass Filter(8000-25000 MHz)	XB	XBLBQ-GTA67	210820-2-3	N/A
Test Software	Tonscend	JS32-RE	V 5.0.0.1	N/A
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/04/01
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22

12.2. Block diagram of test setup



12.3. Limits

All restriction band should comply with 15.209, other emission should be at least 20 dB below the fundamental.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\19

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.620	23.30	27.26	3.57	0.00	54.13	74.00	19.87	PK	Horizontal
2	2390.000	21.40	27.26	3.57	0.00	52.23	74.00	21.77	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.620	14.18	27.26	3.57	0.00	45.01	54.0	8.99	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\20

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2385.600	13.51	27.24	3.57	0.00	44.32	74.00	29.68	PK	Vertical
2	2390.000	11.53	27.26	3.57	0.00	42.36	74.00	31.64	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\13

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	25.69	27.53	3.62	0.00	56.84	74.00	17.16	PK	Horizontal
2	2483.670	29.11	27.53	3.62	0.00	60.26	74.00	13.74	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	13.89	27.53	3.62	0.00	45.04	54.0	8.96	AV	Horizontal
2	2483.670	14.26	27.53	3.62	0.00	45.41	54.0	8.59	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-05-28

Tested By:

Junchang Du

EUT:

High Fidelity Network Audio Component

Model Number:

aurender A1000

Test Mode:

BLE 1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:66.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24030524-1E A1000\FCC ABOVE 1G 遥控器\14

Memo:

Sample Number: S24030524-005

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	22.68	27.53	3.62	0.00	53.83	74.00	20.17	PK	Vertical
2	2483.678	22.95	27.53	3.62	0.00	54.10	74.00	19.90	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.678	15.63	27.53	3.62	0.00	46.78	54.0	7.22	AV	Vertical

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Power Line Conducted Emissions

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
/	/	/	/	/

13.2. Block diagram of test setup



13.3. Limits

Frequency	Quasi-Peak Level dB(mV)	Average Level dB(mV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

13.6. Test result

Not Applicable

Remark: Conducted limits are not required for devices which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines according to 15.207(C).

15. Photos of the EUT

Please refer to DDT-Q24030524-2E appendix I

-----End Report-----