

## FCC SAR Exclusion Report

Product name : Feelchip D  
Applicant : Feel Robotics  
FCC ID : 2AO5N-FCHD18

Test report No. : 180300418 FCC RF exposure v2.00

## Laboratory information

### Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherland

### Testing Location

Test Site	Telefication BV
Test Site location	Edisonstraat 12a 6902 PK Zevenaar The Netherlands  Tel. +31889983600 Fax. +31316583189

## Revision History

Version	Date	Remarks	By
v1.00	17-08-2018	Release version	PvW
v2.00	09-04-2019	Added software version Updated test report reference to clause 1.4.1 Maximum Output Power	PvW

## Table of Contents

Revision History .....	2
1 General Description .....	4
1.1 Applicant .....	4
1.2 Manufacturer .....	4
1.3 Tested Equipment Under Test (EUT) .....	4
1.4 SAR Measurement Evaluation .....	5
1.4.1 Maximum Output Power .....	5
1.4.2 SAR Testing Exclusions .....	5
Note: .....	5
1.5 Summary .....	5

## 1 General Description

### 1.1 Applicant

Client name:	Feel Robotics
Address	Amstelplein 62, Amsterdam, the Netherlands
Zip code:	1096 BC
Telephone:	(0)20 737 1194
E-mail:	<a href="mailto:maurice@kiiroo.com">maurice@kiiroo.com</a>
Contact name:	Maurice op de Beek

### 1.2 Manufacturer

Manufacturer name:	Feel Robotics
Address:	Amstelplein 62, Amsterdam, the Netherlands
Zip code:	1096 BC
Telephone:	(0)20 737 1194
E-mail:	<a href="mailto:maurice@kiiroo.com">maurice@kiiroo.com</a>
Contact name:	Maurice op de Beek

### 1.3 Tested Equipment Under Test (EUT)

Product name:	Feelchip D
Brand name:	Kiiroo
Product type:	Interactive Vibrator
FCC ID:	2A05N-LCHD18
IC ID:	23801-LCHD18
Model(s):	Feelchip D
Software version:	1.0
Hardware version:	PCBA-D-V1

## 1.4 SAR Measurement Evaluation

### 1.4.1 Maximum Output Power

The maximum radiated power including tune-up tolerance is shown as below.

Mode	2.4G Bluetooth
Bluetooth LE	-9.91 dBm*

\* from Telefication report 180300418 003 v2.00.

### 1.4.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

- For the test separation distance  $\leq 50$  mm

$$\frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0$$

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

- For the test separation distance  $> 50$  mm, and the frequency at 100 MHz to 1500 MHz

$$\left[ (\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left( \frac{f_{(MHz)}}{150} \right) \right]_{(mW)}$$

- For the test separation distance  $> 50$  mm, and the frequency at  $> 1500$  MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(mW)}$$

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
Bluetooth LE	-9.91	0.1	5	0.032	No

Note:

- When separation distance  $\leq 50$  mm and the calculated result shown in above table is  $\leq 3.0$ , the SAR testing exclusion is applied.
- When separation distance  $> 50$  mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

## 1.5 Summary

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.