



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel: +86-755-27521059 Fax: +86-755-27521011 Http://www.sz-ctc.com.cn

RF Exposure Evaluation

FCC ID: 2A05W-MOVE100

According to KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

EUT Specification

EUT	Bluetooth Speaker
Model/Type reference:	SACKit Move 100
Listed Model(s):	SACKit Move 150, BN5K, MOVEit, MOVEit X
Frequency band (Operating)	<input checked="" type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input type="checkbox"/> BLE: 2.402GHz ~ 2.480GHz <input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> Others
Device category	<input checked="" type="checkbox"/> Portable (<5mm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Fixed (>20cm separation) <input type="checkbox"/> Others ____
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Antenna gain (Max)	3dBi

Limit

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f_(GHz)] ≤ 3.0

Where

-f_(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.



Measurement Result:

Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up Tolerance (dBm)	Max. Tune up Power (dBm)	Result	Limit
8-DPSK	2480	-1.89	-2±1	-1	0.491	3.0

Note:

1. Calculate by Worst-case mode.
2. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****