

Standard Applicable:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limit

Limits for general population/Uncontrolled exposure

Frequency Range [MHz]	Electric Field Strength (E) [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm ²]	Averaging Time E ² , H ² or S [minutes]
0.3 - 1.34	614	1.63	(100)	30
1.34 - 30	824/f	2.19/f	(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1 500	--	--	f/1 500	30
1 500 - 100 000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance.

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)
 P = power input to the antenna (in appropriate units, e.g., mW)
 G = power gain of the antenna in the direction of interest relative to an isotropic radiator
 R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Measurement Result:

- Maximum peak output power at antenna input : 5.41 dBm (3.475 mW)
- Prediction distance : 20 cm
- Predication frequency : 2 402 MHz
- Antenna gain(Max) : 1.9 dBi (1.549 numeric)
- Power density at predication frequency at 20 cm : 0.001 070 85 mW/cm²

- MPE Limit for : 1 mW/cm²

Test Result

The power density level at 20 cm is 0.001 070 85 mW/cm² which is below the uncontrolled exposure limit of 1 mW/cm² at 2 402 MHz to 2 480 MHz.