




**Fig.A.6.1.79 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 15 GHz-20 GHz)**




**Fig.A.6.1.80 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 20 GHz-26 GHz)**




**Fig.A.6.1.81 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)**




**Fig.A.6.1.82 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-1 GHz)**




**Fig.A.6.1.83 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 1 GHz-2.5 GHz)**




**Fig.A.6.1.84 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 2.5 GHz-7.5 GHz)**




**Fig.A.6.1.85 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 7.5 GHz-10 GHz)**




**Fig.A.6.1.86 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 10 GHz-15 GHz)**




**Fig.A.6.1.87 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 15 GHz-20 GHz)**




**Fig.A.6.1.88 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 20 GHz-26 GHz)**




**Fig.A.6.1.89 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)**




**Fig.A.6.1.90 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-1 GHz)**




**Fig.A.6.1.91 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 1 GHz-2.5 GHz)**



**Fig.A.6.1.92 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 2.5 GHz-7.5 GHz)**




**Fig.A.6.1.93 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 7.5 GHz-10 GHz)**




**Fig.A.6.1.94 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 10 GHz-15 GHz)**





**Fig.A.6.1.95 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 15 GHz-20 GHz)**



**Fig.A.6.1.96 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 20 GHz-26 GHz)**

### A.6.2 Transmitter Spurious Emission - Radiated

**Method of Measurement:** See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Limit in restricted band:**

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Frequency (MHz)	Field strength(µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

### Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

**EUT ID:** EUT1

**Measurement Results:**

**802.11b mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	Power	2.38GHz ~2.43GHz	Fig.A.6.2.1	P
	1	1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P
	6	9 kHz ~30 MHz	--	P
		30 MHz ~1 GHz	--	P
		1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P
	Power	18 GHz~ 26.5 GHz	--	P
		2.45GHz ~2.5GHz	Fig.A.6.2.2	P
		11	1 GHz ~ 3 GHz	--
	3 GHz ~ 18 GHz		--	P

**802.11g mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11g	Power	2.38GHz ~2.43GHz	Fig.A.6.2.3	P
	1	1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P
	6	30 MHz ~1 GHz	--	P
		1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P
		18 GHz~ 26.5 GHz	--	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.4	P
	11	1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P

**802.11n-HT20 mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	Power	2.38GHz ~2.43GHz	Fig.A.6.2.5	P
	1	1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P
	6	30 MHz ~1 GHz	--	P
		1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P
		18 GHz~ 26.5 GHz	--	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.6	P
	11	1 GHz ~ 3 GHz	--	P
		3 GHz ~ 18 GHz	--	P



**802.11n-HT40 mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	Power	2.38GHz ~2.43GHz	Fig.A.6.2.7	<b>P</b>
	3	1 GHz ~ 3 GHz	--	<b>P</b>
		3 GHz ~ 18 GHz	--	<b>P</b>
	6	30 MHz ~1 GHz	--	<b>P</b>
		1 GHz ~ 3 GHz	--	<b>P</b>
		3 GHz ~ 18 GHz	--	<b>P</b>
		18 GHz~ 26.5 GHz	--	<b>P</b>
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.8	<b>P</b>
	9	1 GHz ~ 3 GHz	--	<b>P</b>
		3 GHz ~ 18 GHz	--	<b>P</b>

**Conclusion: Pass**

**Note:**

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

$P_{Mea}$  is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

**802.11b-Average**

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2385.825	40.9	-38.8	27.7	52.000	H
17909.000	38.2	-18.5	45.6	11.100	H
17867.500	37.9	-18.5	45.6	10.800	V
17881.500	37.9	-18.5	45.6	10.800	H
17873.500	37.9	-18.5	45.6	10.800	H
17865.000	37.9	-18.5	45.6	10.800	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17762.000	38.3	-18.5	45.6	11.200	H
17867.500	38.1	-18.5	45.6	11.000	H
17752.000	38.1	-18.5	45.6	11.000	V
17863.000	38.1	-18.5	45.6	11.000	H
17832.500	38.1	-18.5	45.6	11.000	H
17424.500	38.1	-19.2	41.5	15.800	H



Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2488.230	53.4	-38.9	27.7	64.600	H
17742.500	38.2	-18.5	45.6	11.100	H
17844.500	38.2	-18.5	45.6	11.100	V
17872.500	38.1	-18.5	45.6	11.000	H
17826.000	38.1	-18.5	45.6	11.000	H
17881.000	38.1	-18.5	45.6	11.000	H

**802.11b-Peak**

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2385.815	53.3	-38.8	27.7	64.400	H
17735.500	49.4	-18.9	45.6	22.700	H
17736.000	49.2	-18.9	45.6	22.500	V
17921.500	49.2	-17.7	45.6	21.300	H
17873.000	49.2	-18.5	45.6	22.100	H
17465.000	49.1	-19.2	41.5	26.800	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17834.000	49.6	-18.5	45.6	22.500	H
17899.000	49.6	-18.5	45.6	22.500	H
17849.500	49.6	-18.5	45.6	22.500	V
17460.500	49.5	-19.2	41.5	27.200	H
17778.500	49.4	-18.5	45.6	22.300	H
17784.000	49.3	-18.5	45.6	22.200	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2488.230	53.4	-38.9	27.7	64.600	H
17414.000	50.0	-19.2	41.5	27.700	H
17915.500	49.9	-17.7	45.6	22.000	V
17776.000	49.9	-18.5	45.6	22.800	H
17650.500	49.8	-18.9	45.6	23.100	H
17478.500	49.6	-19.2	41.5	27.300	H



**802.11g - Average**

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2383.495	41.0	-38.8	27.7	52.100	H
17876.500	38.3	-18.5	45.6	11.200	H
17841.000	38.3	-18.5	45.6	11.200	V
17922.000	38.2	-17.7	45.6	10.300	H
17863.500	38.2	-18.5	45.6	11.100	H
17906.000	38.2	-18.5	45.6	11.100	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17893.000	38.3	-18.5	45.6	11.200	H
17876.500	38.3	-18.5	45.6	11.200	H
17856.000	38.3	-18.5	45.6	11.200	V
17845.500	38.3	-18.5	45.6	11.200	H
17841.500	38.2	-18.5	45.6	11.100	H
17419.000	38.1	-19.2	41.5	15.800	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2489.285	40.8	-38.9	27.7	52.000	H
17742.500	38.4	-18.5	45.6	11.300	H
17762.000	38.4	-18.5	45.6	11.300	V
17878.500	38.4	-18.5	45.6	11.300	H
17876.500	38.3	-18.5	45.6	11.200	H
17867.000	38.2	-18.5	45.6	11.100	H



**802.11g - Peak**

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2383.510	54.3	-38.8	27.7	65.400	H
17771.000	50.2	-18.5	45.6	23.100	H
17787.000	50.0	-18.5	45.6	22.900	V
17388.000	49.9	-19.2	41.5	27.600	H
17739.500	49.7	-18.5	45.6	22.600	H
17859.000	49.6	-18.5	45.6	22.500	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17827.5	49.9	-18.5	45.6	22.8	H
17504.5	49.9	-19.2	45.6	23.5	H
17449.5	49.9	-19.2	41.5	27.6	V
17027.5	49.7	-19.9	41.5	28.1	H
17388.5	49.6	-19.2	41.5	27.3	H
17663	49.6	-18.9	45.6	22.9	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2489.230	53.7	-38.9	27.7	64.900	H
17877.000	50.1	-18.5	45.6	23.000	H
17759.000	49.9	-18.5	45.6	22.800	V
17543.000	49.5	-19.2	45.6	23.100	H
17392.000	49.4	-19.2	41.5	27.100	H
17863.500	49.3	-18.5	45.6	22.200	H



**802.11n-HT20-Average**

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2385.630	40.9	-38.8	27.7	52.000	H
17765.000	38.4	-18.5	45.6	11.300	H
17847.500	38.3	-18.5	45.6	11.200	V
17884.500	38.3	-18.5	45.6	11.200	H
17869.500	38.3	-18.5	45.6	11.200	H
17937.500	38.3	-17.7	45.6	10.400	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17861.000	38.5	-18.5	45.6	11.400	H
17805.500	38.4	-18.5	45.6	11.300	H
17851.500	38.4	-18.5	45.6	11.300	V
17435.500	38.4	-19.2	41.5	16.100	H
17870.500	38.3	-18.5	45.6	11.200	H
17877.500	38.3	-18.5	45.6	11.200	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2488.125	40.8	-38.9	27.7	52.000	H
17828.500	38.6	-18.5	45.6	11.500	H
17388.500	38.5	-19.2	41.5	16.200	V
17759.500	38.4	-18.5	45.6	11.300	H
17872.500	38.4	-18.5	45.6	11.300	H
17882.000	38.4	-18.5	45.6	11.300	H





**802.11n-HT20-Peak**

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2385.610	53.4	-38.8	27.7	64.500	H
17908.500	50.2	-18.5	45.6	23.100	H
17926.500	50.0	-17.7	45.6	22.100	V
17497.500	49.7	-19.2	41.5	27.400	H
17922.000	49.5	-17.7	45.6	21.600	H
17850.500	49.3	-18.5	45.6	22.200	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17843.000	50.6	-18.5	45.6	23.500	H
17640.500	50.0	-18.9	45.6	23.300	H
17471.000	49.9	-19.2	41.5	27.600	V
17386.500	49.9	-19.5	41.5	27.900	H
17562.500	49.9	-18.9	45.6	23.200	H
17759.000	49.8	-18.5	45.6	22.700	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2488.140	53.9	-38.9	27.7	65.100	H
17770.500	50.3	-18.5	45.6	23.200	H
17669.000	50.3	-18.9	45.6	23.600	V
17363.000	50.0	-19.5	41.5	28.000	H
17432.500	49.9	-19.2	41.5	27.600	H
17887.500	49.7	-18.5	45.6	22.600	H



**802.11n-HT40-Average**

Ch3

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2389.450	41.3	-38.8	27.7	52.400	H
17399.000	38.4	-19.2	41.5	16.100	H
17843.000	38.3	-18.5	45.6	11.200	V
17867.500	38.3	-18.5	45.6	11.200	H
17872.000	38.3	-18.5	45.6	11.200	H
17404.500	38.3	-19.2	41.5	16.000	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17397.500	38.5	-19.2	41.5	16.200	H
17404.000	38.5	-19.2	41.5	16.200	H
17871.000	38.5	-18.5	45.6	11.400	V
17878.500	38.4	-18.5	45.6	11.300	H
17833.500	38.4	-18.5	45.6	11.300	H
17880.500	38.4	-18.5	45.6	11.300	H

Ch9

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2487.040	40.6	-38.9	27.7	51.800	H
17758.000	38.4	-18.5	45.6	11.300	H
17839.500	38.4	-18.5	45.6	11.300	V
17860.500	38.4	-18.5	45.6	11.300	H
17836.000	38.4	-18.5	45.6	11.300	H
17870.000	38.3	-18.5	45.6	11.200	H



**802.11n-HT40-Peak**

Ch3

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2389.460	54.0	-38.8	27.7	65.100	H
17444.500	50.2	-19.2	41.5	27.900	H
17813.500	49.6	-18.5	45.6	22.500	V
17675.500	49.6	-18.9	45.6	22.900	H
17421.500	49.5	-19.2	41.5	27.200	H
17319.000	49.4	-19.5	41.5	27.400	H


Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17543.000	49.9	-19.2	45.6	23.500	H
17420.000	49.6	-19.2	41.5	27.300	H
17557.500	49.4	-19.2	45.6	23.000	V
17897.000	49.3	-18.5	45.6	22.200	H
17465.500	49.2	-19.2	41.5	26.900	H
17664.500	49.2	-18.9	45.6	22.500	H


Ch9

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2487.070	54.7	-38.9	27.7	65.900	H
17377.000	50.3	-19.5	41.5	28.300	H
17875.000	50.1	-18.5	45.6	23.000	V
17362.000	50.0	-19.5	41.5	28.000	H
17559.500	49.8	-19.2	45.6	23.400	H
17028.500	49.6	-19.9	41.5	28.000	H


Test graphs as below for Set1:




**Fig.A.6.2.1 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch1, 2.38 GHz – 2.43GHz**



**Fig.A.6.2.2 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch11, 2.45 GHz - 2.50GHz**




**Fig.A.6.2.3 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.38 GHz - 2.43GHz**




3


**Fig.A.6.2.4 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz**




**Fig.A.6.2.5 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1, 2.38 GHz - 2.45GHz**



**Fig.A.6.2.6 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11, 2.45 GHz - 2.50GHz**



**Fig.A.6.2.7 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch3, 2.38 GHz - 2.43GHz**



**Fig.A.6.2.8 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch9, 2.45 GHz - 2.50GHz**

## **A.7. AC Power-line Conducted Emission**

### **Method of Measurement: See ANSI C63.10-2013-clause 6.2**

- 1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
- 2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
- 3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
- 4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
- 5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.<sup>36</sup> Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

### **Test Condition:**

<b>Voltage (V)</b>	<b>Frequency (Hz)</b>
120	60



**Measurement Result and limit:**

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	<b>P</b>
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)


Frequency range (MHz)	Average Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	<b>P</b>
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**Conclusion: Pass**

Test graphs as below:

Traffic: Set.1



**Fig.A.7.1 AC Powerline Conducted Emission-802.11b**

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.172500	44.1	2000.0	9.000	N	19.8	20.7	64.8
0.523500	44.6	2000.0	9.000	L1	19.9	11.4	56.0
1.027500	42.2	2000.0	9.000	L1	19.6	13.8	56.0
1.432500	44.0	2000.0	9.000	L1	19.6	12.0	56.0
3.003000	41.7	2000.0	9.000	L1	19.7	14.3	56.0
4.299000	40.4	2000.0	9.000	L1	19.6	15.6	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.514500	33.5	2000.0	9.000	L1	19.9	12.5	46.0
1.095000	33.0	2000.0	9.000	L1	19.6	13.0	46.0
1.410000	34.8	2000.0	9.000	L1	19.6	11.2	46.0
3.052500	32.1	2000.0	9.000	L1	19.7	13.9	46.0
4.339500	30.7	2000.0	9.000	L1	19.6	15.3	46.0
10.158000	27.5	2000.0	9.000	L1	19.8	22.5	50.0

Idle: Set.1




Fig.A.7.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.