



TESTING LABORATORY  
CERTIFICATE # 4821.01



## FCC PART 15.247

### TEST REPORT

For

### Epik One America Corporation

170 Ocean Lane Dr. #705, Key Biscayne, FL 33149, United States

**FCC ID: 2AO6ZK500**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Smartphone
<b>Report Number:</b> <u>RSZ180322001-00C</u>	
<b>Report Date:</b>	<u>2018-04-09</u>
<b>Reviewed By:</b>	<u>Jimmy Xiao</u> <i>Jimmy Xiao</i> <u>RF Engineer</u>
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*”.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY.....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	7
EUT EXERCISE SOFTWARE .....	7
DUTY CYCLE .....	8
SUPPORT EQUIPMENT LIST AND DETAILS .....	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP .....	11
<b>SUMMARY OF TEST RESULTS.....</b>	<b>12</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>13</b>
<b>FCC§15.247 (i), §1.1307 (b) (1) &amp; §2.1093 – RF EXPOSURE .....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
ANTENNA CONNECTOR CONSTRUCTION .....	16
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP .....	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE .....	17
CORRECTED FACTOR & MARGIN CALCULATION .....	18
TEST RESULTS SUMMARY .....	18
TEST DATA .....	18
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>23</b>
APPLICABLE STANDARD .....	23
EUT SETUP .....	23
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	24
TEST PROCEDURE .....	24
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	24
TEST RESULTS SUMMARY .....	24
TEST DATA .....	25
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>	<b>36</b>
APPLICABLE STANDARD .....	36
TEST PROCEDURE .....	36
TEST DATA .....	36

<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>46</b>
APPLICABLE STANDARD .....	46
TEST PROCEDURE .....	46
TEST DATA .....	46
<b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>48</b>
APPLICABLE STANDARD .....	48
TEST PROCEDURE .....	48
TEST DATA .....	48
<b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>	<b>54</b>
APPLICABLE STANDARD .....	54
TEST PROCEDURE .....	54
TEST DATA .....	54

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

The *Epik One America Corporation*'s product, model number: *K500* (*FCC ID: 2AO6ZK500*) or the "EUT" in this report was a *Smartphone*, which was measured approximately: 146.3 mm (L) × 73.1 mm (W) × 10.3 mm (H), rated with input voltage: DC 3.8V from rechargeable Li-ion battery or DC 5.0V from adapter.

#### Adapter Information:

Model: ZHY-QU050100S  
Input: AC 100-240V, 50/60Hz, 0.2A  
Output: DC 5.0V, 1A

\*All measurement and test data in this report was gathered from production sample serial number: 1800363 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-03-22.

### Objective

This report is prepared on behalf of *Epik One America Corporation* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 22H/24E PCE and Part 15.247 DSS submissions with FCC ID: 2AO6ZK500

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 DTS Meas Guidance v04.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	±5%	
RF Output Power with Power meter	±0.5dB	
RF conducted test with spectrum	±1.5dB	
AC Power Lines Conducted Emissions	±1.95dB	
Emissions, Radiated	Below 1GHz Above 1GHz	±4.75dB ±4.88dB
Temperature	±3°C	
Humidity	±6%	
Supply voltages	±0.4%	

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	8	2457
4	2437	9	2462
5	2442	/	/

EUT was tested with Channel 1, 5 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

### Equipment Modifications

No modification was made to the EUT tested.


### EUT Exercise Software

BLE & Wi-Fi test in the engineer mode.


The device was tested with worst case as below:

Mode	Data rate	Power level		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	11	11	11
802.11g	6 Mbps	11	11	11
802.11n-HT20	MCS0	10	10	10
802.11n-HT40	MCS0	10	10	10
BLE	/	Default	Default	Default


Pre-scan with all the data rates, the above data rate is the worst case.

**Duty cycle****802.11b mode**


Date: 27.MAR.2018 19:02:01

**802.11g mode**


Date: 27.MAR.2018 19:02:44

**802.11n-HT20 Mode**

Date: 27.MAR.2018 19:03:59

**802.11n-HT40 Mode**

Date: 27.MAR.2018 19:04:32

**BLE Mode**

Date: 27.MAR.2018 17:38:13

Mode	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	10log(1/ Duty Cycle)
802.11b	100	-	-	10Hz	0
802.11g	100	-	-	10Hz	0
802.11n-HT20	100	-	-	10Hz	0
802.11n-HT40	100	-	-	10Hz	0
BLE	63.45	400.6	2.50	3kHz	1.98

**Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
/	/	/	/

**External I/O Cable**

Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

**Block Diagram of Test Setup**

For conducted emission:



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emissions Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2017-08-04	2018-08-04
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2017-12-21	2018-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-11-19	2018-05-17
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2017-11-12	2018-05-12
<b>Radiated Emission Test</b>					
A.H.System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2017-04-24	2018-04-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21
HP	Amplifier	HP8447E	1937A01046	2017-11-19	2018-05-21
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	104PEA	218124002	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	1	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	2	2017-11-22	2018-05-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2017-08-03	2018-08-03
Sinoscite	Notch Filter	BSF2402-2480MN-0898-001	N/A	2017-05-21	2018-05-21
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>RF Conducted Test</b>					
Agilent	P-Series Power Meter	N1912A	MY5000448	2018-01-02	2019-01-02
Agilent	Wideband Power Sensor	N1921A	MY54210016	2018-01-02	2019-01-02
WEINSCHEL	3dB Attenuator	N/A	N/A	2017-11-23	2018-05-22
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2017-12-24	2018-12-24
Ducommun technologies	RF Cable	RG-214	3	2017-11-22	2018-05-22

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE****Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^{1/2}$

$\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

**Measurement Result****For worst case:**

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	-4.5	0.35	5	0.1	3.0	Yes
Wi-Fi	2472	9.0	7.94	5	2.5	3.0	Yes

**Result: No SAR test is required**

## FCC §15.203 - ANTENNA REQUIREMENT

### Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is -6 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\lim} + U_{\text{cisp}}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{\text{cisp}}$ , if  $L_m$  is less than  $L_{\lim}$ , it implies that the EUT complies with the limit.


## Test Data

### Environmental Conditions


<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Simon Wang on 2018-03-27.*

*EUT operation mode: Transmitting & charging*

**BLE Mode: (worst case for High channel)****AC 120V/60 Hz, Line**


Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
0.221500	44.0	25.1	62.8	18.8	QP
0.301410	42.7	25.2	60.2	17.5	QP
0.407850	46.1	25.2	57.7	11.6	QP
0.443430	45.3	25.2	57.0	11.7	QP
0.494470	46.8	25.2	56.1	9.3	QP
0.908350	40.4	25.2	56.0	15.6	QP
0.221500	27.8	25.1	52.8	25.0	Ave.
0.301410	31.0	25.2	50.2	19.2	Ave.
0.407850	35.4	25.2	47.7	12.3	Ave.
0.443430	31.5	25.2	47.0	15.5	Ave.
0.494470	36.7	25.2	46.1	9.4	Ave.
0.908350	27.5	25.2	46.0	18.5	Ave.

**AC 120V/60 Hz, Neutral**


Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
0.150000	60.5	25.1	66.0	5.5	QP
0.177500	53.7	25.1	64.6	10.9	QP
0.181500	53.2	25.1	64.4	11.2	QP
0.225500	47.9	25.1	62.6	14.7	QP
0.265500	44.7	25.2	61.3	16.6	QP
0.313350	45.4	25.2	59.9	14.5	QP
0.150000	38.2	25.1	56.0	17.8	Ave.
0.177500	37.0	25.1	54.6	17.6	Ave.
0.181500	38.2	25.1	54.4	16.2	Ave.
0.225500	38.6	25.1	52.6	14.0	Ave.
0.265500	37.5	25.2	51.3	13.8	Ave.
0.313350	37.1	25.2	49.9	12.8	Ave.

**Wi-Fi Mode:** (worst case for 802.11n20 Mode, High channel)

**AC 120 V/60 Hz, Line:**



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
0.154000	43.8	25.1	65.8	22.0	QP
0.173500	41.2	25.1	64.8	23.6	QP
0.447370	45.2	25.2	56.9	11.7	QP
0.490590	46.7	25.2	56.2	9.5	QP
0.845130	37.3	25.2	56.0	18.7	QP
0.990970	39.3	25.2	56.0	16.7	QP
0.154000	27.1	25.1	55.8	28.7	Ave.
0.173500	26.8	25.1	54.8	28.0	Ave.
0.447370	33.1	25.2	46.9	13.8	Ave.
0.490590	38.7	25.2	46.2	7.5	Ave.
0.845130	27.8	25.2	46.0	18.2	Ave.
0.990970	31.1	25.2	46.0	14.9	Ave.

**AC 120V/ 60 Hz, Neutral:**

Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
0.150000	51.6	25.1	66.0	14.4	QP
0.177500	49.3	25.1	64.6	15.3	QP
0.403850	45.7	25.2	57.8	12.1	QP
0.439370	46.9	25.2	57.1	10.2	QP
0.494590	47.9	25.2	56.1	8.2	QP
1.010610	40.6	25.2	56.0	15.4	QP
0.150000	33.7	25.1	56.0	22.3	Ave.
0.177500	34.7	25.1	54.6	19.9	Ave.
0.403850	36.8	25.2	47.8	11.0	Ave.
0.439370	32.6	25.2	47.1	14.5	Ave.
0.494590	37.9	25.2	46.1	8.2	Ave.
1.010610	30.8	25.2	46.0	15.2	Ave.

**Note:**


- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS****Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

**EUT Setup**

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz <sup>Note 1</sup>	/	Average
	1MHz	>1/T <sup>Note 2</sup>	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\lim} + U_{\text{cisp}}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{\text{cisp}}$ , if  $L_m$  is less than  $L_{\lim}$ , it implies that the EUT complies with the limit.

## Test Data


### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2018-03-25.

EUT operation mode: Transmitting

**30 MHz~1 GHz:** (worst case for 802.11n20 Mode, High channel)



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
30.557119	22.25	162.0	V	281.0	-0.1	40.00	17.75
54.554375	22.94	107.0	H	325.0	-11.4	40.00	17.06
550.974000	27.29	394.0	H	125.0	4.9	46.00	18.71
699.728625	28.66	284.0	V	66.0	6.7	46.00	17.34
789.521125	30.53	270.0	V	110.0	8.7	46.00	15.47
908.960000	30.92	374.0	V	241.0	9.4	46.00	15.08

**1 GHz-25 GHz:****802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247/205/209	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>Low Channel (2412 MHz)</b>									
2412.00	63.19	PK	89	1.1	H	33.92	97.11	/	/
2412.00	58.22	Ave.	89	1.1	H	33.92	92.14	/	/
2412.00	60.31	PK	234	1.6	V	33.92	94.23	/	/
2412.00	54.46	Ave.	234	1.6	V	33.92	88.38	/	/
2370.76	26.81	PK	359	2.2	H	33.92	60.73	74	13.27
2370.76	13.13	Ave.	359	2.2	H	33.92	47.05	54	6.95
2489.12	27.13	PK	261	2.5	H	34.08	61.21	74	12.79
2489.12	13.34	Ave.	261	2.5	H	34.08	47.42	54	6.58
4824.00	45.67	PK	214	2.1	H	5.84	51.51	74	22.49
4824.00	29.02	Ave.	214	2.1	H	5.84	34.86	54	19.14

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247/205/209	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>Middle Channel (2442MHz)</b>									
2442.00	62.29	PK	97	2.2	H	33.92	96.21	/	/
2442.00	57.35	Ave.	97	2.2	H	33.92	91.27	/	/
2442.00	60.34	PK	124	1.8	V	33.92	94.26	/	/
2442.00	54.43	Ave.	124	1.8	V	33.92	88.35	/	/
4884.00	44.23	PK	353	1.1	H	6.21	50.44	74	23.56
4884.00	29.64	Ave.	353	1.1	H	6.21	35.85	54	18.15
<b>High Channel (2472 MHz)</b>									
2472.00	62.27	PK	221	2.1	H	34.08	96.35	/	/
2472.00	57.44	Ave.	221	2.1	H	34.08	91.52	/	/
2472.00	61.16	PK	149	2.3	V	34.08	95.24	/	/
2472.00	56.24	Ave.	149	2.3	V	34.08	90.32	/	/
2356.97	27.02	PK	92	2.4	H	33.92	60.94	74	13.06
2356.97	13.26	Ave.	92	2.4	H	33.92	47.18	54	6.82
2487.50	26.88	PK	305	1.1	H	34.08	60.96	74	13.04
2487.50	13.11	Ave.	305	1.1	H	34.08	47.19	54	6.81
4944.00	43.51	PK	71	2.3	H	6.21	49.72	74	24.28
4944.00	29.24	Ave.	71	2.3	H	6.21	35.45	54	18.55

**802.11g Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247/205/209	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>Low Channel (2412 MHz)</b>									
2412.00	62.93	PK	153	1.7	H	33.92	96.85	/	/
2412.00	50.36	Ave.	153	1.7	H	33.92	84.28	/	/
2412.00	58.92	PK	47	1.3	V	33.92	92.84	/	/
2412.00	48.34	Ave.	47	1.3	V	33.92	82.26	/	/
2348.79	27.37	PK	352	1.6	H	33.83	61.20	74	12.80
2348.79	13.56	Ave.	352	1.6	H	33.83	47.39	54	6.61
2488.55	26.79	PK	79	2.3	H	34.08	60.87	74	13.13
2488.55	13.01	Ave.	79	2.3	H	34.08	47.09	54	6.91
4824.00	44.24	PK	21	2.0	H	5.84	50.08	74	23.92
4824.00	29.57	Ave.	21	2.0	H	5.84	35.41	54	18.59
<b>Middle Channel (2442MHz)</b>									
2442.00	63.14	PK	229	2.5	H	33.92	97.06	/	/
2442.00	50.52	Ave.	229	2.5	H	33.92	84.44	/	/
2442.00	59.17	PK	49	2.0	V	33.92	93.09	/	/
2442.00	48.64	Ave.	49	2.0	V	33.92	82.56	/	/
4884.00	43.27	PK	304	2.1	H	6.21	49.48	74	24.52
4884.00	29.11	Ave.	304	2.1	H	6.21	35.32	54	18.68
<b>High Channel (2472 MHz)</b>									
2472.00	62.55	PK	121	2.0	H	34.08	96.63	/	/
2472.00	51.21	Ave.	121	2.0	H	34.08	85.29	/	/
2472.00	60.65	PK	146	1.0	V	34.08	94.73	/	/
2472.00	47.32	Ave.	146	1.0	V	34.08	81.40	/	/
2358.57	26.59	PK	291	1.9	H	33.92	60.51	74	13.49
2358.57	13.10	Ave.	291	1.9	H	33.92	47.02	54	6.98
2489.39	29.23	PK	213	2.0	H	34.08	63.31	74	10.69
2489.39	15.82	Ave.	213	2.0	H	34.08	49.90	54	4.10
4944.00	43.55	PK	341	1.6	H	6.21	49.76	74	24.24
4944.00	29.18	Ave.	341	1.6	H	6.21	35.39	54	18.61

**802.11n-HT20 Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247/205/209	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>Low Channel (2412 MHz)</b>									
2412.00	62.39	PK	106	1.7	H	33.92	96.31	/	/
2412.00	50.26	Ave.	106	1.7	H	33.92	84.18	/	/
2412.00	58.06	PK	28	2.4	V	33.92	91.98	/	/
2412.00	46.57	Ave.	28	2.4	V	33.92	80.49	/	/
2365.79	26.94	PK	351	2.1	H	33.92	60.86	74	13.14
2365.79	13.15	Ave.	351	2.1	H	33.92	47.07	54	6.93
2491.24	27.23	PK	107	1.7	H	34.08	61.31	74	12.69
2491.24	13.48	Ave.	107	1.7	H	34.08	47.56	54	6.44
4824.00	43.71	PK	263	1.8	H	5.84	49.55	74	24.45
4824.00	29.44	Ave.	263	1.8	H	5.84	35.28	54	18.72
<b>Middle Channel (2442MHz)</b>									
2442.00	62.54	PK	294	1.8	H	33.92	96.46	/	/
2442.00	50.33	Ave.	294	1.8	H	33.92	84.25	/	/
2442.00	58.46	PK	350	1.7	V	33.92	92.38	/	/
2442.00	47.32	Ave.	350	1.7	V	33.92	81.24	/	/
4884.00	44.12	PK	103	2.5	H	6.21	50.33	74	23.67
4884.00	29.16	Ave.	103	2.5	H	6.21	35.37	54	18.63
<b>High Channel (2472 MHz)</b>									
2472.00	61.61	PK	123	2.2	H	34.08	95.69	/	/
2472.00	49.18	Ave.	123	2.2	H	34.08	83.26	/	/
2472.00	58.12	PK	104	1.7	V	34.08	92.20	/	/
2472.00	46.29	Ave.	104	1.7	V	34.08	80.37	/	/
2332.60	26.56	PK	133	1.8	H	33.83	60.39	74	13.61
2332.60	13.10	Ave.	133	1.8	H	33.83	46.93	54	7.07
2483.53	28.69	PK	103	1.2	H	34.08	62.77	74	11.23
2483.53	16.03	Ave.	103	1.2	H	34.08	50.11	54	3.89
4944.00	45.86	PK	260	1.7	H	6.21	52.07	74	21.93
4944.00	29.93	Ave.	260	1.7	H	6.21	36.14	54	17.86

**802.11n-HT40 Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247/205/209	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>Low Channel (2422 MHz)</b>									
2422.00	59.35	PK	222	1.9	H	33.92	93.27	/	/
2422.00	48.14	Ave.	222	1.9	H	33.92	82.06	/	/
2422.00	57.45	PK	355	2.1	V	33.92	91.37	/	/
2422.00	46.02	Ave.	355	2.1	V	33.92	79.94	/	/
2335.97	26.99	PK	203	2.0	H	33.83	60.82	74	13.18
2335.97	13.22	Ave.	203	2.0	H	33.83	47.05	54	6.95
2489.12	27.24	PK	293	1.7	H	34.08	61.32	74	12.68
2489.12	13.48	Ave.	293	1.7	H	34.08	47.56	54	6.44
4844.00	42.57	PK	266	1.5	H	5.84	48.41	74	25.59
4844.00	28.69	Ave.	266	1.5	H	5.84	34.53	54	19.47
<b>Middle Channel (2442MHz)</b>									
2442.00	60.13	PK	335	1.7	H	33.92	94.05	/	/
2442.00	48.57	Ave.	335	1.7	H	33.92	82.49	/	/
2442.00	58.46	PK	111	1.3	V	33.92	92.38	/	/
2442.00	47.13	Ave.	111	1.3	V	33.92	81.05	/	/
4884.00	43.56	PK	293	2.2	H	6.21	49.77	74	24.23
4884.00	29.22	Ave.	293	2.2	H	6.21	35.43	54	18.57
<b>High Channel (2462 MHz)</b>									
2462.00	58.94	PK	346	2.3	H	34.08	93.02	/	/
2462.00	47.71	Ave.	346	2.3	H	34.08	81.79	/	/
2462.00	57.34	PK	93	1.2	V	34.08	91.42	/	/
2462.00	46.25	Ave.	93	1.2	V	34.08	80.33	/	/
2352.64	26.75	PK	56	1.1	H	33.92	60.67	74	13.33
2352.64	13.11	Ave.	56	1.1	H	33.92	47.03	54	6.97
2484.29	27.19	PK	194	2.1	H	34.08	61.27	74	12.73
2484.29	13.27	Ave.	194	2.1	H	34.08	47.35	54	6.65
4924.00	42.56	PK	259	1.0	H	6.21	48.77	74	25.23
4924.00	28.77	Ave.	259	1.0	H	6.21	34.98	54	19.02

**For BLE Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247/205/209	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>Low Channel (2402 MHz)</b>									
2402.00	54.46	PK	45	2.0	H	33.92	88.38	/	/
2402.00	48.48	Ave.	45	2.0	H	33.92	82.40	/	/
2402.00	51.77	PK	193	1.4	V	33.92	85.69	/	/
2402.00	46.02	Ave.	193	1.4	V	33.92	79.94	/	/
2386.39	27.46	PK	48	1.9	H	33.92	61.38	74	12.62
2386.39	13.94	Ave.	48	1.9	H	33.92	47.86	54	6.14
2489.62	26.84	PK	199	1.6	H	34.08	60.92	74	13.08
2489.62	13.41	Ave.	199	1.6	H	34.08	47.49	54	6.51
4804.00	43.57	PK	77	1.0	H	5.84	49.41	74	24.59
4804.00	28.59	Ave.	77	1.0	H	5.84	34.43	54	19.57
<b>Middle Channel (2440 MHz)</b>									
2440.00	55.67	PK	313	2.1	H	33.92	89.59	/	/
2440.00	50.42	Ave.	313	2.1	H	33.92	84.34	/	/
2440.00	51.28	PK	349	1.7	V	33.92	85.20	/	/
2440.00	46.01	Ave.	349	1.7	V	33.92	79.93	/	/
4880.00	43.17	PK	49	1.7	H	6.21	49.38	74	24.62
4880.00	28.62	Ave.	49	1.7	H	6.21	34.83	54	19.17
<b>High Channel (2480 MHz)</b>									
2480.00	55.65	PK	2	2.1	H	34.08	89.73	/	/
2480.00	50.24	Ave.	2	2.1	H	34.08	84.32	/	/
2480.00	51.47	PK	107	1.2	V	34.08	85.55	/	/
2480.00	46.20	Ave.	107	1.2	V	34.08	80.28	/	/
2371.36	27.06	PK	288	1.1	H	33.92	60.98	74	13.02
2371.36	13.82	Ave.	288	1.1	H	33.92	47.74	54	6.26
2499.47	27.14	PK	313	1.1	H	34.08	61.22	74	12.78
2499.47	13.43	Ave.	313	1.1	H	34.08	47.51	54	6.49
4960.00	42.85	PK	96	2.1	H	7.82	50.67	74	23.33
4960.00	28.30	Ave.	96	2.1	H	7.82	36.12	54	17.88

**Note:**



Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor



Corrected Amplitude = Corrected Factor + Reading



Margin = Limit - Corrected. Amplitude



The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.

**Pre-scan with 802.11n20 Mode, High channel  
Horizontal**

**Vertical**

**Pre-scan for Average  
Horizontal**




## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2018-03-27.


**Test Result:** Pass.

Please refer to the following table and plots.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	10.064	≥500
Middle	2442	10.128	≥500
High	2472	10.128	≥500
802.11g mode			
Low	2412	16.731	≥500
Middle	2442	16.731	≥500
High	2472	16.731	≥500
802.11n-HT20 mode			
Low	2412	17.949	≥500
Middle	2442	17.949	≥500
High	2472	17.949	≥500
802.11n-HT40 mode			
Low	2422	36.667	≥500
Middle	2442	36.667	≥500
High	2462	36.667	≥500

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
BLE mode			
Low	2402	0.734	≥500
Middle	2440	0.734	≥500
High	2480	0.734	≥500


**802.11b Low Channel**

Date: 27.MAR.2018 18:00:04

**802.11b Middle Channel**


Date: 27.MAR.2018 18:01:30

### 802.11b High Channel




Date: 27.MAR.2018 18:02:17


### 802.11g Low Channel




Date: 27.MAR.2018 18:03:16

**802.11g Middle Channel**


Date: 27.MAR.2018 18:04:10

**802.11g High Channel**


Date: 27.MAR.2018 18:05:13

**802.11n-HT20 Low Channel**


Date: 27.MAR.2018 18:06:12

**802.11n-HT20 Middle Channel**


Date: 27.MAR.2018 18:07:16

**802.11n-HT20 High Channel**


Date: 27.MAR.2018 18:08:09

**802.11n-HT40 Low Channel**


Date: 27.MAR.2018 18:09:23

**802.11n-HT40 Middle Channel**


Date: 27.MAR.2018 18:10:39

**802.11n-HT40 High Channel**


Date: 27.MAR.2018 18:11:37

**BLE Low Channel**

Date: 27.MAR.2018 17:31:30

**BLE Middle Channel**

Date: 27.MAR.2018 17:30:47

**BLE High Channel**

Date: 27.MAR.2018 17:29:46


## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Simon Wang on 2018-03-27.

EUT operation mode: Transmitting

**Wi-Fi mode**

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b				
Low	2412	10.84	8.34	30
Middle	2442	10.54	8.02	30
High	2472	10.53	8.03	30
802.11g				
Low	2412	14.66	8.74	30
Middle	2442	14.43	8.77	30
High	2472	14.52	8.62	30
802.11n HT20				
Low	2412	13.64	8.15	30
Middle	2442	13.91	8.10	30
High	2472	13.98	8.15	30
802.11n HT40				
Low	2422	13.86	8.50	30
Middle	2442	13.78	8.24	30
High	2462	13.54	8.03	30

**BLE mode**

Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	-4.57	30	Pass
Middle	2440	-5.05	30	Pass
High	2480	-5.67	30	Pass


## FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### Test Data

#### Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2018-03-27.


EUT operation mode: Transmitting

**Test Result:** Compliance


Please refer to the following plots.

**802.11b: Band Edge, Left Side**


Date: 27.MAR.2018 18:23:19

**802.11b: Band Edge, Right Side**


Date: 27.MAR.2018 18:25:29

**802.11g: Band Edge, Left Side**


Date: 27.MAR.2018 18:28:43

**802.11g: Band Edge, Right Side**


Date: 27.MAR.2018 18:29:35

**802.11n-HT20: Band Edge, Left Side**


Date: 27.MAR.2018 18:30:36

**802.11n-HT20: Band Edge, Right Side**


Date: 27.MAR.2018 18:31:23

**802.11n-HT40: Band Edge, Left Side**


Date: 27.MAR.2018 18:32:15

**802.11n-HT40: Band Edge, Right Side**

Date: 27.MAR.2018 18:33:01

**BLE: Band Edge, Left Side**

Date: 27.MAR.2018 17:33:03

**BLE: Band Edge, Right Side**

Date: 27.MAR.2018 17:34:05


## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Data

#### Environmental Conditions


<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Simon Wang on 2018-03-27.


EUT operation mode: Transmitting

**Test Result:** Pass


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-20.90	≤8
Middle	2442	-21.29	≤8
High	2472	-21.04	≤8
802.11g mode			
Low	2412	-20.62	≤8
Middle	2442	-21.33	≤8
High	2472	-21.12	≤8
802.11n-HT20 mode			
Low	2412	-21.16	≤8
Middle	2442	-21.55	≤8
High	2472	-21.60	≤8
802.11n-HT40 mode			
Low	2422	-22.30	≤8
Middle	2442	-23.85	≤8
High	2462	-23.10	≤8
BLE mode			
Low	2402	-19.93	≤8
Middle	2440	-20.64	≤8
High	2480	-21.32	≤8

**Power Spectral Density, 802.11b Low Channel**


Date: 27.MAR.2018 18:39:55

**Power Spectral Density, 802.11b Middle Channel**


Date: 27.MAR.2018 18:41:51

**Power Spectral Density, 802.11b High Channel**


Date: 27.MAR.2018 18:42:59

**Power Spectral Density, 802.11g Low Channel**


Date: 27.MAR.2018 18:44:33

**Power Spectral Density, 802.11g Middle Channel**


Date: 27.MAR.2018 18:45:15

**Power Spectral Density, 802.11g High Channel**


Date: 27.MAR.2018 18:45:51

**Power Spectral Density, 802.11n-HT20 Low Channel**


Date: 27.MAR.2018 18:47:52

**Power Spectral Density, 802.11n-HT20 Middle Channel**


Date: 27.MAR.2018 18:48:39

**Power Spectral Density, 802.11n-HT20 High Channel**


Date: 27.MAR.2018 18:49:22

**Power Spectral Density, 802.11n-HT40 Low Channel**


Date: 27.MAR.2018 18:51:21

**Power Spectral Density, 802.11n-HT40 Middle Channel**


Date: 27.MAR.2018 18:52:17

**Power Spectral Density, 802.11n-HT40 High Channel**


Date: 27.MAR.2018 18:54:52

**Power Spectral Density, BLE Low Channel**

Date: 27.MAR.2018 17:35:28

**Power Spectral Density, BLE Middle Channel**

Date: 27.MAR.2018 17:35:58

**Power Spectral Density, BLE High Channel**

Date: 27.MAR.2018 17:36:17

**\*\*\*\*\* END OF REPORT \*\*\*\*\***