

FCC PART 15C TEST REPORT FOR CERTIFICATION

On Behalf of

Planet Computers Limited

Gemini

Gemini WiFi

FCC ID: 2A07Q-X600W1

Prepared for : Planet Computers Limited

Suite #9, 56 Sloane Square, London, SW1W 8AX, United Kingdom

Prepared By : Audix Technology (Shenzhen) Co., Ltd.

No. 6, Kefeng Road, Science & Technology Park,
Nanshan District , Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F18060

Date of Test : Jan.26~31, 2018

Date of Report : Apr.12, 2018

TABLE OF CONTENTS

Description	Page
1. SUMMARY OF STANDARDS AND RESULTS.....	1-1
1.1. Description of Standards and Results	1-1
2. GENERAL INFORMATION	2-1
2.1. Description of Device (EUT).....	2-1
2.2. Tested Supporting System Details	2-2
2.3. Block Diagram of connection between EUT and simulators	2-2
2.4. Test information.....	2-2
2.5. Test Facility	2-3
2.6. Measurement Uncertainty (95% confidence levels, k=2).....	2-3
3. POWER LINE CONDUCTED EMISSION TEST	3-1
3.1. Test Equipments	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits	3-1
3.4. Configuration of EUT on Test	3-2
3.5. Operating Condition of EUT	3-2
3.6. Test Procedure	3-2
3.7. Power Line Conducted Emission Test Results	3-2
4. RADIATED EMISSION MEASUREMENT	4-1
4.1. Test Equipments	4-1
4.2. Block Diagram of Test Setup.....	4-2
4.3. Radiated Emission Limit Standard:	4-3
4.4. EUT Configuration on Test	4-3
4.5. Operating Condition of EUT	4-3
4.6. Test Procedure	4-3
4.7. Radiated Emission Test Results.....	4-4
5. CONDUCTED SPURIOUS EMISSIONS.....	5-1
5.1. Test Equipments	5-1
5.2. Limit.....	5-1
5.3. Test Procedure	5-1
5.4. Test result.....	5-1
6. 6dB BANDWIDTH TEST	6-1
6.1. Test Equipments	6-1
6.2. Limit.....	6-1
6.3. Test Procedure	6-1
6.4. Test Results.....	6-1
7. MAXIMUM PEAK OUTPUT POWER TEST	7-1
7.1. Test Equipments	7-1
7.2. Limit.....	7-1
7.3. Test Procedure	7-1
7.4. Test Results.....	7-1
8. BAND EDGE COMPLIANCE TEST	8-1
8.1. Test Equipments	8-1
8.2. Limit.....	8-1
8.3. Test Procedure	8-1
8.4. Test Results.....	8-1

9.	POWER SPECTRAL DENSITY TEST	9-1
9.1.	Test Equipments	9-1
9.2.	Limit.....	9-1
9.3.	Test Procedure	9-1
9.4.	Test Results.....	9-1
10.	ANTENNA REQUIREMENT	10-1
10.1.	Standard Applicable.....	10-1
10.2.	Antenna Connected Construction	10-1
11.	DEVIATION TO TEST SPECIFICATIONS.....	11-1
12.	PHOTOGRAPH OF TEST	12-1
12.1.	Photos of Power Line Conducted Emission Test	12-1
12.2.	Photos of Radiated Emission Test	12-2
13.	PHOTOS OF EUT	13-1

TEST REPORT CERTIFICATION

Applicant : Planet Computers Limited
Manufacture : Planet Computers Limited
Product : Gemini
FCC ID : 2A07Q-X600W1
(A) Model No. : Gemini WiFi
(B) Serial No. : N/A
(C) Test Voltage : DC 5V From Adapter Input AC 120V/60Hz

Tested for comply with:

FCC CFR 47 Part 15 Subpart C
Test procedure used: ANSI C63.10: 2013;

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Jan.26~31, 2018 Report of date: Apr.12, 2018

Prepared by : Monica Liu Reviewed by : Sunny Lu
Monica Liu / Assistant Sunny Lu / Deputy Manager



Approved & Authorized Signer : David Jin
David Jin / Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT has been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 :2013	PASS
Radiated Emission Test	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 : 2013	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 : 2013	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 : 2013	PASS
6dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 : 2013	PASS
Maximum Peak Output Power Test	FCC Part 15: 15.247(b)(1) ANSI C63.10 : 2013	PASS
Band Edge Compliance Test	FCC Part 15: 15.247(d) ANSI C63.10 : 2013	PASS
Power Spectral Density Test	FCC Part 15: 15.247(d) ANSI C63.10 : 2013	PASS

2. GENERAL INFORMATION


2.1. Description of Device (EUT)

Product	: Gemini
Model No.	: Gemini WiFi
FCC ID	: 2A07Q-X600W1
Radio	: IEEE802.11 a/b/g/n/ac; Bluetooth V3.0+EDR; Bluetooth V4.0
Operation Frequency	: IEEE 802.11a: 5180MHz—5240MHz; 5745MHz—5825MHz IEEE 802.11ac VHT20: 5180MHz—5240MHz; 5745MHz—5825MHz IEEE 802.11ac VHT40: 5190MHz—5230MHz; 5755MHz—5795MHz IEEE 802.11ac VHT80: 5210MHz; 5775MHz IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE802.11n HT20: 2412MHz—2462MHz; 5180MHz—5240MHz; 5745MHz—5825MHz IEEE802.11n HT40: 2422MHz—2452MHz; 5190MHz—5230MHz; 5755MHz—5795MHz Bluetooth : 2402-2480MHz
Modulation Technology	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11a/g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT20, VHT40, VHT80: OFDM(16QAM, 64QAM, 256QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM,QPSK,BPSK) Bluetooth V3.0+EDR: GFSK, $\pi/4$ DQPSK,8-DPSK Bluetooth V4.0:GFSK
Antenna Assembly Gain	: Antenna Type: PIFA Bluetooth: 2.0dBi WIFI 2.4GHz: 2.0dBi WIFI 5GHz: 0.42dBi
Applicant	: Planet Computers Limited Suite #9, 56 Sloane Square, London, SW1W 8AX, United Kingdom
Manufacturer	: Planet Computers Limited Suite #9, 56 Sloane Square, London, SW1W 8AX, United Kingdom
Factory	: SHENZHEN YIXU ELECTRONICS CO., LTD. Building B, Area E, Yuwei, Qingxiang Rd, Longhua, Shenzhen
Power Adapter	: Manufacturer: Planet, M/N: TPA-10120125UUA-MTK; Cable: Unshielded, Detachable, 1.0m
USB Cable	: Shielded, Detachable, 0.8m
Date of Test	: Jan.26~31, 2018
Date of Receipt	: Dec.26, 2017
Sample Type	: Prototype production

2.2. Tested Supporting System Details

[None]

2.3. Block Diagram of connection between EUT and simulators

**(EUT: Gemini)**

2.4. Test information

A Special Test Software was used to control EUT work in Continuous TX mode (GFSK modulation), and select test channel.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	3	Low :CH 0	2402
	3	Middle: CH19	2440
	3	High: CH39	2480

2.5. Test Facility
Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Kefeng Road, Science & Technology
Park, Nanshan District, Shenzhen, Guangdong,
China

EMC Lab. : Certificated by Industry Canada
Registration Number: IC 5183A-1
Valid Date: May.07, 2020

: Certificated by DAkkS, Germany
Registration No: D-PL-12151-01-00
Valid Date: Dec.07, 2021

: Accredited by NVLAP, USA
NVLAP Code: 200372-0
Valid Date: Mar.31, 2018

: Certificated by FCC, USA
Designation Number: CN5022
Valid Date: Mar.31, 2018

2.6. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.6dB (150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	2.8dB (30~200MHz, Polarization: H)
	2.8dB (30~200MHz, Polarization: V)
	3.0dB (200M~1GHz, Polarization: H)
	3.0dB (200M~1GHz, Polarization: V)
Uncertainty for Radiation Emission test in 3m chamber	5.6dB (1~6GHz, Distance: 3m)
	5.8dB (6~18GHz, Distance: 3m)
	5.8dB (Above 18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.7dB(30MHz~1000MHz)
	3.3dB(1GHz~26.5GHz)
Uncertainty for Conduction Spurious emission test	2.0dB
Uncertainty for Output power test	0.8dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.1 %
Uncertainty for test site temperature and humidity	0.6°C
	3%


3. POWER LINE CONDUCTED EMISSION TEST

3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.17,17	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCI	100842	Apr.22,17	1 Year
3.	L.I.S.N.	Rohde & Schwarz	ENV216	102160	Mar.06.17	1 Year
4.	L.I.S.N.#2	Kyoritsu	K NW-403D	8-1750-2	Apr.22,17	1 Year
5.	I.S.N.	TESEQ	S751	24559	Mar.06.17	1.year
6.	Terminator	Hubersuhner	50Ω	No.1	Apr.23,17	1 Year
7.	Terminator	Hubersuhner	50Ω	No.2	Apr.23,17	1 Year
8.	RF Cable	Fujikura	RG55/U	NO.2	Apr.22,17	1Year
9.	Coaxial Switch	Anritsu	MP59B	6201397223	Apr.22,17	1 Year
10.	Test Software	AUDIX	e3	6.100913a	N/A	N/A

Note: N/A means Not applicable.

3.2. Block Diagram of Test Setup



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Gemini (EUT)

Model Number : Gemini WiFi
Serial Number : N/A

3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turn on the power of all equipments.

3.5.3. PC run test software to control EUT work in Tx mode.

3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.7. Power Line Conducted Emission Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)




Trace: (Discrete)

Site no	:1# CE	Data No	:3
Dis./Lisn	:2017 LISN ENV216-L	LISN phase:	
Limit	:FCC PART 15 C		
Env./Ins.	:21.5*C/53%	Engineer	:Garry
EUT	:Gemini M/N:Gemini WiFi		
Power Rating	:DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	:BT 4.0 TX		

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.158	9.52	0.02	28.92	38.46	65.56	27.10	QP
2	0.579	9.50	0.03	22.63	32.16	56.00	23.84	QP
3	13.479	9.58	0.12	21.86	31.56	60.00	28.44	QP
4	18.328	9.69	0.13	19.50	29.32	60.00	30.68	QP
5	21.715	9.75	0.13	17.73	27.61	60.00	32.39	QP
6	26.699	9.80	0.13	16.01	25.94	60.00	34.06	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)

Site no :1# CE Data No :4

Dis./Lisn :2017 LISN ENV216-N LISN phase:

Limit :FCC PART 15 C

Env./Ins. :21.5*C/53% Engineer :Garry

EUT :Gemini M/N:Gemini WiFi

Power Rating :DC 5V From Adapter Input AC 120V/60Hz

Test Mode :BT 4.0 TX

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.206	9.46	0.02	24.63	34.11	63.36	29.25	QP
2	0.558	9.31	0.03	22.75	32.09	56.00	23.91	QP
3	6.488	9.42	0.10	17.05	26.57	60.00	33.43	QP
4	11.559	9.47	0.11	24.63	34.21	60.00	25.79	QP
5	13.623	9.49	0.12	28.08	37.69	60.00	22.31	QP
6	18.232	9.61	0.12	26.32	36.05	60.00	23.95	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION MEASUREMENT

4.1. Test Equipments

Frequency range: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Mar.28,17	1 Year
2.	Signal Analyzer	R&S	FSV30	103669	Oct.15,17	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESR7	101547	Apr.22,17	1 Year
4.	Amplifier	HP	8447D	2648A04738	Apr.22,17	1 Year
5.	Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	493	Jun.27.17	1 Year
6.	Loop Antenna	Chase	HLA6120	1062	Oct.15,17	1 Year
7.	RF Cable	MIYAZAKI	CFD400NL-LW	No.3	Sep.02.17	1 Year
8.	Coaxial Switch	Anritsu	MP59B	6201397222	Apr.22,17	1 Year
9.	Test Software	AUDIX	e3	6.2009-5-21a(n)	N/A	N/A

Note: N/A means Not applicable.


Frequency range: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	Apr.22,17	1 Year
2.	Horn Antenna	ETC	MCTD 1209	DRH15F03006	May.15,17	1 Year
3.	Amplifier	Agilent	8449B	3008A02495	Apr.22,17	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX104	274094/4	Apr.22,17	1 Year
5.	Horn Antenna	EMCO	3116	0062643	Oct.10,17	1 Year
6.	Test Software	AUDIX	e3	6.2009-5-21a(n)	N/A	N/A


Note: N/A means Not applicable.

4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.3. Radiated Emission Limit Standard:

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

- Remarks :
- (1) Emission level $dB\mu V = 20 \log$ Emission level $\mu V/m$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
 - (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Gemini (EUT)

Model No. : Gemini WiFi
Serial No. : N/A

4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulator as shown as Section 4.2.
- 4.5.2. Turn on the power of all equipments.
- 4.5.3. Let EUT work in Tx mode.

4.6. Test Procedure

Frequency below 30MHz:

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)*2.4m(W)*0.3m(H) on the ground . The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it.EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2013 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESR7) is set at 120kHz for frequency range from 30MHz to 1000MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz.

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.7. Radiated Emission Test Results


PASS.

All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.

Note 1: The duty cycle factor for calculate average level is 2.883dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit


Note 2: The emissions (9kHz~30MHz) not reported for there is no emission be found.

$$\text{Duty cycle factor} = 20\log(1/\text{duty cycle}) = 2.883\text{dB}$$






Frequency: 30MHz~1GHz



Site no. : 3m Chamber Data no. : 3
 Dis. / Ant. : 3m 2017 9168-493 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C (3M)
 Env. / Ins. : 23.7°C/52% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC5V From Adapter input AC 120V/60Hz
 Test Mode : BT4.0 TX

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	19.40	0.63	-0.47	19.56	40.00	20.44	QP
2	47.460	20.29	0.75	-3.17	17.87	40.00	22.13	QP
3	209.450	16.90	1.70	2.83	21.43	43.50	22.07	QP
4	374.350	21.62	2.73	-0.84	23.51	46.00	22.49	QP
5	594.540	25.80	3.65	-0.49	28.96	46.00	17.04	QP
6	823.460	28.66	4.65	-0.62	32.69	46.00	13.31	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 4
 Dis. / Ant. : 3m 2017 9168-493 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C (3M)
 Env. / Ins. : 23.7°C/52% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC5V From Adapter input AC 120V/60Hz
 Test Mode : BT4.0 TX

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	19.40	0.63	8.17	28.20	40.00	11.80	QP
2	80.440	15.20	0.98	7.29	23.47	40.00	16.53	QP
3	194.900	17.20	1.61	3.90	22.71	43.50	20.79	QP
4	354.950	21.17	2.60	-0.87	22.90	46.00	23.10	QP
5	817.640	28.59	4.61	-0.50	32.70	46.00	13.30	QP
6	956.350	30.01	5.33	-1.40	33.94	46.00	12.06	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz


Data: 1

File: F:\2017 Report\Planet\ACS17Q1941-BT4.0-FCC.EM6 (16)

Date: 2018-01-26




Site no. : 3m Chamber Data no. : 1
Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.1*C/52.5% Engineer : Kayle
EUT : Gemini M/N:Gemini WiFi
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : BT4.0 GFSK 2402 Tx Mode




Site no. : 3m Chamber Data no. : 2
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2402 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.96	10.30	81.97	35.61	84.62	74.00	-10.62	Peak
2	4804.00	33.42	14.52	37.84	33.82	51.96	74.00	22.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 3m Chamber	Data no.	: 3
Dis. / Ant.	: 3m 2017 ANT 3006 HF	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.1°C/52.5%	Engineer	: Kayle
EUT	: Gemini M/N:Gemini WiFi		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: BT4.0 GFSK 2402 Tx Mode		



Site no. : 3m Chamber Data no. : 4
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2402 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Amp factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2402.00	27.96	10.30	79.99	35.61	82.64	74.00	-8.64	Peak
2	4804.00	33.42	14.52	36.03	33.82	50.15	74.00	23.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 7
Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
EUT : Gemini M/N:Gemini WiFi
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : BT4.0 GFSK 2440 Tx Mode




Site no. : 3m Chamber Data no. : 8
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2440 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	28.03	10.37	84.06	35.64	86.82	74.00	-12.82	Peak
2	4880.00	33.56	14.62	36.07	33.75	50.50	74.00	23.50	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 3m Chamber	Data no.	: 9
Dis. / Ant.	: 3m 2017 ANT 3006 HF	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.1°C/52.5%	Engineer	: Kayle
EUT	: Gemini M/N:Gemini WiFi		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: BT4.0 GFSK 2440 Tx Mode		




Site no. : 3m Chamber Data no. : 10
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2440 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2445.00	28.03	10.37	78.03	35.68	80.75	74.00	-6.75	Peak
2	4880.00	33.56	14.62	36.97	33.75	51.40	74.00	22.60	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 3m Chamber	Data no.	: 11
Dis. / Ant.	: 3m 2017 ANT 3006 HF	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.1°C/52.5%	Engineer	: Kayle
EUT	: Gemini M/N:Gemini WiFi		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: BT4.0 GFSK 2480 Tx Mode		




Site no. : 3m Chamber Data no. : 12
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2480 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	28.08	10.45	81.43	35.71	84.25	74.00	-10.25	Peak
2	4960.00	33.73	14.73	36.50	33.69	51.27	74.00	22.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 13
Dis. / Ant.	: 3m 2017 ANT 3006 HF	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.1°C/52.5%	Engineer	: Kayle
EUT	: Gemini M/N:Gemini WiFi		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: BT4.0 GFSK 2480 Tx Mode		



Site no. : 3m Chamber Data no. : 14
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2480 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	28.08	10.45	78.68	35.71	81.50	74.00	-7.50	Peak
2	4960.00	33.73	14.73	35.21	33.69	49.98	74.00	24.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

5. CONDUCTED SPURIOUS EMISSIONS

5.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY53311015	Oct.15,17	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	Apr.27,17	1 Year
3.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.15,17	1 Year

5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions With peak detector.

5.4. Test result


PASS (The testing data was attached in the next pages.)

GFSK


2402MHz(30MHz-1GHz)




2402MHz(2.31GHz-2.405GHz)




2402MHz(1GHz-10GHz)




2440MHz(30MHz-1GHz)






2402MHz(10GHz-25GHz)



2440MHz(1GHz-10GHz)





6. 6dB BANDWIDTH TEST

6.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY53311015	Oct.15,17	1 Year
2.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.27,17	1 Year
3.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.15,17	1 Year

6.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

6.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

6.4. Test Results

EUT: Gemini		
M/N: Gemini WiFi		
Test date: 2018-01-26	Pressure: 102.5±1.0 kpa	Humidity: 52.3±3.0%
Tested by: Kayle	Test site: RF site	Temperature: 22.1±0.6 °C


Test Mode	Frequency (MHz)	6 dB bandwidth (KHz)	Limit (KHz)
GFSK	2402	694.4	≥ 500
	2440	701.5	≥ 500
	2480	712.6	≥ 500
Conclusion : PASS			

GFSK

2402MHz



2480MHz



2440MHz



7. MAXIMUM PEAK OUTPUT POWER TEST

7.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY53311015	Oct.15,17	1 Year
2.	Power meter	Anritsu	ML2487A	6K00002472	Apr.22,17	1Year
3.	Power sensor	Anritsu	MA2491A	0033005	Apr.22,17	1Year
4.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.22,17	1 Year
5.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.15,17	1 Year

7.2. Limit

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm).

7.3. Test Procedure

Connected the EUT's antenna port to Power Sensor, and use power meter to test peak output power.

7.4. Test Results

EUT: Gemini		
M/N: Gemini WiFi		
Test date: 2018-01-26	Pressure: 102.1±1.0 kpa	Humidity: 51.1±3.0%
Tested by: Kayle	Test site: RF site	Temperature: 22.8±0.6 °C

Test Mode	Frequency (MHz)	Peak output Power (dBm)	Limit (dBm)
GFSK	2402	-1.859	30
	2440	-2.257	30
	2480	-1.976	30
Conclusion: PASS			

8. BAND EDGE COMPLIANCE TEST

8.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.22,17	1 Year
2.	Amp	HP	8449B	3008A02495	Apr.22.17	1 Year
3.	Horn Antenna	ETC	MCTD 1209	DRH15F03006	May.15,17	1 Year
4.	HF Cable	Hubersuhner	Sucoflex104	274094/4	Apr.22,17	1 Year

8.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

8.3. Test Procedure

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205


For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
 - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
 - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

8.4. Test Results

Pass (The testing data was attached in the next pages.)


Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2402 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.96	10.26	45.64	35.61	48.25	74.00	25.75	Peak
2	2399.30	27.96	10.30	47.95	35.61	50.60	74.00	23.40	Peak
3	2400.00	27.96	10.30	48.58	35.61	51.23	74.00	22.77	Peak
4	2401.84	27.96	10.30	81.37	35.61	84.02	74.00	-10.02	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 6
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2402 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.96	10.26	45.53	35.61	48.14	74.00	25.86	Peak
2	2396.29	27.96	10.30	47.21	35.61	49.86	74.00	24.14	Peak
3	2400.00	27.96	10.30	48.59	35.61	51.24	74.00	22.76	Peak
4	2402.31	27.96	10.30	84.28	35.61	86.93	74.00	-12.93	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2480 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.92	28.08	10.45	82.29	35.71	85.11	74.00	-11.11	Peak
2	2483.50	28.08	10.48	46.30	35.71	49.15	74.00	24.85	Peak
3	2487.38	28.08	10.48	48.78	35.71	51.63	74.00	22.37	Peak
4	2500.00	28.10	10.48	45.84	35.74	48.68	74.00	25.32	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 16
 Dis. / Ant. : 3m 2017 ANT 3006 HF Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.1°C/52.5% Engineer : Kayle
 EUT : Gemini M/N:Gemini WiFi
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : BT4.0 GFSK 2480 Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.92	28.08	10.45	84.38	35.71	87.20	74.00	-13.20	Peak
2	2483.50	28.08	10.48	46.03	35.71	48.88	74.00	25.12	Peak
3	2491.60	28.10	10.48	47.75	35.71	50.62	74.00	23.38	Peak
4	2500.00	28.10	10.48	45.96	35.74	48.80	74.00	25.20	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

9. POWER SPECTRAL DENSITY TEST

9.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY53311015	Oct.15,17	1 Year
2.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.22,17	1 Year
3.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.15,17	1 Year

9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.3. Test Procedure

1. Connected the EUT's antenna port to spectrum analyzer device by 20dB attenuator.
2. Set the test frequency as center frequency, Set RBW=3KHz,VBW=10KHz,Span large enough capture the entire frequency, Read out maximum peak level frequency
3. Set the span to 1.5 times of the DTS Bandwidth Detector= Peak; Sweep time= Auto Couple; Trace Mode= Max hold.
4. Allow trace to fully stabilize use the peak marker function to determine the maximum amplitude level within the RBW.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude


9.4. Test Results

EUT: Gemini		
M/N:Gemini WiFi		
Test date: 2018-01-26	Pressure: 102.5±1.0 kpa	Humidity: 52.3±3.0%
Tested by: Kayle	Test site: RF site	Temperature:22.1±0.6 °C


Test Mode	Frequency (MHz)	Power density (dBm/3KHz)	Limit (dBm/3KHz)
GFSK	2402	-17.406	8
	2440	-17.768	8
	2480	-17.505	8
Conclusion : PASS			

GFSK


2402MHz



2480MHz



2440MHz



10. ANTENNA REQUIREMENT

10.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Antenna Connected Construction

The antennas used for this product are PIFA Antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2.0dBi.

11. DEVIATION TO TEST SPECIFICATIONS

[NONE]