



FCC RF Exposure Evaluation

1. Product Information

FCC ID:	2AO85-WXM30
Product name	Wireless Microphone System
Test Model	WXM30
Model Number	WXM30A, WXM30B, WXM30C, WXM30D, WXM30-1, WXM30-2, WXM30-3, WXM30-4
Model Declaration	PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power supply	DC 3.7V by Rechargeable Li-ion Battery, 800mAh
Modulation Type	FM
Antenna Type	Internal Antenna
Antenna Gain	0dBi
Hardware version	/
Software version	/
Frequency Range	537.5MHz-537.9MHz, 539.0MHz-539.4MHz, 541.5MHz-541.9MHz , 546.5MHz-546.9MHz , 552.5MHz-552.9MHz , 561.5MHz-561.9MHz , 574.5MHz-574.9MHz ,581.5MHz-581.9MHz
Channel Number	40
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Portable Device

Channel list

Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
00	537.5	10	541.5	20	552.5	30	574.5
01	537.6	11	541.6	21	552.6	31	574.6
02	537.7	12	541.7	22	552.7	32	574.7
03	537.8	13	541.8	23	552.8	33	574.8
04	537.9	14	541.9	24	552.9	34	574.9
05	539.0	15	546.5	25	561.5	35	581.5
06	539.1	16	546.6	26	561.6	36	581.6
07	539.2	17	546.7	27	561.7	37	581.7
08	539.3	18	546.8	28	561.8	38	581.8
09	539.4	19	546.9	29	561.9	39	581.9





2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ “

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot [vf \text{ (GHz)}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.





3. Refer evaluation method

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1093: Radiofrequency radiation exposure evaluation: portable devices

4. Conducted Power Results

Test Mode	Channel	Frequency (MHz)	Measured Maximum Peak Power(dBm)	Limits (dBm)	Verdict
FM	02	537.7	9.589	24	Pass
	07	539.2	9.593		
	12	541.7	9.597		
	17	546.7	9.615		
	22	552.7	9.599		
	27	561.7	9.552		
	32	574.7	9.514		
	37	581.7	9.573		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5. Manufacturing tolerance

FM Channel (Peak)	
Channel	Channel 02
Target (dBm)	9.0
Tolerance ±(dB)	1.0
Channel	Channel 07
Target (dBm)	9.0
Tolerance ±(dB)	1.0
Channel	Channel 12
Target (dBm)	9.0
Tolerance ±(dB)	1.0
Channel	Channel 17
Target (dBm)	9.0
Tolerance ±(dB)	1.0
Channel	Channel 22
Target (dBm)	9.0
Tolerance ±(dB)	1.0
Channel	Channel 27
Target (dBm)	9.0
Tolerance ±(dB)	1.0
Channel	Channel 32
Target (dBm)	9.0
Tolerance ±(dB)	1.0
Channel	Channel 37
Target (dBm)	9.0
Tolerance ±(dB)	1.0

6. Evaluation Results

Band/Mode	f (GHz) (Max.)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold(Max.)	SAR Test Exclusion
			dBm(Max.)	mW(Max.)		
FM	0.5479	5	10.0	10.0	1.4804 < 3.0	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 of KDB447498 is applied to determine SAR test exclusion.

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

.....THE END OF REPORT.....

