

Company: DOVEN LLC

Test of: DV11, DV21, DV31

To: FCC CFR 47 Part 1.1310

Report No.: JANU01-U2 _MPE Rev A

MPE/RF EXPOSURE TEST REPORT



MPE/RF EXPOSURE TEST REPORT



Test of: DOVEN LLC – DV11, DV21, DV31

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: JANU01-U2_MPE Rev A

This report supersedes: NONE

Applicant: DOVEN LLC
2408 Timberloch PL Ste A6
The Woodlands TX 77380
USA

Issue Date: 5th March 2018

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4*\pi*d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ (G \text{ (dBi)}/10)$$

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Maximum Permissible Exposure

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
3650 (DV11-AC)	13.0	19.95	-42.3	5.89E-05	2.34E-07	1.0	20
3650 (DV21-AC)	9.28	8.47	-45.4	2.88E-05	4.86E-08	1.0	20
3650 (DV21-DC)	9.28	8.47	-46.1	2.45E-05	4.14E-08	1.0	20
3650 (DV31-DC)	6.0	3.98	-43.5	4.47E-05	3.54E-08	1.0	20

Specification - Maximum Permissible Exposure Limits

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500	--	--	f/1500	30
1,500-100,000	--	--	1.0	30

f = frequency in MHz * = Plane-wave equivalent power density



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com