

TEST REPORT					
90037-24-72-24-PP001					
2024.01.31					
Duke Chen	Rulee Chen				
Jason Gao	Roke Chen Jason gao				
SLG-CPC Testlaboratory Co., Ltd.					
No. 11, Wu Song Road, Dongcheng Dis Province, China 523117	strict, Dongguan, Guangdong				
MOKO TECHNOLOGY Ltd					
Factory 201, 107 Pinshun Rd Guixiang community, Guanlan Street, Longhua, Shenzhen, China 518110					
MOKO TECHNOLOGY Ltd					
Factory 201, 107 Pinshun Rd Guixiang community, Guanlan Street, Longhua, Shenzhen, China 518110					
MOKO TECHNOLOGY Ltd					
Factory 201, 107 Pinshun Rd Guixiar Longhua, Shenzhen, China 518110	ng community, Guanlan Street,				
FCC 47 CFR Part 15, Subpart C					
Bluetooth Beacon					
N/A					
S02R, S02R-CNCNX-TFHA_BS149,	S02R-CNCNX-TFHA_AU500				
2AO94-TOF					
2024.01.15					
2024.01.15- 2024.01.24					
Pass					
ed on a technical opinion belongs to the	standard(s).				
	90037-24-72-24-PP001 2024.01.31 Duke Chen Jason Gao SLG-CPC Testlaboratory Co., Ltd. No. 11, Wu Song Road, Dongcheng Dis Province, China 523117 MOKO TECHNOLOGY Ltd Factory 201, 107 Pinshun Rd Guixiar Longhua, Shenzhen, China 518110 MOKO TECHNOLOGY Ltd Factory 201, 107 Pinshun Rd Guixiar Longhua, Shenzhen, China 518110 MOKO TECHNOLOGY Ltd Factory 201, 107 Pinshun Rd Guixiar Longhua, Shenzhen, China 518110 MOKO TECHNOLOGY Ltd Factory 201, 107 Pinshun Rd Guixiar Longhua, Shenzhen, China 518110 MOKO TECHNOLOGY Ltd Factory 201, 107 Pinshun Rd Guixiar Longhua, Shenzhen, China 518110 FCC 47 CFR Part 15, Subpart C Bluetooth Beacon N/A S02R, S02R-CNCNX-TFHA_BS149, 2AO94-TOF 2024.01.15 2024.01.15- 2024.01.24				

# General disclaimer:

This report shall not be reproduced except in full, without the written approval of SLG-CPC Testlaboratory Co., Ltd. The test results in the report only apply to the tested sample.



# **Table of Contents**

1	EUT	TECHNICAL DESCRIPTION	4
2	SUN	MMARY OF TEST RESULT	5
3	TES	T METHODOLOGY	6
	3.1 3.2 3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS MEASUREMENT EQUIPMENT USED DESCRIPTION OF TEST MODES	6
4	FAC	CILITIES AND ACCREDITATIONS	8
	4.1 4.2	FACILITIES LABORATORY ACCREDITATIONS AND LISTINGS	8
5	TES	ST SYSTEM UNCERTAINTY	9
6	SET	UP OF EQUIPMENT UNDER TEST1	0
	6.1 6.2	RADIO FREQUENCY TEST SETUP 1       1         RADIO FREQUENCY TEST SETUP 2       1	0 0
7	TES	T REQUIREMENTS1	
	7.1 7.2 7.3 7.4 7.5	DTS 6DB BANDWIDTH	5 7 20



# **Modified Information**

Version	Report No.	Revision Data	Summary
Ver.1.0 90037-24-72-24-PP001		2024.01.26	Original Version



# 1 EUT TECHNICAL DESCRIPTION

Product:	Bluetooth Beacon
Model Number:	S02R, ,S02R-CNCNX-TFHA_BS149, S02R-CNCNX-TFHA_AU500
Power supply:	<ul> <li>□:Adapter information</li> </ul>
Modulation:	BLE(GFSK)
Frequency Range:	2402MHz~2480MHz
Number of Channels:	40channels
Antenna Gain:	-0.51dBi
Antenna:	PCB Antenna

Note: for more details, please refer to the User's manual of the EUT.



# 2 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark		
15.247(a)(2)	DTS (6dB) Bandwidth	PASS			
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS			
15.247(e)	Maximum Power Spectral Density Level	PASS			
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS			
15.247(d)	Radiated Spurious Emission	PASS			
15.209					
15.207	Conducted Emission Test	N/A			
15.247(b)	Antenna Application	PASS			
	NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.				

# RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AO94-TOF filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.



# **3 TEST METHODOLOGY**

# 3.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards: FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C FCC KDB 558074 D01 15.247 Meas Guidance v05r02

# 3.2 MEASUREMENT EQUIPMENT USED

Equipment	Model	Manufacturer	S/N	Last Cal.	DUE Cal.			
RF Connected Test								
Vector Signal Generater	Rohde & Schwarz	SMBV100B(6G)	101166	2023/06/04	1 year			
Analog Signal Generator Rohde & Schwarz		SMB100A(40G)	181333	2023/06/02	1 year			
Signal Analyzer	Rohde & Schwarz	FSV40	101527	2023/03/29	1 year			
Power Analyzer	Rohde & Schwarz	OSP-B157W8	N/A	2023/06/04	1 year			
Wideband Radio Communication Tester	R&S	CMW270	101985	2023/06/16	1 year			
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	166898	2023/06/16	1 year			
Spectrum Analyzer	Agilent	E4408B	MY44211139	2023/11/06	1 year			
Temperature&Humidity test chamber	ESPEC	VC 4018	/	2023/03/29	1 year			
	Radia	ated Emission Te	st					
EMI Test Receiver	KEYSIGHT	N9010A	MY56070465	2023/12/06	1 year			
EMI Test Receiver	Rohde & Schwarz	FSV40	101511	2023/03/29	1 year			
Bilog Antenna	Schwarzbeck	VULB 9163	01335	2023/04/21	3 year			
Power Amplifier	EMEC	EM330	060676	2022/12/07	3 year			
Cable	Tuyue	F4309	L-400-NmNm- 12000	2023/12/06	1 year			
Horn Antenna	Schwarzbeck	BBHA9120D	1779	2022/04/21	3 year			
Horn Antenna	Schwarzbeck	BBHA9170	00954	2022/09/13	3 year			
Power Amplifier	Rohde & Schwarz	SCU-18F	180118	2022/04/21	3 year			
Active Loop Antenna	ETS LINDGREN	6512	41623	2022/04/23	3 year			
Test Software	Farad	EZ-EMC	Ver.CPC-3A1	/	/			
	Conducted Emission Test							
LISN	Schwarzbeck	NSLK 8127	8127-892	2023/03/21	1 year			
EMI Test Receiver	R&S	ESR3	102124	2023/12/06	1 year			
Pulse Limiter	R&S	ESH3-Z2	357.8810.52	2023/12/06	1 year			
Test Software	Farad	EZ-EMC	Ver.CPC-3A1	/	/			



## 3.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (BLE :1Mbps) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
0	2402	19	2440			
1	2404	20	2442	37	2476	
2	2406	21	2444	38	2478	
Note: $fc=2402MHz+k\times 1MHz$ k=1 to 39						

Frequency and Channel list for BLE:

Test Frequency and channel for BLE:

Lowest Frequency		st Frequency Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440	39	2480



# **4** FACILITIES AND ACCREDITATIONS

# 4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 11, Wu Song Road, Dongcheng District, Dongguan, Guangdong Province, China 523117 The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.10 and CISPR Publication 32.

# 4.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description EMC Lab.	: Accredited by ISED, October 04 2021 CAB identifier: CN0126 Company Number: 27767 Accredited by A2LA, October 04 2021 The Certificate Registration Number is 6325.01
Name of Firm	<ul> <li>SLG-CPC Testlaboratory Co., Ltd.</li> <li>No. 11, Wu Song Road, Dongcheng District, Dongguan, Guangdong</li></ul>
Site Location	Province, China 523117



# 5 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0%
Conducted Emissions Test	±3.08dB
Radiated Emission Test	±4.60dB
Power Density	±0.9%
Occupied Bandwidth Test	±2.3%
Band Edge Test	±1.2%
Antenna Port Emission	±3dB
Temperature	±3.2%
Humidity	±2.5%

Measurement Uncertainty for a level of Confidence of 95%



# 6 SETUP OF EQUIPMENT UNDER TEST

## 6.1 RADIO FREQUENCY TEST SETUP 1

The BLE component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.

EUT

# 6.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

#### Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


#### 30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

## Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz




90037-24-72-24-PP001



# (b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



# (c) Radiated Emission Test Set-Up, Frequency above 1000MHz





#### **TEST REQUIREMENTS** 7

# 7.1 DTS 6DB BANDWIDTH

#### 7.1.1 **Applicable Standard**

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 7.1.2 **Conformance Limit**

The minimum -6 dB bandwidth shall be at least 500 kHz.

#### 7.1.3 **Test Configuration**

Test according to clause 7.1 radio frequency test setup 1

#### 7.1.4 **Test Procedure**

The EUT was operating in BLE mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

- Set Span=2 times OBW
- Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.


Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Measure and record the results in the test report.

# **Test Results**


Temperature:	23° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (MHz)	Limit (kHz)	Verdict
	0	2402	0.754	>500	PASS
BLE	19	2440	0.764	>500	PASS
	39	2480	0.763	>500	PASS











# 7.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

# 7.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02

## 7.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

# 7.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 7.2.4 Test Procedure



# According to FCC Part15.247(b)(3)

As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. For smart system, Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Set the RBW  $\geq$  DTS bandwidth(about 1MHz).

Set VBW =3\*RBW(about 3MHz)

Set the span ≥3\*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize. Use peak marker function to determine the peak amplitude level.

According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



# **Test Results**

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Test Mode	СН	Result (dBm)	Limit (dBm)			
	CH0	4.01	30			
BLE(GFSK)	CH19	3.67	30			
	CH39	3.43	30			
Conclusion: PASS						



# 7.3 MAXIMUM POWER SPECTRAL DENSITY

#### 7.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02

## 7.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 7.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 7.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer Set analyzer center frequency to DTS channel center frequency. Set the span to 1.5 times the DTS bandwidth. Set the RBW to: 3 kHz Set the VBW to: 10 kHz. Set Detector = peak. Set Sweep time = auto couple. Set Trace mode = max hold. Allow trace to fully stabilize. Use the peak marker function to determine the maximum amplitude level within the RBW.

### 7.3.5 Test Results

Temperature:	23° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Test Mode	СН	Power density (dBm/3kHz)	(dBm/3kHz) Limit			
CH1		1.953	8			
GFSK(BLE)	CH20	1.238	8			
	CH40	1.205	8			
Conclusion: PASS						





Spectrum


RefLevel 20.00 dBm Att 30 dB

**Test Model** 



₩

# Power Spectral Density BLE Channel 39: 2480MHz Offset 2.64 dB • RBW 100 kHz SWT 18.9 µs • VBW 300 kHz Mode Auto FFT



Date: 24.JAN.2024 01:19:20



# 7.4 RADIATED SPURIOUS EMISSION

### 7.4.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 7.4.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	.20775 73-74.6 1645.5-1646.5		9.3-9.5
6.215-6.218	218 74.8-75.2 1660-1710		10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			
8.41425-8.41475 12.29-12.293 12.51975-12.52025 12.57675-12.57725	162.0125-167.17 167.72-173.2 240-285	3260-3267 3332-3339 3345.8-3358	23.6-24.0 31.2-31.8 36.43-36.5

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted	Field Strength (µV/m)	Field Strength	Measurement
Frequency(MHz)		(dBµV/m)	Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	2400/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

## 7.4.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 7.4.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \ge 1$  GHz(1GHz to 25GHz), 100 kHz for f < 1 GHz(30MHz to 1GHz) VBW  $\ge$  RBW Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT,



measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

# 7.4.5 Test Results

Temperature:	23° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Spurious Emission below 30MHz (9KHz to 30MHz)

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor



Spurious Emission Above 1GHz (1GHz to 25GHz)

BLE mode have been tested, and the worst result was report as below:

Test mode:	BLE		Frequency:		Channe	I 0: 2402MH	z
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	H/V
4804	61.39	-4.26	57.13	74	-16.87	peak	Н
4804	49.77	-4.26	45.51	54	-8.49	AVG	Н
7206	53.11	1.18	54.29	74	-19.71	peak	Н
7206	42.01	1.18	43.19	54	-10.81	AVG	Н
4804	60.96	-4.26	56.70	74	-17.30	peak	V
4804	46.79	-4.26	42.53	54	-11.47	AVG	V
7206	51.33	1.18	52.51	74	-21.49	peak	V
7206	39.66	1.18	40.84	54	-13.16	AVG	V

Lest	mode:	
1000	moue.	

BLE

Frequency:

Channel 19: 2440MHz

Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type	H/V
4880	59.63	-4.12	55.51	74	-18.49	peak	Н
4880	46.01	-4.12	41.89	54	-12.11	AVG	Н
7320	51.23	1.46	52.69	74	-21.31	peak	Н
7320	37.66	1.46	39.12	54	-14.88	AVG	Н
4880	60.36	-4.12	56.24	74	-17.76	peak	V
4880	50.01	-4.12	45.89	54	-8.11	AVG	V
7320	49.11	1.46	50.57	74	-23.43	peak	V
7320	39.86	1.46	38.40	54	-15.60	AVG	V



Test mode:	BLE	BLE		quency:	Channe	el 39: 2480M	lHz
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	H/V
4960	49.80	-4.04	45.76	74	-28.24	Peak	Н
7440	49.60	1.57	51.17	74	-22.83	Peak	н
4960	49.16	-4.04	45.12	74	-28.88	Peak	V
7440	48.97	1.57	50.54	74	-23.46	Peak	V

Remark:


1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



## Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz




Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.

2. The emission levels that are 20dB below the official


limit are not reported.






emarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Readin 2. The emission levels that are 20dB below the official limit are not reported.





limit are not reported.






Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading. 2. The emission levels that are 20dB below the official limit are not reported.



# Spurious Emission below 1GHz (30MHz to 1GHz)






Remarks:1. Result=Reading+Antenna+Cable

2. If Peak Result complies with QP Limit, QP Re to comply with QP Limit.





Remarks:1. Result=Reading+Antenna+Cable

If Peak Result complies with QP Limit, QP Result is deemed to comply with QP Limit.



# 7.5 ANTENNA APPLICATION

#### 7.5.1 Antenna Requirement

Standard FCC CRF Part 15.203	Requirement An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 7.5.2 Result

PASS.

Note:

The EUT has 1 antenna: a PCB Antenna for BLE with classic model, the gain is -0.51dBi;

 $\boxtimes$  Antenna use a permanently attached antenna which is not replaceable.

- Not using a standard antenna jack or electrical connector for antenna replacement
- The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

----- END OF REPORT ------