



# KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,  
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China  
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

## RF Exposure Evaluation FCC ID:2A094-W3

### REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

### TEST RESULT

Passed

Not Applicable

BLE

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Tune up Power (mW)	Calculating data	Limit	Results
GFSK_1M	2402	-0.76	-0.76±1	0.24	1.06	0.33	3.00	Pass
	2440	-0.62	-0.62±1	0.38	1.09	0.34		
	2480	-0.62	-0.62±1	0.38	1.09	0.34		
GFSK_2M	2402	-0.61	-0.61±1	0.39	1.09	0.34	3.00	Pass
	2440	-0.63	-0.63±1	0.37	1.09	0.34		
	2480	-0.72	-0.72±1	0.28	1.07	0.34		

Note:

-The exposure safety distance is less than 5mm.

\*\*\*\*\*THE END\*\*\*\*\*