



RF Exposure Evaluation

FCC ID: 2A094-W6

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

Passed

Not Applicable

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Calculating data	Limit	Results
GFSK	2402	-0.03	0±1	1	1.26	0.390	3.00	Pass
	2440	-0.18	0±1	1	1.26	0.393		
	2480	-0.60	0±1	1	1.26	0.397		

Conclusion:PASS

Note:

-The maximum antenna gain is -0.47dBi.

-The exposure safety distance is less than 5mm.

-According to the calculation results, no SAR measurement is required.

--THE END--