

# **FCC Test Report**

Report No.: AGC00796180301FE03

**FCC ID** : 2A09F-S027TWS

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION**: SonaBuds ES

BRAND NAME : Dashbon

MODEL NAME : S027 TWS

**CLIENT**: Dashbon Inc.

**DATE OF ISSUE** : Mar. 22, 2018

STANDARD(S)

TEST PROCEDURE(S) : FCC Part 15 Subpart C Section 15.249

**REPORT VERSION**: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

AGC 3

#### **CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results spowed this jest eport refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a transfer o

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 62

# **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	plience 1 6 miles	Mar. 22, 2018	Valid	Initial release

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.



# TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	
2.1. PRODUCT DESCRIPTION	<b>5</b>
3. MEASUREMENT UNCERTAINTY	6
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	
5.1. CONFIGURATION OF EUT SYSTEM 5.2. EQUIPMENT USED IN EUT SYSTEM 5.3. SUMMARY OF TEST RESULTS	8 8 9
6. TEST FACILITY	10
7. TEST METHOD	11
8. TEST EQUIPMENT LIST	
9. RADIATED EMISSION	12
9.1. TEST LIMIT	12 13 15 17
10. BAND EDGE EMISSION	38
10.1. MEASUREMENT PROCEDURE 10.2 TEST SETUP 10.3 RADIATED TEST RESULT	38 39
11. 20DB BANDWIDTH	43
11.1. MEASUREMENT PROCEDURE	43
12. FCC LINE CONDUCTED EMISSION TEST	
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	51 51 51
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	52
ADDENDIV DE DUOTOOD ADUO OF FUT	



age 4 of 62

# 1. VERIFICATION OF CONFORMITY

Applicant	Dashbon Inc.
Address	4F, No.94, Baozhong Rd, Xindian District, New Taipei City, 23144 Taiwan
Manufacturer	Shenzhen Sande Dacom Electronics Co., Ltd.
Address	Building I, NO.10 East Area of ShangXue Science & Technology Industrial Park,BanTian, LongGang District, Shenzhen, China
Product Designation	SonaBuds ES
Brand Name	Dashbon
Test Model	S027 TWS
Date of test	Mar. 14, 2018 to Mar. 21, 2018
Deviation	None San
Condition of Test Sample	Normal Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249. The test results of this report relate only to the tested sample identified in this report.

Tested By	Honry Zhang	
Toolog Dy	Henry Zhang(Zhang Zhuorui)	Mar. 21, 2018
Reviewed By	Lowers ce	
The Tomphan	Forrest Lei(Lei Yonggang)	Mar. 22, 2018

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 5 of 62

## 2. GENERAL INFORMATION

## 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

A major technical descripti	of of Eo Fis described as following
Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	2.11dBm(Max EIRP Power=Max radiation field-95.2)
<b>Bluetooth Version</b>	V4.1
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK
Number of channels	79
Hardware Version	S027 TWS V2
Software Version	V1.0
Antenna Designation	Ceramic Antenna
Antenna Gain	OdBi ( ) A Market
Power Supply	DC 3.7V by battery
*	

Note: The EUT comprises left and right channel earphone, both are the same and have been tested, only the test data of left earphone recorded in this report.

## 2.2. TABLE OF CARRIER FREQUENCYS

**BR/EDR Channel List** 

Frequency Band	Channel Number	Frequency
2400~2483.5MHz	The O of the condition of	2402MHz
S EL Completion	Endocument C. Tamenton	2403MHz
-C		THE THE PARTY OF T
Co lo	38	2440 MHz
The Thing commit	39	2441 MHz
Complete Complete (C. Marie and Co. Marie an	40	2442 MHz
, 100 VC		不是那
:110	77	2479 MHz
The Companies @	78	2480 MHz



Page 6 of 62

#### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.


- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB

## 4. DESCRIPTION OF TEST MODES


NO.	TEST MODE DESCRIPTION				
1 K Karmundo	Low channel GFSK				
2	Middle channel GFSK				
3	High channel GFSK				
4	Low channel π /4-DQPSK				
5 K 1000	Middle channel π /4-DQPSK				
6	High channel π /4-DQPSK				
7	Low channel 8DPSK				
8	Middle channel 8DPSK				
9 @ Managaran of close	High channel 8DPSK				
10	BT Link				

#### Note:

- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.







The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type of the confirmed at a type of type of type of the confirmed at a type of typ



Page 8 of 62

# 5. SYSTEM TEST CONFIGURATION 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)

EUT

Configure 2: (Control continuous TX)

			KEL.	
EUT	Station C	Control box	O.o.	PC

#### **5.2. EQUIPMENT USED IN EUT SYSTEM**

Item	Equipment	Mfr/Brand	Model/Type No.	Remark	
1	SonaBuds ES	Dashbon	S027 TWS	EUT	
2	Battery	HHX	541114	Accessory	
3	PC 8	APPLE	A1465	A.E	
4	Control box	AIROHA	N/A	A.E	
5	USB Cable	N/A	0.2m unshielded	Accessory	
5	USB Cable	N/A	1m unshielded	A.E	



Page 9 of 62

#### **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249(a) §15.209	Radiated Emission	Compliant
§15.249(d)	Band Edges	Compliant
§15.207	Conduction Emission	N/A
§15.215	Bandwidth	Compliant

Note: N/A means it's not applicable to this item.



Page 10 of 62

# 6. TEST FACILITY

And the second s	
Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012
NVLAP Lab Code	600153-0
Designation Number	CN5028
Test Firm Registration Number	682566
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0



age 11 of 62

#### 7. TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

#### 8. TEST EQUIPMENT LIST

#### TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Jun.20, 2017	Jun.19, 2018
LISN	R&S	ESH2-Z5	100086	Aug.21, 2017	Aug.20, 2018

#### **TEST EQUIPMENT OF RADIATED EMISSION TEST**

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun.20, 2017	Jun.19, 2018
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.20, 2017	Jun.19, 2018
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Loop Antenna	A.H.Systems,Inc	SAS-562B	C Alle	Mar. 01, 2018	Feb. 28, 2020



Page 12 of 62

## 9. RADIATED EMISSION

#### 9.1. TEST LIMIT

## Standard FCC15.249

Fundamental	Field Strength of Fundamental	Field Strength of Harmonics
Frequency	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency	Distance	Field Str	engths Limit
(MHz)	Meters	μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	9
0.490 ~ 1.705	30	24000/F(kHz)	技調
1.705 ~ 30	30	30	Experimental Control C
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3 January Community	Other:74.0 dB(μV)/m (Average)	(Peak) 54.0 dB(μV)/m

Remark:

- (1) Emission level dB $\mu$  V = 20 log Emission level  $\mu$  V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Page 13 of 62

#### 9.2. MEASUREMENT PROCEDURE

- 1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- 2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarization Of the antenna are set to make the measurement.
- 4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- 5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
- 6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 14 of 62


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	Fundamental: 2.4~2.483GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 2MHz/ VBW 10Hz for Average Harmonics: 1GHz~25GHz RBW 1MHz/ VBW 3MHz for Peak, RBW 1MHz/ VBW 10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




#### 9.3. TEST SETUP


#### RADIATED EMISSION TEST-SETUP FREQUENCY BELOW 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz




The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 40°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.





# RADIATED EMISSION TEST SETUP ABOVE 1000MHz



The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type of the report will be con



Page 17 of 62

# 9.4. TEST RESULT

(Worst modulation: GFSK)


FOR BR/EDR

#### **RADIATED EMISSION BELOW 30MHz**

No emission found between lowest internal used/generated frequencies to 30MHz.

#### **RADIATED EMISSION BELOW 1GHz**

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
000	1		101.1333	15.47	10.22	25.69	43.50	-17.81	peak			
	2		282.2000	8.38	12.38	20.76	46.00	-25.24	peak			
	3		361.4166	3.31	18.82	22.13	46.00	-23.87	peak			
	4		642.7167	1.70	23.83	25.53	46.00	-20.47	peak			
	5		793.0667	1.24	27.22	28.46	46.00	-17.54	peak		·	
5	6	*	953.1167	2.03	29.97	32.00	46.00	-14.00	peak			

**RESULT: PASS** 



Page 18 of 62

# RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
e e	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1	*	130.2332	19.73	11.13	30.86	43.50	-12.64	peak			
2		283.8167	15.87	14.92	30.79	46.00	-15.21	peak			
3		400.2167	8.64	19.08	27.72	46.00	-18.28	peak			
4		547.3333	1.89	22.41	24.30	46.00	-21.70	peak			
5		799.5333	1.74	27.31	29.05	46.00	-16.95	peak			
6		941.8000	1.46	29.77	31.23	46.00	-14.77	peak			

#### **RESULT: PASS**


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



Page 19 of 62

# RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL




No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
3	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		110.8332	11.73	7.98	19.71	43.50	-23.79	peak			
2		183.5833	7.12	11.24	18.36	43.50	-25.14	peak			
3		358.1832	4.00	18.79	22.79	46.00	-23.21	peak			
4		644.3333	1.01	23.84	24.85	46.00	-21.15	peak			
5		734.8667	1.71	26.20	27.91	46.00	-18.09	peak			
6	*	936.9500	1.98	29.64	31.62	46.00	-14.38	peak			

RESULT: PASS



Page 20 of 62

# RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL -VERTICAL



#### **RESULT: PASS**

806.0000

951.5000

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

28.77

32.37

27.32

29.99

1.45

2.38

2. The "Factor" value can be calculated automatically by software of measurement system.

46.00

46.00

-17.23

-13.63


peak

peak



Page 21 of 62

# RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL




No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1		128.6167	9.48	9.88	19.36	43.50	-24.14	peak			
2		314.5333	4.78	16.38	21.16	46.00	-24.84	peak			
3		356.5667	3.30	18.78	22.08	46.00	-23.92	peak			
4		584.5167	0.42	23.34	23.76	46.00	-22.24	peak			
5		746.1833	2.12	26.52	28.64	46.00	-17.36	peak			
6	*	943.4167	1.44	29.82	31.26	46.00	-14.74	peak			

RESULT: PASS



Page 22 of 62

# RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		88.2000	17.27	4.74	22.01	43.50	-21.49	peak			
2	*	130.2332	19.34	11.13	30.47	43.50	-13.03	peak			
3		366.2667	6.66	18.85	25.51	46.00	-20.49	peak			
4		430.9333	5.41	20.01	25.42	46.00	-20.58	peak			
5		660.5000	1.93	24.13	26.06	46.00	-19.94	peak			
6		961.2000	2.10	29.89	31.99	54.00	-22.01	peak			

# **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.




Page 23 of 62

#### **RADIATED EMISSION ABOVE 1GHz**

(Worst modulation: GFSK) FOR BR/EDR

#### For Fundamental

## RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




**RESULT: PASS** 



Page 24 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc.gett.com.



Page 25 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 26 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Lable Degree	Comment
2		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
sto	1		2441.000	86.05	10.36	96.41	114.00	-17.59	peak			
	2	*	2441.000	78.22	10.36	88.58	94.00	-5.42	AVG	100	63	


**RESULT: PASS** 

The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KCE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-cert.com.



Page 27 of 62

## RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 28 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



# **RESULT: PASS**

2480.000

78.41

10.41

2

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

88.82

The "Factor" value can be calculated automatically by software of measurement system.

94.00

-5.18

AVG

100

64

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 29 of 62

# Field strength of the fundamental signal

## 1Mbps Result:

## Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	86.14	10.32	96.46	114	-17.54	Horizontal
2402	85.73	10.32	96.05	114	-17.95	Vertical
2441	86.55	10.36	96.91	114	-17.09	Horizontal
2441	86.05	10.36	96.41	114	-17.59	Vertical
2480	86.90	10.41	97.31	114	-16.69	Horizontal
2480	86.42	10.41	96.83	114	-17.17	Vertical

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	78.31	10.32	88.63	94	-5.37	Horizontal	
2402	77.74	10.32	88.06	94	-5.94	Vertical	
2441	78.58	10.36	88.94	94	-5.06	Horizontal	
2441	78.22	10.36	88.58	94	-5.42	Vertical	
2480	78.93	10.41	89.34	94	-4.66	Horizontal	
2480	78.41	10.41	88.82	94	-5.18	Vertical	



Page 30 of 62

## 2Mbps Result:

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	85.66	10.32	95.98	114	-18.02	Horizontal
2402	85.35	10.32	95.67	114	-18.33	Vertical
2441	86.12	10.36	96.48	114	-17.52	Horizontal
2441	85.59	10.36	95.95	114	-18.05	Vertical
2480	86.60	10.41	97.01	114	-16.99	Horizontal
2480	86.06	10.41	96.47	114	-17.53	Vertical

## Average value

3					LE Pro	Test allano
Frequency (MHz)	Reading Level (dBuv)	Factor (dB/m)	Measurement (dBuv/m)	Limit (dBuv/m)	Over	Antenna Polarization
2402	77.34	10.32	87.66	94	-6.34	Vertical
2441	78.24	10.36	88.60	94	-5.40	Horizontal
2441	77.82	10.36	88.23	94	-5.77	Vertical
2480	78.50	10.41	88.91	94	-5.09	Horizontal
2480	78.03	10.41	88.44	94	-5.56	Vertical



Page 31 of 62

#### 3Mbps Result:

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	85.35	10.32	95.67	114	-18.33	Horizontal
2402	84.94	10.32	95.26	114	-18.74	Vertical
2441	85.80	10.36	96.16	114	-17.84	Horizontal
2441	85.30	10.36	95.66	114	-18.34	Vertical
2480	86.12	10.41	96.53	114	-17.47	Horizontal
2480	85.63	10.41	96.04	114	-17.96	Vertical

## Average value

3						
Frequency (MHz)	Reading Level (dBuv)	Factor (dB/m)	Measurement (dBuv/m)	Limit (dBuv/m)	Over	Antenna Polarization
2402	76.86	10.32	87.18	94	-6.82	Vertical
2441	77.86	10.36	88.22	94	-5.78	Horizontal
2441	77.41	10.36	87.77	94	-6.23	Vertical
2480	78.14	10.41	88.55	94	-5.45	Horizontal
2480	77.61	10.41	88.02	94	-5.98	Vertical




Page 32 of 62

# (Worst modulation: GFSK) FOR BR/EDR

#### **For Harmonics**

#### RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




**RESULT: PASS** 



Page 33 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 34 of 62

## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 35 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL




**RESULT: PASS** 



Page 36 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 37 of 62

# RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



### **RESULT: PASS**

3

4960.000

42.91

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

8.09

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

51.00

The "Factor" value can be calculated automatically by software of measurement system.

74.00

-23.00

peak

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 38 of 62

# 10. BAND EDGE EMISSION


## 10.1. MEASUREMENT PROCEDURE

- 1. The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

Start frequency(MHz)	Stop frequency(MHz)				
2200	2405				
2478	2500				

### 10.2 TEST SETUP

# RADIATED EMISSION TEST SETUP



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




Page 39 of 62

# **10.3 RADIATED TEST RESULT**

(Worst modulation: GFSK)

FOR BR/EDR

## TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



sta	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
	1		2283.025	32.09	10.19	42.28	74.00	-31.72	peak			
	2		2390.000	33.50	10.31	43.81	74.00	-30.19	peak			
	3		2400.000	42.47	10.32	52.79	74.00	-21.21	peak			
	4	*	2402.000	86.16	10.32	96.48	74.00	22.48	peak			
	5	Х	2402.000	78.29	10.32	88.61	74.00	14.61	AVG	100	40	

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 40 of 62

# TEST PLOT OF BAND EDGE FOR LOW CHANNEL - Vertical




	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
3		-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB	Γ	cm	degree	
(0)	1		2254.325	32.31	10.16	42.47	74.00	-31.53	peak			
	2		2390.000	31.21	10.31	41.52	74.00	-32.48	peak			
	3		2400.000	36.56	10.32	46.88	74.00	-27.12	peak			
	4	*	2402.000	85.66	10.32	95.98	74.00	21.98	peak			
	5	Х	2402.000	77.71	10.32	88.03	74.00	14.03	AVG	100	71	

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 1000, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trip://www.agc-gett.com.



Page 41 of 62

# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
e			MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
ATÉ	1	*	2480.000	86.87	10.41	97.28	74.00	23.28	peak			
	2	Х	2480.000	78.91	10.41	89.32	74.00	15.32	AVG			
	3		2483.500	33.69	10.41	44.10	74.00	-29.90	peak			
	4		2490.723	34.45	10.42	44.87	74.00	-29.13	peak			

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 42 of 62

# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
3			MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
312	1	*	2480.000	86.40	10.41	96.81	74.00	22.81	peak			
ſ	2	Х	2480.000	78.38	10.41	88.79	74.00	14.79	AVG	100	68	
	3		2483.500	32.76	10.41	43.17	74.00	-30.83	peak			
	4		2493.473	35.83	10.42	46.25	74.00	-27.75	peak			

### **RESULT: PASS**

**Note**: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




Page 43 of 62

# 11. 20DB BANDWIDTH

## 11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ 3RBW; Sweep = auto; Detector function = peak
- 3. Set SPA Trace 1 Max hold, then View.

# 11.2. TEST SET-UP



# 11.3. LIMITS AND MEASUREMENT RESULTS

### FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT										
		Measure	ement Result							
Applicable Limits		Test Data (MHz)								
		99%OBW (MHz)	-20dB BW(MHz)	Result						
Solut Committee C Management	Low Channel	0.976	1.094	PASS						
N/A	Middle Channel	0.961	1.101	PASS						
	High Channel	0.964	1.090	PASS						


The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.




### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.






#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT								
		Measure	ement Result					
Applicable Limits		Doord						
		99%OBW (MHz)	-20dB BW(MHz)	Result				
TO THE	Low Channel	1.238	1.375	PASS				
N/A	Middle Channel	1.243	1.378	PASS				
AGO M	High Channel	1.237	1.378	PASS				


## TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.




#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.





BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT									
DEGETO	SOTTI OMIBI O EM	Measurement Result							
Applicable Limits		Dooult							
		99%OBW (MHz)	-20dB BW(MHz)	Result					
不是 那	Low Channel	1.256	1.381	PASS					
N/A	Middle Channel	1.244	1.391	PASS					
LOC "	High Channel	1.259	1.375	PASS					


## TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 50 of 62

# 12. FCC LINE CONDUCTED EMISSION TEST


## 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage							
Frequency	Q.P.( dBuV)	Average( dBuV)						
150kHz~500kHz	66-56	56-46						
500kHz~5MHz	8 A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	46						
5MHz~30MHz	60	50						

## Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

## 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 51 of 62

### 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

## 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- The test data of the worst case condition(s) was reported on the Summary Data page.

### 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

**Note:** The BT function of EUT isn't work when charging.


The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





# **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**


FCC RADIATED EMISSION TEST SETUP



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true. It www.agc. gett.com.

Attestation of Global Compliance

AGC 8









The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



# APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.

Attestation of Global Compliance



# **BOTTOM VIEW OF EUT**



FRONT VIEW OF EUT



The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission.

Attestation of Global Compliance



# **BACK VIEW OF EUT**



LEFT VIEW OF EUT



The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc. att.com.

Attestation of Global Compliance



# RIGHT VIEW OF EUT




**LEFT**VIEW OF EUT (PORT)




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



# **OPEN VIEW OF EUT**



**INTERNAL VIEW OF EUT-1** 




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gatt.com.


Attestation of Global Compliance



# **INTERNAL VIEW OF EUT-2**



**INTERNAL VIEW OF EUT-3** 



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gatt.com.


Attestation of Global Compliance



**RIGHT**VIEW OF EUT (PORT)




**OPEN VIEW OF EUT** 




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



# **INTERNAL VIEW OF EUT-1**




**INTERNAL VIEW OF EUT-2** 




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a strong way.

Attestation of Global Compliance





# **INTERNAL VIEW OF EUT-3**



----END OF REPORT----

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (60°, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.

Attestation of Global Compliance