	TEST REPO	RT							
FCC ID	2AO9PV60070BT								
Test Report No:	TCT220406E053	$\left(\mathcal{C}^{\prime}\right)$							
Date of issue:	Apr. 15, 2022								
Testing laboratory:	HENZHEN TONGCE TESTING LAB								
Testing location/ address:	TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuh Street, Bao'an District Shenzhen, Guangdong, 518103, Pec Republic of China								
Applicant's name: :	Elita International Limited	$\langle \zeta \rangle$							
Address:	29F 2, Building 2, China Phoe Avenue, Futian District, Shen:		ennan						
Manufacturer's name :	Dongguan Huoge Technology	/ Co., Ltd							
Address:	Floor 8, Building A, Longzhixia Technology Park, No. 203, Xi Chang 'an Town, Dongguan,	ngyi Road, Wusha village							
Standard(s):	FCC CFR Title 47 Part 1.1307	7 (6)							
Product Name:	WIRELESS GROUND SPEAK	KER							
Trade Mark:	VIVITAR								
Model/Type reference:	V60070BT								
Rating(s):	Rechargeable Li-ion Battery	DC 3.7V							
Date of receipt of test item	Apr. 06, 2022		S)						
Date (s) of performance of test:	Apr. 06, 2022 - Apr. 15, 2022								
Tested by (+signature) :	Brews XU	Forens ADAGCE							
Check by (+signature) :	Beryl ZHAO	Boyl 10 TCT	TING						
Approved by (+signature):	Tomsin	Tomsin 45							

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Report No.: TCT220406E053

Table of Contents

1.	General Product Information		Q	3
	1.1. EUT description	<u> </u>	<u></u>	3
	1.2. Model(s) list			3
2.	General Information			4
	2.1. Test environment and mode			4
	2.2. Description of Support Units			
3.	Facilities and Accreditations		<u></u>	5
	3.1. Facilities			5
	3.2. Location			5
4.	Test Results and Measurement Data	<u>(</u> C)	<u>(</u> C)	6





1. General Product Information

1.1. EUT description

Product Name:	WIRELESS GROUND SPEAKER	$\left(\begin{array}{c} \\ \\ \end{array} \right)$
Model/Type reference:	V60070BT	
Sample Number:	TCT220406E012-0101	
Operation Frequency:	2402MHz~2480MHz	
Modulation Type:	For BT: GFSK, π/4-DQPSK, 8DPSK For BLE: GFSK	
Antenna Type:	PCB Antenna	
Antenna Gain:	-0.58dBi	
Rating(s):	Rechargeable Li-ion Battery DC 3.7V	

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.



Report No.: TCT220406E053

2. General Information

2.1. Test environment and mode

ltem		Normal condition							
Temperature		+25°C							
Voltage		DC 3.7V		$\langle \mathcal{C} \rangle$					
Humidity		56%							
Atmospheric Pressure:		1008 mbar			(C				
Test Mode:									
Engineering mode:	Keep the EU	Keep the EUT in continuous transmitting by select channel							

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/			1	1
Notor			(201)	021

Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Report No.: TCT220406E053



3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC Registration No.: 10668A-1
- SHENZHEN TONGCE TESTING LAB
- CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China TEL: +86-755-27673339



4. Test Results and Measurement Data

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison
- BDR+EDR:

ICT通测检测 TESTING CENTRE TECHNOLOGY

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR	
CH 78	2.480	-11.36	-12±1	-11	0.08	5	0.03	3.0	

BLE(1M):

-	DEE(II	•••								_
X	Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR	
	CH 39	2.480	-12.88	-13.5±1	-12.5	0.06	5	0.02	3.0	

BLE(2M):

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR	
CH 39	2.480	-12.84	-13.5±1	-12.5	0.06	5	0.02	3.0	

Result:

Base on the calculation value, No SAR measurement is required.

*****END OF REPORT*****