



RF EXPOSURE Test Report

Report No.: MTi220902008-02E3
Date of issue: 2022-11-29
Applicant: Cherub Technology Co., Ltd
Product: DIGITAL DRUM KIT
Model(s): DM-8, DM-8X, DM-8Xe, DM-8XS
FCC ID: 2AOAA-DM-8

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



Test Result Certification	
Applicant:	Cherub Technology Co., Ltd
Address:	Room507, Block 1, Nanhai E-Cool, No. 6 Xinghua Road, Shekou, Nanshan District, Shenzhen City, Guangdong Province, China, 518067
Manufacturer:	Cherub Technology Co., Ltd
Address:	Room507, Block 1, Nanhai E-Cool, No. 6 Xinghua Road, Shekou, Nanshan District, Shenzhen City, Guangdong Province, China, 518067
Factory:	Cherub Technology Co., Ltd (Zhuhai High-tech Park)
Address:	Room507, Block 1, Nanhai E-Cool, No. 6 Xinghua Road, Shekou, Nanshan District, Shenzhen City, Guangdong Province, China, 518067
Product description	
Product name:	DIGITAL DRUM KIT
Trademark:	NUX
Model name:	DM-8
Serial Model:	DM-8X, DM-8Xe, DM-8XS
Standards:	N/A
Test procedure:	KDB 447498 D01 v06
Date of Test	
Date of test:	2022-10-20~2022-11-29
Test result:	Pass

Test Engineer :

Cindy Qin

(Cindy Qin)

Reviewed By: :

Leon Chen

(Leon Chen)

Approved By: :

Tom Xue

(Tom Xue)

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BT/BLE:

Operation Frequency: 2402-2480MHz,

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna;

WIFI antenna gain: -2.49dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(-2.49/10)}=0.56$

BR+EDR:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	4.26	4±1	5	3.162	-2.49	0.56	0.0004	1
2441		4.1	4±1	5	3.162	-2.49	0.56	0.0004	1
2480		3.65	4±1	5	3.162	-2.49	0.56	0.0004	1
2402	π/4-DQPSK	4.87	4±1	5	3.162	-2.49	0.56	0.0004	1
2441		4.68	4±1	5	3.162	-2.49	0.56	0.0004	1
2480		4.26	4±1	5	3.162	-2.49	0.56	0.0004	1
2402	8DPSK	5.38	5±1	6	3.981	-2.49	0.56	0.0004	1
2441		5.21	5±1	6	3.981	-2.49	0.56	0.0004	1
2480		4.76	5±1	6	3.981	-2.49	0.56	0.0004	1

BLE:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	BLE-1M	4.4	4±1	5	3.162	-2.49	0.56	0.0004	1
2440		4.22	4±1	5	3.162	-2.49	0.56	0.0004	1
2480		3.71	4±1	5	3.162	-2.49	0.56	0.0004	1
2402	BLE-2M	4.22	4±1	5	3.162	-2.49	0.56	0.0004	1
2440		4.05	4±1	5	3.162	-2.49	0.56	0.0004	1
2480		3.55	4±1	5	3.162	-2.49	0.56	0.0004	1

Conclusion:

For the max result: 0.0004 ≤ 1.0 SAR, No SAR is required.

----END OF REPORT----