

# RF TEST REPORT



Report No.: 17071235-FCC-R

Supersede Report No.: N/A

Applicant	Beijing Babel Technology Co.,Ltd	
Product Name	Translator	
Model No.	PE01	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	November 05 to 24, 2017	
Issue Date	November 25, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17071235-FCC-R
Page	3 of 57

---

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	8
6.1 ANTENNA REQUIREMENT.....	8
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH.....	9
6.3 MAXIMUM OUTPUT POWER .....	16
6.4 POWER SPECTRAL DENSITY.....	20
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS .....	24
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	29
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND .....	35
ANNEX A. TEST INSTRUMENT.....	43
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	44
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	52
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	56
ANNEX E. DECLARATION OF SIMILARITY .....	57

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17071235-FCC-R	NONE	Original	November 25, 2017

## 2. Customer information

Applicant Name	Beijing Babel Technology Co.,Ltd
Applicant Add	Rm.409,Block C,Zhongguancun Zhizao Park,45 Chengfu Rd.,Haidian District,Beijing
Manufacturer	Beijing Babel Technology Co.,Ltd
Manufacturer Add	Rm.409,Block C,Zhongguancun Zhizao Park,45 Chengfu Rd.,Haidian District,Beijing

## 3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMС(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

#### **4. Equipment under Test (EUT) Information**

Description of EUT: Translator

Main Model: PE01

Serial Model: N/A

Date EUT received: November 09, 2017

Test Date(s): November 05 to 24, 2017

Equipment Category : DTS

Antenna Gain: 2dBi

Antenna Type: PIFA antenna

Type of Modulation: DSSS, OFDM

Max. Output Power: 802.11b: 7.98dBm  
802.11g: 4.69dBm  
802.11n(20M): 4.85dBm

RF Operating Frequency (ies): WIFI: 802.11b/g/n(20M): 2412-2462 MHz

Number of Channels: 11CH

Port: USB Port

Input Power: Battery:  
Spec: 3.7V, 700mAh

Trade Name : N/A

FCC ID: 2AOAB-PE01

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## **6. Measurements, Examination And Derived Results**

### **6.1 Antenna Requirement**

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 1 antenna:

A permanently attached PIFA antenna for WIFI, the gain is 2dBi for WIFI.

**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	November 15, 2017
Tested By :	Loren Luo

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A


#### Measurement result



Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.324	$\geq 0.5$
	Mid	2437	9.804	$\geq 0.5$
	High	2462	9.325	$\geq 0.5$
802.11g	Low	2412	15.09	$\geq 0.5$
	Mid	2437	15.10	$\geq 0.5$
	High	2462	15.11	$\geq 0.5$
802.11n (20M)	Low	2412	15.10	$\geq 0.5$
	Mid	2437	15.08	$\geq 0.5$
	High	2462	15.10	$\geq 0.5$

Test mode	CH	Freq (MHz)	20dB Bandwidth (MHz)
802.11b	Low	2412	16.19
	Mid	2437	16.22
	High	2462	16.21
802.11g	Low	2412	18.24
	Mid	2437	21.75
	High	2462	22.09
802.11n (20M)	Low	2412	19.39
	Mid	2437	19.84
	High	2462	22.22

## Test Plots


### 6dB Bandwidth measurement result






802.11n20 6dB Bandwidth - Low CH 2412


802.11n20 6dB Bandwidth - Mid CH 2437



802.11n20 6dB Bandwidth - High CH 2462


## 20 dB Bandwidth measurement result





802.11n20 20dB Bandwidth - Low CH 2412

802.11n20 20dB Bandwidth - Mid CH 2437




802.11n20 20dB Bandwidth - High CH 2462

### 6.3 Maximum Output Power

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	November 15, 2017
Tested By :	Loren Luo

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with $\geq$ 75 channels: $\leq$ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq$ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq$ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq$ 50 channels: $\leq$ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq$ 25 & $< 50$ channels: $\leq$ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: $\leq$ 1 Watt	<input checked="" type="checkbox"/>
Test Setup		 <b>Spectrum Analyzer</b> <b>EUT</b>	
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method</p> <p>Maximum output power measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set span to at least 1.5 times the OBW.</li> <li>- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.</li> <li>- c) Set VBW <math>\geq</math> 3 x RBW.</li> <li>- d) Number of points in sweep <math>\geq</math> 2 <math>\times</math> span / RBW. (This gives bin-to-bin spacing <math>\leq</math> RBW/2, so that narrowband signals are not lost between frequency bins.)</li> <li>- e) Sweep time = auto.</li> <li>- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.</li> <li>- g) If transmit duty cycle <math>&lt;</math> 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum</li> </ul>	

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle <math>\geq 98\%</math>, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run” .</p> <ul style="list-style-type: none"> <li>- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.</li> <li>- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’ s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A


#### Output Power measurement result

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	7.73	30	Pass
		Mid	2437	7.74	30	Pass
		High	2462	7.98	30	Pass
	802.11g	Low	2412	4.69	30	Pass
		Mid	2437	4.53	30	Pass
		High	2462	4.45	30	Pass
	802.11n (20M)	Low	2412	4.06	30	Pass
		Mid	2437	4.85	30	Pass
		High	2462	3.60	30	Pass

## Test Plots

### The Average Power





802.11n20 - AV Output power - Low CH 2412



## 802.11n20 - AV Output power - Mid CH 2437



802.11n20 - AV Output power - High CH 2462

## 6.4 Power Spectral Density

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	November 15, 2017
Tested By :	Loren Luo


Test Data  Yes  N/A  
 Test Plot  Yes (See below)  N/A


### Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-11.474	8	Pass
		Mid	2437	-11.236	8	Pass
		High	2462	-11.630	8	Pass
	802.11g	Low	2412	-17.230	8	Pass
		Mid	2437	-13.829	8	Pass
		High	2462	-16.077	8	Pass
	802.11n (20M)	Low	2412	-17.516	8	Pass
		Mid	2437	-14.029	8	Pass
		High	2462	-16.012	8	Pass

## Test Plots

### Power Spectral Density measurement result





PSD - Low CH 2412 - 802.11n20

PSD - Mid CH 2437 – 802.11n20




PSD - High CH 2472 - 802.11n20

## 6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1005mbar
Test date :	November 01, 2017
Tested By :	Evans He

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. A Turn Table is positioned on a Ground Plane. An EUT &amp; Support Units is placed on the turn table. A vertical Ant. Tower is connected to the turn table. A 3m horizontal line extends from the turn table to the Ant. Tower. A 1-4m Variable height is indicated for the Ant. Tower. A Test Receiver is connected to the turn table.</p>		
Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.</li> </ul>		


	<ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below:           <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

## Test Plots


### Band Edge measurement result



Note: Both Horizontal and vertical polarities were investigated



Note: Both Horizontal and vertical polarities were investigated




Note: Both Horizontal and vertical polarities were investigated

## 6.6 AC Power Line Conducted Emissions

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1005mbar
Test date :	November 01, 2017
Tested By :	Loren Luo

### Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dB<math>\mu</math>V)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB $\mu$ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB $\mu$ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 <p><b>Note:</b> 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>																
Procedure	<ol style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol>																

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail <input type="checkbox"/> N/A

Test Data     Yes       N/A

Test Plot     Yes (See below)       N/A


**Test Mode:** Transmitting Mode



Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	L1	0.2124	31.65	QP	10.02	41.67	63.11	-21.44
2	L1	0.2124	26.05	AVG	10.02	36.07	53.11	-17.04
3	L1	0.4659	43.58	QP	10.02	53.60	56.59	-2.99
4	L1	0.4659	33.79	AVG	10.02	43.81	46.59	-2.78
5	L1	0.8871	34.09	QP	10.03	44.12	56.00	-11.88
6	L1	0.8871	13.91	AVG	10.03	23.94	46.00	-22.06
7	L1	1.7490	32.36	QP	10.04	42.40	56.00	-13.60
8	L1	1.7490	8.95	AVG	10.04	18.99	46.00	-27.01
9	L1	3.3994	29.63	QP	10.05	39.68	56.00	-16.32
10	L1	3.3994	18.65	AVG	10.05	28.70	46.00	-17.30
11	L1	17.5236	29.48	QP	10.23	39.71	60.00	-20.29
12	L1	17.5236	19.32	AVG	10.23	29.55	50.00	-20.45

**Test Mode:** Transmitting Mode




**Test Data**


**Phase Neutral Plot at 120Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	N	0.1734	28.48	QP	10.02	38.50	64.80	-26.30
2	N	0.1734	18.07	AVG	10.02	28.09	54.80	-26.71
3	N	0.4698	36.04	QP	10.02	46.06	56.52	-10.46
4	N	0.4698	21.58	AVG	10.02	31.60	46.52	-14.92
5	N	0.7311	29.64	QP	10.02	39.66	56.00	-16.34
6	N	0.7311	18.49	AVG	10.02	28.51	46.00	-17.49
7	N	1.6398	24.38	QP	10.04	34.42	56.00	-21.58
8	N	1.6398	9.52	AVG	10.04	19.56	46.00	-26.44
9	N	3.3588	23.96	QP	10.05	34.01	56.00	-21.99
10	N	3.3588	12.15	AVG	10.05	22.20	46.00	-23.80
11	N	17.5704	25.33	QP	10.23	35.56	60.00	-24.44
12	N	17.5704	15.32	AVG	10.23	25.55	50.00	-24.45

**Test Mode:** Transmitting Mode



**Test Mode:** Transmitting Mode



### Test Data

#### Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	N	0.2514	36.70	QP	10.02	46.72	61.71	-14.99
2	N	0.2514	26.48	AVG	10.02	36.50	51.71	-15.21
3	N	0.4581	38.63	QP	10.02	48.65	56.73	-8.08
4	N	0.4581	21.14	AVG	10.02	31.16	46.73	-15.57
5	N	0.8793	36.45	QP	10.03	46.48	56.00	-9.52
6	N	0.8793	23.85	AVG	10.03	33.88	46.00	-12.12
7	N	1.9713	34.09	QP	10.04	44.13	56.00	-11.87
8	N	1.9713	19.58	AVG	10.04	29.62	46.00	-16.38
9	N	4.2675	30.08	QP	10.06	40.14	56.00	-15.86
10	N	4.2675	16.56	AVG	10.06	26.62	46.00	-19.38
11	N	19.9026	23.61	QP	10.26	33.87	60.00	-26.13
12	N	19.9026	14.52	AVG	10.26	24.78	50.00	-25.22

## 6.7 Radiated Spurious Emissions & Restricted Band

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1005mbar
Test date :	November 01, 2017
Tested By :	Evans He

### Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15. 247(d), RSS210	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (<math>\mu</math>V/m)</th> </tr> </thead> <tbody> <tr> <td>0.009~0.490</td> <td>2400/F(KHz)</td> </tr> <tr> <td>0.490~1.705</td> <td>24000/F(KHz)</td> </tr> <tr> <td>1.705~30.0</td> <td>30</td> </tr> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216~960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength ( $\mu$ V/m)	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216~960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength ( $\mu$ V/m)																		
0.009~0.490	2400/F(KHz)																		
0.490~1.705	24000/F(KHz)																		
1.705~30.0	30																		
30 – 88	100																		
88 – 216	150																		
216~960	200																		
Above 960	500																		
(A8.5)	b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>																
	c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	<input checked="" type="checkbox"/>																

<b>Test Setup</b>	 <p>The diagram illustrates the test setup. An EUT (Equipment Under Test) is placed on a turntable, which is positioned on a ground plane. A loop antenna is positioned 3 meters away from the EUT. An RF test receiver is connected to the loop antenna. The EUT is mounted on a support unit, and the height of the EUT is specified as 0.8m.</p>
<b>Procedure</b>	<ol style="list-style-type: none"> <li>1. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:             <ol style="list-style-type: none"> <li>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> <li>b. The EUT was then rotated to the direction that gave the maximum emission.</li> <li>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</li> </ol> </li> <li>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> </ol>

	<p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A

## Test Result:

Test Mode:	Normal Working Mode
------------	---------------------

Frequency range: 9KHz - 30MHz

Freq. (MHz)	Detection value	Factor (dB/m)	Reading (dBuV/m)	Result (dBuV/m)	Limit@3m (dBuV/m)	Margin (dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log \left( \frac{\text{specific distance}}{\text{test distance}} \right) \text{dB}$ ;

Limit line = specific limits(dBuv) + distance extrapolation factor.

**Test Mode:** Normal Working Mode

**30MHz -1GHz**



### Test Data

#### Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	99.5281	30.69	peak	10.29	22.32	1.11	19.77	43.50	-23.73	100	91
2	H	121.1231	39.82	peak	13.83	22.36	1.16	32.45	43.50	-11.05	100	321
3	H	136.9392	38.55	peak	12.80	22.40	1.25	30.20	43.50	-13.30	100	22
4	H	209.3129	32.99	peak	11.97	22.36	1.57	24.17	43.50	-19.33	100	251
5	H	428.0193	27.74	peak	16.26	21.95	2.08	24.13	46.00	-21.87	100	151
6	H	790.6188	28.71	peak	21.29	21.17	2.94	31.77	46.00	-14.23	100	24

## 30MHz -1GHz



### Test Data

#### Horizontal Polarity Plot @3m

N o.	P/ L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m )		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	V	32.2925	30.72	peak	19.63	22.27	0.68	28.76	40.00	-11.24	100	62
2	V	51.6616	40.82	peak	8.22	22.38	0.79	27.45	40.00	-12.55	100	317
3	V	64.6594	43.89	peak	7.53	22.40	0.87	29.89	40.00	-10.11	100	280
4	V	121.1231	41.82	peak	13.83	22.36	1.16	34.45	43.50	-9.05	100	86
5	V	135.9822	43.71	peak	12.86	22.40	1.24	35.41	43.50	-8.09	100	290
6	V	208.5803	35.62	peak	11.98	22.36	1.57	26.81	43.50	-16.69	100	21

### Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

#### Low Channel (2412 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4824	50.71	AV	V	33.39	7.22	48.46	42.86	54	-11.14
4824	48.22	AV	H	33.39	7.22	48.46	40.37	54	-13.63
4824	68.73	PK	V	33.39	7.22	48.46	60.88	74	-13.12
4824	63.99	PK	H	33.39	7.22	48.46	56.14	74	-17.86
12904	18.24	AV	V	45.12	11.57	32.11	42.82	54	-11.18
12904	17.64	AV	H	45.12	11.57	32.11	42.22	54	-11.78
12904	38.46	PK	V	45.12	11.57	32.11	63.04	74	-10.96
12904	37.28	PK	H	45.12	11.57	32.11	61.86	74	-12.14

#### Middle Channel (2437 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4874	50.52	AV	V	33.62	7.53	48.36	43.31	54	-10.69
4874	48.81	AV	H	33.62	7.53	48.36	41.6	54	-12.4
4874	68.44	PK	V	33.62	7.53	48.36	61.23	74	-12.77
4874	63.14	PK	H	33.62	7.53	48.36	55.93	74	-18.07
8093	18.14	AV	V	45.17	11.63	32.18	42.76	54	-11.24
8093	19.18	AV	H	45.17	11.63	32.18	43.8	54	-10.2
8093	39.46	PK	V	45.17	11.63	32.18	64.08	74	-9.92
8093	38.57	PK	H	45.17	11.63	32.18	63.19	74	-10.81

**High Channel (2462 MHz) (b mode worst case)**

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4924	48.58	AV	V	33.74	7.78	48.34	41.76	54	-12.24
4924	47.32	AV	H	33.74	7.78	48.34	40.5	54	-13.5
4924	67.38	PK	V	33.74	7.78	48.34	60.56	74	-13.44
4924	64.69	PK	H	33.74	7.78	48.34	57.87	74	-16.13
17871	18.33	AV	V	45.19	11.61	32.24	42.89	54	-11.11
17904	19.51	AV	H	45.19	11.61	32.24	44.07	54	-9.93
17904	38.98	PK	V	45.19	11.61	32.24	63.54	74	-10.46
17904	40.58	PK	H	45.19	11.61	32.24	65.14	74	-8.86

**Note:**

- 1, The testing has been conformed to  $10 \times 2462\text{MHz} = 24,620\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
- 4, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
ISN	ISN T800	34373	09/23/2017	09/22/2018	<input type="checkbox"/>
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Horn Antenna	BBHA9170	3145226D1	09/27/2017	09/26/2018	<input checked="" type="checkbox"/>
Active Antenna (9kHz-30MHz)	AL-130	121031	10/12/2017	10/11/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>

## Annex B. EUT and Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo

Whole Package View




EUT - Front View



EUT - Rear View




EUT - Top View




EUT - Bottom View



EUT - Left View



EUT - Right View



### Annex B.ii. Photograph: EUT Internal Photo


Cover Off - Top View 1




Cover Off - Top View 2



Mainboard - Front View




Mainboard - Rear View



## WIFI - Antenna View




**Annex B.iii. Photograph: Test Setup Photo**




## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .



Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	N/A
DCA	Adaptor	E2164A	N/A

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

Test Report No.	17071235-FCC-R
Page	56 of 57

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

## Annex E. DECLARATION OF SIMILARITY

N/A