

RF Exposure Requirements

Product Description: Mini Boom

Model No.: UBTSPKMB, UBTSPKMBBK-TE, UBTSPKMBGD-TE, UBTSPKMBSL-TE

FCC ID: 2AOAF-UBTSPKMB

According to the KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Bluetooth(EDR)

Conducted Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	Result	Limit
-3.03	0.50	5	2.442	0.16	3

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$: $0.50/5 \cdot \sqrt{2.442} = 0.16$

The exclusion thresholds is less than 3, therefore, the RF exposure evaluation is not required.