



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20181000069E-02

Applicant: Shenzhen HCY Electrics and Technology Co., Ltd

Address of Applicant: The 1st building , No 2 Gangbei Road, Bogang Village Shajing Town, Baoan, Shenzhen, China

Manufacturer: Shenzhen HCY Electrics and Technology Co., Ltd

Address of Manufacturer: The 1st building , No 2 Gangbei Road, Bogang Village Shajing Town, Baoan, Shenzhen, China

Factory: Shenzhen HCY Electrics and Technology Co., Ltd

Address of Factory: The 1st building , No 2 Gangbei Road, Bogang Village Shajing Town, Baoan, Shenzhen, China

Equipment Under Test (EUT):

Product: Remote control

Model No.: HCY-63A

Brand Name: N/A

FCC ID: 2AOBUHCY-63A

Standards: 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-10-25 to 2018-11-10

Date of Issue: 2018-11-10

Test Result : PASS*

Tested By:

Tiny You

(Tiny You)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

James

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20181000069E-02	Rev.01	Initial report	2018-11-10

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits.....	5
4.1.3 EUT RF Exposure	5

3 General Information

3.1 Client Information

Applicant:	Shenzhen HCY Electrics and Technology Co., Ltd
Address of Applicant:	The 1st building , No 2 Gangbei Road, Bogang Village Shajing Town, Baoan, Shenzhen, China
Manufacturer:	Shenzhen HCY Electrics and Technology Co., Ltd
Address of Manufacturer:	The 1st building , No 2 Gangbei Road, Bogang Village Shajing Town, Baoan, Shenzhen, China
Factory:	Shenzhen HCY Electrics and Technology Co., Ltd
Address of Factory:	The 1st building , No 2 Gangbei Road, Bogang Village Shajing Town, Baoan, Shenzhen, China

3.2 General Description of EUT

Name:	Remote control
Model No.:	HCY-63A
Trade Mark :	N/A
Hardware Version:	V1.0
Software Version:	V11
Frequency Range:	2430MHz
Modulation Type:	GFSK
Number of Channels:	1 (declared by the client)
Sample Type:	Portable production
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	Battery, DC3.7V, charge by USB

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, $-10^{((\text{dB}\mu\text{V/m})/20)/10^6}$,

d = measurement distance in meters (m)---3m,

So $\text{pt} = (\text{E} \times \text{d})^2 / 30 / \text{gt}$

The worst case (refer to report CQASZ20181000069E-01) is below:

For 2.4G wireless:

Field strength = 97.5dB μ V/m @3m

Ant. gain 0dBi; so Ant numeric gain=1

So $\text{pt} = \{[10^{(97.5/20)/10^6} \times 3]^2 / 30 / 1\} \times 1000 \text{mW} = 1.687 \text{mW}$

So $(1.746 \text{mW} / 5 \text{mm}) \times \sqrt{2.430 \text{GHz}} = 0.526$

$0.526 < 3.0$ for 1-g SAR

So the SAR report is not required.