



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20200800807E-02
Applicant: Shenzhen HCY Electrics and Technology Co.,Ltd
Address of Applicant: 5th Floor, Block 8, Shangxiawei Industrial Park, Shasan Road, Shajing, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Intelligent remote control
Model No.: CHY-Q40
Brand Name: N/A
FCC ID: 2AOBUHCY-Q40
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2020-08-06
Date of Test: 2020-08-06 to 2020-08-18
Date of Issue: 2020-08-19
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Tiny You

(Tiny You)

Reviewed By:

Sheek Luo

(Sheek Luo)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200800807E-02	Rev.01	Initial report	2020-08-19

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 RF EXPOSURE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.2 EUT RF EXPOSURE EVALUATION	6

3 General Information

3.1 Client Information

Applicant:	Shenzhen HCY Electrics and Technology Co.,Ltd
Address of Applicant:	5th Floor, Block 8, Shangxiawei Industrial Park, Shasan Road, Shajing, Shenzhen, China
Manufacturer:	Shenzhen HCY Electrics and Technology Co.,Ltd
Address of Manufacturer:	5th Floor, Block 8, Shangxiawei Industrial Park, Shasan Road, Shajing, Shenzhen, China
Factory:	Shenzhen HCY Electrics and Technology Co.,Ltd
Address of Factory:	5th Floor, Block 8, Shangxiawei Industrial Park, Shasan Road, Shajing, Shenzhen, China

3.2 General Description of EUT

Product Name:	Intelligent remote control
Model No.:	CHY-Q40
Trade Mark:	N/A
Hardware Version:	HCYQ40-TX001-V12
Software Version:	hcy_q40_rc1163__18431751_v1.0
Frequency Range:	2404MHz ~ 2480MHz
Modulation Type:	GFSK
Number of Channels:	65 (declared by the client)
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	-3.0dBi
Power Supply:	lithium battery:DC3.7V, 550mAh, Charge by DC5.0V

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.2 EUT RF Exposure Evaluation

1) For 2.4G

$$e_{irp} = p_t \times g_t = (E \times d)^2 / 30$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, $10^{((dB\mu V/m)/20)/10^6}$,

d = measurement distance in meters (m)---3m,

$$\text{So } p_t = (E \times d)^2 / 30 / g_t$$

The worst case (refer to report CQASZ20200700685E-01) is below:

Antenna polarization: Horizontal		
Frequency (MHz)	Level (dBuV/m)	Polarization
2440	83.41	Peak
2440	77.67	Average

For 2440MHz wireless:

Field strength = 83.41dBuV/m @3m

Ant. gain -3.0dBi; so Ant numeric gain=0.5

$$\text{So } p_t = \{ [10^{(83.41/20)} / 10^6 \times 3]^2 / 30 / 0.5 \} \times 1000 \text{mW} = 0.131 \text{mW}$$

$$\text{So } (0.131 \text{mW} / 5 \text{mm}) \times \sqrt{2.440 \text{GHz}} = 0.041,$$

0.041 < 3.0 for 1-g SAR

So the SAR report is not required.