

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : W17NR-D089

AGR No. : A17OA-257

Applicant : Spacosa Corporation

Address : 11-41, Simin-daero 327beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, South Korea

Manufacturer : Spacosa Corporation

Address : 11-41, Simin-daero 327beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, South Korea

Type of Equipment : Gper

FCC ID. : 2AODFGPER-L200

Model Name : Gper-L200

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 6 pages (including this page)

Date of Incoming : October 26, 2017

Date of issue : November 30, 2017


SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:



Jae-Ho Lee / Chief Engineer
ONETECH Corp.

Approved by:



Keun-Young, Choi / Vice President
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION.....	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6
4.1 EUT DESCRIPTION.....	6
4.2 TEST RESULT	6

REVISION HISTORY

Issued Report No.	Issued Date	Revisions	Effect Section
W17NR-D089	November 30, 2017	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : Spacosa Corporation

Address : 11-41, Simin-daero 327beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, South Korea

Contact Person : Byungjoo Jo

Telephone No. : +82-70-7016-2380

FCC ID : 2AODFGPER-L200

Model Name : Gper-L200

Brand Name : N/A

Serial Number : N/A

Date : November 30, 2017

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Gper
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 DTS Meas Guidance
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The Spacosa Corporation, Model Gper-L200 (referred to as the EUT in this report) is a Gper. Product specification information described herein was obtained from product data sheet or user's manual.

Device Type	Gper
Operating Frequency	LE: 2 402 MHz ~ 2 480 MHz LoRa: 903.0 ~ 914.2 MHz (500 kHz)
RF Output Power	LE: -2.31 dBm LoRa: 11.29 dBm
Number of Channel	LE: 40 Channels LoRa: 8 Channels
Modulation Type	LE: GFSK LoRa: CSS
Antenna Type	LE: Chip Antenna LoRa: Quarter wave-length Monopole Helical Antenna
Antenna Gain	LE: 2.51 dBi LoRa: 1.37 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	16 MHz
Rated Supply Voltage	DC 3.7 V

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 EUT Description

Kind of EUT	Gper
Operating Frequency Band	☐ Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz ☐ WLAN: 2 412 MHz ~ 2 462 MHz ☐ WLAN: 5 180 MHz ~ 5 240 MHz ☐ WLAN: 5 745 MHz ~ 5 825 MHz ☐ Bluetooth: 2 402 MHz ~ 2 480 MHz ☐ Bluetooth BLE: 2 402 MHz ~ 2 480 MHz ☒ 900 MHz : 902 MHz ~ 928 MHz
Device Category	☐ Portable (< 20 cm separation) ☐ Mobile (> 20 cm separation) ☒ Others
Exposure Evaluation Applied	☐ MPE ☐ SAR ☒ N/A
Antenna Gain	1.37 dBi
Max. RF Output Power	11.29 dBm

4.2 Test Result


According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

$$[(\text{Max. Power of channel, including tune-up tolerance, mW})/(\text{Mim. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3$$

$$= (13.46/5) \times \sqrt{0.903} = 2.56$$

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and excluded SAR Test.

Operating Freq. Band (MHz)	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
902 ~ 928	903	10.79 ± 0.5	11.29	13.46	5	2.56


Tested by: Ha-Ram, Lee / Assistant Manager