

# TEST REPORT

**Applicant:** Zhejiang Lierda Internet of Things Technology Co., Ltd.  
**Address:** Room 1402, Building 1, No. 1326, Wenyi West Road, Cangqian street, Yuhang District, Hangzhou, Zhejiang Prov.  
**Equipment Type:** UB37 Series Wi-Fi6 Modules  
**Model Name:** L-NLEUB37-G5NN4 (refer to section 2.3)  
**Brand Name:** Lierda  
**FCC ID:** 2AOFDL-NLEUB37  
**Test Standard:** 47 CFR Part 2.1091  
KDB 447498 D04 v01  
**Sample Arrival Date:** Sep. 18, 2024  
**Test Date:** Sep. 19, 2024 - Oct. 12, 2024  
**Date of Issue:** Nov. 12, 2024


**ISSUED BY:**

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Xu Rui



**Checked by:** Liyao Zong



**Approved by:** Tolan Tu  
(Testing Director)



Revision History		
Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Nov. 04, 2024</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Nov. 12, 2024</u>	<u>Added a note in section 5.3 that simultaneous transmission is not supported</u>

## TABLE OF CONTENTS

- 1 GENERAL INFORMATION..... 3
  - 1.1 Test Laboratory .....3
  - 1.2 Test Location.....3
- 2 PRODUCT INFORMATION ..... 4
  - 2.1 Applicant Information ..... 4
  - 2.2 Manufacturer Information..... 4
  - 2.3 General Description for Equipment under Test (EUT)..... 4
  - 2.4 Technical Information .....5
- 3 SUMMARY OF TEST RESULT ..... 6
  - 3.1 Test Standards ..... 6
  - 3.2 Limit Standards..... 6
- 4 DEVICE CATEGORY AND LEVELS LIMITS ..... 7
- 5 ASSESSMENT RESULT ..... 9
  - 5.1 Output Power .....9
  - 5.2 Tune-up power ..... 9
  - 5.3 RF Exposure Evaluation Result ..... 9
  - 5.4 Conclusion..... 9

# 1 GENERAL INFORMATION

## 1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

## 1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input checked="" type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	Zhejiang Lierda Internet of Things Technology Co., Ltd.
Address	Room 1402, Building 1, No. 1326, Wenyi West Road, Cangqian street, Yuhang District, Hangzhou, Zhejiang Prov.

### 2.2 Manufacturer Information

Manufacturer	Zhejiang Lierda Internet of Things Technology Co., Ltd.
Address	Room 1402, Building 1, No. 1326, Wenyi West Road, Cangqian street, Yuhang District, Hangzhou, Zhejiang Prov.

### 2.3 General Description for Equipment under Test (EUT)

EUT Name	UB37 Series Wi-Fi6 Modules
Model Name Under Test	L-NLEUB37-G5NN4
Series Model Name	L-NLEUB37-G5NN4-U, L-NLEUB37-G5NN4-P, L-NLEUB37-G5NN4-L, L-NLEUB37-G5NN4-E
Description of Model name differentiation	<p>All models have the same hardware and software, only differ in the following content:</p> <p>L-NLEUB37-G5NN4 without IPEX terminal, no TVS electrostatic protection;</p> <p>L-NLEUB37-G5NN4-P with IPEX terminal, no TVS electrostatic protection;</p> <p>L-NLEUB37-G5NN4-U with IPEX terminal, no TVS electrostatic protection;</p> <p>L-NLEUB37-G5NN4-L with IPEX terminal, no TVS electrostatic protection, LDO power supply;</p> <p>L-NLEUB37-G5NN 4-E without IPEX terminal, no TVS electrostatic protection.</p> <p>(this information provided by the applicant)</p>
Hardware Version	01
Software Version	01
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

## 2.4 Technical Information

Network and Wireless connectivity	Bluetooth BLE WIFI 802.11b, 802.11g, 802.11n and 802.11ax
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	Bluetooth, WIFI	
Frequency Range	Bluetooth	2400 ~ 2483.5 MHz
	802.11b/g/n(HT2040)/ax(HE20)	2412 MHz ~ 2462 MHz
Antenna Type	Bluetooth	Dipole Antenna
	WIFI	Dipole Antenna
Exposure Category	General Population/Uncontrolled Exposure	
Product Type	Mobile Device	

### 3 SUMMARY OF TEST RESULT

#### 3.1 Test Standards

No.	Identity	Document Title
1	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

#### 3.2 Limit Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices

## 4 DEVICE CATEGORY AND LEVELS LIMITS

### Mobile Devices:

CFR Title 47 §2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

### FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad \text{(B.2)}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20\text{cm}}$  is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169



## 5 ASSESSMENT RESULT

### 5.1 Output Power

Bluetooth	
Mode	BLE
Conducted Power (dBm)	8.23
Antenna Gain (dBi)	2.46
EIRP (dBm)	10.69
Note: This table listed the worst case power value, please refer to BL-SZ2490729-601 report for more details.	

Mode	2.4G WIFI
Conducted Power (dBm)	19.02
Antenna Gain (dBi)	2.46
EIRP (dBm)	21.48
Note: This table listed the worst case power value, please refer to BL-SZ2490729-602 report for more details.	

### 5.2 Tune-up power

Mode	Conducted Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)
Bluetooth BLE	[7.00,9.00]	[10.00,12.00]	[7.85,9.85]
2.4G WIFI	[18.00,20.00]	[20.00,22.00]	[17.85,19.85]
Note1: ERP= EIRP -2.15dB.			
Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.			

### 5.3 RF Exposure Evaluation Result

Evolution mode	Frequency(MHz)	Maximum power (dBm)	Maximum power (mw)	Distance (mm)	Threshold Power (mW)	Verdict
Bluetooth BLE	2480	9.85	9.66	200	3060.00	Pass
2.4G WIFI	2462	20.00	100.00	200	3060.00	Pass

Note: WIFI 2.4GHz and Bluetooth will not be transmitting at same time, so simultaneous transmission evaluation is not required in this report.

### 5.4 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

## Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--