

FCC

RF

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
LoRaWAN Gateway

ISSUED TO
Zhejiang Lierda Internet of Things Technology Co.,Ltd

Lierda IoT park, No.1326 Wenyi Xi Road, Hangzhou, Zhejiang Prov.,
China



Tested by: Heng Aiping
Heng Aiping
(Engineer)

Date: Sep. 18, 2019

Approved by: Wei Yanquan
Wei Yanquan
(Chief Engineer)

Date: Sep. 18, 2019

Report No.: BL-SZ1980061-601

EUT Name: LoRaWAN Gateway

Model Name: LSD4WN-2332XGW1

Brand Name: lierda

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: 2AOFDLSD4WN2332XGW1

Test Conclusion: Pass

Test Date: Aug. 08, 2019 ~ Aug. 29, 2019

Date of Issue: Sep. 18, 2019

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Sep. 06, 2019</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Sep. 18, 2019</u>	<u>Correct antenna information on page</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
2	PRODUCT INFORMATION	7
2.1	Applicant Information	7
2.2	Manufacturer Information	7
2.3	Factory Information	7
2.4	General Description for Equipment under Test (EUT)	7
2.5	Technical Information	8
2.6	Additional Instructions	10
3	SUMMARY OF TEST RESULTS	11
3.1	Test Standards	11
3.2	Verdict	12
4	GENERAL TEST CONFIGURATIONS	13
4.1	Test Environments	13
4.2	Test Equipment List	13
4.3	Measurement Uncertainty	15
4.4	Description of Test Setup	15
4.4.1	For Antenna Port Test	15
4.4.2	For AC Power Supply Port Test	16
4.4.3	For Radiated Test (Below 30 MHz)	16
4.4.4	For Radiated Test (30 MHz-1 GHz)	17
4.4.5	For Radiated Test (Above 1 GHz)	17
4.5	Measurement Results Explanation Example	18

4.5.1	For conducted test items:	18
5	TEST ITEMS.....	19
5.1	Antenna Requirements.....	19
5.1.1	Relevant Standards.....	19
5.1.2	Antenna Anti-Replacement Construction	19
5.1.3	Antenna Gain	19
5.2	Number of Hopping Frequencies	20
5.2.1	Limit.....	20
5.2.2	Test Procedure.....	20
5.2.3	Test Result	20
5.3	Peak Output Power and E.I.R.P.....	21
5.3.1	Test Limit.....	21
5.3.2	Test Setup.....	21
5.3.3	Test Procedure.....	21
5.3.4	Test Result	21
5.4	Occupied Bandwidth	22
5.4.1	Limit.....	22
5.4.2	Test Setup.....	22
5.4.3	Test Procedure.....	22
5.4.4	Test Result	22
5.5	Carrier Frequency Separation	23
5.5.1	Limit.....	23
5.5.2	Test Setup.....	23
5.5.3	Test Procedure.....	23
5.5.4	Test Result	23
5.6	Time of Occupancy (Dwell time)	24
5.6.1	Limit.....	24
5.6.2	Test Setup.....	24
5.6.3	Test Procedure.....	24
5.6.4	Test Result	24
5.7	Conducted Spurious Emission & Authorized-band band-edge	25
5.7.1	Limit.....	25

5.7.2	Test Setup	25
5.7.3	Test Procedure	25
5.7.4	Test Result	25
5.8	Conducted Emission	26
5.8.1	Limit.....	26
5.8.2	Test Setup	26
5.8.3	Test Procedure	26
5.8.4	Test Result	26
5.9	Radiated Spurious Emission	27
5.9.1	Limit.....	27
5.9.2	Test Setup	27
5.9.3	Test Procedure	27
5.9.4	Test Result	28
5.10	Band Edge (Restricted-band band-edge).....	29
5.10.1	Limit.....	29
5.10.2	Test Setup	29
5.10.3	Test Procedure	29
5.10.4	Test Result	29
ANNEX A	TEST RESULT	30
A.1	Number of Hopping Frequency	30
A.2	Peak Output Power	31
A.3	20 dB and 99% bandwidth	32
A.4	Hopping Frequency Separation.....	34
A.5	Average Time of Occupancy	35
A.6	Conducted Spurious Emissions & Authorized-band band-edge	36
A.7	Conducted Emissions.....	40
A.8	Radiated Spurious Emission	42
A.9	Band Edge (Restricted-band band-edge).....	48
ANNEX B	TEST SETUP PHOTOS	49
ANNEX C	EUT EXTERNAL PHOTOS	49
ANNEX D	EUT INTERNAL PHOTOS	49

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.</p> <p>The laboratory is a testing organization accredited by American Association for Laboratory Accreditation (A2LA) according to ISO/IEC 17025. The accreditation certificate is 4344.01.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v2.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without

prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Zhejiang Lierda Internet of Things Technology Co.,Ltd
Address	Lierda IoT park, No.1326 Wenyi Xi Road, Hangzhou, Zhejiang Prov., China

2.2 Manufacturer Information

Manufacturer	Zhejiang Lierda Internet of Things Technology Co.,Ltd
Address	Lierda IoT park, No.1326 Wenyi Xi Road, Hangzhou, Zhejiang Prov., China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Type	LoRaWAN Gateway
Model Name Under Test	LSD4WN-2332XGW1
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	02
Software Version	02
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	Lora, GPS, GLONASS
-----------------------------------	--------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	Frequency hopping system
Modulation Type	Lora
Product Type	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Frequency Range	The frequency range used is 902 MHz to 928 MHz.
Number of channel	64
Tested Channel	0 (902.3 MHz), 32 (908.7 MHz), 63 (914.9 MHz)
Antenna Type	Lora Antenna
Antenna Gain	2 dBi (In test items related to antenna gain, the final results reflect this figure.)
Antenna System(MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	902.3	20	906.3	40	910.3	60	914.3
1	902.5	21	906.5	41	910.5	61	914.5
2	902.7	22	906.7	42	910.7	62	914.7
3	902.9	23	906.9	43	910.9	63	914.9
4	903.1	24	907.1	44	911.1	-	-
5	903.3	25	907.3	45	911.3	-	-
6	903.5	26	907.5	46	911.5	-	-
7	903.7	27	907.7	47	911.7	-	-
8	903.9	28	907.9	48	911.9	-	-
9	904.1	29	908.1	49	912.1	-	-
10	904.3	30	908.3	50	912.3	-	-
11	904.5	31	908.5	51	912.5	-	-
12	904.7	32	908.7	52	912.7	-	-
13	904.9	33	908.9	53	912.9	-	-
14	905.1	34	909.1	54	913.1	-	-
15	905.3	35	909.3	55	913.3	-	-
16	905.5	36	909.5	56	913.5	-	-
17	905.7	37	909.7	57	913.7	-	-
18	905.9	38	909.9	58	913.9	-	-
19	906.1	39	910.1	59	914.1	-	-

2.6 Additional Instructions


EUT Software Settings:

Mode	<input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	Secure CRT		
Support Units (Software installation media)	Description	Manufacturer	Model
		Notebook	Lenovo
Mode	Channel		Soft Set
Lora	ALL		20

Run Software



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	FCC PUBLIC NOTICE DA 00-705 (Mar. 30, 2000)	Filling and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES

3.2 Verdict

No.	Description	FCC Part No.	Modulation Technology	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	N/A	--	Pass	Note ¹
2	Number of Hopping Frequencies	15.247(a)	Frequency hopping system	Hopping Mode	ANNEX A.1	Pass	
3	Peak Output Power	15.247(b)	Frequency hopping system,	Low/Middle/High	ANNEX A.2	Pass	
4	Occupied Bandwidth	15.247(a)	Frequency hopping system,	Low/Middle/High	ANNEX A.3	Pass	
5	Carrier Frequency Separation	15.247(a)	Frequency hopping system,	Hopping Mode	ANNEX A.4	Pass	
6	Time of Occupancy (Dwell time)	15.247(a)	Frequency hopping system,	Hopping Mode	ANNEX A.5	Pass	
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Frequency hopping system,	Low/Middle/High, Hopping Mode	ANNEX A.6	Pass	
8	Conducted Emission	15.207	Frequency hopping system,	Low/Middle/High	ANNEX A.7	Pass	
9	Radiated Spurious Emission	15.209 15.247(d)	Frequency hopping system,	Low/Middle/High, Hopping Mode	ANNEX A.8	Pass	
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Frequency hopping system,	Low/Middle/High, Hopping Mode	ANNEX A.9	Pass	
Note ¹ : Please refer to section 5.1							

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	220 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2019.06.13	2020.06.12
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	260592	2019.06.13	2020.06.12
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2019.08.23	2020.08.22
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2019.06.13	2020.06.12
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2018.11.08	2019.11.07
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2019.06.13	2020.06.12
LISN	SCHWARZBECK	NSLK 8127	8127-687	2019.06.13	2020.06.12
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2019.06.13	2020.06.12
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2019.06.13	2020.06.12
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2019.06.13	2020.06.12
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2019.07.02	2020.07.01
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.11.07	2019.11.08
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2018.08.22	2020.08.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2019.07.11	2020.07.10
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2019.06.21	2020.06.20
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	N/A	2020.01.06
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2019.02.21	2021.02.20
Anechoic Chamber	EMC TECHNOLOGY LTD	21.1m*11.6m*7.35m	N/A	2018.07.19	2020.07.18
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2019.06.12	2020.06.11
Power Amplifier	OPHIR RF	5225F	1037	2019.02.17	2020.02.16

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Power Amplifier	OPHIR RF	5273F	1016	2019.02.17	2020.02.16
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Feld Strength Meter	Narda	EP601	511WX51129	2019.05.22	2020.05.21
Mouth Simulator	B&K	4227	2423931	2018.11.16	2019.11.15
Sound Calibrator	B&K	4231	2430337	2018.11.16	2019.11.15
Sound Level Meter	B&K	NL-20	00844023	2018.11.16	2019.11.15
Ear Simulator	B&K	4185	2409449	2018.11.16	2019.11.15
Ear Simulator	B&K	4195	2418189	2018.11.16	2019.11.15
Audio analyzer	B&K	UPL 16	100129	2018.11.16	2019.11.15

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
An antenna uses a unique coupling to the intentional radiator	Unique coupling between antenna and product

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Number of Hopping Frequencies

5.2.1 Limit

FCC §15.247(a) (1) (i); RSS-247, 5.1 (4)

For frequency hopping systems operating in the 902-928 MHz band: the system shall use at least 50 hopping frequencies.

Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.2 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.2.3 Test Result

Please refer to ANNEX A.1.

5.3 Peak Output Power and E.I.R.P

5.3.1 Test Limit

FCC § 15.247(b)(1)

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

RSS-247, 5.4 (2)

For FHSs operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Occupied Bandwidth

5.4.1 Limit

FCC §15.247(a)(1)(i); RSS-247, 5.1 (1)

Measurement of the 20dB bandwidth of the modulated signal. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Carrier Frequency Separation

5.5.1 Limit

FCC §15.247(a)(1); RSS-247, 5.1 (2)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) \geq 1% of the span

Video (or Average) Bandwidth (VBW) \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Time of Occupancy (Dwell time)

5.6.1 Limit

FCC §15.247(a)(1)(i); RSS-247, 5.1 (4)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.6.4 Test Result

Please refer to ANNEX A.5

5.7 Conducted Spurious Emission & Authorized-band band-edge

5.7.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.7.4 Test Result

Please refer to ANNEX A.6 and A.7

5.8 Conducted Emission

5.8.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.8.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Radiated Spurious Emission

5.9.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	902/F(kHz)	300
0.490 - 1.705	9020/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dB $\mu\text{V}/\text{m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V}/\text{m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dB $\mu\text{V}/\text{m}@3\text{m}$ (AV) and 74dB $\mu\text{V}/\text{m}@3\text{m}$ (PK).

5.9.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.9.4 Test Result

Please refer to ANNEX A.8.

5.10 Band Edge (Restricted-band band-edge)

5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
LoRa	902-928	64	50	Pass

Test plots

LoRa



Date: 25.AUG.2019 16:15:55


A.2 Peak Output Power

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	LoRa		dBm	mW	
	dBm	mW			
Low	21.47	140.28	30	1000	Pass
Middle	21.58	143.88			Pass
High	21.28	134.28			Pass


Test plots

LOW CHANNEL




Date: 25 AUG 2019 15:27:19

MIDDLE CHANNEL



Date: 25 AUG 2019 15:49:52

HIGH CHANNEL



Date: 25 AUG 2019 15:57:58


A.3 20 dB and 99% bandwidth

Test Data

LoRa			
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Verdict
Low	0.169556	0.126032	Pass
Middle	0.165222	0.126407	Pass
High	0.168152	0.125656	Pass


Test plots (20 dB Bandwidth)

LOW CHANNEL




Date: 25.AUG.2019 15:43:40

MIDDLE CHANNEL



Date: 25.AUG.2019 15:50:34

HIGH CHANNEL



Date: 25.AUG.2019 15:58:27

Test plots (99% Bandwidth)

LOW CHANNEL



Date: 25 AUG 2019 15:44:55

MIDDLE CHANNEL



Date: 25 AUG 2019 15:51:20

HIGH CHANNEL



Date: 25 AUG 2019 15:59:34


A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	Max 20 dB Bandwidth (MHz)	Verdict
LoRa	200.7	0.169556	Pass

Test Plots

LoRa




Date: 25.AUG.2019 16:23:35

A.5 Average Time of Occupancy

Test Data

Total of Dwell(ms)	Limit (sec)	Verdict
345.100	0.4	Pass

LoRa



Date: 25.AUG.2019 16:38:58

A.6 Conducted Spurious Emissions & Authorized-band band-edge


Test Data

LoRa				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-15.91	21.12	1.12	Pass
Middle	-18.87	21.57	1.57	Pass
High	-18.41	21.24	1.24	Pass

LoRa				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Hopping	-19.56	21.46	1.46	Pass


Test Plots

LOW CHANNEL, CARRIER LEVEL




Date: 25 AUG 2019 15:45:13

LOW CHANNEL, Band Edge




Date: 25 AUG 2019 15:47:59

LOW CHANNEL, SPURIOUS 30 MHz ~ 1 GHz




Date: 25 AUG 2019 15:46:41

LOW CHANNEL, SPURIOUS 1 GHz ~ 10 GHz




Date: 25 AUG 2019 15:47:17

MIDDLE CHANNEL, CARRIER LEVEL




Date: 25 AUG 2019 15:51:36

MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 1 GHz




Date: 25 AUG 2019 15:52:42

MIDDLE CHANNEL , SPURIOUS 1 GHz ~ 10 GHz




Date: 25 AUG 2019 15:53:40

HIGH CHANNEL, CARRIER LEVEL




Date: 25 AUG 2019 16:00:10

HIGH CHANNEL , BAND EDGE




Date: 25 AUG 2019 16:02:53

HIGH CHANNEL , SPURIOUS 30 MHz ~ 1 GHz




Date: 25 AUG 2019 16:01:16

HIGH CHANNEL , SPURIOUS 1 GHz ~ 10 GHz




Date: 25 AUG 2019 16:01:57

HOPPING, CARRIER LEVEL




Date: 25 AUG 2019 16:28:25

Hopping BAND EDGE (LOW)




Date: 25 AUG 2019 16:31:45

Hopping BAND EDGE (HIGH)




Date: 25 AUG 2019 16:33:16

Hopping Mode, SPURIOUS 30 MHz ~ 1 GHz



Date: 25 AUG 2019 16:29:58

Hopping Mode, SPURIOUS 1GHz ~ 10 GHz



Date: 25 AUG 2019 16:30:22


A.7 Conducted Emissions

Note¹: The EUT is working in the Normal link mode.

Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Note³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.154	47.38	10.41	65.78	-18.40	Peak	L	Pass
1**	0.154	35.43	10.41	55.78	-20.35	AV	L	Pass
2	0.202	46.82	10.38	63.53	-16.71	Peak	L	Pass
2**	0.202	39.44	10.38	53.53	-14.09	AV	L	Pass
3	0.674	35.35	10.27	56.00	-20.65	Peak	L	Pass
3**	0.674	23.77	10.27	46.00	-22.23	AV	L	Pass
4	1.776	36.74	10.26	56.00	-19.26	Peak	L	Pass
4**	1.776	24.28	10.26	46.00	-21.72	AV	L	Pass
5	4.398	35.69	10.31	56.00	-20.31	Peak	L	Pass
5**	4.398	23.63	10.31	46.00	-22.37	AV	L	Pass
6	18.242	41.45	10.50	60.00	-18.55	Peak	L	Pass
6**	18.242	36.14	10.50	50.00	-13.86	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.160	52.00	10.40	65.46	-13.46	Peak	N	Pass
1**	0.160	40.21	10.40	55.46	-15.25	AV	N	Pass
2	0.200	47.13	10.38	63.61	-16.48	Peak	N	Pass
2**	0.200	40.97	10.38	53.61	-12.64	AV	N	Pass
3	0.814	36.54	10.27	56.00	-19.46	Peak	N	Pass
3**	0.814	23.71	10.27	46.00	-22.29	AV	N	Pass
4	2.684	35.80	10.28	56.00	-20.20	Peak	N	Pass
4**	2.684	24.16	10.28	46.00	-21.84	AV	N	Pass
5	6.178	36.84	10.34	60.00	-23.16	Peak	N	Pass
5**	6.178	24.36	10.34	50.00	-25.64	AV	N	Pass
6	18.244	42.51	10.49	60.00	-17.49	Peak	N	Pass
6**	18.244	37.15	10.49	50.00	-12.85	AV	N	Pass

A.8 Radiated Spurious Emission

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The worst configurations is below 1 GHz, only the worst configuration (Low Channel) shown here.


Test Data and Plots

Below 1GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	30.000	34.59	-26.61	40.0	-5.41	Peak	149.20	100	Vertical	Pass
2	49.400	34.28	-23.27	40.0	-5.72	Peak	259.20	200	Vertical	Pass
3	53.637	38.17	-23.41	40.0	-1.83	Peak	299.40	103	Vertical	N/A
3*	53.637	32.79	-23.41	40.0	-7.21	QP	299.40	103	Vertical	Pass
4	98.385	36.54	-24.93	43.5	-6.96	Peak	264.60	100	Vertical	Pass
5	574.898	40.84	-15.33	46.0	-5.16	Peak	125.00	100	Vertical	Pass
6	902.273	86.06	-10.58	46.0	40.06	Peak	187.30	100	Vertical	N/A

Below 1GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	55.462	32.24	-23.72	40.0	-7.76	Peak	148.80	200	Horizontal	Pass
2	94.505	32.37	-25.61	43.5	-11.13	Peak	1.60	200	Horizontal	Pass
3	170.165	32.08	-26.83	43.5	-11.42	Peak	329.20	200	Horizontal	Pass
4	375.078	41.09	-19.96	46.0	-4.91	Peak	360.60	100	Horizontal	Pass
5	499.965	42.26	-16.97	46.0	-3.74	Peak	0.00	200	Horizontal	Pass
6	902.273	92.04	-10.58	46.0	46.04	Peak	338.40	100	Horizontal	N/A

LOW CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1128.000	22.56	-18.29	54.0	-31.44	AV	240.00	150	Vertical	Pass
1	1128.000	38.33	-18.29	74.0	-35.67	Peak	240.00	150	Vertical	Pass
2**	3059.000	29.94	-7.08	54.0	-24.06	AV	121.00	150	Vertical	Pass
2	3059.000	45.76	-7.08	74.0	-28.24	Peak	121.00	150	Vertical	Pass
3**	3590.000	30.28	-7.13	54.0	-23.72	AV	139.00	150	Vertical	Pass
3	3590.000	46.01	-7.13	74.0	-27.99	Peak	139.00	150	Vertical	Pass
4**	5066.000	41.46	-2.80	54.0	-12.54	AV	94.00	150	Vertical	Pass
4	5066.000	49.90	-2.80	74.0	-24.10	Peak	94.00	150	Vertical	Pass
5**	6738.000	38.16	0.26	54.0	-15.84	AV	289.00	150	Vertical	Pass
5	6738.000	53.59	0.26	74.0	-20.41	Peak	289.00	150	Vertical	Pass
6**	9023.500	37.62	-0.32	54.0	-16.38	AV	216.00	150	Vertical	Pass
6	9023.500	49.39	-0.32	74.0	-24.61	Peak	216.00	150	Vertical	Pass

LOW CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1137.500	22.43	-18.24	54.0	-31.57	AV	197.00	150	Horizontal	Pass
1	1137.500	38.85	-18.24	74.0	-35.15	Peak	197.00	150	Horizontal	Pass
2**	3063.000	29.41	-7.36	54.0	-24.59	AV	150.00	150	Horizontal	Pass
2	3063.000	46.39	-7.36	74.0	-27.61	Peak	150.00	150	Horizontal	Pass
3**	3592.000	30.12	-7.06	54.0	-23.88	AV	141.00	150	Horizontal	Pass
3	3592.000	46.28	-7.06	74.0	-27.72	Peak	141.00	150	Horizontal	Pass
4**	4512.000	36.28	-4.77	54.0	-17.72	AV	179.00	150	Horizontal	Pass
4	4512.000	49.43	-4.77	74.0	-24.57	Peak	179.00	150	Horizontal	Pass
5**	6007.000	38.16	-1.12	54.0	-15.84	AV	179.00	150	Horizontal	Pass
5	6007.000	51.87	-1.12	74.0	-22.13	Peak	179.00	150	Horizontal	Pass
6**	7523.500	36.41	-2.48	54.0	-17.59	AV	122.00	150	Horizontal	Pass
6	7523.500	48.47	-2.48	74.0	-25.53	Peak	122.00	150	Horizontal	Pass

MIDDLE CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1125.000	24.03	-18.29	54.0	-29.97	AV	278.00	150	Vertical	Pass
1	1125.000	38.61	-18.29	74.0	-35.39	Peak	278.00	150	Vertical	Pass
2**	3079.000	29.66	-7.98	54.0	-24.34	AV	239.00	150	Vertical	Pass
2	3079.000	45.12	-7.98	74.0	-28.88	Peak	239.00	150	Vertical	Pass
3**	3694.000	30.64	-6.07	54.0	-23.36	AV	294.00	150	Vertical	Pass
3	3694.000	46.75	-6.07	74.0	-27.25	Peak	294.00	150	Vertical	Pass
4**	5337.000	42.21	-3.09	54.0	-11.79	AV	344.00	150	Vertical	Pass
4	5337.000	52.21	-3.09	74.0	-21.79	Peak	344.00	150	Vertical	Pass
5**	6447.000	36.44	-0.32	54.0	-17.56	AV	133.00	150	Vertical	Pass
5	6447.000	52.91	-0.32	74.0	-21.09	Peak	133.00	150	Vertical	Pass
6**	9361.750	38.04	-0.96	54.0	-15.96	AV	157.00	150	Vertical	Pass
6	9361.750	50.32	-0.96	74.0	-23.68	Peak	157.00	150	Vertical	Pass

MIDDLE CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1125.000	23.50	-18.29	54.0	-30.50	AV	325.00	150	Horizontal	Pass
1	1125.000	40.24	-18.29	74.0	-33.76	Peak	325.00	150	Horizontal	Pass
2**	2233.500	29.15	-12.97	54.0	-24.85	AV	210.00	150	Horizontal	Pass
2	2233.500	44.71	-12.97	74.0	-29.29	Peak	210.00	150	Horizontal	Pass
3**	3059.000	29.59	-7.08	54.0	-24.41	AV	71.00	150	Horizontal	Pass
3	3059.000	45.79	-7.08	74.0	-28.21	Peak	71.00	150	Horizontal	Pass
4**	4043.000	31.44	-4.98	54.0	-22.56	AV	331.00	150	Horizontal	Pass
4	4043.000	47.75	-4.98	74.0	-26.25	Peak	331.00	150	Horizontal	Pass
5**	6406.000	42.69	-0.49	54.0	-11.31	AV	181.00	150	Horizontal	Pass
5	6406.000	52.82	-0.49	74.0	-21.18	Peak	181.00	150	Horizontal	Pass
6**	8789.500	37.89	-0.91	54.0	-16.11	AV	270.00	150	Horizontal	Pass
6	8789.500	48.97	-0.91	74.0	-25.03	Peak	270.00	150	Horizontal	Pass

HIGH CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1125.500	30.04	-18.27	54.0	-23.96	AV	87.00	150	Vertical	Pass
1	1125.500	38.52	-18.27	74.0	-35.48	Peak	87.00	150	Vertical	Pass
2**	2575.000	30.53	-12.05	54.0	-23.47	AV	13.00	150	Vertical	Pass
2	2575.000	47.13	-12.05	74.0	-26.87	Peak	13.00	150	Vertical	Pass
3**	3059.000	29.35	-7.08	54.0	-24.65	AV	85.00	150	Vertical	Pass
3	3059.000	44.78	-7.08	74.0	-29.22	Peak	85.00	150	Vertical	Pass
4**	5015.000	34.12	-3.34	54.0	-19.88	AV	29.00	150	Vertical	Pass
4	5015.000	51.17	-3.34	74.0	-22.83	Peak	29.00	150	Vertical	Pass
5**	6680.000	38.40	0.17	54.0	-15.60	AV	300.00	150	Vertical	Pass
5	6680.000	53.16	0.17	74.0	-20.84	Peak	300.00	150	Vertical	Pass
6**	9267.250	37.18	-1.04	54.0	-16.82	AV	327.00	150	Vertical	Pass
6	9267.250	49.12	-1.04	74.0	-24.88	Peak	327.00	150	Vertical	Pass

HIGH CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1126.500	22.28	-18.21	54.0	-31.72	AV	312.00	150	Horizontal	Pass
1	1126.500	38.53	-18.21	74.0	-35.47	Peak	312.00	150	Horizontal	Pass
2**	2189.000	28.81	-13.12	54.0	-25.19	AV	266.00	150	Horizontal	Pass
2	2189.000	45.08	-13.12	74.0	-28.92	Peak	266.00	150	Horizontal	Pass
3**	3060.000	33.13	-7.03	54.0	-20.87	AV	102.00	150	Horizontal	Pass
3	3060.000	45.03	-7.03	74.0	-28.97	Peak	102.00	150	Horizontal	Pass
4**	4192.000	32.76	-4.93	54.0	-21.24	AV	171.00	150	Horizontal	Pass
4	4192.000	47.70	-4.93	74.0	-26.30	Peak	171.00	150	Horizontal	Pass
5**	5789.000	35.67	-2.10	54.0	-18.33	AV	97.00	150	Horizontal	Pass
5	5789.000	51.21	-2.10	74.0	-22.79	Peak	97.00	150	Horizontal	Pass
6**	8308.750	37.92	-0.60	54.0	-16.08	AV	155.00	150	Horizontal	Pass
6	8308.750	49.06	-0.60	74.0	-24.94	Peak	155.00	150	Horizontal	Pass

Hopping Mode 1 GHz to 10 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1125.000	24.20	-18.29	54.0	-29.80	AV	85.00	150	Vertical	Pass
1	1125.000	38.84	-18.29	74.0	-35.16	Peak	85.00	150	Vertical	Pass
2**	2315.500	29.62	-12.87	54.0	-24.38	AV	204.00	150	Vertical	Pass
2	2315.500	46.51	-12.87	74.0	-27.49	Peak	204.00	150	Vertical	Pass
3**	3059.000	30.53	-7.08	54.0	-23.47	AV	80.00	150	Vertical	Pass
3	3059.000	46.47	-7.08	74.0	-27.53	Peak	80.00	150	Vertical	Pass
4**	5296.000	38.71	-3.12	54.0	-15.29	AV	330.00	150	Vertical	Pass
4	5296.000	55.04	-3.12	74.0	-18.96	Peak	330.00	150	Vertical	Pass
5**	6671.000	38.88	0.03	54.0	-15.12	AV	321.00	150	Vertical	Pass
5	6671.000	53.68	0.03	74.0	-20.32	Peak	321.00	150	Vertical	Pass
6**	9081.250	37.87	-0.91	54.0	-16.13	AV	308.00	150	Vertical	Pass
6	9081.250	48.97	-0.91	74.0	-25.03	Peak	308.00	150	Vertical	Pass

Hopping Mode 1 GHz to 10 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1125.000	23.01	-18.29	54.0	-30.99	AV	301.00	150	Horizontal	Pass
1	1125.000	37.57	-18.29	74.0	-36.43	Peak	301.00	150	Horizontal	Pass
2**	2294.500	30.16	-12.44	54.0	-23.84	AV	132.00	150	Horizontal	Pass
2	2294.500	45.98	-12.44	74.0	-28.02	Peak	132.00	150	Horizontal	Pass
3**	3065.000	29.18	-7.33	54.0	-24.82	AV	71.00	150	Horizontal	Pass
3	3065.000	44.91	-7.33	74.0	-29.09	Peak	71.00	150	Horizontal	Pass
4**	5025.000	44.89	-3.27	54.0	-9.11	AV	121.00	150	Horizontal	Pass
4	5025.000	52.65	-3.27	74.0	-21.35	Peak	121.00	150	Horizontal	Pass
5**	5816.000	35.18	-2.42	54.0	-18.82	AV	360.00	150	Horizontal	Pass
5	5816.000	50.91	-2.42	74.0	-23.09	Peak	360.00	150	Horizontal	Pass
6**	8749.750	37.78	-1.06	54.0	-16.22	AV	103.00	150	Horizontal	Pass
6	8749.750	50.19	-1.06	74.0	-23.81	Peak	103.00	150	Horizontal	Pass

A.9 Band Edge (Restricted-band band-edge)

Pass

Note: The adjacent to the restricted frequency band (608-614MHz and 960-1240MHz) is far away the fundamental, it is noise only. Please refer to Section A.8 for test data.

ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ1980061-AR.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1980061-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ1980061-AI.PDF".

--END OF REPORT--