

RF Exposure Report

Report No.: FCC_RF_SL20030501-PHA-101_MPE Rev_1.0

FCC ID: 2AOHB-PI00034

Test Model: PI-N261-DF10400A

Series Model: N/A

Issued Date: 06/17/2020

Applicant: JMA Tech, PHAZR

Address: 8 Prestige Circle, Suite 104, Allen, TX 75002

Manufacturer: JMA Wireless, John Mezzalingua Associates

Address: 7645 Henry Clay Boulevard, Liverpool, NY 13088

Issued By: Bureau Veritas Consumer Products Services, Inc.

Lab Address: 775 Montague Expressway, Milpitas, CA 95035

Test Location (1): 775 Montague Expressway, Milpitas, CA 95035

**FCC Registration /
Designation Number:** 540430



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Radiated Power	6
3 Conclusion	6

Release Control Record

Issue No.	Description	Date Issued
FCC_RF_SL20030501-PHA-101_MPE	Initial Release	06/08/2020
FCC_RF_SL20030501-PHA-101_MPE Rev_1.0	Minor error updata	06/17/2020

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (Mw/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

Where

Pd = power density in Mw/cm²

Pout = output power to antenna in Mw

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as Mobile Device.

2.4 Calculation Result of Maximum Radiated Power

Frequency (GHz)	E.I.R.P (dBm)	Turn-Up Tolerance	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
28.15	44.08	± 1dB	55	0.847	1

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Calculate SAR test exclusion thresholds from condition "1" formulas.

3 Conclusion

Conclusion:

$$0.847/1 = 0.847 < 1$$

The maximum calculations of above situations are less than the "1" limit.

--- END ---