


# FCC RF EXPOSURE REPORT

## FCC ID: 2AOHHTURBOXC7230C

**Equipment** : Smart Module  
**Model No.** : C7230C  
**Trademark** : TurboX  
**Product No.** : POC230731014-S001  
**Applicant** : Thundercomm Technology Co., Ltd  
**Address** : No. 107, Middle Datagu Road, Xiantao Street, Yubei District, Chongqing, China, 401122  
**Manufacturer** : Thundercomm Technology Co., Ltd  
**Address** : No. 107, Middle Datagu Road, Xiantao Street, Yubei District, Chongqing, China, 401122  
**Receipt Date** : 2023.08.02  
**Issued Date** : 2023.08.31  
**Test Sample** : Final Sample  
**Standard(s)** : CFR47 FCC Part 1: Section 1.1310  
 CFR47 FCC Part 2: Section 2.1091  
 FCC KDB Publication 447498 v06  
 FCC KDB Publication 865664 D02 v01r02

Prepared By:	Checked By:	Approved By:	
Jason huang	Tim Zhang	Misue Su	
<i>Jason huang</i>	<i>Tim.zhang</i>	<i>Misue Su</i>	

**Note:** This report shall not be reproduced except in full, without the written approval of Shenzhen Haiyun Standard Technical Co., Ltd. This document may be altered or revised by Shenzhen Haiyun Standard Technical Co., Ltd. Personnel only, and shall be noted in the revision section of the document. The test results of this report relate only to the tested sample identified in this report.



## 1. TEST FACILITY

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier:	CN0145
A2LA Certificate Number:	6823.01
Telephone:	0755-26024411

## 2. MPE CALCULATION METHOD

### ➤ Product Classification

This device defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

Max 3.35 dBi for Bluetooth, Max 6.36 dBi for 2.4GHz Wi-Fi MIMO mode, Max 5.09 dBi for 5GHz Wi-Fi MIMO mode

### ➤ Radio Frequency Exposure Limit

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )
300-1,500	--	--	f/1500
1,500-100,000	--	--	1.0

### ➤ Radio Frequency Exposure Calculation Formula

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:

$$S = \frac{EIRP}{4\pi R^2}$$

where: EIRP = equivalent (or effective) isotropically radiated power

➤ **Table for Filed Antenna**

For BDR+EDR & BLE

Ant.	Brand	Antenna Type	Connector	Gain (dBi)
1	N/A	PIFA	N/A	3.35

For 2.4G WIFI

Ant.	Brand	Antenna Type	Connector	Gain (dBi)
1	N/A	PIFA	N/A	3.35
2	N/A	PIFA	N/A	3.35

For 5G WIFI

Ant.	Brand	Antenna Type	Connector	Gain (dBi)
1	N/A	PIFA	N/A	2.08
2	N/A	PIFA	N/A	2.08

### 3. TEST RESULTS

Worse case data:

Mode	*Measured RF Output Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	FCC Limit (mW/cm <sup>2</sup> )
Bluetooth	7.23	3.35	20	0.0023	1.0
2.4G Wi-Fi MIMO	24.69	6.36	20	0.2533	1.0
5G Wi-Fi MIMO	19.96	5.09	20	0.0636	1.0

Note:

1. BT(hopping) RF Output Power: Refer to SZ22110114W02
2. BLE RF Output Power: Refer to SZ22110114W01
3. \*2.4GHz Band RF Output Power: Refer to RF230731014-01-001
4. \*5GHz Bands RF Output Power: Refer to SZ22110114W04

#### a) Simultaneous transmission MPE:

Per KDB 447498 D01 v06, simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is  $\leq 1.0$ .

Simultaneous transmission Scenarios

No.	Simultaneous transmission Scenarios
1	Bluetooth
2	2.4GHz Wi-Fi MIMO
3	5GHz Wi-Fi MIMO
4	2.4GHz Wi-Fi MIMO + 5GHz Wi-Fi MIMO

#### 1) For Bluetooth

The MPE ratio for Bluetooth can be calculated as follow:

=The power density at 20cm distance/MPE limit  
=0.0023 mW/cm<sup>2</sup>

#### 2) For 2.4GHz MIMO:

The MPE ratio for 2.4GHz Wi-Fi MIMO can be calculated as follow:

=The power density at 20cm distance/MPE limit  
=0.2533 mW/cm<sup>2</sup>

#### 3) For 5GHz Wi-Fi MIMO:

The MPE ratio for 5GHz Wi-Fi MIMO can be calculated as follow:

=The power density at 20cm distance/MPE limit  
=0.0636 mW/cm<sup>2</sup>

#### 4) For 2.4GHz MIMO + 5GHz Wi-Fi MIMO:

The sum of the MPE ratios for all simultaneous transmitting antennas:

=0.2533+0.0636  
=0.3169 <1.0

As the sum of MPE ratios for all simultaneous transmitting antennas is  $\leq 1.0$ , simultaneous transmission MPE test exclusion will be applied.

➤ **Conclusion**

Therefore the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.

---

(END OF REPORT)