


# FCC RF EXPOSURE REPORT

## FCC ID: 2AOHHTURBOXC7230C

**Project No.** : 2307C207A  
**Equipment** : Smart Module  
**Brand Name** : TurboX  
**Test Model** : C7230C  
**Series Model** : N/A  
**Applicant** : Thundercomm Technology Co., Ltd  
**Address** : No. 107, Middle Datagu Road, Xiantao Street, Yubei District,  
Chongqing, China, 401122  
**Manufacturer** : Thundercomm Technology Co., Ltd  
**Address** : No. 107, Middle Datagu Road, Xiantao Street, Yubei District,  
Chongqing, China, 401122  
**Factory** : Thundercomm Technology Co., Ltd  
**Address** : No. 107, Middle Datagu Road, Xiantao Street, Yubei District,  
Chongqing, China, 401122  
**Issued Date** : May 28, 2024  
**Report Version** : R00  
**Standard(s)** : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091  
FCC Title 47 Part 2.1091 & KDB 447498 D01 v06


The above equipment has been evaluated and found compliance with the requirement of the relative standards by BTL Inc.

**Prepared by** :



Chella Zheng

**Approved by** :



Chay Cai

Room 108, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong,  
People's Republic of China

Tel: +86-769-8318-3000

Web: [www.newbtl.com](http://www.newbtl.com)

Service mail: [btl\\_qa@newbtl.com](mailto:btl_qa@newbtl.com)

**REPORT ISSUED HISTORY**

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-5-2307C207A	R00	Original Report.	May 28, 2024	Valid

## 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## 2. CALCULATED RESULT

Worse case data:

Mode	*Measured RF Output Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	FCC Limit (mW/cm <sup>2</sup> )
Bluetooth	7.23	3.35	20	0.0023	1.0
2.4G Wi-Fi MIMO	24.69	6.36	20	0.2533	1.0
5G Wi-Fi MIMO	19.96	5.09	20	0.0636	1.0

Note:

1. BT(hopping) RF Output Power: Refer to SZ22110114W02
2. BLE RF Output Power: Refer to SZ22110114W01
3. \*2.4GHz Band RF Output Power: Refer to RF230731014-01-001
4. \*5GHz Bands RF Output Power: Refer to SZ22110114W04

### For the max simultaneous transmission MPE:

Simultaneous transmission Scenarios

No.	Simultaneous transmission Scenarios
1	Bluetooth
2	2.4GHz Wi-Fi MIMO
3	5GHz Wi-Fi MIMO
4	2.4GHz Wi-Fi MIMO + 5GHz Wi-Fi MIMO

1) For Bluetooth

The MPE ratio for Bluetooth can be calculated as follow:

=The power density at 20cm distance/MPE limit  
=0.0023 mW/cm<sup>2</sup>

2) For 2.4GHz MIMO:

The MPE ratio for 2.4GHz Wi-Fi MIMO can be calculated as follow:

=The power density at 20cm distance/MPE limit  
=0.2533 mW/cm<sup>2</sup>

3) For 5GHz Wi-Fi MIMO:

The MPE ratio for 5GHz Wi-Fi MIMO can be calculated as follow:

=The power density at 20cm distance/MPE limit  
=0.0636 mW/cm<sup>2</sup>

4) For 2.4GHz MIMO + 5GHz Wi-Fi MIMO:

The sum of the MPE ratios for all simultaneous transmitting antennas:

=0.2533+0.0636  
=0.3169 <1.0

As the sum of MPE ratios for all simultaneous transmitting antennas is ≤ 1.0, simultaneous transmission MPE test exclusion will be applied.

Note: The test results reference to report which is provided by the manufacturer.  
(Report No.: RF230731014-01-005)

**End of Test Report**