




# TEST REPORT

**APPLICANT** : Thundercomm Technology Co., Ltd  
**PRODUCT NAME** : Smart Module  
**MODEL NAME** : C865C, C2130C, C5165C  
**BRAND NAME** : TurboX  
**FCC ID** : 2AOHHTURBOXC865C  
**STANDARD(S)** : 47 CFR Part 15 Subpart C  
**RECEIPT DATE** : 2022-11-11  
**TEST DATE** : 2022-11-27 to 2022-12-05  
**ISSUE DATE** : 2022-12-27

Edited by:

  
Zeng Xiaoying (Rapporteur)

Approved by:

  
Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information ..... 3**
- 1.1. Applicant and Manufacturer Information ..... 3**
- 1.2. Equipment Under Test (EUT) Description ..... 3**
- 1.3. The Channel Number and Frequency ..... 4**
- 1.4. Test Standards and Results ..... 5**
- 1.5. Environmental Conditions ..... 6**
- 2. 47 CFR Part 15C Requirements ..... 7**
- 2.1. Antenna Requirement ..... 7**
- 2.2. Duty Cycle of Test Signal ..... 8**
- 2.3. Maximum Peak Conducted Output Power ..... 8**
- 2.4. Maximum Average Conducted Output Power ..... 14**
- 2.5. 6 dB Bandwidth ..... 16**
- 2.6. Conducted Spurious Emissions and Band Edge ..... 21**
- 2.7. Power Spectral Density (PSD) ..... 28**
- 2.8. Conducted Emission ..... 33**
- 2.9. Restricted Frequency Bands ..... 37**
- 2.10. Radiated Emission ..... 50**
- Annex A Test Uncertainty ..... 66**
- Annex B Testing Laboratory Information ..... 67**

Change History		
Version	Date	Reason for change
1.0	2022-12-27	First edition



# 1. Technical Information

Note: Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	Thundercomm Technology Co., Ltd
<b>Applicant Address:</b>	Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China
<b>Manufacturer:</b>	Thundercomm Technology Co., Ltd
<b>Manufacturer Address:</b>	Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Smart Module	
<b>Sample No.:</b>	1#	
<b>Hardware Version:</b>	DT865_DEq_LA-IOB V03	
<b>Software Version:</b>	FlatBuild_Turbox-QCS8250_xx.xx_la1.0.D.userdebug.202210 24.1345	
<b>Equipment Type:</b>	Bluetooth LE	
<b>Bluetooth Version:</b>	5.1	
<b>Modulation Type:</b>	GFSK	
<b>Data Rate:</b>	1Mbps, 2Mbps	
<b>Operating Frequency Range:</b>	2402MHz-2480MHz	
<b>Antenna Information:</b>	Antenna Type A	
	Antenna Type:	Dipole Antenna
	Antenna Gain:	2.6dBi
	Part No.:	1461531100
	Manufacturer:	MOLEX
	Antenna Type B	
	Antenna Type:	PIFA Antenna
	Antenna Gain:	1.84dBi
	Part No.:	F-0G-JV-0211-002-00
	Manufacturer:	Speed Wireless Technical Co., LTD.



**Note1:** This is a variant report of original report (Report No.: SZ22030287W01, FCC ID: 2AOHHTURBOXC865C). Based on the similarity between before, made the following changes:

1. A new antenna is added.
2. Change the C11201 capacitor, the role is BT power supply filter, does not change the power control, does not affect the RF.
3. Change the shelf under the shield cover.
4. Update software version number.
5. Reduce 2.4G WiFi and 5G WiFi conducted output power.

Except for the differences shown above, the other parts are the same as before. No other changes. We have evaluated those changes in restricted frequency bands and radiated emissions and added the test results for antenna B in this report.

**Note2:** The EUT will not sell with the antenna.

**Note 3:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

### 1.3. The Channel Number and Frequency

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>0</b>	<b>2402</b>	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	<b>19</b>	<b>2440</b>	29	2460	<b>39</b>	<b>2480</b>

**Note 1:** The black bold channels were selected for test.



## 1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS <sub>Note1</sub>	No deviation
2	N/A	Duty Cycle of Test Signal	Mar. 30, 2022	Su Xiaoxian	PASS <sub>Note1</sub>	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Mar. 30, 2022	Su Xiaoxian	PASS <sub>Note1</sub>	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Mar. 30, 2022	Su Xiaoxian	PASS <sub>Note1</sub>	No deviation
5	15.247(a)	Bandwidth	Apr. 15, 2022	Su Xiaoxian	PASS <sub>Note1</sub>	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Apr. 15, 2022	Su Xiaoxian	PASS <sub>Note1</sub>	No deviation
7	15.247(e)	Power Spectral Density	Apr. 15, 2022	Su Xiaoxian	PASS <sub>Note1</sub>	No deviation
8	15.207	Conducted Emission	Apr. 27, 2022	Wu Zhaoling	PASS <sub>Note1</sub>	No deviation
9	15.247(d)	Restricted Frequency Bands	Dec. 05, 2022	Lin Jiayong	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Nov. 27, 2022 Dec. 05, 2022	Lin Jiayong	PASS	No deviation

**Note1:** The test results of these test items in this report refer to the test report (Report No.: SZ22030287W01).



**Note 2:** The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013 and KDB558074 D01 v05r02.

**Note 3:** The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The Ref offset 1.5dB means the cable loss is 1.5dB.

**Note 4:** Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

**Note 5:** When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

### 1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



## 2. 47 CFR Part 15C Requirements

### 2.1. Antenna Requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Test Result: Compliant

Inside of the EUT has a permanently attached Dipole antenna fixed to PCB with solder. Please refer to the EUT internal photos.

## 2.2. Duty Cycle of Test Signal


### 2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be non constant.

### 2.2.2. Test Description

#### Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

### 2.2.3. Test Result

Test Mode	Data Rate	Duty Cycle (%) (D)	Duty Factor ( $10 \cdot \lg[1/D]$ )
GFSK	1Mbps	62.50	2.04
	2Mbps	32.69	4.86



## 2.3. Maximum Peak Conducted Output Power


### 2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

### 2.3.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

#### Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

### 2.3.3. Test Procedure

The measured output power was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for Peak Output Power test on the spectrum analyzer:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 1MHz
- c) Set VBW to 3MHz
- d) Set span to 3MHz
- e) Sweep time = auto couple
- f) Detector = peak
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use peak marker function to determine the peak amplitude level



2.3.4. Test Result

1Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	6.63	0.0046	30	1	PASS
19	2440	7.45	0.0056			PASS
39	2480	5.08	0.0032			PASS


B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)




2Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	6.68	0.0047	30	1	PASS
19	2440	<b>7.49</b>	<b>0.0056</b>			PASS
39	2480	5.13	0.0033			PASS


B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)

## 2.4. Maximum Average Conducted Output Power


### 2.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

### 2.4.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

#### Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

### 2.4.3. Test Procedure

KDB 558074 Section 8.3.2 was used in order to prove compliance.



**2.4.4. Test Result**

**1Mbps**

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated		dBm	W	
				dBm	W			
0	2402	3.96	2.04	6.00	0.0040	30	1	PASS
19	2440	5.33		<b>7.37</b>	<b>0.0055</b>			PASS
39	2480	2.50		4.54	0.0028			PASS

**2Mbps**

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated		dBm	W	
				dBm	W			
0	2402	1.21	4.86	6.07	0.0040	30	1	PASS
19	2440	1.72		6.58	0.0045			PASS
39	2480	-1.17		3.69	0.0023			PASS


## 2.5. 6 dB Bandwidth

### 2.5.1. Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

### 2.5.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

### 2.5.3. Test Procedure

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission





The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥6 dB.

**2.5.4. Test Result**

**1Mbps**

**A. Test Verdict:**

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	0.672	≥500	PASS
19	2440	0.671	≥500	PASS
39	2480	0.671	≥500	PASS

**B. Test Plot:**



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)




2Mbps

**A. Test Verdict:**

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	1.146	≥500	PASS
19	2440	1.156	≥500	PASS
39	2480	1.154	≥500	PASS

**B. Test Plot:**



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)


## 2.6. Conducted Spurious Emissions and Band Edge

### 2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 2.6.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

### 2.6.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.




2.6.4. Test Result

1Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-48.32	5.15	-14.85	PASS
19	2440	-48.77	5.46	-14.54	PASS
39	2480	-48.66	4.07	-15.93	PASS

B. Test Plot:




(30MHz to 25GHz, Channel 0)






(Band Edge, Channel 0)



(30MHz to 25GHz, Channel 19)



(30MHz to 25GHz, Channel 39)



(Band Edge, Channel 39)






2Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-48.62	2.33	-17.67	PASS
19	2440	-49.08	4.48	-15.52	PASS
39	2480	-48.85	-1.07	-21.07	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 0)



(Band Edge, Channel 0)



(30MHz to 25GHz, Channel 19)



(30MHz to 25GHz, Channel 39)



(Band Edge, Channel 39)


## 2.7. Power Spectral Density

### 2.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 2.7.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

### 2.7.3. Test Procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW




2.7.4. Test Result

1Mbps


A. Test Verdict:

Spectral Power Density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-8.17	8	PASS
19	2440	-7.38	8	PASS
39	2480	-9.80	8	PASS


B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)






2Mbps


**A.Test Verdict:**

Spectral Power Density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-11.33	8	PASS
19	2440	-10.31	8	PASS
39	2480	-12.68	8	PASS


**B.Test Plot:**



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)



## 2.8. Conducted Emission

### 2.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.8.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



### 2.8.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

#### A. Test Setup:

Test Mode: EUT+Adapter+PC+ BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

$U_R$ : Receiver Reading


$A_{\text{Factor}}$ : Voltage division factor of LISN

**B. Test Plot:**



(L Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1635	52.18	38.10	65.28	55.28	Line	PASS
2	0.2037	53.39	37.99	63.46	53.46		PASS
3	0.2632	54.01	38.43	61.33	51.33		PASS
4	0.3699	50.11	35.01	58.50	48.50		PASS
5	0.4576	55.28	39.26	56.74	46.74		PASS
6	0.8040	45.02	30.29	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2441	48.11	30.59	61.95	51.95	Neutral	PASS
2	0.3043	47.48	30.16	60.13	50.13		PASS
3	0.4687	49.83	31.11	56.54	46.54		PASS
4	0.5078	42.19	27.31	56.00	46.00		PASS
5	0.8238	39.79	25.84	56.00	46.00		PASS
6	1.3582	35.89	23.68	56.00	46.00		PASS


## 2.9. Restricted Frequency Bands

### 2.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 2.9.2. Test Description

#### Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



### 2.9.3. Test Procedure

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 kHz for  $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

### 2.9.4. Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

#### Antenna Type A


##### 1Mbps

##### A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dB $\mu$ V)	$A_T$ (dB)	$A_{\text{Factor}}$ (dB@3m)	Max. Emission E (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
		PK/ AV						
0	2389.57	PK	22.67	6.74	27.20	56.61	74	PASS
0	2390.00	AV	9.76	6.74	27.20	43.70	54	PASS
39	2483.82	PK	20.84	6.74	27.20	54.78	74	PASS
39	2483.50	AV	9.53	6.74	27.20	43.47	54	PASS




B. Test Plot:



(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



(AVERAGE, Channel 39)






2Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading	A <sub>T</sub> (dB)	A <sub>Factor</sub> (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV	U <sub>R</sub> (dBμV)					
0	2388.74	PK	21.92	6.74	27.20	55.86	74	PASS
0	2389.57	AV	9.72	6.74	27.20	43.66	54	PASS
39	2484.29	PK	22.50	6.74	27.20	56.44	74	PASS
39	2483.50	AV	9.70	6.74	27.20	43.64	54	PASS

B. Test Plot:




(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



(AVERAGE, Channel 39)




**Antenna Type B**

**1Mbps**


**A. Test Verdict:**

Channel	Frequency (MHz)	Detector	Receiver Reading	A <sub>T</sub> (dB)	A <sub>Factor</sub> (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV	U <sub>R</sub> (dBμV)					
0	2390.00	PK	24.09	6.74	27.20	58.03	74	PASS
0	2389.54	AV	10.73	6.74	27.20	44.67	54	PASS
39	2483.90	PK	24.36	6.74	27.20	58.30	74	PASS
39	2483.65	AV	10.38	6.74	27.20	44.32	54	PASS


**B. Test Plot:**




(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



(AVERAGE, Channel 39)




2Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading	A <sub>T</sub> (dB)	A <sub>Factor</sub> (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV	U <sub>R</sub> (dBμV)					
0	2382.68	PK	23.23	6.74	27.20	57.17	74	PASS
0	2387.67	AV	10.68	6.74	27.20	44.62	54	PASS
39	2483.63	PK	26.79	6.74	27.20	60.73	74	PASS
39	2483.50	AV	10.39	6.74	27.20	44.33	54	PASS


B. Test Plot:



(PEAK, Channel 0)




(AVERAGE, Channel 0)



(PEAK, Channel 39)





(AVERAGE, Channel 39)



## 2.10. Radiated Emission

### 2.10.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


**Note1:** For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

**Note2:** For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


**2.10.2. Test Description**

**Test Setup:**


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



## 3) For radiated emissions above 1GHz



The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



### 2.10.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}/\text{m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.


**Note1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

**Note2:** For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note3:** For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


**Antenna Type A, 1Mbps**

**Plot for Channel 0**



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	30.19	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
541.190	32.66	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2494.400	45.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4734.440	45.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8750.760	47.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12197.280	46.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
110.510	29.70	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
579.020	31.46	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
5689.240	46.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8482.800	45.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10333.880	45.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12881.040	46.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
97.900	29.47	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
359.800	30.36	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2495.467	45.96	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5778.560	45.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8467.400	46.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12754.760	45.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
96.930	30.40	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
558.650	33.50	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1990.933	46.08	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5639.960	45.62	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8864.720	45.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13210.600	45.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
102.750	28.83	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
458.740	30.67	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2494.933	46.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5753.920	45.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8991.000	45.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12585.360	46.03	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
96.930	29.71	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
438.370	29.62	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2409.067	47.52	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5680.000	45.41	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8941.720	46.31	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12533.000	45.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**2Mbps**

**Plot for Channel 0**



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
104.690	29.84	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
570.290	32.42	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2409.600	45.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5689.240	46.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8411.960	46.02	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12332.800	45.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
102.750	30.08	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
655.650	32.78	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2411.200	45.25	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5695.400	45.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7986.920	46.54	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12539.160	46.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
106.630	29.54	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
349.130	29.93	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2408.533	45.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5784.720	45.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9225.080	45.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12308.160	45.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
101.780	28.98	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
539.250	31.78	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2419.200	45.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4737.520	45.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8941.720	45.43	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11880.040	46.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
99.840	29.79	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
597.450	32.51	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2353.600	46.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5399.720	45.88	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8079.320	45.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12736.280	45.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
99.840	29.41	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
386.960	28.76	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2409.600	46.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5171.800	45.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8433.520	45.62	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
15006.240	45.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**Antenna Type B, 1Mbps**

Plot for Channel 0



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
99.840	30.85	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
349.130	30.99	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
547.010	33.13	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
4497.280	44.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8221.000	45.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12483.720	46.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
107.600	30.69	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
347.190	30.07	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
690.570	33.80	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
5744.680	45.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9043.360	45.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12533.000	45.86	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
102.750	30.57	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
324.880	29.53	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
576.110	33.36	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
4330.960	44.81	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8418.120	45.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
16453.840	46.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
102.750	31.72	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
335.550	30.17	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
689.600	33.36	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
5384.320	45.30	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8479.720	46.06	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12489.880	46.04	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 39



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
107.600	31.98	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
340.400	29.70	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
681.840	33.24	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
4500.360	45.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8390.400	45.93	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12169.560	46.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
102.750	31.03	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
350.100	30.01	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
580.960	33.08	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
5695.400	45.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8615.240	46.15	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12579.200	47.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




**2Mbps**

**Plot for Channel 0**



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
103.720	32.24	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
581.930	34.50	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1116.267	43.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1902.933	43.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4494.200	46.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12148.000	47.67	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
116.330	31.27	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
584.840	34.20	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1116.267	47.03	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2131.733	43.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5997.240	48.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12739.360	48.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
103.720	31.30	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
577.080	33.97	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1115.200	42.93	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2040.000	42.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5202.600	47.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12151.080	48.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
104.690	31.53	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
790.480	36.07	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1198.400	43.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2123.733	43.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5732.360	46.86	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12730.120	47.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 39



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
102.750	32.00	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
358.830	31.76	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1111.467	41.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2479.467	47.73	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4694.400	47.09	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12520.680	47.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
106.630	32.13	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
580.960	33.46	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1119.467	46.45	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1938.133	42.33	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3197.520	45.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8421.200	48.32	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



## Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test Items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power Spectral Density	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .



## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Laboratory Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



#### 4. Test Equipments Utilized

##### 4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2022.03.01	2023.02.28
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

##### 4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY5640009 3	N9038A	KEYSIGHT	2022.03.03	2023.03.02
LISN	8127449	NSLK 8127	Schwarzbeck	2022.03.03	2023.03.02
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2022.07.06	2023.07.05
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2022.07.08	2023.07.07
NOTEBOOK	DF2DR A01 DPC	VOSTRO 5370	DELL	N/A	N/A
ADAPTER	OKXTTW	LA45NM140	DELL	N/A	N/A

##### 4.3 List of Software Used

Description	Manufacturer	Software Version
Test System	Tonscend	V2.5.77.0418
Morlab EMCR V1.2	Morlab	V1.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2022.07.06	2023.07.05
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2022.02.11	2025.02.10
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2022.07.13	2025.07.12
Test Antenna – Horn	BBHA9170#773	BBHA 9170	Schwarzbeck	2022.07.14	2025.07.13
Preamplifier (2GHz-18GHz)	61171/61172	S020180L3203	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (10MHz-6GHz)	46732	S10M100L3802	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2022.07.23	2023.07.22
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2022.07.08	2023.07.07
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2022.07.08	2023.07.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

END OF REPORT