

**With regards to FCC identifier 2AOHPBST50A and 2AOHPMP50A**

With reference to KDB634817 Section (d) (1) (iii), the PNG system with the two components MP50 and BST50, certified under the above references are developed to support world wide markets, civilian and military. The equipment may contain functions that are not operational in U.S Territories except as noted in the filing.

Equipment with FCC identifier 2AOHPBST50A and 2AOHPMP50A used in the U.S. Territories, will be limited to be operated the frequency bands listed below:

FCC Rule Parts	Frequency Range (MHZ)	Output Watts	Frequency Tolerance	Emission Designator
90	406.1 - 420.0	0.4	2.0 PM	20K0D7W
90	421.0 - 430.0	0.4	2.0 PM	20K0D7W
90	450.0 - 454.0	0.4	2.0 PM	20K0D7W
90	456.0 - 460.0	0.4	2.0 PM	20K0D7W
90	460.0 - 462.5375	0.4	2.0 PM	20K0D7W
90	462.7375 - 467.5375	0.4	2.0 PM	20K0D7W
90	467.7375 - 470.0	0.4	2.0 PM	20K0D7W

Precise frequency operation within the band must be agreed with the frequency coordinator at the time of licensing.



.....  
Petter Johnsen (Chief Technical Officer)  
on behalf of Axnes AS

Document number: AX-PNG-OTH-1745  
Revision: Issue A  
Date: 28 Jan 2019