

## FCC RF Exposure

EUT Description: Robot Vacuum cleaner

ModelNo.: M1-WBL

FCC ID: 2AOIA-M1-WBL

Equipment type: mobile device

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                               |                               |                                     |                          |
| 0.3–3.0   | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0–30  | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30–300  | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500  |                               |                               | f/300                               | 6                        |
| 1500–100,000  |                               |                               | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3–1.34  | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30   | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30–300  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500  |                               |                               | f/1500                              | 30                       |
| 1500–100,000  |                               |                               | 1.0                                 | 30                       |

F = frequency in MHz

Formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where :

Pd = power density in mW/cm<sup>2</sup>,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi = 3.14$ ;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and

highest channel individually.

### 3. Test Result of RF Exposure Evaluation

| Modulation | Channel Freq. (MHz) | Conducted power (dBm) | Max tune-up power (mW) | Antenna Gain (dBi) | Antenna gain numeric | Evaluation result (mW/cm2 ) | Power density Limits (mW/cm2) |
|------------|---------------------|-----------------------|------------------------|--------------------|----------------------|-----------------------------|-------------------------------|
| 802.11b    | 2412                | 11.23                 | 13.27                  | 1.80               | 1.51                 | 0.00398                     | 1                             |
|            | 2437                | 10.78                 | 11.97                  | 1.80               | 1.51                 | 0.00359                     | 1                             |
|            | 2462                | 10.75                 | 11.89                  | 1.80               | 1.51                 | 0.00357                     | 1                             |
| 802.11g    | 2412                | 10.92                 | 12.36                  | 1.80               | 1.51                 | 0.00371                     | 1                             |
|            | 2437                | 10.33                 | 10.79                  | 1.80               | 1.51                 | 0.00324                     | 1                             |
|            | 2462                | 10.60                 | 11.48                  | 1.80               | 1.51                 | 0.00345                     | 1                             |
| 802.11n    | 2412                | 10.80                 | 12.02                  | 1.80               | 1.51                 | 0.00361                     | 1                             |
|            | 2437                | 10.70                 | 11.75                  | 1.80               | 1.51                 | 0.00353                     | 1                             |
|            | 2462                | 9.89                  | 9.75                   | 1.80               | 1.51                 | 0.00293                     | 1                             |

Conclusion: the max result :  $0.00398 \leq 1.0$  compliance with FCC's RF Exposure.