

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: SHENZHEN SASWELL TECHNOLOGY INC.
Address of applicant: Room 1601-1602 ,Floor16,Building4,Tianan Cloud Park,
No.2018 Xuegang Road,Bantian Street,Longgang District,
Shenzhen, China

Manufacturer: SHENZHEN SASWELL TECHNOLOGY INC.
Address of manufacturer: Room 1601-1602 ,Floor16,Building4,Tianan Cloud Park,
No.2018 Xuegang Road,Bantian Street,Longgang District,
Shenzhen, China

General Description of EUT:

Product Name: Thermostat
Trade Name: /
Model No.: T18UTW-7-WIFI
Adding Model(s): /
FCC ID: 2AOIFT18UTW
Rated Voltage: DC 24V

Technical Characteristics of EUT	
Frequency Range:	915.75MHz
RF Output Power:	10.72dBm (Conducted)
Type of Modulation:	FSK
Quantity of Channels:	1
Type of Antenna:	Integral Antenna
Antenna Gain:	0.01dBi
Wi-Fi	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20 2422-2452MHz for 802.11n-HT40
RF Output Power:	14.63dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20 7 for 802.11n-HT40
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	3.0dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Product is a fixed use device

Wi-Fi:

Maximum Tune-Up output power: 15(dBm)

Maximum peak output power at antenna input terminal: 31.62(mW)

Prediction distance: >20(cm)

Prediction frequency: 2437 (MHz)

Antenna gain: 3.0(dBi)

Directional gain (numeric gain): 2

The worst case is power density at prediction frequency at 20cm: 0.013(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

RF 915.75MHz

Maximum Tune-Up output power: 11(dBm)

Maximum peak output power at antenna input terminal: 12.59(mW)

Prediction distance: >20(cm)

Prediction frequency: 915.75 (MHz)

Antenna gain: 0.01(dBi)

Directional gain (numeric gain): 1

The worst case is power density at prediction frequency at 20cm: 0.0025(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

All the power density is less than the MPE limit

Result: Pass